We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists



186,000

200M



Our authors are among the

TOP 1% most cited scientists





WEB OF SCIENCE

Selection of our books indexed in the Book Citation Index in Web of Science™ Core Collection (BKCI)

# Interested in publishing with us? Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected. For more information visit www.intechopen.com



# Distributed Fusion Prediction for Mixed Continuous-Discrete Linear Systems

Ha-ryong Song<sup>1</sup>, Moon-gu Jeon<sup>1</sup> and Vladimir Shin<sup>2</sup> <sup>1</sup>School of Information and Communications, Gwangju Institute of Science and Technology Department of Information statistics, Gyeong sang National University South Korea

# 1. Introduction

The integration of information from a combination of different types of observed instruments (sensors) are often used in the design of high-accuracy control systems. Typical applications that benefit from this use of multiple sensors include industrial tasks, military commands, mobile robot navigation, multi-target tracking, and aircraft navigation (see (hall, 1992, Bar-Shalom, 1990, Bar-Shalom & Li, 1995, Zhu, 2002, Ren & Key, 1989) and references therein). One problem that arises from the use of multiple sensors is that if all local sensors observe the same target, the question then becomes how to effectively combine the corresponding local estimates. Several distributed fusion architectures have been discussed in (Alouani, 2005, Bar-Shalom & Campo, 1986, Bar-Shalom, 2006, Li et al., 2003, Berg & Durrant-Whyte, 1994, Hamshemipour et al., 1998) and algorithms for distributed estimation fusion have been developed in (Bar-Shalom & Campo, 1986, Chang et al., 1997, Chang et al, 2002, Deng et al., 2005, Sun, 2004, Zhou et al., 2006, Zhu et al., 1999, Zhu et al., 2001, Roecker & McGillem, 1998, Shin et al, 2006). To this end, the Bar-Shalom and Campo fusion formula (Bar-Shalom & Campo, 1986) for two-sensor systems has been generalized for an arbitrary number of sensors in (Deng et al., 2005, Sun, 2004, Shin et al., 2007) The formula represents an optimal mean-square linear combination of the local estimates with matrix weights. The analogous formula for weighting an arbitrary number of local estimates using scalar weights has been proposed in (Shin et al., 2007, Sun & Deng, 2005, Lee & Shin 2007).

However, because of lack of prior information, in general, the distributed filtering using the fusion formula is globally suboptimal compared with optimal centralized filtering (Chang et al., 1997). Nevertheless, in this case it has advantages of lower computational requirements, efficient communication costs, parallel implementation, and fault-tolerance (Chang et al., 1997, Chang et al, 2002, Roecker & McGillem, 1998). Therefore, in spite of its limitations, the fusion formula has been widely used and is superior to the centralized filtering in real applications.

The aforementioned papers have not focused on prediction problem, but most of them have considered only distributed filtering in multisensory continuous and discrete dynamic models. Direct generalization of the distributed fusion filtering algorithms to the prediction problem is impossible. The distributed prediction requires special algorithms one of which for discrete-time systems was presented in (Song et al. 2009). In this paper, we generalize the results of (Song et al. 2009) on mixed continuous-discrete systems. The continuous-discrete

approach allows system to avoid discretization by propagating the estimate and error covariance between observations in continuous time using an integration routine such as Runge-Kutta. This approach yields the optimal or suboptimal estimate continuously at all times, including times between the data arrival instants. One advantage of the continuousdiscrete filter over the alternative approach using system discretization is that in the former, it is not necessary for the sample times to be equally spaced. This means that the cases of irregular and intermittent measurements are easy to handle. In the absense of data the optimal prediction is given by performing only the time update portion of the algorithm.

Thus, the primary aim of this paper is to propose two distributed fusion predictors using fusion formula with matrix weights, and analysis their statistical properties and relationship between them. Then, through a comparison with an optimal centralized predictor, performance of the novel predictors is evaluated.

This chapter is organized as follows. In Section 2, we present the statement of the continuous-discrete prediction problem in a multisensor environment and give its optimal solution. In Section 3, we propose two fusion predictors, derived by using the fusion formula and establish the equivalence between them. Unbiased property of the fusion predictors is also proved. The performance of the proposed predictors is studied on examples in Section 4. Finally, concluding remarks are presented in Section 5.

# 2. Statement of problem – centralized predictor

We consider a linear system described by the stochastic differential equation

$$\dot{\mathbf{x}}_t = \mathbf{F}_t \mathbf{x}_t + \mathbf{G}_t \mathbf{v}_t, \quad t \ge 0, \tag{1}$$

where  $\mathbf{x}_t \in \mathfrak{R}^n$  is the state,  $\mathbf{v}_t \in \mathfrak{R}^q$  is a zero-mean Gaussian white noise with covariance  $\mathbf{E}(\mathbf{v}_t \mathbf{v}_s^T) = \mathbf{Q}_t \delta(t-s)$ , and  $F_t \in \mathfrak{R}^{n \times n}$ ,  $G_t \in \mathfrak{R}^{n \times q}$ , and  $Q_t \in \mathfrak{R}^{q \times q}$ .

Suppose that overall discrete observations  $Y_{t_k} \in \Re^m$  at time instants  $t_1, t_2, ...$  are composed of *N* observation subvectors (local sensors)  $y_{t_k}^{(1)}, ..., y_{t_k}^{(N)}$ , i.e.,

$$Y_{t_{k}} = [y_{t_{k}}^{(1)^{T}} \dots y_{t_{k}}^{(N)^{T}}]^{T}, \qquad (2)$$
  
where  $y_{t_{k}}^{(i)}$ ,  $i=1,\dots,N$  are determined by the equations  
 $y_{t_{k}}^{(1)} = H_{t_{k}}^{(1)} x_{t_{k}} + w_{t_{k}}^{(1)}, y_{t_{k}}^{(1)} \in \Re^{m_{1}},$   
 $\vdots$   
 $y_{t_{k}}^{(N)} = H_{t_{k}}^{(N)} x_{t_{k}} + w_{t_{k}}^{(N)}, y_{t_{k}}^{(N)} \in \Re^{m_{N}},$   
 $k=1,2,\dots; t_{k+1} > t_{k} \ge t_{0} = 0; m=m_{1} + \dots + m_{N},$ 

where  $y_{t_k}^{(i)} \in \Re^{m_i}$  is the local sensor observation,  $H_{t_k}^{(i)} \in \Re^{n \times m_i}$ , and  $\left\{w_{t_k}^{(i)} \in \Re^{m_i}, k = 1, 2, ...\right\}$  are zero-mean white Gaussian sequences,  $w_{t_k}^{(i)} \sim \mathbb{N}(0, R_{t_k}^{(i)})$ , i=1,...,N. The distribution of the initial state  $x_0$  is Gaussian,  $x_0 \sim \mathbb{N}(\bar{x}_0, P_0)$ , and  $x_0$ ,  $v_t$ , and  $\left\{w_{t_k}^{(i)}\right\}$ , i=1,...,N are assumed mutually uncorrelated.

A problem associated with such systems is to find the distributed weighted fusion predictor  $\hat{x}_{t+\Delta}$ ,  $\Delta \ge 0$  of the state  $x_{t+\Delta}$  based on overall current sensor observations

$$Y_{t_1}^{t_k} = \{Y_{t_1}, ..., Y_{t_k}\}, \quad t_1 < ... < t_k \le t \le t + \Delta, \quad \Delta \ge 0.$$
(4)

### 2.1 The optimal centralized predictor

The optimal centralized predictor is constructed by analogy with the continuous-discrete Kalman filter (Lewis, 1986, Gelb, 1974). In this case the prediction estimate  $\hat{x}_{t+\Delta}^{opt}$  and its error covariance  $P_{t+\Delta}^{opt}$  are determined by the combining of *time update and observation update*,

$$\dot{\hat{x}}_{s}^{opt} = F_{s}\hat{x}_{s}^{opt}, \quad t_{k} \leq s \leq t+\Delta, \quad \hat{x}_{s=t_{k}}^{opt} = \hat{x}_{t_{k}}^{opt},$$

$$\dot{P}_{s}^{opt} = F_{s}P_{s}^{opt} + P_{s}^{opt}F_{s}^{T} + \tilde{Q}_{s}, \quad P_{s=t_{k}}^{opt} = P_{t_{k}}^{opt},$$
(5)

where the initial conditions represent filtering estimate of the state  $\hat{x}_{t_k}^{opt}$  and its error covariance  $P_{t_k}^{opt}$  which are given by the continuous-discrete Kalman filter equations (Lewis, 1986, Gelb, 1974):

Time update between observations:

$$\begin{cases} \dot{x}_{\tau}^{opt^{-}} = F_{\tau} \hat{x}_{\tau}^{opt^{-}}, \quad t_{k-1} \leq \tau \leq t_{k}, \quad \hat{x}_{\tau=t_{k-1}}^{opt^{-}} = \hat{x}_{t_{k-1}}^{opt}, \\ \dot{P}_{\tau}^{opt^{-}} = F_{\tau} P_{\tau}^{opt^{-}} + P_{\tau}^{opt^{-}} F_{\tau}^{T} + \tilde{Q}_{\tau}, \quad P_{\tau=t_{k-1}}^{opt^{-}} = P_{t_{k-1}}^{opt}, \end{cases}$$
(6a)

Observation update at time  $t_k$ :

$$\hat{x}_{t_{k}}^{opt} = \hat{x}_{t_{k}}^{opt^{-}} + L_{t_{k}}^{opt} \left( Y_{t_{k}} - H_{t_{k}} \hat{x}_{t_{k}}^{opt^{-}} \right),$$

$$L_{t_{k}}^{opt} = P_{t_{k}}^{opt^{-}} H_{t_{k}}^{T} \left( H_{t_{k}} P_{t_{k}}^{opt^{-}} H_{t_{k}}^{T} + R_{t_{k}} \right)^{-1},$$

$$P_{t_{k}}^{opt} = \left( I_{n} - L_{t_{k}}^{opt} H_{t_{k}} \right) P_{t_{k}}^{opt^{-}}.$$

$$(6b)$$

Here  $I_n$  is the  $n \times n$  identity matrix,  $\tilde{Q}_t = G_t Q_t G_t^T$ ,  $Y_{t_k}^T = \begin{bmatrix} y_{t_k}^{(1)^T} & \dots & y_{t_k}^{(N)^T} \end{bmatrix}$ ,  $H_{t_k}^T = \begin{bmatrix} H_{t_k}^{(1)^T} & \dots & H_{t_k}^{(N)^T} \end{bmatrix}$ ,  $R_{t_k} = \text{diag} \begin{bmatrix} R_{t_k}^{(1)} & \dots & R_{t_k}^{(N)} \end{bmatrix}$ , and the matrices  $F_t$ ,  $G_t$ ,  $Q_t$  and  $R_{t_k}^{(i)}$ are defined in (1)-(3). Note that in the absence of observation  $Y_{t_k}$ , the centralized predictor includes two *time update* equations (5) and (6a), and in case of presence at time  $t=t_k$  the initial conditions  $\hat{x}_{t_k}^{opt}$  and  $P_{t_k}^{opt}$  for (5) computed by the *observation update* equations (6b).

Many advanced systems now make use of a large number of sensors in practical applications ranging from aerospace and defence, robotics automation systems, to the monitoring and control of process generation plants. Recent developments in integrated sensor network systems have further motivated the search for decentralized signal processing algorithms. An important practical problem in the above systems is to find a fusion estimate to combine the information from various local estimates to produce a global

(fusion) estimate. Moreover, there are several limitations for the centralized estimators in practical implementation, such as computational cost and capacity of data transmission. Also numerical errors of the centralized estimator design are drastically increased with dimension of the state  $x_t \in \Re^n$  and overall observations  $Y_{t_k} \in \Re^m$ . In these cases the centralized estimators may be impractical. In next Section, we propose two new fusion predictors for multisensor mixed continuous-discrete linear systems (1), (3).

# 3. Two distributed fusion predictors

The derivation of the fusion predictors is based on the assumption that the overall observation vector  $Y_{t_k}$  combines the local subvectors (individual sensors)  $y_{t_k}^{(1)}, ..., y_{t_k}^{(N)}$ , which can be processed separately. According to (1) and (3), we have N unconnected dynamic subsystems (i = 1,...,N) with the common state  $x_t$  and local sensor  $y_{t_k}^{(i)}$ :

$$\begin{aligned} \dot{\mathbf{x}}_{t} &= F_{t} \mathbf{x}_{t} + G_{t} \mathbf{v}_{t}, \quad t \geq t_{0}, \\ \mathbf{y}_{t_{k}}^{(i)} &= H_{t_{k}}^{(i)} \mathbf{x}_{t_{k}} + \mathbf{w}_{t_{k}}^{(i)}, \\ \mathbf{k} &= 1, 2, \dots; \quad t_{k+1} > t_{k} \geq t_{0} = 0, \end{aligned}$$
(7)

where *i* is the index of subsystem. Then by the analogy with the centralized prediction equations (5), (6) the optimal local predictor  $\hat{x}_{t+\Delta}^{(i)}$  based on the overall local observations  $\{y_{t_1}^{(i)}, \dots, y_{t_k}^{(i)}\}, t_k \le t \le t + \Delta$  satisfies the following *time update and observation update* equations:

$$\begin{cases} \dot{\hat{x}}_{s}^{(i)} = F_{s} \hat{x}_{s}^{(i)}, \quad t_{k} \leq s \leq t + \Delta, \quad \hat{x}_{s=t_{k}}^{(i)} = \hat{x}_{t_{k}}^{(i)}, \\ \dot{P}_{s}^{(ii)} = F_{s} P_{s}^{(ii)} + P_{s}^{(ii)} F_{s}^{T} + \tilde{Q}_{s}, \quad P_{s=t_{k}}^{(ii)} = P_{t_{k}}^{(ii)}, \end{cases}$$
(8)

where the initial conditions  $\hat{x}_{t_k}^{(i)}$  and its error covariance  $P_{t_k}^{(ii)}$  are given by the continuous-discrete Kalman filter equations

$$\begin{array}{l} \text{Time update between observations:} \\ \left\{ \begin{array}{l} \dot{\hat{x}}_{\tau}^{(i)^{-}} = F_{\tau} \hat{x}_{\tau}^{(i)^{-}}, \ t_{k-1} \leq \tau \leq t_{k}, \ \hat{x}_{\tau=t_{k-1}}^{(i)^{-}} = \hat{x}_{t_{k-1}}^{(i)}, \\ \dot{P}_{\tau}^{(ii)^{-}} = F_{\tau} P_{\tau}^{(ii)^{-}} + P_{\tau}^{(ii)^{-}} F_{\tau}^{T} + \tilde{Q}_{\tau}, \ P_{\tau=t_{k-1}}^{(ii)^{-}} = P_{t_{k-1}}^{(ii)}, \\ Observation update at time t_{k}: \\ \left\{ \begin{array}{l} \hat{x}_{t_{k}}^{(i)} = \hat{x}_{t_{k}}^{(i)^{-}} + L_{t_{k}}^{(i)} \left( y_{t_{k}}^{(i)} - H_{t_{k}}^{(i)} \hat{x}_{t_{k}}^{(i)^{-}} \right), \\ L_{t_{k}}^{(i)} = P_{t_{k}}^{(ii)^{-}} H_{t_{k}}^{(i)^{-}} \left( H_{t_{k}}^{(i)} P_{t_{k}}^{(ii)^{-}} + R_{t_{k}}^{(i)} \right)^{-1}, \\ P_{t_{k}}^{(ii)} = \left( I_{n} - L_{t_{k}}^{(i)} H_{t_{k}}^{(i)} \right) P_{t_{k}}^{(ii)^{-}}. \end{array} \right.$$

Thus from (8) we have N local filtering  $\hat{x}_t^{(i)} = \hat{x}_{s=t}^{(i)}$  and prediction  $\hat{x}_{t+\Delta}^{(i)} = \hat{x}_{s=t+\Delta}^{(i)}$  estimates, and corresponding error covariances  $P_t^{(ii)}$  and  $P_{t+\Delta}^{(ii)}$  for i=1,...,N and  $t \ge t_k$ . Using these values we propose two fusion prediction algorithms.

# 3.1 The fusion of local predictors (FLP Algorithm)

The fusion predictor  $\hat{x}_{t+\Delta}^{FLP}$  of the state  $x_{t+\Delta}$  based on the overall sensors (2), (3) is constructed from the local predictors  $\hat{x}_{t+\Delta}^{(i)}$ , i = 1,...,N by using the fusion formula (Zhou et al., 2006, Shin et al., 2006):

$$x_{t+\Delta}^{\text{FLP}} = \sum_{i=1}^{N} a_{t+\Delta}^{(i)} \hat{x}_{t+\Delta}^{(i)}, \qquad \sum_{i=1}^{N} a_{t+\Delta}^{(i)} = I_n,$$
(10)

where  $a_{t+\Delta}^{(1)},...,a_{t+\Delta}^{(N)}$  are  $n \times n$  time-varying matrix weights determined from the mean-square criterion,

$$J_{t+\Delta}^{\text{FLP}} = E\left[ \left\| \mathbf{x}_{t+\Delta} - \sum_{i=1}^{N} a_{t+\Delta}^{(i)} \mathbf{x}_{t+\Delta}^{(i)} \right\|^2 \right].$$
(11)

The Theorems 1 and 2 completely define the fusion predictor  $\hat{x}_{t+\Delta}^{FLP}$  and its overall error covariance  $P_{t+\Delta}^{FLP} = cov(\tilde{x}_{t+\Delta}^{FLP}, \tilde{x}_{t+\Delta}^{FLP}), \quad \tilde{x}_{t+\Delta}^{FLP} = x_{t+\Delta} - \hat{x}_{t+\Delta}^{FLP}$ .

**Theorem 1:** Let  $\hat{x}_{t+\Delta}^{(1)}, \dots, \hat{x}_{t+\Delta}^{(N)}$  are the local predictors of an unknown state  $x_{t+\Delta}$ . Then

a. The weights  $a_{t+\Delta}^{(1)}, \dots, a_{t+\Delta}^{(N)}$  satisfy the linear algebraic equations

$$\sum_{i=1}^{N} a_{t+\Delta}^{(i)} \left[ P_{t+\Delta}^{(ij)} - P_{t+\Delta}^{(iN)} \right] = 0, \quad \sum_{i=1}^{N} a_{t+\Delta}^{(i)} = I_n, \quad j = 1, \dots, N-1;$$
(12)

b. The local covariance  $P_{t+\Delta}^{(ii)} = \operatorname{cov}(\tilde{\mathbf{x}}_{t+\Delta}^{(i)}, \tilde{\mathbf{x}}_{t+\Delta}^{(i)})$ ,  $\tilde{\mathbf{x}}_{t+\Delta}^{(i)} = \mathbf{x}_{t+\Delta} - \hat{\mathbf{x}}_{t+\Delta}^{(i)}$  satisfies (8) and local crosscovariance  $P_{t+\Delta}^{(ij)} = \operatorname{cov}(\tilde{\mathbf{x}}_{t+\Delta}^{(i)}, \tilde{\mathbf{x}}_{t+\Delta}^{(j)})$ ,  $i \neq j$  describes the time update and observation update equations:

$$\begin{cases} \dot{P}_{\tau}^{(ij)^{-}} = F_{\tau} P_{\tau}^{(ij)^{-}} + P_{\tau}^{(ij)^{-}} F_{\tau}^{T} + \tilde{Q}_{\tau}, \quad P_{\tau=t_{k-1}}^{(ij)^{-}} = P_{t_{k-1}}^{(ij)}, \quad t_{k-1} \leq \tau \leq t_{k}, \\ P_{t_{k}}^{(ij)} = \left(I_{n} + L_{t_{k}}^{(i)} H_{t_{k}}^{(i)}\right) P_{t_{k}}^{(ij)^{-}} \left(I_{n} + L_{t_{k}}^{(j)} H_{t_{k}}^{(j)}\right)^{T}, \quad t=t_{k}, \\ \dot{P}_{s}^{(ij)} = F_{s} P_{s}^{(ij)} + P_{s}^{(ij)} F_{s}^{T} + \tilde{Q}_{s}, \quad P_{s=t_{k}}^{(ij)} = P_{t_{k}}^{(ij)}, \quad t_{k} \leq s \leq t+\Delta; \end{cases}$$
(13)

*c.* The fusion error covariance  $\mathbf{P}_{t+\Delta}^{FLP}$  is given by

$$P_{t+\Delta}^{FLP} = \sum_{i,j=1}^{N} a_{t+\Delta}^{(i)} P_{t+\Delta}^{(ij)} a_{t+\Delta}^{(j)^{T}}.$$
(14)

**Theorem 2:** The local predictors  $\hat{x}_{t+\Delta}^{(1)}, \dots, \hat{x}_{t+\Delta}^{(N)}$  and fusion predictor  $\hat{x}_{t+\Delta}^{FLP}$  are unbiased, i.e.,  $E(\hat{x}_{\tau}^{(i)}) = E(x_{\tau})$  and  $E(\hat{x}_{t+\Delta}^{FLP}) = E(x_{t+\Delta})$  for  $0 \le \tau \le t+\Delta$ .

The proofs of Theorems 1 and 2 are given in Appendix.

Thus the local predictors (8) and fusion equations (10)-(14) completely define the FLP algorithm. In particular case at N = 2, formulas (10)-(12) reduce to the Bar-Shalom and Campo formulas (Bar-Shalom & Campo, 1986):

$$\hat{\mathbf{x}}_{t+\Delta}^{\text{FLP}} = \mathbf{a}_{t+\Delta}^{(1)} \hat{\mathbf{x}}_{t+\Delta}^{(1)} + \mathbf{a}_{t+\Delta}^{(2)} \hat{\mathbf{x}}_{t+\Delta}^{(2)}, \\ \mathbf{a}_{t+\Delta}^{(1)} = \left[ \mathbf{P}_{t+\Delta}^{(22)} - \mathbf{P}_{t+\Delta}^{(21)} \right] \left[ \mathbf{P}_{t+\Delta}^{(11)} + \mathbf{P}_{t+\Delta}^{(22)} - \mathbf{P}_{t+\Delta}^{(12)} - \mathbf{P}_{t+\Delta}^{(21)} \right]^{-1},$$

$$\mathbf{a}_{t+\Delta}^{(2)} = \left[ \mathbf{P}_{t+\Delta}^{(11)} - \mathbf{P}_{t+\Delta}^{(12)} \right] \left[ \mathbf{P}_{t+\Delta}^{(11)} + \mathbf{P}_{t+\Delta}^{(22)} - \mathbf{P}_{t+\Delta}^{(12)} - \mathbf{P}_{t+\Delta}^{(21)} \right]^{-1}.$$
(15)

Further, in parallel with the FLP we offer the other algorithm for fusion prediction.

# 3.2 The prediction of fusion filter (PFF Algorithm)

This algorithm consists of two parts. The first part fuses the local filtering estimates  $\hat{x}_{t_{k}}^{(1)}, \dots, \hat{x}_{t_{k}}^{(N)}$ . Using the fusion formula, we obtain the fusion filtering (FF) estimate

$$\hat{x}_{t_{k}}^{FF} = \sum_{i=1}^{N} b_{t_{k}}^{(i)} \hat{x}_{t_{k}}^{(i)}, \quad \sum_{i=1}^{N} b_{t_{k}}^{(i)} = I_{n},$$
(16)

where the weights  $b_{t_k}^{(1)}, \dots, b_{t_k}^{(N)}$  do not depend on lead  $\Delta$ . In the second part we predict the fusion filtering estimate  $\hat{x}_{t_k}^{FF}$  using the *time update* prediction equations. Then the fusion predictor  $\hat{x}_{t+\Delta}^{PFF}$  and its error covariance  $P_{t+\Delta}^{PFF} = cov(\tilde{x}_{t+\Delta}^{PFF}, \tilde{x}_{t+\Delta}^{PFF}), \quad \tilde{x}_{t+\Delta}^{PFF} = x_{t+\Delta} - \hat{x}_{t+\Delta}^{PFF}$  satisfy the following equations:

Next Theorem completely defines the PFF algorithm.

**Theorem 3:** Let  $\hat{x}_{t_k}^{(1)}, \dots, \hat{x}_{t_k}^{(N)}$  are the local filtering estimates of an unknown state  $x_t$ . Then

*a.* The weights  $b_{t_k}^{(1)}, \dots, b_{t_k}^{(N)}$  satisfy the linear algebraic equations

$$\sum_{i=1}^{N} b_{t_{k}}^{(i)} \left[ P_{t_{k}}^{(ij)} - P_{t_{k}}^{(iN)} \right] = 0, \quad \sum_{i=1}^{N} b_{t_{k}}^{(i)} = I_{n}, \quad j = 1, \dots, N-1;$$
(18)

- *b.* The local covariance  $P_{t_k}^{(ii)}$  and cross-covariance  $P_{t_k}^{(ij)}$  in (18) are determined by equations (9) and (13), respectively;
- c. The initial conditions  $\hat{\mathbf{x}}_{t_k}^{FF}$  and  $\mathbf{P}_{t_k}^{FF}$  in (17) are determined by (16) and formula  $\mathbf{P}_{t_k}^{FF} = \sum_{k=1}^{N} \mathbf{b}_{k}^{(i)} \mathbf{P}_{k}^{(ij)} \mathbf{b}_{k}^{(j)^{T}}.$ (19)

$$P_{t_{k}}^{FF} = \sum_{i,j=1}^{N} b_{t_{k}}^{(i)} P_{t_{k}}^{(ij)} b_{t_{k}}^{(j)^{T}}, \qquad (19)$$

respectively;

*d.* The fusion predictor  $\hat{x}_{t+\Delta}^{PFF}$  in (17) is unbiased, i.e.,  $E(\hat{x}_{t+\Delta}^{PFF})=E(x_{t+\Delta})$ . The proof of Theorem 3 is given in Appendix.

# 3.3 The relationship between FLP and PFF

Here we establish the relationship between the prediction fusion estimates  $\hat{x}_{t+\Delta}^{FLP}$  and  $\hat{x}_{t+\Delta}^{PFF}$  determined by (10) and (16), respectively.

**Theorem 4:** Let  $\hat{x}_{t+\Delta}^{FLP}$  and  $\hat{x}_{t+\Delta}^{PFF}$  be the fusion prediction estimates determined by (10) and (16), respectively, and the local error covariances  $P_s^{(ij)}$ ,  $t_k \le s \le t+\Delta$ , i,j = 1,...,N are nonsingular. Then

$$\hat{\mathbf{x}}_{t+\Delta}^{\text{FLP}} = \hat{\mathbf{x}}_{t+\Delta}^{\text{PFF}} \quad \text{for} \quad \Delta > 0.$$
(20)

The proof of Theorem 4 is given in Appendix.

*Remark* **1** (*Uniqueness solution*): When the local prediction covariances  $P_{t+\Delta}^{(ij)}$ , i, j = 1, ..., N are nonsingular, the quadratic optimization problem (11) has a unique solution, and the wights  $a_{t+\Delta}^{(1)}, ..., a_{t+\Delta}^{(N)}$  are defined by the expressions (11). The same result is true for the covariance  $P_{t_k}^{(ij)}$  and the weights  $b_{t_k}^{(1)}, ..., b_{t_k}^{(N)}$  (Zhu et al., 1999, Zhu, 2002). *Remark* **2** (*Computational complexity*): According to Theorem 4, both the predictors FLP and

*Remark* 2 (*Computational complexity*): According to Theorem 4, both the predictors FLP and PFF are equivalent; however, from a computational point of view they are different. To predict the state  $x_{t+\Delta}$  using FLP we need to compute the matrix weights  $a_{t+\Delta}^{(1)}, \ldots, a_{t+\Delta}^{(N)}$  for each lead  $\Delta > 0$ . This contrasts with PFF, wherein the weights  $b_{t_k}^{(1)}, \ldots, b_{t_k}^{(N)}$  are computed only once, since they do not depend on the leads  $\Delta$ . Therefore, FLP is deemed more complex than PFF, especially for large leads.

*Remark* 3 (*Real-time implementation*): We may note that the local filter gains  $L_t^{(i)}$ , the error cross-covariances  $P_t^{(ij)}$ ,  $P_{t+\Delta}^{(ij)}$ , and the weights  $a_{t+\Delta}^{(i)}$ ,  $b_{t_k}^{(i)}$  may be pre-computed, since they do not depend on the current observations  $y_{t_k}^{(i)}$ , i = 1, ..., N, but only on the noises statistics  $Q_t$  and  $R_t^{(i)}$ , and system matrices  $F_t$ ,  $G_t$ ,  $H_t^{(i)}$ , which are part of the system model (1), (3). Thus, once the observation schedule has been settled, the real-time implementation of the fusion predictors FLP and PFF requires only the computation of the local estimates  $\hat{x}_t^{(i)}$ ,  $\hat{x}_{t+\Delta}^{(i)}$ , i = 1, ..., N and final fusion predictors  $\hat{x}_{t+\Delta}^{FLP}$  and  $\hat{x}_{t+\Delta}^{PFF}$ .

*Remark* **4** (*Parallel implementation*): The local estimates  $\hat{x}_{t}^{(i)}$ ,  $\hat{x}_{t+\Delta}^{(i)}$ , i = 1,...,N are separated for different sensors. Therefore, they can be implemented in parallel for various types of observations  $y_t^{(i)}$ , i = 1,...,N.

# 4. Examples

#### 4.1 The damper harmonic oscillator motion

System model of the harmonic oscillator is considered in (Lewis, 1986). We have

$$\dot{\mathbf{x}}_{t} = \begin{bmatrix} 0 & 1 \\ -\omega_{n}^{2} & -2\alpha \end{bmatrix} \mathbf{x}_{t} + \begin{bmatrix} 0 \\ 1 \end{bmatrix} \mathbf{v}_{t}, \ 0 \le t \le t^{*},$$
(21)

where  $x_t = [x_{1,t} x_{2,t}]^T$ , and  $x_{1,t}$  is position,  $x_{2,t}$  is velocity, and  $v_t$  is zero-mean white Gaussian noise with intensity q,  $E(v_t v_s) = q\delta_{t-s}$ ,  $x_0 \sim \mathbb{N}(\overline{x}_0, P_0)$ . Assume that the observation system contains N sensors which are observing the position  $x_{1,t}$ . Then we have

$$y_{t_{k}}^{(1)} = H_{t_{k}}^{(1)} x_{t_{k}} + w_{t_{k}}^{(1)},$$

$$\vdots$$

$$y_{t_{k}}^{(N)} = H_{t_{k}}^{(N)} x_{t_{k}} + w_{t_{k}}^{(N)}, \quad 0 = t_{0} < t_{1} < t_{2} < \dots < t^{*},$$
(22)

where  $H_{t_k}^{(j)} = \begin{bmatrix} 1 & 0 \end{bmatrix}$ , and  $w_{t_k}^{(j)}$ , j = 1, ..., N are uncorrelated zero-mean white Gaussian noises with constant variances  $r^{(j)}$ , respectively.

For model (21), (22), three predictors are applied: centralized predictor (CP) in (5), (6), FLP in (10) and PFF in (16), (17). The performance comparison of the fusion predictors for N = 2,3 was expressed in the terms of computation load (CPU time  $T_{CPU}$ ) and MSEs,  $P_{i,t+\Delta} = E(x_{i,t+\Delta} - \hat{x}_{i,t+\Delta})^2$ , where  $\hat{x}_{i,t+\Delta} = \hat{x}_{i,t+\Delta}^{CP}$ , or  $\hat{x}_{i,t+\Delta}^{PFF}$ , i=1, 2. The model parameters, noise statistics, initial conditions, and lead are taken to

$$\omega_{n}^{2}=3, \ \alpha=2.5, \ t^{*}=3, \ q=5, \ r^{(1)}=3.0, \ r^{(2)}=2.0, \ r^{(3)}=1.0,$$

$$\overline{x}_{0}=\begin{bmatrix}10.0 & 0.0\end{bmatrix}^{T}, \ P_{0}=diag\begin{bmatrix}0.5 & 0.5\end{bmatrix},$$

$$\Delta=0.1\sim0.5 \ (sec), \ t_{k}-t_{k-1}=0.1.$$
(23)

Figs. 1 and 2 illustrate the MSEs for position  $(x_1)$ ,  $P_{1,t+\Delta}^{CP}$ ,  $P_{1,t+\Delta}^{FLP}$ ,  $P_{1,t+\Delta}^{PFF}$ , and analogously for velocity  $(x_2)$ ,  $P_{2,t+\Delta}^{CP}$ ,  $P_{2,t+\Delta}^{FLP}$ ,  $P_{2,t+\Delta}^{PFF}$ ,  $P_{1,t+\Delta}^{PFF}$ ,  $P_{1,t+\Delta}^{PFF$ 



Fig. 1. Position MSE comparison of three predictors at N = 2,3 and lead  $\Delta$  =0.2.



Fig. 2. Velocity MSE comparison of three predictors at N = 2,3 and lead  $\Delta$  =0.2.

Number of sensors	Lead $\Delta$ (sec)	CPU time (sec)		
		$T_{CPU}^{CP}$	$T_{CPU}^{FLP}$	$T_{CPU}^{PFF}$
N = 2	0.1	0.172	0.826	0.185
	0.2	0.298	1.475	0.310
	0.3	0.384	1.863	0.405
	0.4	0.500	2.552	0.550
	0.5	0.656	3.137	0.691
N = 3	0.1	0.187	1.024	0.200
	0.2	0.305	1.743	0.340
	0.3	0.452	2.454	0.471
	0.4	0.602	3.306	0.621
	0.5	0.754	4.203	0.776

Table 1. Comparison of CPU time at N = 2,3 and  $\Delta = 0.1 \sim 0.5$ 

### 4.2 The water tank mixing system

Consider the water tank system which accepts two types of different temperature of the water and throw off the mixed water simultaneously (Jannerup & Hendricks, 2006). This system is described by

$$\dot{x}_t = \begin{bmatrix} -0.0139 & 0 & 0\\ 0 & -0.0277 & 0\\ 0 & 0.1667 & -0.1667 \end{bmatrix} x_t + \begin{bmatrix} 1\\ 1\\ 1\\ 1 \end{bmatrix} v_t, \ t \ge 0,$$
(24)

where  $x_t = [x_{1,t} x_{2,t} x_{3,t}]^T$  and  $x_{1,t}$  is water level,  $x_{2,t}$  is water temperature,  $x_{3,t}$  is sensor temperature, and  $v_t$  is a white Gaussian noise with intensity q,  $E(v_t v_s) = q \delta_{t-s}$ ,  $x_0 \sim \mathbb{N}(\overline{x}_0, P_0)$ . The measurement model contains two sensors (N = 2) which sense water level. Then we have

$$y_{t_k}^{(i)} = \begin{bmatrix} 1 & 0 & 0 \end{bmatrix} x_{t_k} + w_{t_k}^{(i)}, \ 0 = t_0 < t_1 < t_2 < \dots < t^*, \ i = 1, 2,$$
(25)

where  $w_{t_k}^{(1)}$  and  $w_{t_{k-1}}^{(2)}$  are uncorrelated white Gaussian sequences with zero-mean and constant intensities  $r^{(1)}$  and  $r^{(2)}$ , respectively.



Fig. 3. CP, FLP and PFF MSEs for water level at lead  $\Delta$  = 0.2s



Fig. 4. Computational time of water tank mixing system using 3 predictors at leads  $\Delta = 0.05, 0.1, \dots, 0.5$ s.

The parameters are subjected to q = 1,  $r^{(1)} = 2$ ,  $r^{(2)} = 1$ ,  $t^* = 3$ ,  $\overline{x}_0 = \begin{bmatrix} 1 & 1 & 0 \end{bmatrix}^T$ ,  $P_0 = diag \begin{bmatrix} 0.7 & 0.7 & 0.1 \end{bmatrix}$ ,  $t_k - t_{k-1} = 0.1$ ,  $\Delta = 0.05 \sim 0.5$ . Fig. 3 illustrates the MSEs of the water level  $P_{1,t+\Delta}^{CP}$ ,  $P_{1,t+\Delta}^{FLP}$  and  $P_{1,t+\Delta}^{PFF}$  at lead  $\Delta = 0.2$ . As we can see in Fig. 3 the CP is better than the fusion predictors and the fusion MSEs for water level  $(x_1)$  of FLP and PFF are equal, i.e.,  $P_{1,t+\Delta}^{CP} < P_{1,t+\Delta}^{FLP} = P_{1,t+\Delta}^{PFF}$ . The CPU times for CP, FLP and PFF are represented in Fig. 4, where it is shown that FLP requires considerably more CPU time than PFF, but CPU time of PFF is similar to CP.

Thus, from Examples 4.1 and 4.2 we can confirm that PFF is preferable to FLP in terms of computation efficiency.

# 5. Conclusions

In this chapter, two fusion predictors (FLP and PFF) for mixed continuous-discrete linear systems in a multisensor environment are proposed. Both of these predictors are derived by using the optimal local Kalman estimators (filters and predictors) and fusion formula. The fusion predictors represent the optimal linear combination of an arbitrary number of local Kalman estimators and each is fused by the MSE criterion. Equivalence between the two fusion predictors is established. However, the PFF algorithm is found to more significantly reduce the computational complexity, due to the fact that the PFF's weights  $b_{t_k}^{(i)}$  do not depend on the leads  $\Delta > 0$  in contrast to the FLP's weights  $a_{t+\Delta}^{(i)}$ .

# Appendix

#### **Proof of Theorem 1**

(*a*), (*c*) Equation (12) and formula (14) immediately follow as a result of application of the general fusion formula [20] to the optimization problem (10), (11).

(b) In the absence of observations differential equation for the local prediction error  $\tilde{x}_{\tau}^{(i)} = x_{\tau} - \hat{x}_{\tau}^{(i)}$  takes the form

$$\dot{\tilde{x}}_{\tau}^{(i)} = \dot{x}_{\tau} - \dot{\tilde{x}}_{\tau}^{(i)} = F_{\tau} \tilde{x}_{\tau}^{(i)} + G_{\tau} v_{\tau}.$$
(A.1)

Then the prediction cross-covariance  $P_{\tau}^{(ij)} = E\left(\tilde{x}_{\tau}^{(i)}\tilde{x}_{\tau}^{(j)^{T}}\right)$  associated with the  $\tilde{x}_{\tau}^{(i)}$  and  $\tilde{x}_{\tau}^{(j)}$  satisfies the time update Lyapunov equation (see the first and third equations in (13)). At  $t=t_{k}$  the local error  $\tilde{x}_{t_{k}}^{(i)}$  can be written as

 $\tilde{\mathbf{x}}_{t_{k}}^{(i)} = \mathbf{x}_{t_{k}} - \hat{\mathbf{x}}_{t_{k}}^{(i)} = \mathbf{x}_{t_{k}} - \hat{\mathbf{x}}_{t_{k}}^{(i)^{-}} - \mathbf{L}_{t_{k}}^{(i)} \left[ \mathbf{y}_{t_{k}}^{(i)} - \mathbf{H}_{t_{k}}^{(i)} \hat{\mathbf{x}}_{t_{k}}^{(i)^{-}} - \mathbf{L}_{t_{k}}^{(i)} \left[ \mathbf{H}_{t_{k}}^{(i)} \mathbf{x}_{t_{k}}^{(i)} - \mathbf{H}_{t_{k}}^{(i)} \hat{\mathbf{x}}_{t_{k}}^{(i)^{-}} \right] = \left( \mathbf{I}_{n} - \mathbf{L}_{t_{k}}^{(i)} \mathbf{H}_{t_{k}}^{(i)} \right) \tilde{\mathbf{x}}_{t_{k}}^{(i)^{-}} - \mathbf{L}_{t_{k}}^{(i)} \mathbf{W}_{t_{k}}^{(i)}$  (A.2) Given that random vectors  $\tilde{\mathbf{x}}_{t_{k}}^{(i)}$ ,  $\mathbf{W}_{t_{k}}^{(i)}$  and  $\mathbf{W}_{t_{k}}^{(j)}$  are mutually uncorrelated at  $i \neq j$ , we obtain

observation update equation (13) for  $P_{t_k}^{(ij)} = E\left(\tilde{\mathbf{x}}_{t_k}^{(i)} \tilde{\mathbf{x}}_{t_k}^{(j)^T}\right)$ .

# This completes the proof of Theorem 1.

#### **Proof of Theorem 2**

It is well known that the local Kalman filtering estimates  $\hat{x}_{\tau}^{(i)}$  are unbiased, i.e.,  $E(\hat{x}_{\tau}^{(i)})=E(x_{\tau})$  or  $E(\tilde{x}_{\tau}^{(i)})=E(x_{\tau}-\hat{x}_{\tau}^{(i)})=0$  at  $0 \le \tau \le t_k$ . With this result we can prove unbiased property at  $t_k < \tau \le t+\Delta$ . Using (8) we obtain

$$\dot{\tilde{x}}_{\tau}^{(i)} = \dot{x}_{\tau} - \dot{\tilde{x}}_{\tau}^{(i)} = F_{\tau} \tilde{x}_{\tau}^{(i)} + G_{\tau} v_{\tau}, \quad \tilde{x}_{\tau=t_{k}}^{(i)} = \tilde{x}_{t_{k}}^{(i)}, \quad t_{k} \le \tau \le t + \Delta,$$
(A.3)

or

$$\frac{\mathrm{d}}{\mathrm{d}\tau} \mathrm{E}\left(\tilde{\mathbf{x}}_{\tau}^{(i)}\right) = F_{\tau} \mathrm{E}\left(\tilde{\mathbf{x}}_{\tau}^{(i)}\right), \quad \mathrm{E}\left(\tilde{\mathbf{x}}_{\tau=t_{k}}^{(i)}\right) = \mathrm{E}\left(\tilde{\mathbf{x}}_{t_{k}}^{(i)}\right) = 0, \quad t_{k} \leq \tau \leq t + \Delta.$$
(A.4)

Differential equation (A.4) is homogeneous with zero initial condition therefore it has zero solution  $E(\tilde{x}_{\tau}^{(i)}) \equiv 0$  or  $E(\hat{x}_{\tau}^{(i)}) = E(x_{\tau})$ ,  $t_k \leq \tau \leq t + \Delta$ .

Since the local predictors  $\, \hat{x}_{t+\Delta}^{(i)}\,, \ i=1,...,N\,$  are unbiased, then we have

$$E\left(\hat{\mathbf{x}}_{t+\Delta}^{\text{FLP}}\right) = \sum_{i=1}^{N} a_{t+\Delta}^{(i)} E\left(\hat{\mathbf{x}}_{t+\Delta}^{(i)}\right) = \left[\sum_{i=1}^{N} a_{t+\Delta}^{(i)}\right] E\left(\mathbf{x}_{t+\Delta}\right) = E\left(\mathbf{x}_{t+\Delta}\right). \tag{A.5}$$

This completes the proof of Theorem 2.

#### **Proof of Theorem 3**

*a., c.* Equations (18) and (19) immediately follow from the general fusion formula for the filtering problem (Shin et al., 2006)

*b*. Derivation of observation update equation (13) is given in Theorem 1.

*d*. Unbiased property of the fusion estimate  $\hat{x}_{t+\Delta}^{PFF}$  is proved by using the same method as in Theorem 2.

This completes the proof of Theorem 3.

#### **Proof of Theorem 4**

By integrating (8) and (17), we get

$$\hat{x}_{t+\Delta}^{(i)} = \Phi(t+\Delta, t_k) \hat{x}_{t_k}^{(i)}, \quad i = 1, ..., N, \quad \hat{x}_{t+\Delta}^{PFF} = \Phi(t+\Delta, t_k) \hat{x}_{t_k}^{FF},$$
(A.6)

where  $\Phi(t,s)$  is the transition matrix of (8) or (17). From (10) and (16), we obtain

$$\hat{x}_{t+\Delta}^{\text{FLP}} = \sum_{i=1}^{N} a_{t+\Delta}^{(i)} \hat{x}_{t+\Delta}^{(i)} = \sum_{i=1}^{N} a_{t+\Delta}^{(i)} \Phi(t+\Delta,t_k) \hat{x}_{t_k}^{(i)} = \sum_{i=1}^{N} A_{t,t_k,\Delta}^{(i)} \hat{x}_{t_k}^{(i)},$$

$$\hat{x}_{t+\Delta}^{\text{PFF}} = \Phi(t+\Delta,t_k) \hat{x}_{t_k}^{\text{FF}} = \sum_{i=1}^{N} \Phi(t+\Delta,t_k) b_{t_k}^{(i)} \hat{x}_{t_k}^{(i)} = \sum_{i=1}^{N} B_{t,t_k,\Delta}^{(i)} \hat{x}_{t_k}^{(i)},$$
(A.7)

where the new weights take the form:

$$A_{t,t_k,\Delta}^{(i)} = a_{t+\Delta}^{(i)} \Phi(t+\Delta,t_k), \quad B_{t,t_k,\Delta}^{(i)} = \Phi(t+\Delta,t_k) b_{t_k}^{(i)}.$$
(A.8)

Next using (12) and (18) we will derive equations for the new weights (A.8). Multiplying the first (N-1) homogeneous equations (18) on the left hand side and right hand side by the nonsingular matrices  $\Phi(t+\Delta,t_k)$  and  $\Phi(t+\Delta,t_k)^T$ , respectively, and multiplying the last non-homogeneous equation (18) by  $\Phi(t+\Delta,t_k)$  we obtain

$$\sum_{i=1}^{N} \Phi(t+\Delta,t_{k}) b_{t_{k}}^{(i)} \left[ P_{t_{k}}^{(ij)} - P_{t_{k}}^{(iN)} \right] \Phi(t+\Delta,t_{k})^{T} = 0, \ j=1,...,N-1;$$

$$\sum_{i=1}^{N} \Phi(t+\Delta,t_{k}) b_{t_{k}}^{(i)} = \Phi(t+\Delta,t_{k}).$$
(A.9)

Using notation for the difference  $\delta P_s^{(ijN)} = P_s^{(ij)} - P_s^{(iN)}$  we obtain equations for  $B_{t,t_k,\Delta}^{(i)}$ , i = 1,...,N such that

$$\sum_{i=1}^{N} B_{t,t_{k},\Delta}^{(i)} \delta P_{t_{k}}^{(ijN)} \Phi(t+\Delta,t_{k})^{T} = 0, \ j=1,...,N-1; \ \sum_{i=1}^{N} B_{t,t_{k},\Delta}^{(i)} = \Phi(t+\Delta,t_{k}).$$
(A.10)

Analogously after simple manipulations equation (12) takes the form

$$\sum_{i=1}^{N} a_{t+\Delta}^{(i)} \Phi(t+\Delta,t_{k}) \Phi(t+\Delta,t_{k})^{-1} \Big[ P_{t+\Delta}^{(ij)} - P_{t+\Delta}^{(iN)} \Big] = \sum_{i=1}^{N} A_{t,t_{k},\Delta}^{(i)} \Phi(t+\Delta,t_{k})^{-1} \delta P_{t+\Delta}^{(ijN)} = 0,$$

$$\sum_{i=1}^{N} a_{t+\Delta}^{(i)} \Phi(t+\Delta,t_{k}) = \sum_{i=1}^{N} A_{t,t_{k},\Delta}^{(i)} = \Phi(t+\Delta,t_{k}).$$
(A.11)

$$\sum_{i=1}^{N} A_{t,t_{k},\Delta}^{(i)} \Phi(t+\Delta,t_{k})^{-1} \delta P_{t+\Delta}^{(ijN)} = 0, \quad j = 1,...,N-1; \quad \sum_{i=1}^{N} A_{t,t_{k},\Delta}^{(i)} = \Phi(t+\Delta,t_{k}).$$
(A.12)

As we can see from (A.10) and (A.12) if the equality

$$\delta P_{t_k}^{(ijN)} \Phi(t+\Delta,t_k)^T = \Phi(t+\Delta,t_k)^{-1} \delta P_{t+\Delta}^{(ijN)}$$
(A.13)

will be hold then the new weights  $A_{t,t_k,\Delta}^{(i)}$  and  $B_{t,t_k,\Delta}^{(i)}$  satisfy the identical equations. To show that let consider differential equation for the difference  $\delta P_s^{(ijN)} = P_s^{(ij)} \cdot P_s^{(iN)}$ . Using (13) we obtain the Lyapunov homogeneous matrix differential equation

$$\delta \dot{P}_{s}^{(ijN)} = \dot{P}_{s}^{(ij)} - \dot{P}_{s}^{(iN)} = F_{s} \left( P_{s}^{(ij)} - P_{s}^{(iN)} \right) + \left( P_{s}^{(ij)} - P_{s}^{(iN)} \right) F_{s}^{T} = F_{s} \delta P_{s}^{(ijN)} + \delta P_{s}^{(ijN)} F_{s}^{T}, \quad t_{k} \le s \le t + \Delta, \quad (A.14)$$

which has the solution

$$\delta P_{t+\Delta}^{(ijN)} = \Phi(t+\Delta, t_k) \delta P_{t_k}^{(ijN)} \Phi(t+\Delta, t_k)^{\mathrm{T}}.$$
(A.15)

By the nonsingular property of the transition matrix  $\Phi(t+\Delta,t_k)$  the equality (A.13) holds, then  $A_{t,t_k,\Delta}^{(i)} = B_{t,t_k,\Delta}^{(i)}$ , and finally using (A.7) we get

$$\hat{\mathbf{x}}_{t+\Delta}^{FLP} = \sum_{i=1}^{N} \mathbf{A}_{t,t_{k},\Delta}^{(i)} \hat{\mathbf{x}}_{t_{k}}^{(i)} = \sum_{i=1}^{N} \mathbf{B}_{t,t_{k},\Delta}^{(i)} \hat{\mathbf{x}}_{t_{k}}^{(i)} = \hat{\mathbf{x}}_{t+\Delta}^{PFF}.$$
(A.16)

#### This completes the proof of Theorem 4.

#### 6. References

- Alouani, A. T. & Gray, J. E. (2005). Theory of distributed estimation using multiple asynchronous sensors, *IEEE Transations on Aerospace and Electronic Systems*, Vol. 41, No. 2, pp. 717-722.
- Bar-Shalom, Y. & Campo, L. (1986). The effect of the common process noise on the twosensor fused track covariance, *IEEE Transactions on Aerospace and Electronic Systems*, Vol. 22, No. 6, pp. 803–805.
- Bar-Shalom, Y. (1990). *Multitarget-multisensor tracking: advanced applications*, Artech House, Norwood, MA.
- Bar-Shalom, Y. & Li, X. R. (1995). Multitarget-multisensor tracking: principles and techniques, YBS Publishing.
- Bar-Shalom, Y. (2006). On hierarchical tracking for the real world, *IEEE Transactions on Aerospace and Electronic Systems*, Vol. 42, No, 3, pp. 846–850.
- Berg, T. M. & Durrant-Whyte, H. F. (1994). General decentralized Kalman filter, *Proceedings* of American Control Conference, pp. 2273-2274, Maryland.
- Chang, K. C.; Saha, R. K. & Bar-Shalom, Y. (1997). On Optimal track-to-track fusion, *IEEE Transactions on Aerospace and Electronic Systems*, Vol. 33, No. 4, pp. 1271–1275.

- Chang, K. C.; Tian, Z. & Saha, R. K. (2002). Performance evaluation of track fusion with information matrix filter, *IEEE Transactions on Aerospace and Electronic Systems*, Vol. 38, No. 2, pp. 455–466.
- Deng, Z. L.; Gao, Y.; Mao, L. & Hao, G. (2005). New approach to information fusion steadystate Kalman filtering, *Automatica*, Vol. 41, No, 10, pp. 1695-1707.
- Gelb, A. (1974). Applied Optimal Estimation, MIT Press, Cambridge, MA.
- Hall, D. L. (1992). Mathematical techniques in multisensor data Fusion, Artech House, London.
- Hashemipour, H. R.; Roy, S. & Laub, A. J. (1998). Decentralized structures for parallel Kalman filtering, *IEEE Transactions on Automatic Control*, Vol. 33, No. 1, pp. 88-94.
- Jannerup, O. E. & Hendricks, E. (2006). *Linear Control System Design*, Technical University of Denmark.
- Lee, S. H. & Shin, V. (2007). Fusion Filters Weighted by Scalars and Matrices for Linear Systems, *World Academy of Science, Engineering and Technology*, Vol. 34, pp. 88-93.
- Lewis, F. L. (1986). *Optimal Estimation with an Introduction to Stochastic Control Theory*, John Wiley & Sons, New York.
- Li, X. R.; Zhu, Y. M.; Wang, J. & Han, C. (2003). Optimal Linear Estimation Fusion Part I: Unified Fusion Rules, *IEEE Transations on Information Theory*, Vol. 49, No. 9, pp. 2192-2208.
- Ren, C. L. & Kay, M. G. (1989). Multisensor integration and fusion in intelligent systems, *IEEE Transactions on Systems, Man, and Cybernetics*, Vol. 19, No. 5, pp. 901-931.
- Roecker, J. A. & McGillem, C. D. (1998). Comparison of two-sensor tracking methods based on state vector fusion and measurement fusion, *IEEE Transactions on Aerospace and Electronic Systems*, Vol. 24, No. 4, pp. 447–449.
- Shin, V.; Lee, Y. & Choi, T. (2006). Generalized Millman's formula and its applications for estimation problems, *Signal Processing*, Vol. 86, No. 2, pp. 257–266.
- Shin, V.; Shevlyakov, G. & Kim, K. S. (2007). A new fusion formula and its application to continuous-time linear systems with multisensor environment, *Computational Statistics & Data Analysis*, Vol. 52, No. 2, pp. 840-854.
- Song, H. R.; Joen, M. G.; Choi, T. S. & Shin, V. (2009). Two Fusion Predictors for Discrete-Time Linear Systems with Different Types of Observations, *International Journal of Control, Automation, and Systems*, Vol. 7, No. 4, pp. 651-658.
- Sun, S. L. (2004). Multi-sensor optimal information fusion Kalman filters with applications, *Aerospace Science and Technology*, Vol. 8, No. 1, pp. 57–62.
- Sun, S. L. & Deng, Z. L. (2005). Multi-sensor information fusion Kalman filter weighted by scalars for systems with colored measurement noises, *Journal of Dynamic Systems*, *Measurement and Control*, Vol. 127, No. 4, pp. 663–667.
- Zhou, J.; Zhu, Y.; You, Z. & Song, E. (2006). An efficient algorithm for optimal linear estimation fusion in distributed multisensor systems, IEEE Transactions on System, Man, Cybernetics, Vol. 36, No. 5, pp.1000–1009.
- Zhu,Y. M. & Li, X. R. (1999). Best linear unbiased estimation fusion, Proceeding of International Conference on Multisource-Multisensor Information Fusion, Sunnyvale, CA, pp. 1054-1061.
- Zhu,Y. M.; You, Z.; Zhao, J.; Zhang, K. & Li, X. R. (2001) The optimality for the distributed Kalman filtering fusion with feedback, *Automaica*, Vol. 37, No. 9, pp.1489–1493.
- Zhu, Y. M. (2002) Multisensor decision and estimation fusion, Kluwer Academic, Boston.



Discrete Time Systems Edited by Dr. Mario Alberto JordÃin

ISBN 978-953-307-200-5 Hard cover, 526 pages Publisher InTech Published online 26, April, 2011 Published in print edition April, 2011

Discrete-Time Systems comprehend an important and broad research field. The consolidation of digital-based computational means in the present, pushes a technological tool into the field with a tremendous impact in areas like Control, Signal Processing, Communications, System Modelling and related Applications. This book attempts to give a scope in the wide area of Discrete-Time Systems. Their contents are grouped conveniently in sections according to significant areas, namely Filtering, Fixed and Adaptive Control Systems, Stability Problems and Miscellaneous Applications. We think that the contribution of the book enlarges the field of the Discrete-Time Systems with signification in the present state-of-the-art. Despite the vertiginous advance in the field, we also believe that the topics described here allow us also to look through some main tendencies in the next years in the research area.

# How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Ha-ryong Song, Moon-gu Jeon and Vladimir Shin (2011). Distributed Fusion Prediction for Mixed Continuous-Discrete Linear Systems, Discrete Time Systems, Dr. Mario Alberto JordÃin (Ed.), ISBN: 978-953-307-200-5, InTech, Available from: http://www.intechopen.com/books/discrete-time-systems/distributed-fusion-predictionfor-mixed-continuous-discrete-linear-systems



# InTech Europe

University Campus STeP Ri Slavka Krautzeka 83/A 51000 Rijeka, Croatia Phone: +385 (51) 770 447 Fax: +385 (51) 686 166 www.intechopen.com

# InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai No.65, Yan An Road (West), Shanghai, 200040, China 中国上海市延安西路65号上海国际贵都大饭店办公楼405单元 Phone: +86-21-62489820 Fax: +86-21-62489821 © 2011 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the <u>Creative Commons Attribution-NonCommercial-ShareAlike-3.0 License</u>, which permits use, distribution and reproduction for non-commercial purposes, provided the original is properly cited and derivative works building on this content are distributed under the same license.



