We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists

6,300

Open access books available

172,000

International authors and editors

190M

Downloads

Our authors are among the

154

Countries delivered to

TOP 1%

most cited scientists

12.2%

Contributors from top 500 universities

WEB OF SCIENCE™

Selection of our books indexed in the Book Citation Index
in Web of Science™ Core Collection (BKCI)

Interested in publishing with us?
Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected.
For more information visit www.intechopen.com

Biofuel From Cellulosic Mass with Incentive for Feed Industry Employing Thermophilic Microbes

Javed Iqbal Qazi, Naureen Chaudhary and Saima Shahzad Mirza
*Department of Zoology University of the Punjab, Lahore
 Pakistan*

1. Introduction

Drastically depleting fossil fuels' supplies and the associated environmental concern dictate for immediate, renewable and environmental friendly alternatives. Cellulosic biomass has a great potential for bioethanol production. Many problems of the way have been solved by isolating and employing thermophilic, cellulolytic and ethanologenic microorganisms. Many workers have established simultaneous saccharification and ethanol fermentation from agro-industrial wastes rich in cellulosic material and some soluble sugars. The latter substances provide quick carbon and energy sources to the bacteria and yeasts inoculants. In Pakistan sugarcane bagasse is a very appealing potential agro-industrial waste in this regard. Owing to the great sun shine in majority of the country area throughout the year, solar energy has been dreamt for disinfecting the fermentation facility as well as providing steam for pretreatment of the substrate.

Another source of clean fuel is H_2 . We have also been able to isolate and cultivate purple-non sulfur bacteria for the production of H_2 employing certain agro-industrial waste including the one just referred as major media ingredients. Biohydrogen can be obtained economically, by employing bacteria capable of fixing sun energy and utilizing agroindustrial wastes including cellulosic material heterotrophically.

A very appealing notion about the potential of microorganisms isolated from industrially contaminated aquatic and soil habitats from developing countries is their pollutants' resistance. This ability renders such microorganisms capable of biofuel generation from industrial effluents containing biomass as well as different chemical pollutants. It is very right time to conserve such pollutants' resistant microbial diversity before the developing countries progress for in situ treatments plants for their industries and the polluted areas recover back to their uncontaminated nature, alongwith losing the pollutants selective pressures mediated and thus evolved microbial communities. This journey is expected to be completed earlier than the time frame the developed countries had passed through. As the developing countries are benefitting from the experiences of the developed nations and thus are striving to escalate the process of progress.

This chapter outlines the possibilities of ethanol and hydrogen fermentations for the application of agro/food industrial wastes. The related issues have been dealt in depth and the chapter comprises two major sections i.e. bioethanol and biohydrogen.

2. Ethanol a renewable biofuel

Energy needs of most nations of the world have increased over the time. Following industrial revolution in the late 18th century, societies that had been based largely on agriculture turned to industry to meet the needs of their growing populations. Energy plays an essential role in modern society. Fuel consumption has not only increased by factories, rather more fuel is required to distribute the market products. Ever increasing human population density and the desire for higher life standards, demanding more and more comforts, had necessitated large scale exploitation of fossil fuel energy resources, in the recent centuries. Between 1900 and 2000, world energy consumption increased by a factor of fourteen while the population increased threefold. Owing to the facts of ever increasing consumption and rapidly depleting resources of fossil fuels, scientists have rightly sensed that to feed and provide other requirements to the human population at a reduced environmental cost is a real target for future biotechnological improvements. Fueling both the humans and the required mechanical engines necessitates various developments in the agricultural and energy sectors, respectively. (Enger & Smith, 2002; Gray *et al.*, 2006; Smith, 1996).

Besides environmental deterioration, one of consequences of fossil fuels usage, their supply is being exhausted rapidly. Priorities are being shifted from building power stations, oil fields and coal mines, to active pursuit of energy and efficiency improvement and identifying renewable energy sources. One such resource is the bioconversion of plant biomass to ethanol. Motor cars in some countries are being driven by gasoline-alcohol mixture (4:1) called gasohol (Bernstein *et al.*, 1996; Preuss *et al.*, 1998; Van Haandel, 2005).

Biofuels represented by biologically produced alcohols, gasses, and oil represent renewable energy resources, unlike petroleum, coal and nuclear fuels. Rising energy and environmental problems have led to increased interest in the production from diverse routes and resources and utilization of alcohols as fuel (Atiyeh & Duvnjak, 2002; Lawford *et al.*, 2001; Von *et al.*, 1994).

The subject matter is reviewed here under the following headlines:

1. Ethanol as fuel
2. Ethanologenic fermentations
3. Ethanol from lignocellulosic biomass
4. Consolidated bioprocess: Simultaneous Saccharification and Fermentation (SSF).
5. Thermophilic ethanologenic microbes.
6. Sugarcane bagasse a resource rather than a waste.
7. Single Cell Protein (SCP) from agro industrial wastes.

Some of the highlights regarding the above referred topics are described in the forthcoming pages.

3. Ethanol as fuel

Ethanol has been used as biofuel in the United States, Europe and Brazil. In Brazil industrial scale ethanol is produced from sugarcane for blending with gasoline. While in the U.S. corn is used for ethanol production and is then blended with gasoline to produce gasohol (Enger & Smith, 2002; Lynd, 1995; Wheals *et al.*, 1999). Apart from being a renewable fuel made from plants, with high octane at low cost, ethanol is a much cleaner fuel than petrol. Ethanol blends dramatically reduce emissions of hydrocarbons, major

sources of ground level ozone formation, cancer-causing benzene and butadiene, sulphur dioxide and particulate matter. Moreover, ethanol blends can be used in all petrol engines without modifications (Miller, 2003).

Lynd (1995) has condensed valuable information in his essay on biological fuel production. Accordingly, ethanol is the most widely used biologically produced transportation fuel. Major ethanol industries arose during the 1980s in Brazil and the United States. Ethanol has a higher economic value in low level (e.g., 10%) gasoline blends than in neat (unblended) form. However, the fuel properties of neat ethanol are in general excellent and decreased emissions of ozone precursors are expected for neat ethanol.

Brazil is the largest producer of bioethanol, and sugarcane is the main raw material. In this country ethanol has been used as an octane enhancer in gasoline in the form of 22% anhydrous ethanol at 99.6 Gay-Lussac (GL) and 0.4% water or in neat ethanol engines in the form of hydrated ethanol at 95.5 GL. In other countries gasohol blends typically contain only 10% ethanol. Ethanol makes an excellent motor fuel: it has a research octane number of 109 and a motor octane number of 90, both of which exceed those of gasoline. Ethanol has a lower vapour pressure than gasoline, which results in lower evaporative emission. Ethanol's flammability in air is also much lower than that of gasoline, which reduces the number and severity of vehicle fires. These properties of ethanol have led to the development of dedicated (E-100) and modified (E-22) engines for the ethanol-gasoline mixture in Brazil (Goldemberg & Macedo, 1994; Zanin *et al.*, 2000).

Sixty eight percent of the ethanol produced in the world is used as fuel. Production of ethanol is not evenly distributed throughout the world. North America contributes for 66%, Asian and Pacific Ocean countries for 18%, Europe for 14% and Africa for 2%. Brazil and United States contribute a great share of global production with 53% and 19%, respectively. Brazilian sugarcane ethanol is now a global energy commodity that is fully competitive with motor gasoline and appropriate for replication in many countries (Goldemberg, 2007; Zanin *et al.*, 2000).

4. Ethanologenic fermentations

Ethanologenic fermentation is the microbial conversion of sugars into carbon dioxide and ethyl alcohol. Regarding the provision of sugars for ethanol fermentation, it is pertinent to note that development of several novel sweeteners, many times sweeter than sucrose could ultimately lead to a reduction in the traditional sugar market for sugarcane and sugar beet. In this way, these economics predominately in developing countries could experience severe financial and employment discretion with alternatives difficult to find (Smith, 1996). The ethanol fermentations meant to generate biofuel would then be amongst the considered alternatives. Sugars may also be derived from starches and cellulosic materials in addition to black strap molasses, a by-product of cane sugar manufacture. Once simple sugars, the monomeric units are formed, enzymes from yeasts and bacteria can readily ferment them into ethanol.

Moat *et al.* (2004) have summarized the fermentative pathways occurring in some of the major groups of microorganisms (Fig.1). They have described that a thorough evaluation of the pathways of carbohydrate fermentation requires qualitative identification of and quantitative accounting for the amount of products recovered. To assess the accuracy of the analytical determinations, a carbon balance or carbon recovery is calculated. Oxidation-reduction (O-R) reactions play a major role in the fermentative metabolism of carbohydrates.

The O-R balance provides an indication as to whether the formed products balance with regard to their oxidized or reduced states. It may not be possible to balance the hydrogen and oxygen of the substrate directly because hydrations or dehydrations may occur as intermediary steps in the fermentation pathways.

Fig. 1. Major pathways of fermentation products formation from pyruvate. Number in parentheses are the oxidation values calculated on the basis of the number of oxygen atoms less one-half the number of hydrogen atoms (Moat *et al.*, 2004).

If the ratio of oxidized products to reduced products is close to the theoretical value of 1.0, this provides further indication that the products are in balance. The oxidation value of a compound is determined from the number of oxygen atoms less one-half number of hydrogen atoms. For glucose, which has 6 oxygen atoms and 12 hydrogen atoms the oxidation value is 0. Thus, glucose is referred to as a neutral compound, and to be equally balanced the fermentation products should contain equivalent amounts of oxidized and reduced products. Another aspect of fermentation balances is the C_1 balance. The amount of expected C_1 product is calculated from the amounts of those products for which CO_2 or format is expected as an accompanying product. For example, if a C_2 compound such as ethanol or acetate is among the final products, an equal amount of CO_2 will be expected, since ethanol is derived from pyruvate by decarboxylation.

5. Ethanol from lignocellulosic biomass

Having technologically difficult boundaries but abundantly available cellulosic material has been conceived by contemporary biotechnologists for bioethanol production. For instance, Wheals *et al.* (1999) while discussing commercial viability of fuel ethanol had described that there will only be sufficient, low-cost ethanol if lignocellulose feedstock is also used. Similarly, Farrell *et al.* (2006) have explained that large-scale use of ethanol for fuel will almost certainly require cellulosic technology.

Amongst the plant biomass, cellulose is the primary substance that is produced following chemical transformation of the solar energy. It is one of most abundant organic compound in the biosphere. Some 10^{15} Kg of cellulose is synthesized by converting more than 100 billions metric tons of CO_2 and water into this and other plant products. A comparable amount of cellulose is also degraded on earth every year. It is an unbranched polymer of glucose residues joined by β -1,4 linkages consisting of 10,000-15,000 D-glucose units (Stryer, 1995). The β -1, 4-linked glucose polymer occurs in crystalline or amorphous forms and is usually found along with other oligosaccharides in the walls of plants and fungi. Cellulose-digesting microorganisms in the rumen of herbivorous animals are responsible for the ability of ruminants to use cellulose as a source of energy and building blocks for biosynthesis. The ubiquitous distribution of cellulose in municipal, agricultural and forestry wastes emphasizes its potential use for conversion to useful products such as single-cell protein or fermentation products such as methane or alcohol. As a consequence, the degradation of cellulose has been a continuing subject of intense study. Cellulose constitutes much of mass of wood and cotton is almost pure cellulose. Many manufactured products; including paper, cardboard, rayon and insulating tiles are derived from cellulose. (Moat *et al.*, 2004; Nelson & Cox, 2000; Stryer, 1995). When first discovered, it was believed that polysaccharide bound and trapped in the cellulose structure of plant extractable with alkali, comprised of smaller molecules, which would be eventually converted to cellulose by plant. For this reason they were termed hemicelluloses. It is now known that this was an erroneous belief. Upon hydrolysis hemicelluloses may yield pentoses and hexoses or both, together with uronic acids. The most abundant polysaccharides in this group are the xylans, which occur particularly in all land and some marine plants. They constitute some 15-30% of corncobs, grains and nuts etc. They are composed of almost D-xylose (Oser, 1965). Five-carbon sugar xylose is stereo-chemically similar to glucose but one carbon shorter, bind to hexokinase, but in a position where it cannot be phosphorylated. Xylose is sufficient to induce a change in a hexokinase (Nelson & Cox, 2000).

Hemicelluloses are closely associated with cellulose and occur in matrix of plant cell wall. They include, for example, galactomannans, glucomannans, mixed beta glucans, xylans and xyloglucans etc. In plant cell wall the cellulose fibers are embedded in and cross-linked by a matrix containing other polysaccharides and lignin, a plastic like phenolic polymer (Singleton & Sainbury, 2001; Voet *et al.*, 1999). Lignin is perhaps second to cellulose in term of biomass. It protects cellulose and hemicellulose from enzymatic attack. Lignin is also important structural component of plants. It provides structural rigidity and resistance to the compression, bending and resistance to pathogens. They are richest sources of aromatic compounds in nature (Coyne, 1999).

While considering production of ethanol from cellulosic biomass complete conversion of its suitable constituents is critical for the development of an efficient and economically feasible fermentation process. Since pentose sugar can comprise up to 30% of the biomass substrate, therefore there is considerable economic incentive to develop strains of yeast that will efficiently ferment this biomass component too. If xylose were converted, in addition to glucose to ethanol, the final ethanol yield would be expected to increase several folds (Ho *et al.*, 1999; Wilke *et al.*, 1981). Moat *et al.* (2004) have described that cellulose degradation requires the combined activities of three basic types of enzymes (Fig.2). Initially, an *endo*- β -1,4-glucanase cleaves cellulose to smaller oligosaccharides with free-chain ends. Then *exo*- β -1, 4-glucanases remove disaccharide cellobiose units from either the reducing or nonreducing ends of the oligosaccharide chains. Cellobiose is then hydrolyzed to glucose by β -glucosidases.

The cellulolytic enzymes may be produced as extracellular proteins by organisms such as *Trichoderma*, *Phanerochaete* (filamentous fungi), *Cellulomonas*, *Microbispora*, and *Thermomonaspora* (Actinomycetes). Rumen bacteria such as *Ruminococcus flavofaciens* and *Fibrobacter succinogenes*, or gram-positive anaerobes such as *Clostridium thermocellum*, *C. cellulovorans*, or *C. cellulolyticum*, produce a cell-bound multienzyme complex called the cellulosome. With the aid of the electron microscope, cellulosomes can be seen as protuberances on the cell surface. The cellulosome of *C. cellulovorans* contains three major subunits: a scaffolding protein, CipA; an exoglucanase, ExgS; and an endoglucanase, EngE. Also present are endoglucanases EngB, EngL, and EngY, and a mannanase, ManA. The scaffolding protein serves as a cellulose-binding factor. Another component, present in duplicate and referred to as dockerin, mediates the association of cellulose fibers with the scaffolding protein. Various models have been proposed to conceptualize the complete interaction of the cellulosome with cellulose fibers during the digestion process. A wide diversity of actively cellulolytic organisms is important in industrial applications, in the rumen of animals, and in the digestive systems of arthropods that degrade wood. Termites and other arthropods that degrade wood owe their ability to digest cellulose in the presence of specific microbial symbionts in their digestive tract (Moat *et al.*, 2004).

Future processes will increasingly make use of organic materials that are renewable in nature and/or occur as low value wastes, valueless or adding negative value to the produce, that may presently cause environmental pollution. Currently more than ten times more energy is generated annually by photosynthesis than is consumed by mankind. On a worldwide basis land plants produce 24 tons of cellulose per person per year. Definitely, lignocellulose is the most abundant and renewable natural resource available to humanity throughout the world. It has been documented that massive technological difficulties such as expensive energy-demanding pretreatment processes have to be overcome before economic

use may be made of the plentiful renewable resource. Following its chemical and/or enzymatic hydrolysis soluble sugar products of cellulose can then be converted to form ethanol, butanol, acetone, single cell protein and methane, etc. (Anderson *et al.*, 2005; Nelson & Cox, 2000; Smith, 1996). Hill *et al.* (2006) have described that negative environmental consequences of fossil fuels and concerns about petroleum supplies have spurred the search for renewable transportation biofuels, but to be a viable alternative, a biofuel should provide a net energy gain, have environmental benefits, be economically competitive and be producible in large quantities without reducing food supplies. These authors have reported that dedicatedly even if all the U.S. corn and soybean productions were dedicated to produce the biofuels, it would only cover 12% of gasoline and 6% of diesel demands. Thus, fuels such as cellulosic ethanol produced from low-input biomass grown on agriculturally marginal land or from waste biomass could provide much greater supplies and environmental benefits than food-based biofuels. Likewise, Taherzadeh & Karimi (2007) have recently indicated that lignocelluloses can be expected to be major feedstocks for ethanol production in future. Evans (2005) has earlier explained that being 50% of the total dry matter of plants, the cellulose is potentially a huge renewable energy store, and vast amounts of this material are routinely thrown away. However, until recently, the prospect of realizing this potential fuel source was viewed as difficult and expensive; the combination of cellulase-resistant links and its close association with lignin discouraged its large-scale hydrolysis to sugars. Energy involved in rendering various cellulosic materials into acceptable form had been considered a major limiting factor. Nevertheless contemporary technologies employing whole organisms and isolated enzyme technique appear to be promising to make the commercial processing of cellulose to alcohol a reality.

Xylose is represented by 20 to 40% of the contents of different cellulosic materials (Bicho *et al.*, 1988). Economic ethanol fermentations of cellulose are required to use this pentose sugar along with glucose following the saccharification of the fibrous matter. As majority of the well known microbial diversity in this regard has been reported capable of utilizing only glucose. Previously reported scarcity of xylose fermenting pathways in the microorganisms has been discouraging for cellulosic materials to be employed for economic ethanol generation. However, recently naturally occurring as well as genetically engineered xylose fermenting microorganisms have also been well documented (Chaudhary & Qazi, 2006a; Sonderegger *et al.*, 2004; Toivari *et al.*, 2001). It has been, however, reported variously that glucose is preferred by fermenting microorganisms capable of fermenting the both categories of the monosaccharides i.e., the glucose and xylose. In such cases glucose depletion within a fermenting substrate may allow for xylose utilization (Govindaswamy & Vane, 2006). Many strategies can be attempted to overcome co-substrate inhibition of xylose consumption by glucose considering the nature and diversity of fermenting microorganism(s). For instance, in case of microbial consortia first the glucose be utilized and then the residual material be attempted with xylose utilizers. Regarding other sugars, microbes could be found capable of co-utilization. Karhumaa *et al.* (2006) have reported simultaneous co-utilization of xylose and arabinose in recombinant strains of *S. cerevisiae*. This is well clear that economic ethanol generation from lignocelluloses requires the maximum utilization of all the diverse sugars monomers derived through any feasible saccharification process.

Responding above referred situations requires the isolation and construction of microorganisms capable of fermenting glucose and xylose at appropriate levels. Fermenting

microbes that would prefer xylose and/or be incapable of glucose utilizations may find increasing utilization in one or two-chambered fermentative processes. In the latter case, a fermented matter in which glucose has been used maximally would serve feed stock for xylose-fermenting microorganisms. Mutants or genetically modified organisms with derived characteristics would be required to develop processes for obtaining ethanol from cellulose.

Fig. 2. Enzymatic degradation of cellulose (Moat *et al.*, 2004).

Infact, the afore-mentioned approach could play a major part in addressing the largest environmental issue of our time, energy and waste. Energy extraction accompanied by environmentally safe disposable of a cellulosic waste may render the process economically feasible. A large number of point and non-point/plant biomass loads, to the natural water

systems result in higher BOD values. Processing such wastes for ethanol fermentation is highly appealing to reduce the pollutants (Evans, 2005). Converting cellulose to ethanol is accomplished in essentially four stages, discussed below:

Acid/microbial hydrolysis: This process breakdowns the cellulose into a slurry of sugars in acid water and solid lignin particles. While reviewing acid-based hydrolysis processes for ethanol from lignocellulosic material, Taherzadeh & Karimi (2007) have summarized that concentrated-acid processes operated at low temperatures gave high sugar yield. On the other hand, dilute-acid processes operated at high temperature gave low sugar yield. Both categories of the hydrolyses result, however, into equipment corrosion.

Acid recovery: Following acid hydrolysis sugary liquid is separated from the previous stage and the process acid is recovered partly and reused. Van Groenestijin *et al.* (2006) have claimed that recovery of sulphuric acid in the form of H_2S from anaerobic waste water treatment has a low overall cost for ethanol production.

Fermentation: The derived sugars are fermented by yeast and/or bacteria into alcohol. As already indicated efficient fermentation of lignocellulosic hydrolyzates requires employing microorganisms capable of fermenting the maximum variety of monomeric sugars and to resist inhibitory products of the hydrolyses process as well.

Distillation: It is required to collect the market grade ethanol. Economizing these four phases necessitates understanding and optimizing the diversity of the processes involved. Fortunately, a large number of efforts in this regards have been continuously reported in the literature (Anderson *et al.*, 2005; Ballesteros *et al.*, 2001; Negro *et al.*, 2003). For instance, the latter authors have described that crops such as switch grass, bermudagrass, or napiegrass have the capacity to produce large quantities of lignocellulose for biofuel. To facilitate use of lignocellulosic material for the production of ethanol, it will be necessary to determine cost efficient pretreatments to enhance of the substrate conversion to fermentable sugars.

6. Consolidated bioprocess: Simultaneous Saccharification and Fermentation (S.S.F.)

Apart from the distillation step, which is required to separate the produce from the fermentation chamber, actual process of obtaining ethanol from lignocellulosic material essentially comprises of two phases i.e., saccharification of the substrate and the efficient utilization of all types of monosaccharides by suitable microbe(s) for producing the ethanol. Usually the two processes are accomplished in separate facilities. Science of process economics has dictated for developing some consolidated processes to allow the individual phases of the two processes to be completed simultaneously. This has been elaboratively described as Simultaneous Saccharification and Fermentation (SSF). Lynd (1995) described that biological conversion of cellulosic biomass typically involves four stages: production of cellulose enzymes, enzymatic hydrolysis of cellulase, hexose fermentation and pentose fermentation. And if a single organism or system of organisms were to carry out all four elements of ethanol production with high rates and yields, process economics would benefit profoundly.

The SSF has been conceptualized by many workers as a promising economical strategy for converting plant biomass to ethanol. In case of cellulosic ethanol production, developing genetically engineered microbes with the traits necessary for one-step processing of cellulosic biomass to ethanol appear to achieve the goal. Genetic improvements of microorganisms have been made either to enlarge the range of substrate utilization or to

channel metabolic intermediates specifically toward ethanol for simultaneous saccharification and fermentation of lignocellulosic biomass from various sources (Chandrakant & Bisaria, 1998; Greer, 2005; Teixeira *et al.*, 2000). In their findings, Stenberg and co-workers (2000) pointed out that economic optimization of the production of ethanol by SSF requires knowledge about the influence of substrate and enzyme concentration on yield and productivity. These investigators obtained highest ethanol yield 68% of the theoretical based on the glucose and mannose present in the original wood at 5% substrate concentration. Compared with separate hydrolysis and fermentation, SSF gave a higher yield and doubled the productivity.

Lynd *et al.* (2002) have described that developing microorganisms capable of substrate utilization and product formation required for consolidated bioprocess can be pursued by two strategies. The native cellulolytic strategy involves engineering naturally occurring cellulolytic microorganisms to improve product related properties, such as yield and titer. While, the recombinant cellulolytic strategy involves engineering non-cellulolytic organisms that exhibit high product yields and titers so that they express a heterologous cellulose system that enables cellulose utilization.

Fujita *et al.* (2004) achieved efficient direct fermentation of amorphous cellulose to ethanol by developing a yeast strain and have reported the role of whole-cell biocatalysts for reducing the cost of ethanol production from cellulosic biomass. They described the advantages of the engineered yeast strain displaying three types of cellulolytic enzymes. The advantages included: conversion of cellobiose and glucose, which inhibit cellulase and β -glucosidase activities; lower sterilization requirements, as glucose was immediately taken up by the cells for ethanol production in a single cell reactor.

Considering process kinetics is very important. Microorganisms tend to disturb the optimum conditions provided to them due to their own growth and metabolic activities. Further feed back inhibition is an important limiting factor for both saccharification and ethanologenic levels. Thus microorganisms with a wide range of activities are to be worked out. Different bacteria and yeast have varying levels of ethanol tolerance. Here thermophilic ethanologenic microorganisms become important as the produce, recovery can be achieved under elevated temperatures, while not stopping or influencing negatively the fermentation process. Last but no the least, is the requirement for large scale microbial decontamination of the process material for controlled microbial hydrolysis and subsequent fermentation. This is surely energy demanding activity. A plant that has recently been proposed will work by intensifying solar radiations to provide heat for decontaminating the substrate and enabling cellulose substrate to be hydrolyzed as well as fermented to ethanol by thermophilic microorganisms (Chaudhary & Qazi, 2007). The proposed plant has technically been designed; its outcome is likely to be reported soon. The designed plant derives maximum benefits from sun heat and in this regard pivotal role of thermophilic ethanologenic microorganisms has been discussed.

7. Potential of thermophilic ethanologenic microbes

Production of ethanol from low cost plant biomass is influenced by a number of phenomena. Majors of which are saccharification and fermentation efficiencies of the microbial culture(s) involved. The fermentation efficiency is in part influenced negatively with the raising levels of product accumulation and its inhibitory effect for further production. This can be overcome by employing thermophilic fermenting microorganisms as con-comittant removal of product, the

bioethanol, at elevated temperature may delay or practically keep away accumulation of inhibitory level of the produce. Moreover, employing thermophilic microorganisms can bring support to the process economics by reducing the efforts required to keep the process facilities decontaminated by mesophilic bacteria and to reduce the cost of cooling that must be provided to maintain the correct temperature range required for optimal functioning of the mesophilic bacteria. These considerations have well earlier been taken into account by various workers (Budden & Spencer, 1993; Lamed & Zeikus, 1980; Thomas *et al.*, 1981).

While, commenting on yeast in their book "Thermophilic Microbes in Ethanol Production" Slapack *et al.* (1987) concluded that it is evident that thermotolerant yeasts would offer many advantages to the fermentation industry. Energy costs (cooling, distilling, and mixing) would be minimized and theoretically, productivity and growth rates should increase. Thermotolerant yeasts would be especially attractive in tropical countries where cooling costs are very expensive, and they are paramount for efficient simultaneous saccharification fermentation processes currently being investigated. In view of their many advantages, it is surprising that so few attempts have been made to select for thermotolerant yeasts and in particular, yeasts that can produce ethanol efficiently at high temperatures.

Sree *et al.* (1999) reported a novel solid substrate fermentation system to produce fuel ethanol from sweet sorghum and sweet potato using a thermotolerant *Saccharomyces cerevisiae* strain (VS#) and an isolate of amylolytic *Bacillus* sp. (VB9). They recorded maximum amount of ethanol production in co-culture with a mixed substrate as to be 5g/100 g of substrate at 37°C and 3.5 g/100g of substrate at 42°C. Likewise, Ueno *et al.* (2002) have evaluated a thermotolerant, fermentative yeast strain (RND 13) from a hot spring drainage for ethanol producing ability at elevated temperatures at 15% concentration of glucose. The RND 13 utilized glucose almost completely at 40°C with increasing inoculum size producing ethanol upto 6.6% (w/v). These workers found maximum rate of ethanol production of 9.00 g/L at 40°C with 5% inoculum size in batch fermentation.

It appears that further research on thermophilic microbes both prokaryotes and the eukaryotes with higher ethanologenic potential would continue. And the present, incipient successes are promising to dig more in this field for isolating, optimizing and developing thermophilic ethanologenic microbes for designing economically and environmentally friendly strategies. For obtaining the bioethanol from agro-industrial low cost residues, various lignocellulosic materials are under trials. One of the such cellulosic materials under consideration by various workers for conversion to biofuel is sugarcane bagasse, a waste by product of sugar industry.

8. Sugarcane bagasse-a resource rather than a waste

Sugarcane bagasse is an important, renewable, abundant and cheap or even having negative value agricultural waste in many countries (Bustos *et al.*, 2003; Molina Junior *et al.*, 1995; Rodrigues *et al.*, 2001; Van Haandel, 2005). Composition of the fibrous residue may vary based on its different varieties, age of cane at the time of harvesting and efficiency of milling operation for extracting the juice

Besides the compositional analysis, different fractions of bagasse can be separated employing suitable techniques. For example, Bustos *et al.* (2003), while describing sugarcane bagasse hydrolysis with HCl have mentioned 128°C, 2% HCl and 51.1 minutes as optimal conditions. At these conditions they obtained 22.6 g xylose, 3.31 g arabinose, 3.77g glucose, 3.59 g acetic acid and 1.54 g furfural/L.

Concerning the bioconversion of the substrate, products such as alcohol, alkaloids, mushrooms, protein enriched animal feed, enzymes L-glutamic acid, fruity aroma, and xylitol have been reported to be obtained from the waste sugarcane bagasse (Alonso *et al.*, 2007; Christen *et al.*, 1994; Liu *et al.*, 2006, 2007; Martinez *et al.*, 2000; Pereira *et al.*, 2007; Sasaki *et al.*, 2003; Van Haandel, 2005). Besides the above mentioned diverse and usually bench scale utilities of the substrate Meunchang *et al.* (2005) have rightly commented that one of the under utilized sources of organic materials, is the sugarcane industry. Global sugar production from sugarcane releases large amounts of sugar mill by-products as filter cake and bagasse. It had been reported that in Brazil at the end of last century during the ethanol production season more than 60×10^6 tons of sugarcane bagasse containing 50% moisture were produced annually.

Like any other lignocellulosic material the sugarcane bagasse is a complex and stable substrate. Any significant and efficient utilization would require first its hydrolysis. Following acid, enzymatic or microbial hydrolysis of the sugarcane bagasse the monosaccharides yield can find many applications in different bioconversion processes. One consideration is their conversion into biofuel, the ethanol. Sugarcane bagasse has relatively earlier been considered a source of fermentable carbohydrates (Du Toit *et al.*, 1984). However, pretreatment of the bagasse has been found useful for the microbial attack, which may results into its saccharification, fermentation or the both processes simultaneously. Chemical as well as microbial enzymatic pre-treatments have been described by various workers (Chaudhary & Qazi, 2006a; Dominguez *et al.*, 1996; Laser *et al.*, 2002; Lavarack *et al.*, 2002; Martin *et al.*, 2002; Zheng *et al.*, 2002). Martin *et al.* (2002) have described that sugarcane bagasse is a potential lignocellulosic feedstock for ethanol production, since it is cheap, readily available and has a high carbohydrate content. These workers performed different pretratments of the substrate at 205°C for 10 minutes followed by its hydrolysis using cellulolytic enzymes. They found highest yield of xylose (16.2 g/100g dry bagasse), arabinose (1.5 g/100g) and total sugar (59.9 g/100g) in the hydrolysis of the SO₂-impregnated bagasse. The H₂SO₄ impregnated bagasse gave highest glucose yield (35.0 g/100g) but the lowest total sugar yield (42.3 g/100g). Sulfuric acid impregnation led to a three-fold increase in the concentration of the fermentation inhibitors, the furfural and 5-hydroxymethyl furfural and a two fold increase in the concentration of inhibitory aliphatic acids (formic, acetic and levulinic acids) compared to the without any impregnation and sulfur dioxide impregnation yields. They found no major differences in the content of inhibitors in the hydrozylates obtained from SO₂-impregnated and non-impregnated bagasse. When Martin and colleagues studied fermentability of the three hydrolyzates with a xylose utilizing *Saccharomyces cerevisiae* with and without nutrient supplementation they found that the H₂SO₄ impregnated bagasse fermented considerably poorer than the situations found in the other two categories of the bagasse. Cheng *et al.* (2007) have reported the ethanologenic fermentation of sugarcane bagasse hemicellulose hydrolyzates, pretreated by over-liming as well as electrodialysis and supplemented with nutrient materials employing *Pachysolen tannophilus* DW 06. These workers found that compared with detoxification by over-liming, detoxification by electrodialysis decreased the loss of sugars and increased the acetic acid removal. This lead to better fermentability and the Cheng's team found that a batch culture employing electrodialytically pretreated hydrolyzate substrate gave 21g ethanol L⁻¹ with a yield of 0.35 g L⁻¹ sugar and productivity of 0.59 g L⁻¹ h⁻¹. For better yield of the produce ethanol from sugarcane hydrolyzates, the above described studies highlight two important notions. That is detoxification of inhibitory substances, that

may emerge within the hydrolyzates, of different nature and varying levels depending upon the specific pre-treatment employed. Secondly bagasse hydrolyzate would mainly consists of carbohydrates content, its supplementation with a suitable nutritive material is likely to enhance the growth and/or fermentative potential of the microorganism(s).

Fermentation inhibitors can be tackled at two levels i.e., their removal/detoxification or employing the inhibitors' resistant fermentative microorganisms. Martinez *et al.* (2000) reported that hemicellulose syrups from dilute sulfuric acid hydrolyzates of hemicellulose contain inhibitors that prevent efficient fermentation by yeast and bacteria. These workers have optimized overliming treatments for sugarcane bagasse hydrolyzates and found a substantial reduction in furfural, hydroxymethyl furfural and three un-identified high-performance liquid chromatography peaks. They further demonstrated that the extent of furan reduction correlated with increasing fermentability, although furan reduction was not found to be the sole cause of reduced toxicity. Rodrigues *et al.* (2001) studied the influence of pH, temperature and degree of hydrolyzate concentration on the removal of volatile and non-volatile compounds from sugarcane bagasse hemicellulosic hydrolyzate treated with activated charcoal before and after the vacuum evaporation process. They found that furfural and 5-hydroxymethyl furfural were almost totally removed irrespective of pH, temperature and whether the charcoal was added before or after the vacuum evaporation process. Adding activated charcoal before the vacuum evaporation process favoured the removal of phenolic compounds for all values of pH. Acetic acid was most effectively removed when the activated charcoal was added after the vacuum evaporation process at an acid pH (0.92).

Regarding the use of fermentation inhibitory products' resistant microorganisms, Morita & Silva (2000) reported the fermentation of precipitated sugarcane bagasse hemicellulosic hydrolyzate containing acetic acid, employing *Candida guilliermondii* FT 120037 under different operational conditions for the production of xylose. At pH 7.0 and K_{La} of 35/h (4.5 vvm), the acetic acid was rapidly consumed and that the acetic inhibition was not important. They concluded that the acetic acid assimilation by the yeast indicates the ability of this strain to ferment a partially detoxified medium and makes possible the utilization of the sugarcane bagasse hydrolyzate in this manner.

For simultaneous bioconversion of cellulose and hemicellulose to ethanol, need of xylose fermenting microorganisms has been established (Chandrakant & Bisari, 1998; Sedlak & Ho, 2004; Toivari *et al.*, 2001; Yang *et al.*, 1997). De-Castro *et al.* (2003) have described a new approach for the utilization of hemicellulosic hydrolyzates from sugarcane bagasse. They diluted the conventional feedstock, sugarcane juice; by the bagasse hydrolyzate to the usual sugar concentration of 150 gm per liter that is employed for industrial production of ethanol. These workers used a pentose fermenting yeast strain, and achieved ethanol productivity of about 11.0 gm per liter per h and overall sugar conversion of more than 95%. Katzen and Fowler *et al.* (1994) reported first commercial application of unique fermenting organism capable of converting five carbon sugars and oligomers of cellulose directly to ethanol. These worker described conversion of hemicellulose content of sugarcane bagasse to the five-carbon sugar by mild acid prehydrolysis, followed by fermentation of the 5-carbon sugar extract with recombinant *Escherichia coli*. The process also recovered the majority of sucrose normally lost with the bagasse fibers to ethanol. Sun & Cheng (2002) have described the benefits of simultaneous saccharification and fermentation that it effectively removed glucose, which is an inhibitor to cellulase activity thus increasing the yield and rate of cellulose hydrolysis.

Various workers have reported different protocols and models for fermenting cellulosic biomass to ethanol and considered it the cleanest liquid fuel alternatives to fossil fuels (Gray *et al.*, 2006; Lawford & Rousseau, 2003; Lin & Tanaka, 2006; Sun & Cheng, 2002). From above cited literature it appears that relatively recently considered renewable resource, the sugarcane bagasse process much potential for the bioethanol production. In Brazil sugarcane cultivation and its dependent sugar industry is well developed. Consequently, a huge amount of bagasse is generated. It consists mainly of 37% cellulose, 28% hemicellulose and 21% lignin (Bon, 1996). A reasonable number of cellulose saccharifying and/or ethanologenic bacteria as well yeast have been isolated and characterized in our laboratory (Chaudhary & Qazi, 2006a; Saeed, 2005).

Above referred studies suffice to highlight different achievements and areas that require more research concerning the developments of bioprocesses to utilize sugarcane bagasse lignocellulosic material for obtaining bioethanol at economically feasible levels. As in all such bioprocess developments subsidiary supports are very important. Benefits derived from appropriate utilization of auxiliary products/often process wastes, have an influential bearing on the main process economics. In this regard Pandey *et al.* (2000) pointed out an important aspect. Accordingly, developing associated or complimentary technologies, during the fuel ethanol production from sugarcane bagasse which could produce other value-added by-products would improve the overall economy of ethanol production. It is pertinent here to mention that the non-fermentable residues of variously processed sugarcane bagasse would contain the microorganisms employed for the saccharification and/or fermentation of the substrate. Thus the residue may attain the levels of protein (due to single cell protein) that may render them to the status of animal feed / supplement. This may bring additional support to the process economics. Following is a brief review of single cell protein in connection with microbiological utilization of lignocellulosic materials including sugarcane bagasse.

9. Single Cell Protein (SCP) from agro-industrial wastes; Sugarcane bagasse

Growth of microbial cells both bacterial and yeast on any material means that the substrate ingredients are being transferred or altered to proteins along with synthesis and accumulation of other contents of protoplasm. Upgradation of a large number of agro-industrial wastes, which after being fortified with S.C.P. may find their useful application in preparing or supplementing animal feed. The S.C.P. from various agro-industrial wastes has been well documented from several laboratories (Chaudhary & Sharma, 2005; Dimmling & Seipenbusch, 1978; Hongpattarakere & Kittikum, 1995; Kamel, 1979). Stabnikova *et al.* (2005) used extracts of cabbage, watermelon, a mixture of residual biomass of green salads and tropical fruits for yeast cultivation and concluded that the yield was comparable with the yield of yeast biomass grown in potato dextrose broth. These workers commented that the yeast biomass can be considered as protein source. Single cell protein production from sugarcane bagasse has relatively earlier been reported by various workers (Molina *et al.*, 1984; Sindhu & Sandhu, 1980). Molina and colleagues treated sugarcane bagasse pith with 1% NaOH solution at room temperature, at a NaOH/pith ratio of 10%. They used different contact times and found that the shortest period required for maximum protein production was 24h at 25°C. These workers used mixed culture of *Cellulomonas* sp. and *Bacillus subtilis*. Rodriguez *et al.* (1993) reported optimal production of *Cellulomonas* with 1% (w/v) bagasse pith pre-treated with either 0.2M NaOH for 1h at 80°C or 0.4M NaOH for 40h at 28°C to

30°C. With these milder pretreatments they obtained growth comparable to the one found for the substrate prepared with a more severe treatment. Growth was also comparable with other reports for cellulolytic bacteria cultivated on pre-treated bagasse pith. Rodriguez & Gallardo (1993) studied association of *Cellulomonas* sp. with an isolate of *Pseudomonas* sp. for S.C.P. production from bagasse pith. They found a mutualistic symbiotic relationship during their mixed growth on bagasse pith, the *Cellulomonas* supplying carbon source (glucose produced from bagasse) to the *Pseudomonas* and the latter producing the vitamin supplements necessary for *Cellulomonas* growth. The metabolic symbiosis allowed the growth of the mixed culture in a minimal medium, without any growth factor supplement. Fed-batch cultivation of the mixed culture yielded high biomass production (19.4 g/L). Perez *et al.* (2002) while reporting use of sugarcane bagasse complemented with a mineral medium and inoculated with *Candida utilis* as bio-filter for ethanol concluded that 57% of the carbon from ethanol was converted to CO₂ and 8.7% into biomass. They found final yeast population of 7×10⁹ cells/g of dry matter corresponding to 56 mg protein/g dry matter. Perez *et al.* (2002) concluded that this much protein offers potential for using the protein enriched bagasse as feed too. The above described studies clearly indicate that the sugarcane bagasse or its pith can be upgraded with the generation of S.C.P. by employing the suitable microorganisms on untreated as well as pretreated substrates.

As has been introduced earlier, that being an agriculture country, sugarcane is cultivated at large commercial scale in Pakistan. The produce is largely used for obtaining sucrose. The bagasse is a waste of the sugar industries. Instead of other lignocellulosic material, its usage as substrate for biofuel ethanol production has two advantages. Tackling of a waste and presence of some amounts of soluble sugars that may be assimilated quickly by the inoculated microorganisms meant for saccharification and/or ethanol fermentation of the substrate. Moreover, the fermented residual material enriched with microbial cells may find its application as animal feed or its supplement there of. The latter notion is likely to bring support to the economic constraints regarding the process developments for obtaining ethanol from lignocellulosic materials in general and specifically from sugarcane bagasse. In our lab. Ahlam (2005) and Chaudhry (2008) conducted studies on the same lines and reported isolation, characterization and optimization of microorganisms both prokaryotic and eukaryotic, which are useful for saccharifying and fermenting fruits and vegetables' wastes and the sugarcane bagasse, respectively. Following maximum yield extraction, the fermented residue is likely to find its application to supplement animal feed with S.C.P.

10. Biohydrogen; Another potential for biofuel provision

Regarding the provision of the clean and sustainably available fuel, hydrogen gas (H₂) has been claimed as an alternative source of energy due to non-emission of pollutants (Das & veziroglu, 2001; Gest *et al.*, 1950; Prince & Kheshgi, 2005; Valdez-vazquez *et al.*, 2005). It is plentiful element in universe (Bockris, 1981; Levin *et al.*, 2004; Suzuki, 1982) and has a wide range of uses (Czuppon *et al.*, 1996; Kalia *et al.*, 2003; Ramachandran & Menon, 1998). Das & Veziroglu (2001) have summarized the uses of H₂ as reactant in hydrogenation processes, O₂ scavenger, fuel in rocket engines and coolant in electrical generators etc. Thus it is expected that commercial and domestic uses of hydrogen gas will increase in the coming next years. And there are signs that hydrogen may finally become an important component of the energy balance of a global economy (Benemann, 1996; Gregoire-Padro, 1998; Kalia *et al.*,

2003). Despite the green nature of hydrogen as a fuel, it is still primarily produced from nonrenewable sources such as natural gas, naphtha, and coal.

Different methods used for hydrogen production from fossil fuels include steam methane reforming of natural gas. Nearly 90% of hydrogen is produced by the reactions of natural gas or light oil fractions with steam at high temperature by the process of steam reforming (Armor, 1999; Casper, 1978; Cox & Williamson, 1979; Lodhi, 1987; Rosen & Scott, 1998; Sastri, 1989), coal gasification, thermal cracking of natural gas, and partial oxidation of heavier than naphtha hydrocarbons (Claassen *et al.*, 2006; Hawkes *et al.*, 2002). Pyrolysis or gassification is a method for the production of hydrogen from biomass (Claassen *et al.*, 1999; Hofbauer, 2007). Electrolysis, photolysis, thermochemical process, direct thermal decomposition and thermolysis are some of the conventional methods of hydrogen production from biomass. However, these are highly energy-intensive and not environmentally benign. For instance, electrochemical hydrogen production via solar battery-based water splitting requires the use of solar batteries with high-energy requirements (Basak & Das, 2007).

In order for hydrogen to become a more sustainable source of energy, it must be produced either through photosynthetic or fermentative routes using wastes or renewable substrates (Benemann, 1996; Czernik *et al.*, 2002; Dunn, 2001; Hawkes *et al.*, 2007).

The biological production of hydrogen is less energy intensive than chemical and electrochemical methods, because it is carried out largely at ambient temperatures and pressures (Benemann, 1997; Greenbaum, 1990; Miyamoto *et al.*, 1979; Sasikala *et al.*, 1993; Tanisho *et al.*, 1983).

Favoring process economics and rendering environmental improvement, the use of domestic/ agroindustrial wastes as substrates for cultivation of energy yielding microorganisms appears imperative. Conventional anaerobic treatment of organic pollutants results into the generation of methane (Fang & Liu, 2000; Hulshoff Pol & Lettinga, 1986) and solid wastes (Iglesias *et al.*, 1998). However, methane and its combustion products are themselves greenhouse gases (Cecchi *et al.*, 1989; Dickinson & Cicerone, 1986; Oleszkiewicz & Poggi-varaldo, 1997; Poggi-varaldo *et al.*, 1997, 1999, 2002). By contrast hydrogen gas is clean and produces no green house gases. It has high-energy yield of 122kJ/g, which is 2.75 fold greater than that of hydrocarbon fuels (Hart, 1997; Kirk *et al.*, 1985; Mizuno *et al.*, 2000; Onodera *et al.*, 1999).

Light dependent production of molecular hydrogen by photosynthetic bacteria was first observed in cultures of *Rhodospirillum rubrum* growing photoheterotrophically (anaerobically) in media containing dicarboxylic acids of the citric acid cycle and either glutamate or aspartate as nitrogen source (Gest & Kamen, 1949a, 1949b). Efficiency of light energy conversion to hydrogen, and proper supply of an appropriate carbon source, are the key factors for hydrogen production by biological systems (Basak & Das, 2007; Hillmer & Gest, 1976; Miyake *et al.*, 2001, 2004; Rocha *et al.*, 2001; Zaborsky, 1998). The phototrophic purple non-sulfur bacteria (PNSB or PPNS) produce a high ratio of molecular hydrogen to carbon dioxide ranging from 85:15 to 98:2 (v/v). They can also utilize organic substrates as electron donors for hydrogen production (Hillmer & Gest, 1976; Ormerod *et al.*, 1961; Segers & Verstraete, 1983).

The purple non-sulfur bacteria (PNSB or PPNS) have been grown at temperature ranges from 28-32 °C (Jung *et al.*, 1999; Mehrabi *et al.*, 2001). Hydrogen production yield is much higher at extreme thermophilic conditions than mesophilic and thermophilic conditions (Fang *et al.*, 2002a; Hussy *et al.*, 2003; Shin *et al.*, 2005; Wu *et al.*, 2006; Yokoyama *et al.*, 2007).

However, molecular hydrogen production by thermotolerant (purple non sulfur bacteria) *Rubrivivax gelatinosus* using raw cassava starch as an electron donor have been reported which may be suitable for out door cultivation using solar energy (Buranakarl *et al.*, 1985, 1988; Watanabe *et al.*, 1979). Mostly glucose, sucrose, molasses, lactate and cellulose have been used as substrates for hydrogen production (Kotsopoulos *et al.*, 2006; Van Niel *et al.*, 2003; Wu *et al.*, 2007; Zhang *et al.*, 2003, 2008).

Logan (2002) has reported that similar hydrogen conversion efficiencies for glucose and sucrose and lower for molasses and lowest for lactate and cellulose. It has also been demonstrated that very low pH's and high substrates concentrations can reduce biohydrogen production (Eroglu *et al.*, 2009). Increasing the substrate loading increases the relative production of volatile acids and decreases the pH, which can shift the reaction to solvent production (Jones & Woods, 1986).

Metabolic diversity of purple non-sulfur bacteria allows them to occupy a broad range of environments (Hiraishi & Ueda, 1994; Imhoff & Truper, 1992; Imhoff *et al.*, 2005; Madigan, 2003). It is one of the most diverse groups of the photoorganotrophic bacteria, as they utilize organic compounds as electron donors and carbon sources (Das & Veziroglu, 2001; Hiraishi *et al.*, 1984; Montgomery, 2004; Nandi & Sengupta, 1998). Facultatively microaerophilic to aerobic nature of these bacteria renders them versatile (Pfenning, 1977; Pfenning & Truper, 1974). However, their presence in nature, is evaluated from results obtained by enrichment techniques (Kaiser, 1966) or by membrane filtration (Biebl & Drews, 1969; Swoagar & Linderstrom, 1971). Extent of organic pollutants, mainly controls the presence of purple non sulfur bacteria in a given water body. Wide variety of organic compounds in a water body can be photoassimilated by purple non-sulfur bacteria (Cooper *et al.*, 1975; Holm & Vennes, 1970; Sunita & Mitra, 1993). Thermophilic nature, however, is limited to only among few genera of anoxygenic phototrophic bacteria (Fardeau *et al.*, 2004; Hanada, 2003). However, thermotolerant or mildly thermophilic PPNS bacteria, having optimum growth temperature, are well documented around 40°C (Ahn *et al.*, 2005; Fang *et al.*, 2002b; Hisada *et al.*, 2007; Madigan, 2003; Shin *et al.*, 2005; Ueno *et al.*, 2001b; Wu *et al.*, 2006). Low dissolved oxygen (DO) tension and availability of light and simple organic nutrients, as is the case in nutrient rich stagnant water bodies, are important factors promoting proliferation of PPNS bacteria. They occasionally occur in high numbers in wastewater treatment plants operating under highly aerated and illuminated conditions (Hiraishi *et al.*, 1989, 1991; Okubo *et al.*, 2006).

PPNS bacteria also have the capacity to grow rapidly in simple synthetic media under either anaerobic or aerobic photosynthetic conditions (Sojka & Gest, 1968). Hydrogenase, which catalyzes irreversible interconversion of hydrogen to protons and electrons is central metabolic feature of some microorganisms including most prokaryotic genera and some lower eukaryotes (Adams, 1990; Kleihues *et al.*, 2000; Noda *et al.*, 1998). Purple bacteria are also able to produce molecular H₂ catalyzed by nitrogenase under nitrogen limiting conditions (Tsygankov *et al.*, 1998).

A biological wastewater treatment process using purple non sulfur bacteria (PNSB), has been used for purifying various organic wastewater, especially food industrial wastes of high BOD strength, extreme thermophilic conditions offer better destruction for digested residues (Kobayashi & Tchan, 1973; Sahlstrom, 2003) and full scale wastewater treatment plants for food industry had been reported by Sasikala & Ramana, (1995). PNSB will grow selectively in a reactor under illumination and heterotrophically remove organic carbon. Wastewater treatment by PNSB is considered to be effective because they are metabolically the most versatile among all prokaryotes. Anaerobically photoautotrophic and

photoheterotrophic in presence of light and aerobically chemoheterotrophic microbes in the dark can accomplish consumption of various types of organic matter (Levin *et al.*, 2004; Nakadomi *et al.*, 1999). Concentrated latex wastewater (Choorit *et al.*, 2002), aquarium wastewater (Nakadomi *et al.*, 1999) and agricultural waste (Arooj *et al.*, 2007; Fang & Liu, 2002; Hiraishi *et al.*, 1989; Liu & Shen, 2004; Wang *et al.*, 2007; Yang & Shen, 2006; Yokoi *et al.*, 2001) and sewage wastewater treatment (Li & Fang, 2007; Nagadomi *et al.*, 2000) are main types of wastes that are treated with purple non sulfur bacteria. These bacteria directly convert organic carbon into biomass that is suitable for direct reuse e.g., single cell protein (Kobayashi & Tchan, 1973). Cell mass of purple non sulfur bacteria has been reported to be a good alternative of manure, fish feed or agriculture supplement because of its richness in proteins and vitamins (Getha, *et al.*, 1998; Kobayashi & Tchan, 1973).

Single cell protein (SCP) is one of the very attractive facets of agricultural and industrial waste upgradation/ treatment. The microbial biomass surely attains higher levels of proteins and other nutritionally important parameters than the non-cultivated substrate/ waste. Many workers have advocated SCP as potential animal feed or supplement thereof. This aspect renders the waste treatment process economically feasible or at least cost-compatible. Following is a comprehensive review of some useful attributes of hydrogen producing bacteria.

10.1 H₂ gas production and phototrophic bacteria

Hydrogen gas has been perceived one of future renewable energy resources as well as an environmentally compatible one as it does not evolve the “greenhouse gas” CO₂ at combustion (Abraham, 2002; Hansel & Lindblad, 1998; Matsunaga *et al.*, 2000; Woodward *et al.*, 1996). Further combustion of H₂ liberates large amounts of energy per unit weight and is easily converted to electricity by fuel cells (Miyamoto, 1993; Ueno *et al.*, 1995; Rupprecht *et al.*, 2006). Hydrogen may be produced by electrolysis of water, thermocatalytic reformation of hydrogen-rich organic compounds and biological processes. At present it is almost exclusively produced by electrolysis of water or by steam reformation of methane. Whilst, biological hydrogen production has several advantages over hydrogen production by photochemical or thermochemical processes. Various routes of biological hydrogen production such as direct biophotolysis, indirect biophotolysis, photo and dark fermentations has been described (Kapdan & Kargi, 2006; Levin *et al.*, 2004).

Numerous prokaryotes produce hydrogen gas, while some photosynthetic microorganisms also produce light dependent hydrogen from organic substrates. Among the photosynthetic microorganisms, photosynthetic bacteria exhibit a high level of hydrogen production. Nonetheless, low conversion efficiencies of other biological systems can be compensated for, by low energy requirements and reduced initial investment costs (Macler *et al.*, 1979; Oh *et al.*, 2002).

Moreover, in laboratory experiments, high light energy conversion efficiency upto 7% has been reported for photoheterotrophic processes (Nakada *et al.*, 1995; Sunita & Mitra, 1993; Ueno *et al.*, 1995). It is reported by Rupprecht *et al.* (2006) that continuously depleting oil reserves had necessitated for search of alternative energy sources. of clean fuels and less CO₂ emission to reduce the impact of global warming is met by employing photoheterotrophic and photoautotrophic organisms in bio-H₂ production process.

In the mid-1920s, Van Niel, was attracted by the color of these purple and green sulfur bacteria which ranges from purple-red to yellowish green. These bacteria impart their coloration to their habitats too. Ecophysiology of these anoxygenic phototrophic bacteria

became a topic of scientific interest in the late 1960s. Later on, Van Niel (1929), morphologically and physiologically characterized pure cultures of purple and green sulfur bacteria. These anoxygenic phototrophs play crucial roles in the biogeochemical cycling of sulfur. In addition to being photosynthetic purple sulfur bacteria also have a chemosynthetic metabolism (Bryant & Frigaard, 2006; Madigan, 2003; Overmann, 2001; Pfenning, 1987). Photosynthetic process of purple sulfur bacteria differs from that of green plants in respect of photochemical reduction of CO₂ with hydrogen which is ultimately derived, not from water as in green plants, but from H₂S. But purple non sulfur bacteria utilizing (needed for phototrophic growth by these organisms) no hydrogen sulfide, in addition to light source and anaerobicity. Hence the use of "non-sulfur" in purple non sulfur group name derived from no use of H₂S under photoautotrophic conditions (Van Niel, 1929, 1931).

Van Niel (1944), reported that purple bacteria are characterized with a complex pigment system, made up of a green pigment, "bacteriochlorin" and one or more red pigments, "bacteriopurpurin." Diagnostically, these were distinguished by the occurrence of sulfur droplets in the cells by their accumulation in the external environment and fundamental difference of autotrophic and heterotrophic modes of life (Holt *et al.*, 1994; Imhoff & Truper, 1992; Jansen & Harfoot, 1991; Pfenning, 1977; Pfenning & Truper, 1974).

Hiraishi *et al.* (1984), examined fifty five strains of 13 species of purple bacteria *Rhodospirillaceae* and one strain of *Chromatium vinosum* for presence and composition of isoprenoid quinine. The author also discussed significance of quinine system in *Rhodospirillaceae* taxonomy and divided the bacteria into five categories based on their predominant quinine pattern.

10.2 Nature of the bacterial pigments

Presence of bacteriochlorophyll **a** and carotenoids of spirilloxanthin series have been also detected by spectroscopic analyses. Ubiquinone-10 was found to be major quinine. A clone library also showed that all of the clones derived from the members of the genera *Rhodobacter* and *Rhodopseudomonas*. The dominant phototrophic bacteria identified by studying 16S rRNA and *pufM* gene sequence information were *Rhodopseudomonas* and *Rhodobacter* (Brock & Madigan, 1991; Imhoff & Truper, 1998; Madigan, 2003). The investigation concluded that *Rhodopseudomonas* isolates had been reported to have a wider spectrum of carbon utilization and higher affinity for acetate than *Rhodobacter* isolates. This was demonstrated by oxygen uptake with lower fatty acids. A laminated mitochondria-like structure, resembling the chloroplast of higher plants has been found the pigment bearing portion of the *Rhodospirillum rubrum* (Nianzhi *et al.*, 2003; Niklowitz & Drews, 1955; Okubo *et al.*, 2006). Disrupted cells of *Rhodospirillum rubrum* yield discrete subcellular particles with a sedimentation constant of 190S and a diameter, when dried on a membrane, of about 1100Å. Since these units were found to contain all of the photosynthetic pigments of the cell, they were accordingly named chromatophores (Padree *et al.*, 1952; Schachman *et al.*, 1952; Yasa *et al.*, 2006). Due to intracellular deposition of sulfur and presence of pigments the bacteria are called as purple sulfur bacteria with purple or violet growth.

10.3 Purple non-sulfur bacteria and their natural occurrence

Laboratory culture of purple non-sulfur bacteria appear as pink, violet, to deep-red (Bryant & Frigaard, 2006; Melis, 2005; Proctor, 1997).

Lake Fryxell of Antarctica, show extensive diversity and highly stratified distribution of purple non-sulfur bacteria, as determined by analysis of a photosynthesis-specific gene, *pufM*. Enrichment cultures for purple bacteria from the Lake have been found to yield two morphotypes possessing gas vesicles and buoyancy structures previously not reported in purple non-sulfur bacteria. These structures have been explained necessary for the organisms to position themselves at specific depths within the nearly freezing water column (Jones *et al.*, 1998; Yasa *et al.*, 2006). Wide variety of photosynthetic purple and green bacteria has been isolated from cool drink refilling stations' wastewater. A fastest growing isolate of a *Rhodopseudomonas* sp. has been reported to produce hydrogen gas in the presence of light and its Immobilized cells yielded significant amounts of hydrogen from both sewage and wastewater. A number of microbes can metabolize conversion of water and carbon monoxide into hydrogen and carbon dioxide. Rate of CO conversion and H₂ production performed on trickle-bed reactor (TBR). Overall performance of reactor controlled by liquid recirculation rate and reactor support material both affects the mass transfer coefficient. A good agreement was obtained between two reactor scales after comparing simple reactor and TBR (Karr *et al.*, 2003; Sunita, & Mitra, 1993; Wolfrum & Watt, 2002).

Purple non sulfur bacteria have been described to be present in relatively high numbers (10^5 - 10^7 viable cells/ ml) in surface water of ditches, paddy fields and tide pools under oxygen-limited conditions. Whereas in eutrophic pond and river waters where sufficient amount of oxygen is present they have been demonstrated to be absent or found in small numbers. However, activated sludge and other aquatic environments mainly have facultative aerobic phototrophic purple non sulfur bacterial flora richness and diversity of which depends on organic nutrients composition of the waste water (Hiraishi & Kitamura, 1984; Oda *et al.*, 2003; Van Ginkel & Sung, 2001).

Okubo *et al.* (2006), while studying microbial mat of swine waste ditch reported that wastewater of the ditch contained acetate and propionate as major carbon nutrients based upon independent biomarker and molecular methods as well conventional cultivation methods, these authors revealed that the microbial mats were dominated by rod shaped cells containing intracytoplasmic membranes and small number of oval cells with vesicular internal membrane.

10.4 Appealing characteristics of phototrophic bacteria

Photosynthetic bacteria evolve hydrogen at much higher rates than do other classes of photosynthetic microorganisms. In addition, they can metabolize common biomass waste material, genetically may be easily manipulated to enhance rate of hydrogen production, grow rapidly, use both visible and near infrared light rays and tolerate harsh environments. Photosynthetic bacteria show vigorous evolution of H₂ gas when DL-malate or DL-lactate is used as an electron donor (Fascetti & Todini, 1995; Federov *et al.*, 1998; He *et al.*, 2005). Various agricultural products and wastes have been used as substrates for photosynthetic bacteria and the non-sulfur purple photosynthetic bacteria producing hydrogen from raw starch, corn, potato, or cassava as well as soluble starch under phototrophic conditions have been described (Buranakarl *et al.*, 1985; Ike *et al.*, 1996, 1998; Weaver *et al.*, 1979).

Hydrogen production by *Rhodospirillum rubrum* with lactate containing wastes, including yogurt waste and whey has been reported. While soluble starch and cooked cassava starch have been described for the growth of *Rhodopseudomonas gelatinosa* to produce vitamin B₁₂, ubiquinone and single cell protein respectively (Noparatnaraporn *et al.*, 1983; Sasaki & Nagar, 1979; Zurrer & Bachofen, 1979).

Besides the H_2 production, successful cultivation of the fastidious anaerobes on natural and preferably agroindustrial wastes has opened new gate for the production of single-cell protein (Honda, *et al.*, 2006; Robert & Wolfe, 1970; Weaver, *et al.*, 1975). Further purple non-sulfur bacteria like *Rhodobacter sphaeroides* O.U. 001 produce useful by product in addition to hydrogen gas when grown anaerobically. Poly- β -hydroxy (PHB) has been reported to be produced in maximum concentration when bacteria have anaerobically grown in standard growth media containing L-malic acid, sodium glutamate and 30% wastewater from sugar refinery (Yigit *et al.*, 1999). Wastewater from sugar refinery has been partially replaced carbon source of bacterial growth medium (Arik *et al.*, 1996; Yetis *et al.*, 1998). It is pertinent here to stress another applicable offshoot of the purple non-sulfur bacterial metabolism that PHB is a biodegradable thermoplastic that can be synthesized during unfavorable growth conditions by a wide range of bacteria (Byrom, 1987; Page, 1989; Kim *et al.*, 1994; Yamagishi, 1995).

Anderson and Dawes (1990) reported that in addition to some important medical applications PHB can be used to construct biodegradable carriers for long term dosage of herbicides and insecticides, packaging containers, bottles and bags.

10.5 Factors influencing production of H_2 by purple non-sulfur bacteria

Like any microbiological process performance parameters including pH, temperature, hydraulic retention time, seed sludge, nutrients, inhibitors, reactor design, and the means used for lowering hydrogen partial pressure are very important (Chen *et al.*, 2001; Fang & Liu, 2002; Khanal *et al.*, 2004; Lay *et al.*, 2000; Lay, 2001). As for example, for the optimizing the cultivation of the non-sulfur purple bacteria over accumulation of dissolved hydrogen in the liquid and high hydrogen partial pressures are thought to inhibit the process of hydrogen production (Chenlin & Herbert, 2007; Doremus *et al.*, 1985; Fennell & Gossett, 1998; Pauss *et al.*, 1990).

Infact, various factors have been studied in relation to bacterial hydrogen production including enzymes, of the process and inhibitory effects of NH_4 on gas production (Kim *et al.*, 1980; Koku *et al.*, 2003; Yoch & Gotto, 1982; Zhu *et al.*, 2001).

Besides the identification of proper cultivation strategies for obtaining higher and/or continuous yield potential/nature of the organism is of prime importance. For instance mutants of *Rhodospseudomonas palustris* capable of producing hydrogen constitutively, even in the presence of ammonium has been reported. It is pertinent to note here that wild-type cells do not accumulate detectable amounts of hydrogen in the presence of ammonium. Two purple non sulfur bacteria *Rhodospseudomonas palustris* and *Rhodobacter sphaeroides* grow with taurine as a sole electron donor, sulfur and nitrogen sources (Oda *et al.*, 2003; Qian *et al.*, 2002; Rey *et al.*, 2007).

Bao (2002) reported that *Rhodospseudomonas palustris* Z strain produced maximum H_2 by using acetate as carbon source and electron donor. The author also concluded that temperature, light intensity and acetate and glutamate concentrations significantly affected hydrogen photo evolution and cell growth. Rate of hydrogen production was found to be inversely related to substrate concentration, while directly to cell growth.

Efficiency of conversion of light energy to hydrogen is the key factor for the realization of hydrogen production from biological systems (Barbosa *et al.*, 2001; Kondo *et al.*, 2002; Shi & Yu, 2005). Batch tests using mixed cultures have demonstrated that very low pH's and high substrates, such as starch concentrations can reduce biohydrogen production (Liu & Shen, 2004; Van Ginkel & Sung, 2001; Zhang & Shen, 2006).

Regarding effect of light intensity on hydrogen production by photosynthetic bacteria *Rhodospseudomonas sp.* has been demonstrated to produce highest volume of hydrogen at a production rate of $25 \text{ ml H}_2 \text{ l}^{-1} \text{ h}^{-1}$, under a light intensity of $680 \mu\text{mol photons m}^{-2} \text{ s}^{-1}$. Decrease in the electron donor concentration organic acid resulted in decreased hydrogen evolution (Barbosa *et al.*, 2001; Fang *et al.*, 2006; Miyake *et al.*, 1999; Najafpour *et al.*, 2004; Oh *et al.*, 2004). Light dependent hydrogen production was first observed by *Rhodospirillum rubrum* in a media containing dicarboxylic acids of the citric acid cycle and either glutamate or aspartate as nitrogen sources. Hydrogen is not evolved, however, when nitrogen is provided in the form of ammonium salts, which repress synthesis of the hydrogen-evolving system (Barbosa *et al.*, 2001; Gest & Kamen, 1949a, 1949b; Hillmer & Gest, 1976; Ormerod *et al.*, 1961).

Concerning the illumination patterns for phototrophic bacterial growth it has been claimed that single-step illumination method provides an appropriate simulation of sunlight and its dependent hydrogen production. While indoor hydrogen production rate found to be independent of the mode of illumination. However, actual outdoor research has been considered difficult owing to the fluctuation of sunlight due to the weather time of the day solar spectrum etc. (Katsuda *et al.*, 2006; Kim *et al.*, 1987; Noparatnaraporn *et al.*, 1982; Novak *et al.*, 2004).

10.6 Mechanism of biological H_2 production

Amongst microbial diversity strict anaerobes and facultative anaerobic chemoheterotrophes are efficient producers of hydrogen. However, lower rate of hydrogen evolution by fermentative processes necessitates research for improving yield (Kim *et al.*, 2004; Nath & Das, 2004). Accumulation of hydrogen and other degradation byproducts during fermentation however can make the hydrogen-acetate reaction unfavorable leading to solvent production (Bahl *et al.*, 1982; Fond *et al.*, 1985; Grupe & Gottchalk, 1992; Jones & Wood, 1986).

Such investigations advocate the necessity of simultaneous removal of H_2 from a fermentation system. Thus for higher yield of hydrogen, a system is capable of removing H_2 before its accumulation to the level where repression of its production comes and to prevent interspecies hydrogen transfer leading to methanogenesis, would have to be developed.

Various attempts have been made to enhance hydrogen production by using proper cultivation conditions, such as provision of nitrogen atmosphere, and various organic acids as electron donors (Buranakarl *et al.*, 1988; Kim *et al.*, 1981; Mizuno *et al.*, 2000; Segers & Verstraete, 1983; Watanabe *et al.*, 1979).

Anaerobic photosynthetic bacterium, *Rhodospirillum* has been evaluated for bioconversion of syngas (synthesis gas) to hydrogen in continuous stirred tank bioreactor utilizing acetate as a carbon source upto period of two months. Such continuous process have been considered as alternative method of conventional Fischer-Tropsch synthetic reaction for the conversion of syngas into hydrogen (Miyake *et al.*, 1982; Najafpour *et al.*, 1995; Younesi *et al.*, 2008). Predominant commercial technology for syngas has been steam methane reforming, in which methane and steam were catalytically and endothermically converted to hydrogen and carbon monoxide. *Rhodospirillum rubrum* the purple non-sulfur anaerobic bacterium, is capable of catalyzing the Fisher-Tropsch type reaction and water gas shift reaction (Barbosa *et al.*, 2001; Czerink *et al.*, 2000).

Rhodospirillum rubrum has been reported for CO uptake with faster growth and higher cell dry weight as compared to other hydrogen producing microorganisms (Koku *et al.*, 2002,

2003; Lee *et al.*, 2002). It is interesting to note three times faster rate of carbon monoxide (CO) consumption than that of acetate. Two species of purple non sulfur bacteria, *Rhodopseudomonas gelatinosa* and *Rhodospirillum rubrum* are known to perform the water- gas shift reaction to produce hydrogen (Klasson *et al.*, 1990; Najafpour *et al.*, 2003, 2004; Oh *et al.*, 2002, 2004).

In certain bacterial strains, like massive non-sulfur photosynthetic bacterium (*Rhodovulum* sp.) rate of hydrogen production depends on light and addition of a small amount of oxygen (Maeda *et al.*, 2003; Matsunaga *et al.*, 2000). Four times higher rate of hydrogen production under microaerobic conditions as compared to anaerobic conditions, emphasizes the need of but little oxygen in such processes. Bacterium *gelatinosus* CBS has been described for CO oxidation and equal rates of H₂ production rate of H₂ in light and dark conditions in the presence of electron transport uncoupler carbonyl-cyanide m-Chlorophenylhydrazine (CCCP) (Fascetti & Todini, 1995; Federov *et al.*, 1998; He *et al.*, 2005; Maness *et al.*, 2004; Matsunaga *et al.*, 2000).

A modified pour plate technique with an overlay of wax has been worked out for isolation and enumeration of purple non-sulfur bacteria (PNSB) with equal efficiency as that of agar shake culture. Owen and respirometric methods can be choice for evaluating biological production of hydrogen from fermentation in batch tests by using different substrate. However, 43% more hydrogen gas has been reported to be produced by respirometric method. Comparable hydrogen conversion efficiencies for sucrose and molasses and much lower for lactate and cellulose have been documented (Archana *et al.*, 2004; Logan, 2002).

Regarding the provision of photons, Hai *et al.* (2000) have described use of a low-cost closed tubular glass photobioreactor for cultivations of axenic/ anoxygenic phototrophic bacteria, oxygenic phototrophic cyanobacterium and microalgae.

10.7 Treatment of wastewater by purple non-sulfur bacteria

Various agricultural/industrial wastes containing organic acids and sugar residues have been identified and used as feedstocks for microbial fermentations designed to yield value added products (Yetis *et al.*, 2000; Yigit *et al.*, 1999, Zhu *et al.*, 1999, 2002). Besides the availability of rich diversity of other microbes for such fermentative processes phototrophic, purple non-sulfur bacteria, have to been exploited for example they have been explored to treat odorous swine based water (Kim *et al.*, 2004; Nath & Das, 2004).

Likewise purple non-sulfur bacteria have been described for treatment of domestic and industrial effluents of varying chemical nature (Lay, 2001; Najafpour *et al.*, 2006; Nakashimada *et al.*, 2002; Nath & Shukla, 1997; Zhu *et al.*, 1995).

10.8 Role of different enzymes in hydrogen production

Direct and efficient photoproduction of H₂ gas by biological means have encountered several challenges. In this regard sensitivity of hydrogenases (the H₂ evolving enzyme) to O₂ and different approaches to overcome the enzyme's limitation has been emphasized. Simultaneous production of hydrogen and oxygen gas have been demonstrated for a nitrogen fixing cyanobacterium, *Anabaena cylindrica* in an argon atmosphere for several hours (Asada *et al.*, 1985; Miyake *et al.*, 1989; Miyamoto *et al.*, 1979; Weissman & Benemann, 1977; Wolk *et al.*, 1994).

Biological nitrogen fixation is a major route for hydrogen production by purple photosynthetic bacteria in which nitrogenase act as reducer of atmospheric nitrogen to

ammonia with the concomitant production of molecular hydrogen. However, it is rather inefficient process because about 75% of the reductant consumed by the nitrogenase is used to generate ammonia (Takabatake *et al.*, 2004; Zhu *et al.*, 2001). Albeit some of the strains have been isolated of purple photosynthetic bacteria in which hydrogen production is necessary for growth and independent of nitrogen fixation (Benemann & Weare, 1974; Ghirardi *et al.*, 2005; Miyake *et al.*, 1989; Proctor, 1997).

Many bacteria contain enzymes (hydrogenases) that can produce hydrogen during the fermentation of a variety of substrates. ATP is produced by substrate level or electron transport phosphorylation, but the ATP yields of fermentation are quite low as compared to those of aerobic oxidation reactions. Fermentation reactions can produce many different end products such as hydrogen, acetate, ethanol, and others. The hydrogen-acetate couple produces more ATP per mole of substrate than alcohols, such as ethanol and butanol, and represents energetically a “preferred” bacterial fermentation product for a sugar. The green alga, *Scenedesmus*, also produces molecular hydrogen under light after being kept under anaerobic conditions (Asada & Miyake, 1999; Florin *et al.*, 2001; Gaffron and Rubin, 1942; Gottschalk, 1986).

Unique type of hydrogenase activity found in some photosynthetic bacteria that function in darkness to shift CO and H₂O into H₂ and CO₂ has been exploited in hollow-fiber and bubble-train bioreactors employing immobilized and free-living bacteria. These efforts proven effective for enhancing the mass transfer of CO (Mao *et al.*, 1986; Miyake & Kawamura, 1987). Occurrences of these biological processes at ambient temperatures and pressures requires minimum energy inputs and thus appear promising for low cost are need for the process developments (Klasson *et al.*, 1992; Markov & Weaver, 2008; Najafpour *et al.*, 2004).

10.9 Implication of phototrophs in environmental clean up and upgradation

Constructed microbial mats including photo-organotrophic purple non-sulfur bacteria have been used for bioremediation of heavy metals and organic chemical pollutants. A gram-negative rod shaped bacterium, characterized with production of dark red culture under phototrophic conditions, budding, bacteriochlorophyll a and carotenoids has been found to possess multiple metal resistances and to be effective in the reductive removal of Cr (VI) and the degradation of 2,4,6-trichlorophenol (Mehrabi *et al.*, 2001; Miyoshi, 1997; Moucha *et al.*, 2003; Okubo *et al.*, 2006).

Production of hydrogen gas has been reported for anaerobes, facultative anaerobes, aerobes, methylotrophs and photosynthetic bacteria. Anaerobic *Clostridia* are potential producers of H₂ (Cohen *et al.*, 1985; Taguchi *et al.*, 1995; Yokoi *et al.*, 1998). Spontaneous production of H₂ from formate and glucose by immobilized *Escherichia coli* showed 100% and 60% efficiencies, respectively. *Enterobacteriaceae* produce H₂ at similar efficiency range from different mono-saccharides (Fabiano & Perego, 2002; Nakashimada *et al.*, 2002; Tanisho & Ishiwata, 1995; Yokoi, *et al.*, 1997, 1998, 2001). Among methylotrophs, methanogenes, rumen bacteria and thermophilic archae, *Ruminococcus albus*, are promising. Photosynthetic *Rhodospirillum rubrum* produces 4, 7, and 6 mol of H₂ from acetate, succinate and malate, respectively. Excellent productivity (6.2 mol H₂/mol glucose) by co-cultures has been achieved. *A. cylindrica* produced H₂ (20 ml/g dry wt/h) continually for 1 year. *Synechococcus* sp. has a high potential for H₂ production in fermentors and outdoor cultures (Aoyama *et al.*, 1996; Miyake & Asada, 1996; Miyake *et al.*, 1992, 1996). Simultaneous productions of oxychemicals and H₂ by *Klebsiella* sp. and by enzymatic methods have also been attempted. The fate of H₂

biotechnology is presumed to be dictated by the stock of fossil fuel and state of pollution in future (Gorman, 2002; Koku *et al.*, 2002; Nandi & Sengupta, 1998). Mirza (unpublished data) has successfully cultivated PNSB employing sugarcane bagasse and food industrial waste waters for the production of biohydrogen, essentially following the scheme depicted in Fig.3.

Of the above described nutrient diversity of the phototrophic bacteria (Photoheterotrophes) are highly relevant for upgradation of food industrial wastes. These heterotrophes from nature can use organic remnants in the effluents that can yield the photohydrogen as well as cell biomass to single cell protein. This process supporting aspect of biofuels fermentations has been described in detail at the end of bioethanol section.

Fig. 3. Schematic Description of Anaerobic Bioreactor for Hydrogen Production

11. Conclusions & recommendations

Bacterial and yeast isolates capable of simultaneous saccharification and ethanol fermentation of agro-industrial wastes such as sugarcane bagasse, an industrial cellulosic waste material, may be exploited to convert the very stable carbohydrate material to its monomeric constituents and the biofuel. The consolidated processing of the substrate (sugarcane bagasse) employing mono as well as co-cultures of the microorganisms can be escalated by identifying a suitable low-cost or preferably value-less or even having a negative value substrate that can act as nutritional supplement. Fortification of the bagasse suspensions with processed yogurt whey gave fruitful results in terms of the magnificent microbial growths and ethanol yields (Chaudhary, 2008). Further the ferment remnants by virtue of their relative higher protein/carbohydrate ratio as compared to the intact substrate may find their involvement in raising animal feed from otherwise, an agro-waste and an environmental issue. Identifying the nature and mode(s) of generation of fermentation inhibitors following different pretreatments of lignocellulosic biomass appear to highlight hindrances at the industrial level bioconversion of such substrates to biofuel. Removal or developing the inhibitors detoxification agents, both microbial and/or chemical appears imperative. Testing the reported bacterial and yeast isolates for their detoxification potential and tolerance levels for the inhibitors formed during various pretreatments of the bagasse would be major attribute defining the process development.

Albeit the largest renewable resource, the lignocellulosic matter, is recycled in the nature, the process, which directly and/or indirectly supports its own regeneration too within the biosphere. However, owing to slow turn over rates of the huge and abundantly found piled up reservoirs encountered both in natural ecosystems and agro-industrial sectors which represent a pollutant in select situations allow and demand its biotechnological utilizations, respectively. The former notion reminds, in a real sense, using water at human scale from an ocean and fearing decrease in the water to a level that may disturb the ocean.

Whilst the saccharification and ethanol fermentation of various lignocellulosic materials have been and are being reported by different workers from different regions of the world. The research in this area should be further promoted and encouraged. As more diverse data are required to extract valuable information, which hopefully would be employed to make the dream, obtaining biofuel from lignocellulosic material, at commercial level, a reality.

Likewise, biotechnological exploitation of purple non-sulfur bacteria for obtaining H_2 following their cultivation in agro/food industrial waste waters appears promising. Heterotrophic nature of such microbes dictates simultaneous provision of H_2 source as well as removal of organic load from agro-industrial effluents which otherwise are the source and non-source pollutants of water bodies in many country. Well illuminated land areas throughout the year are also promising for development of photon based bioreactors in an cost-effective way. Biological hydrogen production a clean/rich energy source represents an exciting new area of technology development for bioenergy generation. Low cost, environmental acceptability, renewability and evolution of no CO_2 following combustion are attractive features of H_2 as compared to hydrocarbon fuels .

In addition to hydrogen production purple non-sulfur bacteria are applicable for treatment of wastewater for lowering the level of volatile fatty acids, organic matter and Biological oxygen demand. Cell mass of purple non-sulfur bacteria may be used as good alternate of manure, fish feed or agricultural supplement because of its richness in proteins and vitamins.

12. References

- Abraham, S., 2002. *Toward a more secure and cleaner energy future for America: national hydrogen energy road map: production, delivery, storage, conversion, applications, public education and outreach*. U.S. Department of energy, Washington D.C.
- Adams, M.W.W., 1990. The structure and mechanism of iron hydrogenases. *Biochimica et Biophysica Acta*, 1020: 115-145.
- Ahlan, A.W., 2005. *Microbiological conversion of waste fruits and vegetables into ethanol*. Ph.D.thesis Univ.Punjab.Lahore Pakistan.
- Ahn, Y., Park, E.J., Oh, Y.K., Park, S., Webster, G. & Weightman, A.J., 2005. Biofilm microbial community of a thermophilic trickling biofilter used for continuous biohydrogen production. *FEMS Microbiology Letters*, 249: 31-38.
- Alonso, P.W., Garzone, P. & Cornacchia, G., 2007. Agro-industry sugarcane residues disposal: the trends of their conversion into energy carriers in Cuba. *Waste Manag.*, 27: 869-885.
- Anderson, A.J. & Dawes, E.A., 1990. Occurrence, metabolism, metabolic role, and industrial uses of bacterial poly hydroxy alkanolates. *Microbiological Review*, 54: 450-472.

- Anderson, W.F., Peterson, J., Akin, D.E. & Morrison, W.H., 2005. Enzyme pretreatment of grass lignocellulose for potential high-value co-products and an improved fermentable substrate. *Appl. Biochem. Biotechnol.*, 124: 303-310.
- Aoyama, K., Miyake, M. & Yamada, J., 1996. Application of the vector, pKE4-9 carrying strong promoter to the expression of foreign proteins in *Synechococcus* PCC7942. *Journal of Marine Biotechnology*, 4(1): 64-67.
- Archana, A., Sasikala, Ch., Ramana, Ch. V. & Arunasri, K., 2004. "Paraffin wax-overlay of pour plate", a method for the isolation and enumeration of purple non-sulfur bacteria. *Journal of Microbiological Methods*, 59(3): 423-425.
- Arik, T., Gunduz, U., Yucel, M., Turker, L., Sedirolu, V. & Eroglu, I., 1996. Photoproduction of hydrogen by *Rhodobacter sphaeroides* O.U.001. *Proceedings of the 11th World Hydrogen Energy Conference, Stuttgart, Germany*, 3: 2417-2424.
- Armor, J.N., 1999. The multiple roles for catalysis in the production of H₂. *Applied Catal A: Gen*, 176: 159-176.
- Arooj, M.F., Han, S.K., Kim, S.H., Kim, D.H. & Shin, H.S., 2007. Sludge characteristics in anaerobic SBR system producing hydrogen gas. *Water Research*, 41: 1177-1184.
- Asada, Y. & Miyake, J., 1999. Photobiological hydrogen production. *Journal of Bioscience and Bioengineering*, 88(1): 1-6.
- Asada, Y., Tomizuka, N. & Kawamura, S., 1985. Prolonged hydrogen evolution by a cyanobacterium (blue-green alga), *Anabaena* sp. *Journal of Fermentation Technology*, 63: 85-90.
- Atiyeh, H. & Duvnjak, Z., 2002. Production of fructose and ethanol from sugar beet molasses using *Saccharomyces cerevisiae* ATCC 36858. *Biotechnol. Prog.*, 18: 234-239.
- Bahl, H., Andersch, W., Braun, K. & Gottschalk, G., 1982. Effect of pH and butyrate concentration on the production of acetone and butanol by *Clostridium acetobutylicum* grown in continuous culture. *Applied Microbiology and Biotechnology*, 14: 17-20.
- Ballesteros, I., Oliva, J.M., Saez, F. & Ballesteros, M., 2001. Ethanol production from lignocellulosic byproducts of olive oil extraction. *Appl. Biochem. Biotechnol.*, 93: 237-252.
- Bao, S.W.G.C.X., 2002. Hydrogen production from acetate by *Rhodospseudomonas palustris*. *Chinese Journal of Biotechnology*, 18(4): 486-91.
- Barbosa, M.J., Rocha, J.M.S., Tramper, J. & Wijffels, R.H., 2001. Acetate as a carbon source for hydrogen production by photosynthetic bacteria. *Journal of Biotechnology*, 85(1): 25-33.
- Basak, N. & Das, D., 2007. The prospect of purple non-sulfur (PNS) photosynthetic bacteria for hydrogen production: The present state of art. *World Journal of Microbial Biotechnology*, 23: 31-42.
- Benemann, 1996. Partial characteristics of hydrogen production by fermentative hydrogen producing bacterial strain B49. *Journal of nature biotechnology*, 14: 1101-1103.
- Benemann, J.R. & Weare, N.M., 1974. Hydrogen Evolution by Nitrogen-Fixing *Anabaena cylindrica* Cultures. *Science*, 184: 174-175.
- Benemann, J.R., 1997. Feasibility analysis of photobiological hydrogen production. *International Journal of Hydrogen Energy*, 22: 979-87.
- Bernstein, Winkler and Zierdt-Warshaw, 1996. *Addison - Wesley Environmental science. Ecology and human impact*. Addison - Wesley publishing Co. New York. USA.

- Bicho, P.A., Runnals, P.L., Cunnid, J.D. & Lee, H., 1988. Induction of xylose reductase and xylitol dehydrogenase activities in *Pachysolen cannothilus* and *Pichia stipitis* on mixed sugar. *Appl. Environ. Microbiol.* Washington, 1: 50-51.
- Biebl, H. & Drews, G., 1969. Das in-vivo-pektrum als taxonomisches Merkmal bei Untersuchungen zur Verbreitung von Athiorhodaceae. *Zentralbl Bakteriologie Parasitenkd. Infektionskr. Hyg. Abt. 2* (123): 425-452.
- Bockris, J.O'M., 1981. The economics of hydrogen as a fuel. *International Journal of Hydrogen Energy*, 6: 223-41.
- Bon, E.P.S., 1996. Ethanol production via enzymatic hydrolysis of sugarcane bagasse and straw. *Brazilian bioethanol project* Financial support. Ministry of science and technology/FINEP.
- Brock, T.D. & Madigan, M.T., 1991. *Biology of microorganisms*. 6th Ed. Prentice Hall, New York.
- Bryant, D.A. and Frigaard, N.U., 2006. Prokaryotic photosynthesis and phototrophy illuminated. *Trends in Microbiology*, 14 (11): 488.
- Budden, J.R. & Spencer, P.A., 1993. Tolerance to temperature and water quality for bacterial oxidation: the benefits of BacTech's moderately thermophilic culture. *FEMS Microbiology Reviews* 11: 191-196.
- Buranakarl, L., Cheng-Ying, F., Ito, K., Izaki, K. & Takahashi, H., 1985. Production of molecular hydrogen by photosynthetic bacteria with raw starch. *Agricultural and Biological Chemistry*, 49 (11): 3339-3341.
- Buranakarl, L., Ito, K., Izaki, K. & Takahashi, H., 1988. Purification and characterization of raw starch digestion amylase from non-sulfur purple photosynthetic bacteria. *Agricultural and Biological Chemistry*, 10(3): 173-9.
- Bustos, G., Ramirez, J.A., Garrote, G. & Vazquez, M., 2003. Modelling of the hydrolysis of sugarcane bagasse with hydrochloric acid. *Appl. Biochem. Biotechnol.*, 104: 51-68.
- Byrom, D., 1987. Polymer synthesis by microorganisms; Technology and economics. *Trend in Biotechnology*, 5: 246-250.
- Casper, M.S., 1978. *Hydrogen manufacture by electrolysis, thermal decomposition and unusual techniques*, NJ: Naves Data Corp, Park Ridge.
- Cecchi, F., Marcomini, A., Pavan, P., Fazzini, G. & Mata-Alvarez, J., 1989. Mesophilic digestion of the refuse organic fraction sorted by plant. Performance and kinetic. *Waste Management Research*, 8: 33-44.
- Chandrakant, P. & Bisaria, V.S., 1998. Simultaneous bioconversion of cellulose and hemicellulosic to ethanol. *Crit. Rev. Biotechnol.*, 18: 295-331.
- Chaudhary, N. & Qazi, J.I., 2006a. Microbiological saccharification and ethanol production from sugarcane bagasse. *Biotechnol.*, 5: 517-521.
- Chaudhary, N. & Qazi, J.I., 2007. Producing ethanol from cellulosic material – an economic strategy. 27th Pakistan Congress of Zoology, held at B.Z. University Multan, Pakistan (February 27 to March 1, 2007). Abstract pp. 158.
- Chaudhary, N. & Sharma, C.B., 2005. Production of citric acid and single cell protein from agrowaste. *National Academy Science Letter*, 28: 189-193.
- Chaudhary, N. 2008. Designing microbial consortium for ethanol production from sugarcane bagasse. *Ph.D Thesis* University of the Punjab, Lahore, Pakistan.
- Chen, C.C., Lin, C.Y. & Chang, J.S., 2001. Kinetics of hydrogen production with continuous anaerobic cultures utilizing sucrose as the limiting substrate. *Appl. Microbiol. Biotechnol.*, 57: 56-64.

- Cheng, K.K., Ge, J.P., Zhang, J.A., Ling, H.Z., Zhou, Y.J., Yang, M.D. & Xy, J.M., 2007. Fermentation of pretreated sugarcane bagasse hemicellulose hydrolysate to ethanol by *Pachysolen tannophilus*. *Biotechnol. Lett.*, 29: 1051-1055.
- Chenlin, L. & Herbert, F., 2007. Fermentative hydrogen production from wastewater and solid wastes by mixed cultures. *Critical Reviews in Environmental Science and Technology*, 37(1): 1-39.
- Choorit, W., Thanakoset, P., Thongpradistha, J., Sasaki, K. & Noparatnaraporn, N., 2002. Identification and cultivation of photosynthetic bacteria in wastewater from a concentrated latex processing factory. *Letters of Biotechnology*, 24: 1055-1058.
- Christen, P., Villegas, E. & Revah, S., 1994. Growth and aroma production by *Ceratocystis fimbriata* in various fermentation media. *Biotechnol. Lett.*, 16: 1183-1188.
- Claassen, P.A.M., Mars, A.E., Budde, M.A.W., Lai, M., van Niel, E.W.J. & de Vrije, T., 2006. Biological hydrogen production from biomass by thermophilic bacteria. *WHEC*, 16:13-16.
- Claassen, P.A.M., van Lier, J.B., Lopez, C.A.M., van Niel, E.W.J., Sijtsma, L., & Stams, A.J.M., 1999. Utilization of biomass for the supply of energy carriers. *Applied Microbiology and Biotechnology*, 52: 741-755.
- Cohen, A., Distel, B., van Deursen, A. & van Andel, J.G., 1985. Role of anaerobic spore-forming bacteria in the acidogenesis of glucose changes induced by discontinuous or low-rate fed supply. *A. van Leeuw Journal of Microbiology*, 51(2): 179-192.
- Cooper, P.E., Rands, M.B. & Woo, C-P., 1975. Sulphide reduction in felmongery effluents by red sulphur bacteria. *Journal of Water Pollution and Control Federation*, 47: 2088-2099.
- Cox, K. E., & Williamson, Jr. K. D., 1979. *Hydrogen: its technology and implications*. Boca Raton, Chemical Rubber Company Press, Florida.
- Coyne, M.S., 1999. *Soil Microbiology*. Delmar publishers 3 Columbia Circle, Box 15015 Albany, New York.
- Czerink, S., French, R., Feik, C. & Chorennet, E., 2000. Production of hydrogen from biomass-derived liquids. *Proceedings of the 2000 DOE hydrogen production Review*, Nrel/CP-570-28890.
- Czernik, S., French, R., Feik, C. & Chornet, E., 2002. Hydrogen by catalytic steam reforming of liquid byproducts from biomass thermoconversion processes. *Industrial & Engineering Chemistry Research*, 41: 4209-4215.
- Czuppon, T. A., Knez, S. A. & Newsome, D. S., 1996. *Othmer Encyclopedia of Chemical Technology*, Wiley, New York: P.884.
- Das, D. & Veziroglu, T. N., 2001. Hydrogen production by biological process: a survey of literature. *International Journal of Hydrogen Energy*, 26: 13-28.
- De-Castro, H.F, Oliveira, S.C. & Furlan, S.A., 2003. Alternative approach for utilization of pentose stream from sugarcane bagasse by an induced flocculant *Pichia stipitis*. *Appl. Biochem. Biotechnol.*, 105-108:547 - 555.
- Dickinson, R.E. & Cicerone, R.J., 1986. Future global warming from atmospheric trace gases. *Nature*, 319: 109-135.
- Dimmling, W. & Seipenbusch, R., 1978. Raw materials for the production of SCP. *Proc. Biochem.*, 13: 9-15.
- Dominguez, J.M., Gong, C.S. & Tsao, G.T., 1996. Pretreatment of sugarcane bagasse hemicellulose hydrolysate for xylitol production by yeast. *Appl. Biochem. Biotechnol.*, 57-58: 49-56.

- Doremus, M.G., Linden, J.C. & Moreira, A.R., 1985. Agitation and pressure effects on acetone and butanol fermentation. *Biotechnology and Bioengineering*, 27: 852-860.
- Du Toit, P.J., Olivier, P.L. & Bilijon, V., 1984. Sugarcane bagasse as a possible source of fermentable carbohydrates. I. Characterization of bagasse with regard to monosachride, hemicellulose and amino acid composition. *Biotechnol. Bioeng.*, 26: 1071-1078.
- Dunn, S., 2001. *Hydrogen futures: Towards a sustainable energy system* paper Worldwatch Institute, Washington, DC. 157.
- Enger, E.D. & Smith, B.F., 2002. *Environmental Science: A study of interrelationships*. McGraw Hill Co. Inc. New York NY 10020.
- Eroglu, E., Eroglu, I., Gündüz, U. & Yücel, M., 2009. Comparison of physicochemical characteristics and photofermentative hydrogen production potential of wastewaters produced from different olive oil mills in Western-Anatolia, Turkey. *Biomass and Bioenergy*, 33: 706-711.
- Evans, G., 2005. *Biowaste and biological waste treatment*. James & James Ltd. 35-37 William road London NW1 3ER, UK.
- Fabiano, B. & Perego, P., 2002. Thermodynamic study and optimization of hydrogen production by *Enterobacter aerogenes*. *International Journal of hydrogen Energy*, 27: 149-56.
- Fang, H. H. P. & Liu, Y., 2000. Anaerobic wastewater treatment in (sub-) tropical regions. In: *Proceedings of the Symposium on Establishment and Evaluation of Advanced water Treatment Technology Systems Using Functions of Complex Microbial Community*, Tokyo, March 6-8, Japan, 109-118.
- Fang, H., Li, C. & Zhang, T., 2006. Acidophilic biohydrogen production from rice slurry. *International Journal of Hydrogen Energy*, 31(6): 683-692.
- Fang, H.H.P. & Liu, H., 2002. Effect of pH on hydrogen production from glucose by a mixed culture. *Bioresource Technology*, 82: 87-93.
- Fang, H.H.P., Liu, H. & Zhang, T., 2002a. Characterization of a hydrogen producing granular sludge. *Biotechnology Bioengineering*, 78(1): 44-52.
- Fang, H.H.P., Zhang, T. & Liu, H., 2002b. Microbial diversity of a mesophilic hydrogen-producing sludge. *Applied Microbiology and Biotechnology*, 58(1): 112-118.
- Fardeau, M.L., Salinas, M.B., L'Haridon, S., Jeanthon, C., Verhe, F., Cayol, J.L., Patel, B.K.C., Garcia, J.L. & Ollivier, B., 2004. Isolation from oil reservoirs of novel thermophilic anaerobes phylogenetically related to *Thermoanaerobacter subterraneus* reassignment of *T. subterraneus*, *Thermoanaerobacter yonseiensis*, *Thermoanaerobacter tengcongensis* and *Carboxydrachium pacificum* to *Caldanaerobacter subterraneus* gen. nov., sp. Nov., comb. Nov. as four novel subspecies. *International Journal of Evolutionary Microbiology*, 54: 467-474.
- Farrell, A.E., Plevin, R.J., Turner, B.T., Jones, A.D., O'Hare, M. & Kammen, D.M., 2006. Ethanol can contribute to energy and environmental goals. *Science*, 311: 506-508.
- Fascetti, E. & Todini, O., 1995. *Rhodobacter sphaeroides* RV cultivation and hydrogen production in one and two-stage chemostat. *Applied Microbiology and Biotechnology*, 44: 330-305.
- Federov, A.S., Tsygankov, A.A., Rao, K.K. & Hall, D.O., 1998. Hydrogen photoproduction by *Rhodobacter sphaeroides* immobilized on polyurethane foam. *Biotechnology Letters*, 20: 1007-1009.

- Fennell, D.E. & Gossett, J.M., 1998. Modeling the production of and competition for hydrogen in a dechlorinated culture. *Environmental Science and Technology*, 32: 2450-2460.
- Florin, L., Tsokoglou, A. & Happe, T., 2001. A novel type of iron hydrogenase in the green alga *Scenedesmus obliquus* is linked to the photosynthetic electron transport chain. *J. Biol. Chem.*, 276: 6125-6132.
- Fond, O., Matta-Ammouri, G., Petitdemange, H. & Engasser, J. M., 1985. The role acids on the production of acetone and butanol by *clostridium acetobutylicum*. *Applied Science and Technology*, 22: 195-200.
- Fujita, Y., Ito, J., Ueda, M., Fukuda, H. & Kondo, A., 2004. Synergistic saccharification and direct fermentatio to ethanol of amorphous cellulose by use of an engineered yeast strain co-displaying three types of cellulolytic enzyme. *Environ. Microbiol.* 70: 1207-1212.
- Gaffron, H. & Rubin, J., 1942. Fermentative and photochemical production of hydrogen in algae. *Journal of General Physiology*, 26: 219-240.
- Gest, H. & Kamen, M. D. 1949b. Studies on the metabolism of photosynthetic bacteria IV. Photochemical production of molecular hydrogen by growing cultures of photosynthetic bacteria. *Journal of Bacteriology*, 58: 239-245.
- Gest, H. & Kamen, M. D., 1949a. Photoproduction of molecular hydrogen by *Rhodospirillum rubrum*. *Science*, 109: 558-559.
- Gest, H., Kamen, M.D. & Bregoff, H.M., 1950. Studies on the metabolism of photosynthetic bacteria. Photoproduction of hydrogen and nitrogen fixation by *rhodospirillum rubrum*. *Journal of Biology and Chemistry*, 182: 153-170.
- Getha, K., Chong, V.C. & Vikineswary, S., 1998. Potential use of the phototrophic bacteria, *Rhodopseudomonas palustris* as an aquaculture feed. *Asian Fish Science*, 10: 223-232.
- Ghirardi, M.L., King, P.W., Posewitz, M. C., Ching M.P., Fedorov, A., Kim, K., Cohen, J., Schulten, K. & Seibert, M., 2005. Approaches to developing biological H₂-photoproducing organisms and processes. *Biochemical Society transactions*, 33(1): 70-72.
- Goldemberg, J. & Macedo, I.C., 1994. Brazilian alcohol program – an overview. *Energy for Sustainable Development*, 1: 17-22.
- Goldemberg, J., 2007. Ethanol for a sustainable energy future. *Science*, 315: 808-810.
- Gorman, J., 2002. A Cheap, unlimited hydrogen production method for the third world discovered. *Biological Production of Hydrogen fuel*. Science News, 12 October.
- Gottschalk, G., 1986. *Bacterial metabolism*. 2nd edition. Springer: New York.
- Govindaswamy, S. & Vane, L.M., 2006. Kinetics of growth and ethanol production on different carbon substrates using genetically engineered xylose-fermenting yeast. *Bioresour. Technol.* [Epub ahead of print].
- Gray, K.A., Ahao, L. & Emptage, M., 2006. Bioethanol. *Curr. Opin. Chem. Biol.*, 10: 141-146.
- Greenbaum, E., 1990. Hydrogen production by photosynthetic water splitting. In: *Hydrogen energy progress VIII. Proceedings 8th World Hydrogen Energy Conference*, (eds, T. N. Veziroglu., P. K. Takashashi), Pergamon Press, Hawaii, New York, 743-54.
- Greer, D., 2005. Creating cellulosic ethanol: spinning straw into fuel. *Cellulosic Ethanol*. [Epub ahead of print].
- Gregoire-Padro, C. E., 1998. Hydrogen: the once and future fuel. *Energy Fuels*, 12:1-2.

- Grupe, H. & Gottschalk, G., 1992. Physiological events in *Clostridium acetobutylicum* during the shift from acidogenesis to solventogenesis in continuous culture and presentation of a model for shift induction. *Applied and Environmental Microbiology*, 58: 3896-3902.
- Hai, T., Ahlers, H., Gorenflo, V. & Steinbuchel, A., 2000. Axenic cultivation of anoxygenic phototrophic bacteria, cyanobacteria and microalgae in new closed tubular glass photobioreactor. *Applied Microbiology and Biotechnology*, 53: 383-389.
- Hanada, S., 2003. Filamentous anoxygenic phototrophes in hot springs. *Microbes and Environment*, 18: 51-61.
- Hansel, A. & Lindblad, P., 1998. Towards optimization of *Cyanobacteria* as biotechnological relevant producers of molecular hydrogen a clean and renewable energy source. *Applied Journal of Microbiology and Biotechnology*, 50: 153-160.
- Hart, D., 1997. *Hydrogen Power: The Commercial Future of the Ultimate Fuel*. Financial Times Energy Publishing, London.
- Hawkes, F.R., Dinsdale, R., Hawkes, D.L. & Hussy, I., 2002. Sustainable fermentative hydrogen production: challenges for process optimization. *International Journal of Hydrogen Energy*, 27: 1339-1347.
- Hawkes, F.R., Hussy, I., Kyazze, G., Dinsdale, R. & Hawkes, D.L., 2007. Continuous dark fermentative hydrogen production by mesophilic microflora: principles and progress. *International Journal of Hydrogen Energy*, 32(2): 172-184.
- He, D., Bultel, Y., Magnin, J. P., Roux, C. & Willison, J. C., 2005. Hydrogen photosynthesis by *Rhodobacter capsulatus* and its coupling to PEM fuel cell. *Journal of Power Sources*, 141: 19-23.
- Hill, J., Nelson, E., Tilman, D., Polasky, S. & Tiffany, D., 2006. Environmental, economic and energetic costs and benefits of biodiesel and ethanol biofuels. *Proc. Natl. Acad. Sci. U.S.A.*, 103(30): 11206-11210.
- Hillmer, P. & Gest, H., 1976. H₂ metabolism in the photosynthetic bacterium *Rhodopseudomonas capsulata*: H₂ production by growing cultures. *Journal of Bacteriology*, 129(2): 724-731.
- Hiraishi, A. & Kitamura, H., 1984. Distribution of phototrophic purple non sulfur bacteria in activated sludge systems and other aquatic environment. *Bulletin of the Japanese Society of Scientific Fisheries*, 50(11): 1929-1937.
- Hiraishi, A. & Ueda, Y., 1994. *Rhodoplanes* gen. nov., a new genus of phototrophic bacteria including *Rhodopseudomonas rosea* as *Rhodoplanes roseus* comb. Nov. and *Rhodoplanes elegans* sp. Nov. *International Journal of Systematic Bacteriology*, 44: 665-673.
- Hiraishi, A., Hoshino, Y. & Kitamura, H., 1984. Isoprenoid quinone composition in the classification of *Rhodospirillaceae*. *Journal of General and Applied Microbiology*, 30: 197-210.
- Hiraishi, A., Morishima, Y. & Kitamura, H., 1991. Use of isoprenoid quinone profiles to study the bacterial community structure and population dynamics in the photosynthetic sludge system. *Water and Science Technology*, 23: 937-945.
- Hiraishi, A., Shi, J. L. & Kitamura, H., 1989. Effects of organic nutrient strength on purple non sulfur bacterial content and metabolic activity of photosynthetic sludge for waste water treatment. *Journal of Fermentation and Bioengineering*, 68: 269-276.

- Hisada, T., Okamura, K. & Hiraishi, A., 2007. Isolation and characterization of phototrophic purple nonsulfur bacteria from *Chloroflexus* and Cyanobacterial mats in hot springs. *Microbes and Environment*, 22(4): 405-411.
- Ho, N. W., Chen, Z., Brainard, A.P. & Sedlak, M., 1999. Successful design and development of genetically engineered *Saccharomyces* yeasts for effective co-fermentation of glucose and xylose from cellulosic biomass to fuel ethanol. *Adv. Biochem. Eng. Biotechnol.* 65: 163-192.
- Hofbauer, H., 2007. Conversion technologies: gasification overview. In: *Proceedings of the 15th European Biomass Conference and Exhibition*. Berlin (Germany).
- Holm, H.W. & Vennes, I.W., 1970. Occurrence of purple sulphur bacteria in sewage treatment lagoon. *Applied journal of Microbiology*, 19: 988-996.
- Holt, G. J., Krieg, N. R., Sneath, P.H., Staley, J.T. & Williams, S.T., 1994. *Bergey's Manual of Determinative Bacteriology*, 9th ed. Williams and Wikins Co Baltimore.P. 787.
- Honda, R., Fukushi, K. & Yamamoto, K., 2006. Optimization of wastewater feeding for single-cell protein production in an anaerobic wastewater treatment process utilizing purple non-sulfur bacteria in mixed culture condition. *Journal of Biotechnology*, 125 (4): 565-573.
- Hongpattarakere, T. & Kittikun, A.H., 1995. Optimization of single-cell-protein production from cassava starch using *Schwanniomyces castellii*. *Biomedical and Life Science*, 11: 607-609.
- Hulshoff Pol, L. W. & Lettinga, G., 1986. New technologies for anaerobic wastewater treatment. *Water Science and technology*, 18(12): 41-53.
- Hussy, I., Hawkes, F.R., Dinsdale, R. & Hawkes, D.L., 2003. Continuous fermentative hydrogen production from a wheat starch co-product by mixed microflora. *Biotechnology and Bioengineering*, 84: 33-44.
- Iglesias, J. R., Castrillon, L., Maranon, E. & Sastre, H. 1998. Solid state anaerobic digestion of unsorted municipal solid waste in a pilot plant scale digester. *Bioresource Technology*, 63(1): 29-35.
- Ike, A., Saimura, C., Hirata, K. & Miyamoto, K., 1996. Environmentally friendly production of H₂ incorporating microalgal CO₂ fixation. *Journal of Marine Biotechnology*, 4: 47-51.
- Ike, A., Yoshihara, K., Nagase, h., Hirata, K. & Miyamoto, K., 1998. Algal CO₂ fixation and H₂ photoproduction,. In: *BioHydrogen* (ed. Zaborsky, O.R.), Plenum Press, London.p. 265-271.
- Imhoff, J.F. & Truper, H.G., 1992. The genus *Rhodospirillum* and related genera, In: *The prokaryotes*, 2nd ed. (eds. Balows, A., Truper, H.G., Dworkin, M., Harder, W. and Schleifer, K.H.), Springer-Verlag. New York, N.Y. 2141-2155.
- Imhoff, J.F. & Truper, H.G., 1998. The purple nonsulfur bacteria in *Bergey's Manual of Systematic Bacteriology*. Vol 3, (eds. Staley, J.T., Bryant, M.P., Pfennig, N. and Holt, J.G.), Williams and Wilkins Co. Baltimore.pp. 1658-1661.
- Imhoff, J.F., Hirashi, A. & Suling, J., 2005. Anoxygenic phototrophic purple bacteria. In: *Bergey's manual of systematic bacteriology* (eds., Brenner, D.J., Krieg, N.R., Staley, J.T. and Garrity, G.M.), 2nd ed., vol. 2. The proteobacteria, part A, introductory essays. Springer-Verlag, New York, N. Y. 119-132.
- Jansen, P.H. & Harfoot, C.G., 1991. *Rhodopseudomonas rosea* sp. nov., a new purple nonsulfur bacterium. *International Journal of Systematic Bacteriology*, 41(1): 26-30.

- Jones, B.E., Grant, W.D., Duckworth, A.W. & Owenson, G.G., 1998. Microbial diversity of soda lakes. *Extremophiles*, 2: 191-200.
- Jones, D. T. & Woods, D. R., 1986. Acetone-butanol fermentation revisited. *Microbiology Reviews*, 50: 484-524.
- Jung, G. Y., Jung, H. O. Kim, J. R., Ahn, Y. & Park, S., 1999. Isolation and characterization of *Rhodopseudomonas palustris* P4 which utilizes CO with the production of H₂. *Biotechnology Letters*, 21: 525-529.
- Kaiser, D., 1966. Contribution an l' etude de L'ecologic des bacteries photosynthetic. *Annales de l'Institut Pasteur / Virologie*, 111: 732-749.
- Kalia, V., Lal, S., Ghai, R., Mandal, M. & Chauhan, A., 2003. Mining genomic databases to identify novel hydrogen producers. *Trends in Biotechnology*, 21(4): 152-156.
- Kamel, B.S., 1979. Utilization of date carbohydrate as substrate in microbial fermentation. *Proc. Biochem.*, 14: 95-100.
- Kapdan, I.K. & Kargi, F., 2006. Bio-hydrogen production from waste materials, *Enzyme and Microbial Technology*, 38: 569-582.
- Karhumaa, K., Weidemann, B., Hagerdal, H.B., Boles, E. & Grauslund, G.M.F., 2006. Co-utilization of L-arabinose and D-xylose by laboratory and industrial *Sacchromyces cerevisiae* strains. *Microb. Cell Fact.*, 5:18.
- Karr, E.A., Sattley, M.W., Jung, D.O., Madigan, M.T. & Achenbach, L.A., 2003. Remarkable diversity of phototrophic purple bacteria in a permanently frozen Antarctic lake. *Applied and Environmental Microbiology*, 69(8): 4910-4914.
- Katsuda, T., Ooshima, H., Azuma, M. & Kato, J., 2006. New detection method for hydrogen gas for screening hydrogen-producing microorganisms using water-soluble wilkinson's catalyst derivatives. *Journal of Bioscience and Bioengineering*, 102(3):220-226.
- Katzen, R. & Fowler, D.E., 1994. Ethanol from lingo-cellulosic wastes with utilization of recombinant bacteria. *Appl. Biochem. Biotechnol.*, 45: 697 – 707.
- Khanal, S. K., Chen, W. H., Li, L. & Sung, S., 2004. Biological hydrogen production: effects of pH and intermediate products. *International Journal Hydrogen Energy*, 29: 1123-31.
- Kim, B.C., Lee, S.C., Lee, S.Y., Chang, H.N., Chang, Y.K. & Woo, S.I., 1994. Production of poly (3- hydroxybutyric acid) by fed-batch culture of *Alcaligenes eutrophus* with glucose concentration control. *Biotechnology and Bioengineering*, 43: 892-898.
- Kim, J. S., Ito, K. & Takahashi, H., 1980. The relationship between nitrogenase activity and hydrogen evolution in *Rhodopseudomonas palustris*. *Agricultural Biology Chemistry*, 44(4): 827-833.
- Kim, J.S., Ito, K. & Takahashi, H., 1981. Production of molecular hydrogen by *Rhodopseudomonas* sp. *Journal of Fermentation Technology*, 59(3): 185-90.
- Kim, J.S., Ito, K., Izaki, K. & Takahashi, H., 1987. Production of Molecular hydrogen by a semi-continuous outdoor culture of *Rhodopseudomonas sphaeroides*. *Agricultural and Biological Chemistry*, 51(4): 1173-1174.
- Kim, M.K., Choi, K-M., Yin, C-R., Lee, K-Y., Im, W-T., Lim, J. H. & Lee, S-T., 2004. Odorous swine wastewater treatment by purple non-sulfur bacteria, *Rhodopseudomonas palustris*, isolated from eutrophic ponds. *Biotechnology letters*, 26: 819-822.
- Kirk, R. E., Othmer, D. F., Grayson, M. & Eckroth, D., 1985. In *Concise Encyclopedia of Chemical Technology XIII*. Wiley-Inter-science, New York, 838-893.

- Klasson, K.T., Ackerson, M.D., Clausen, E. C. & Gaddy, J.L., 1992. Bioconversion of synthesis gas into liquid or gaseous fuels. *Enzyme and Microbial Technology*, 14: 602-608.
- Klasson, K.T., Cowger, J.P., Ko, C.W., Vega, J.L., Clausen, E.C. & Gaddy, J.L., 1990. Methane production of synthesis gas using mixed culture of *R. rubrum*, *M. barkeri* and *M. formicum*. *Applied Biochemistry and Biotechnology*, (24/25): 2273-2289.
- Kleihues, L., Lenz, O., Bernhard, M., Buhrke, T. & Friedrich, B., 2000. The H₂ sensor of *Ralstonia eutropha* is a member of the subclass of regulatory [NiFe] hydrogenase. *Journal of Bacteriology*, 182: 2716-2724.
- Kobayashi, M. & Tchan, Y. T., 1973. Treatment of industrial waste solutions and production of useful by-products using a photosynthetic bacterial method. *Water Resource*, 7: 1219-1224.
- Koku, H., Eroglu, I., Gunduz, U., Yucel, M. & Turker, L., 2002. Aspects of the metabolism of hydrogen production by *Rhodobacter sphaeroides*. *International Journal of Hydrogen Energy*, 27: 1315-1329.
- Koku, H., Eroglu, I., Gunduz, U., Yucel, M. & Turker, L., 2003. Kinetics of biological hydrogen production by the photoproduction bacterium *Rhodobacter sphaeroides* O. U. 001. *International Journal of Hydrogen Energy*, 28: 381-388.
- Kondo, T., Arakawa, M., Hirai, T., Wakayama, T., Hara, M., & Miyake, J., 2002. Enhancement of hydrogen production by a photosynthetic bacterium mutant with reduced pigment. *Journal of Bioscience bioengineering*, 93: 145-150.
- Kotsopoulos, T., Zeng, R. & Angelidaki, I., 2006. Biohydrogen production in granular up-flow anaerobic sludge blanket (UASB) reactors with mixed cultures under hyper-thermophilic temperature (70°C). *Biotechnology and Bioengineering*, 94(2): 296-302.
- Lamed, R.J. & Zeikus, J.G., 1980. Ethanol production by thermophilic bacteria: relationship between fermentation product yields of and catabolic enzyme activities in *Clostridium thermocellum* and *Thermoanaerobium brockii*. *J. Bacteriol.*, 144: 569-578.
- Laser, M., Schulman, D., Allen, S.G., Lichwa, J., Antal, M.J. Jr. & Lynd, L.R., 2002. Comparison of liquid hot water and steam pretreatments of sugarcane bagasse for biconversion to ethanol. *Bioresour. Technol.*, 81:33 – 44.
- Lavarack, B.P., Griffin, G.J. & Rodman, D., 2002. The acid hydrolysis of sugarcane bagasse hemicellulose to produce xylose, arabinose, glucose and other products. *Biomass and Bioenergy*, 23: 367-380.
- Lawford, H.G. & Rousseau, J.D., 2003. Cellulosic ethanol: alternative fermentation process designs with wild type and recombinant *Zymomonas mobilis*. *Appl. Biochem. Biotechnol.*, 105-108: 457-69.
- Lawford, H.G., Rousseau, J.D. & Tolan J.S., 2001. Comparative ethanol productivities of different *Zymomonas* recombinants fermenting oat hull hydrolysate. *Appl. Biochem. Biotechnol.*, 93: 133-146.
- Lay, J. J.; Lee, Y. J. & Noike, T., 2000. Feasibility of biological hydrogen production from organic fraction of municipal solid waste. *Water Research*, 33: 2579-2586.
- Lay, J.J., 2001. Modelling and optimization of anaerobic digested sludge converting starch to hydrogen. *Biotechnology and Bioengineering*, 68(3): 269-278.
- Lee, I. G., Kim, M. S. & Ihm, S. K., 2002. Gasification of glucose in supercritical water. *Industrial & Engineering Chemistry Research*, 41: 1182-1188.
- Levin, D.B., Pitt, L. & Love, M., 2004. Biohydrogen production: prospects and limitations to practical application. *International Journal of Hydrogen Energy*, 29: 173-185.

- Li, C. & Fang, H.H.P., 2007. Fermentative hydrogen production from wastewater and solid wastes by mixed cultures. *Critical Review of Environment and Science Technology*, 37: 1-39.
- Lin, Y. & Tanaka, S., 2006. Ethanol fermentation from biomass resources: current state and prospects. *Appl. Microbiol. Biotechnol.*, 69: 627-642.
- Lin, C. Y., Hung, C. H., Chen, C. H., Chung, W. T. & Cheng, L. H., 2006. Effects of initial cultivation pH on fermentative hydrogen production from xylose using natural mixed cultures. *Process Biochemistry*, 41: 1383-1390.
- Liu, C.F., Ren, J.L., Xu, F., Lin, J.J., Sun, J.X. & Sun, R.C., 2006. Isolation and characterization of cellulose obtained from ultrasonic irradiated sugarcane bagasse. *J. Agric. Food Chem.*, 54: 5742-5748.
- Liu, C.F., Sun, R.C., Qin, M.H., Zhang, A.P., Ren, J.L., Ye, J., Luo, W. & Cao, Z.N., 2007. Succinoylation of sugarcane bagasse under ultrasound irradiation. *Bioresour. Technol.*, [Epub ahead of print].
- Liu, G. & Shen, J., 2004. Effects of culture and medium conditions on hydrogen production from starch using anaerobic bacteria. *Journal of Bioscience and Bioengineering*, 98(4): 251-256.
- Lodhi, M. A. K., 1987. Hydrogen production from renewable sources of energy. *International Journal of Hydrogen Energy*, 12: 461-8.
- Logan, B. E., 2002. Biological hydrogen production measured in batch anaerobic respirometers. *Environmental Science and Technology*, 36(11): 2530-2535.
- Lynd, L.R., 1995. Fuel production biological. In: *Molecular Biology and Biotechnology* (Robert, A. Meyers, ed.), pp.331-333. VCH Publishers, Inc. New York, NY 10010, U.S.A.
- Lynd, L.R., Weimer, P.J., van Zyl, W.H. & Pretorius, I.S., 2002. Microbial cellulose utilization: fundamentals and biotechnology. *Microbiol. Mol. Biol. Rev.*, 66: 506-577.
- Macler, B., Pelroy, R., Bassham, J., 1979. Hydrogen formation in nearly stoichiometric amounts from glucose by a *Rhodospseudomonas sphaeroides* mutant. *Journal of Bacteriology*, 138: 446-452.
- Madigan, M.T., 2003. Anoxygenic phototrophic bacteria from extreme environments. *Photosyn. Res.*, 76: 157-171.
- Maeda, I., Miyasaka, H., Umeda, F., Kawase, M. & Yagi, K., 2003. Maximization of hydrogen production ability in high-density suspension of *Rhodovulum sulfidophilum* cells using intracellular poly(3-hydroxybutyrate) as sole substrate. *Biotechnology Bioengineering*, 81: 474-81.
- Maness, P.C., Huang, J., Smolinski, S., Tek, V. & Vanzin, G., 2004. Energy generation from the CO Oxidation-Hydrogen Production pathway in *Rubrivivax gelatinosus*. *Applied and Environmental Microbiology*, 71(6): 2870-2874.
- Mao, X.Y., Miyake, J. & Kawamura, S., 1986. Screening photosynthetic bacteria for hydrogen production from organic acid. *Journal of Fermentation Technology*, 64: 245-249.
- Markov, S.A. & Weaver, P.F., 2008. Bioreactors for H₂ production by purple non sulfur bacteria. *Applied Biochemistry and Biotechnology*, 145(1-3): 79-86.
- Martin, C., Galbe, M., Nilvebrant, N.I. & Jönsson, L.J., 2002. Comparison of the fermentability of enzymatic hydrolyzates of sugarcane bagasse pretreated by steam explosion using different impregnating agents. *Appl. Biochem. Biotechnol.*, 98-100: 699-716.

- Martinez, A., Rodriguez, M.E., York, S.W., Preston, J.F. & Ingram, L.O., 2000. Effects of $\text{Ca}(\text{OH})_2$ treatments "overliming" on the composition and toxicity of bagasse hemicellulose hydrolysates. *Biotechnol. Bioeng.*, 69: 526-536.
- Matsunaga, T., Hatano, T., Yamada, A. & Matsumoto, M., 2000. Microaerobic hydrogen production by photosynthetic bacteria in a double phase photobioreactor. *Biotechnology and Bioengineering*, 68(6): 647-651.
- Mehrabi, S., Ekanemesang, U. M., Aikhionbare, F. O., Kimbro, K. S. and Bender, J., 2001. Identification and characterization of *Rhodospseudomonas spp.*, a purple non-sulfur bacterium from microbial mats. *Biomolecular Engineering*, 18: 49-56.
- Melis, T., 2005. Integrated biological hydrogen production. *Proceeding International Hydrogen Energy Congress and Exhibition IHEC 2005*. Istanbul, Turkey.
- Meunchang, S., Panichsakpatana, S. & Weaver, R.W., 2005. Inoculation of sugar mill by-products compost with N_2 -fixing bacteria. *Plant and Soil*, 271: 219-225.
- Miller, G.T. Jr., 2003. *Environmental science working with the earth*. Brooks/Cole-Thomson Learning 511 Forest Lodge Road Pacific Grove, CA 93950, USA.
- Miyake, J. & Kawamura, S., 1987. Efficiency of light energy conversion to hydrogen by the photosynthetic bacterium *Rhodobacter sphaeroides*. *International Journal of Hydrogen Energy*, 39: 147-149.
- Miyake, J., Asada, Y. & Kawamura, S., 1989. Nitrogenase,. In: Biomass hand-book (eds. Kitani, O. and Hall, C.W.), Gordon and Breach Science Publishers, New york.362-370.
- Miyake, J., Igarashi, Y. & Roegner, M., 2004. Biohydrogen III. Renewable energy system by biological solar energy conversion. London: Elsevier, 1-187.
- Miyake, J., Matsunaga, T., & San Pietro, A., 2001. Biohydrogen II. An approach to environmentally acceptable technology London: Pergamon-Elsevier, 1-273.
- Miyake, J., Miyake, M. & Asada, Y., 1999. Biotechnological hydrogen production: research for efficient light energy conversion. *Journal of Bacteriology*, 70(1-3): 89-101.
- Miyake, J., Tomizuk, N. & Kamibayashi, A., 1982. Prolonged photohydrogen production by *Rhodospirillum rubrum*. *Journal of Fermentation Technology*, 60: 199-203.
- Miyake, M. & Asada, Y., 1996. Efficient transformation of a thermophilic cyanobacterium, *Synechococcus elongates*. *Journal of Marine Biotechnology*, 4: 113-116.
- Miyake, M., Kotani, H. & Asada, Y., 1992. Isolation and identification of restriction endonuclease, Sell from a cyanobacterium, *Synechococcus elongates*. *Nuclear Acids Research*, 20: 2605.
- Miyake, M., Yamada, J., Aoyama, K., Uemura, I., Hoshino, T., Miyake, J. & Asada, Y., 1996. Strong expression of foreign protein in *Synechococcus* sp. PCC7942. *Journal of Marine Biotechnology*, 4: 64-67.
- Miyamoto, K., 1993. Hydrogen production by photosynthetic bacteria and microalgae, p. In: *Recombinant microbes for industrial and agricultural applications* (eds. Murooka, Y. and Imanaka, T.). Marcel Dekker, Basel and Hong Kong, Inc., New York, 771-786.
- Miyamoto, K., Benemanu, J.R. & Hallenbeck, P.C., 1979. Nitrogen fixation by thermophilic blue-green algae (cyanobacteria): temperature characteristics and potential use in biophotolysis. *Applied Environmental Microbiology*, 37: 454-458.
- Miyoshi, M., 1997. Studien uber die Schwefelrasenbildung und die Schwefelbakterien der Thermen von Yumoto bei Nikko. *Zentralbl. Bakteriologie. Parasiten Infek. Abt.,2*: 526-527.

- Mizuno, O., Dinsdale, R., Hawkes, F.R., Hawkes, D.L. & Noike, T., 2000. Enhancement of hydrogen production from glucose by nitrogen gas sparging. *Bioresource Technology*, 73(1): 59-65.
- Moat, A.G., Foster, J.W. & Spector, M.P., 2004. *Microbial physiology*. Willey-Liss A John Wiley & Sons, Inc. publication replica press pvt. Ltd., India.
- Molina, J.W.F., Ripoli, T.C., Geraldi, R.N. & Amaral, J.R., 1995. Aspectos econômicos e Operacionais do Enfardamento de Resíduo de Colheita de Cana-de-Açúcar para Aproveitamento Energético. *STAB-Açúcar, Alcool e Subprodutos*, 13: 28.
- Molina, O.E., Perotti de Gálvez, N.I., Frigerio, C.I. & Córdoba, P.R., 1984. Planta piloto de Procesos Industriales microbiológicos, PROIMI, Avda Belgrano y Pje Caseros, 4000 S.M. de Tucumán, Argentina. [Epub ahead of print].
- Montgomery, R., 2004. Development of biobased products. *Bioresource Technology*, 91: 1-29.
- Morita, T.A. & Silva, S.S., 2000. Inhibition of microbial xylitol production by acetic acid and its relation with fermentative parameters. *Appl. Biochem. Biotechnol.*, 84-86: 801-808.
- Moucha, T., Linek, V. & Prokopova, E., 2003. Gas hold-up, mixing time and gas liquid volumetric mass transfer coefficient of various multiple- impeller configuration: Rushton turbine, pitched blade and techmix impeller and their combination. *Chemical Engineering Science*, 58(9): 1839-1896.
- Nagadomi, H., Kitamura, T., Watanabe, M. & Sasaki, K., 2000. Simultaneous removal of chemical oxygen demand (COD) phosphate, nitrate and H₂S in the synthetic sewage wastewater using porous ceramic immobilized photosynthetic bacteria. *Letters of Biotechnology*, 22: 1369-1374.
- Najafpour, G. D., Basu, R., Clausen, E. C. & Gaddy, G. L., 1995. Water-gas shift reaction for synthesis gas: a biological route. *International Journal of Engineering Science*, 6: 39-49.
- Najafpour, G., Younesi, H. & Mohamed, A.R., 2003. Continuous hydrogen production via fermentation of synthesis gas. *International Journal of Petrol Process.: Petrochemical. Coal Process*, 45(3-4): 154-158.
- Najafpour, G.D., Younesi, H. & Mohamed, A.R., 2004. Effect of organic substrate on hydrogen production from synthesis gas using *Rhodospirillum rubrum*, in batch culture. *Journal of Biochemical Engineering*, 21 (2): 123-130.
- Najafpour, G.D., Younesi, H. & Mohamed, A.R., 2006. A survey on various carbon sources for biological hydrogen production via water-gas reaction using photosynthetic bacterium *Rhodospirillum rubrum*. *Energy sources*, 28: 1013-1026.
- Nakada, E., Asada, Y., Arai, T. & Miyake, J., 1995. Light penetration into cell suspensions of photosynthetic bacteria and relation to hydrogen production. *Journal of Fermentation and Bioengineering*, 80(1): 53-57.
- Nakadomi, H., Hiromatsu, T., Takeno, K., Watanabe, M. & Sasaki, K., 1999. Treatment of aquarium water by denitrifying photosynthetic bacteria using immobilized polyvinyl alcohol beads. *Journal of Bioscience and Bioengineering*, 87: 625-629.
- Nakashimada, Y., Rachman, M.A., Kakizono, T. & Nishio, N., 2002. Hydrogen production of *Enterobacter aerogene* altered by extracellular and intracellular redox states. *International Journal of Hydrogen Energy*, 27: 1399-1405.
- Nandi, R. & Sengupta, S., 1998. Microbial Production of Hydrogen: An Overview. *Critical Reviews in Microbiology*, 24(1): 61-84.
- Nath, K. & Das, D., 2004. Improvement of fermentative hydrogen production: various approaches. *Applied Microbiology and Biotechnology*, 65(5): 520-529.

- Nath, S. & Shukla, V., 1997. A new approach to evaluate kinetic parameters and mass transfer coefficients in continuous stirred tank reactor. Application to antibiotic separations. *Chemical and Engineering Journal*, 65: 63-69.
- Negro, M.J., Manzanares, P., Ballesteros, I., Oliva, J.M., Cabanas, A. & Ballesteros, M., 2003. Hydrothermal pretreatment conditions to enhance ethanol production from popular biomass. *Appl. Biochem. Biotechnol.*, 108: 87-100.
- Nelson, D.L. & Cox, M.M., 2000. *Lehninger Principles of Biochemistry*. Macmillan worth publishers ,41 Madison avenue New York .Ny10010 USA.
- Nianzhi, J., Sieracki, M.E., Yao, Z. & Hailian, D., 2003. Aerobic anoxygenic phototrophic bacteria and their roles in marine ecosystems. *Chinese Science Bulletin*, 48(11): 1064-1068.
- Niklowitz, W. & Drews, G., 1955. Zur Elektronenmikroskopischen Darstellung der feinstruktur von *Rhodospirillum rubrum*.*Archives of Microbiology*,23: 123-129.
- Noda, N., Zorin, N. A., Nakamura, C., Miyake, M., Gogotov, I. N., Asada, Y., Akutsu, H. & Miyake, J. 1998. Langmuir-Blodgett film of hydrogenase for electrochemical hydrogen production. *Thin Solid Films*, 327-329: 639-642.
- Noparatnaraporn, N., Nishizawa, Y., Hayashi, M. & Nagai, S., 1983. Single cell protein production from cassava starch by *Rhodopseudomonas gelatinosa*. *Journal of Fermentation Technology*, 61(5): 515-519.
- Noparatnaraporn, N., Sasaki, K., Nishizawa, Y., Hayashi, M. & Nagai, S., 1982. *International union of Microbiological Societies, 13th International Congress of Microbiology*, Boston, Mass., U. S. A. 150.
- Novak, T.N., Gritzer, R.F., Leadbetter, E.R. & Godchaux, W., 2004. Photrophic utilization of taurine by the purple nonsulfur bacteria *Rhodopseudomonas palustris* and *Rhodobacter sphaeroides*. *Microbiology*, 150: 1881-1891.
- Oda, Y., Star, B., Huisman, L. A., Gottschal, J. C. & Forney, L. J., 2003. Biogeography of the purple non-sulfur bacterium *Rhodopseudomonas palustris*. *Applied and Environmental Microbiology*, 69(9): 5186-5191.
- Oh, Y. K., Kim, S. H., Kim, M. & Park, S., 2004. Thermophilic biohydrogen production from glucose with trickling biofilters. *Biotechnology Bioengineering*, 88: 690-8.
- Oh, Y., Seol, E., Lee, E. & Park, S., 2002. Fermentative hydrogen production by a new Chemohetrotrophic bacterium *Rhodopseudomonas palustris* P4. *International Journal of Hydrogen Energy*,27: 1373-1379.
- Okubo, Y., Futamata. H. & Hiraishi, A., 2006. Distribution and capacity for utilization of lower fatty acids of phototrophic purple nonsulfur bacteria in wastewater environments. *Microbes and Environment*,20: 135-143.
- Oleszkiewicz, J. & Poggi-Varaldo, H.M., 1997. High solids anaerobic digestion of mixed municipal and industrial waste. *Journal of Environment and Engineering*, 123: 1087-1092.
- Onodera, H., Miyahara, T. & Noike, T., 1999. Influence of ammonia concentration on hydrogen transformation of sucrose. Asian waterquality'99, 8th IAWQ Asian –Pacific Regional conference, 2: 1139-1144.
- Ormerod, J.G., Ormerod, K.S. and Gest, H., 1961. Light dependent utilization of organic compounds and photoproduction of molecular hydrogen by photosynthetic bacteria: relationships with nitrogen metabolism. *Archives of Biochemistry Biophysics*, 94: 449-463.

- Oser, B.L., 1965 *Physiological chemistry*. The Blakiston Division McGraw-Hill Book C.New York , U.S.A.
- Overmann, J., 2001. Diversity and ecology of phototrophic sulfur bacteria. *Microbiology Today*, 28: 116-118.
- Padree, A.B., Schachman, H.K. & Stanier, R.Y., 1952. Chromatophores of *Rhodospirillum rubrum*. *Nature*, 169: 282-283.
- Page, W. J., 1989. Production of poly- β -hydroxybutyrate by *Azotobacter vinelandii* strain UWD during growth on molasses and other complex carbon source. *Applied Journal of Microbiology and Biotechnology*, 31: 329-33.
- Pandey, A., Soccol, C. R., Nigam, P. & Soccol, V. T., 2000. Biotechnological potential of agroindustrial residues.1: Sugarcane bagasse. *Bioresource Technol.*, 74: 69-80.
- Pauss, A., Andre, G., Perrier, M. & Guiot, S.R., 1990. Liquid to gas mass transfer in anaerobic processes: inevitable transfer limitations of methane and hydrogen in the biomethanation process. *Applied and Environmental Microbiology*, 56: 1636-1644.
- Pereira, A.A., Martins, G.F., Antunes, P.A., Conrrado, R., Pasquini, D., Job, A.E., Curvelo, A.A., Ferreira, M., Riul, A.Jr. & Constantino, C.J., 2007. Lignin from sugarcane bagasse: extraction, fabrication of nanostructured films and application. *Langmuir*, 23: 6652-6659.
- Perez, J.M., Rodriguez, F., Alonso, M.V., Oliet, M. & Echeverria, J.M., 2002. Characterization of a novolac resin substituting phenol by ammonium lignosulfonate as filler or extender. *Bio. Res.*, 2: 270-283.
- Pfennig, N., 1987. Van Niel Remembered. *Features*, 53 (2): 75-77.
- Pfennig, N. & Truper, H.G., 1974. Bergey's Manual of Determinative Bacteriology, In: *Order 1. Rhodospirilleae*, 8th ed., (eds., Buchanan, R. E. and Gibbons, N. E), Williams and Wilkins Co., Baltimore, 25-6974.
- Pfennig, N., 1977. Phototrophic green and purple bacteria: a comparative, systematic survey. *Annual Review of Microbiology*, 31: 275-290.
- Poggi-Varaldo, H.M., Gomez-Cisneros, E., Rodriguez-Vazquez, T., Trejo-Espino, J., Rinderknecht-Seijas, N., Rodriquez-Vazquez, R., Fernandez-Villagomez, G. & Esparza-Garcia, F., 2002. Unsuitability of anaerobic compost from solid substrate anaerobic digestion as soil amendment. In: *Microbiology of composting Heidelberg*, (eds., Insam, H., Riddech, N. and Klammer, S.), Springer, Germany, p. 287-297.
- Poggi-Varaldo, H.M., Rodriquez-Vazquez, R., Fernandez-Villagomez, G. & Esparza-Garcia, F., 1997. Inhibition of mesophilic solid substrate anaerobic digestion by ammonia nitrogen. *Applied Microbiology and Biotechnology*, 47: 284-291.
- Poggi-Varaldo, H.M., Trejo-Espino, J., Fernandez-Villagomez, G., Esparza-Garcia, F., Caffarel-Mendez, S. & Rinderknecht-Seijas, N., 1999. Quality of anaerobic compost for soil amendment. *Water Science Technology*, 40(11-12): 179-186.
- Preuss, V.P, Duke, G. & Rogers, J., 1998. *A sustainable earth*. Cambridge university press. The Edinburgh building Cambridge CB2 2RU, UK.
- Prince, R.C. & Kheshgi, H.S., 2005. The photobiological production of hydrogen: potential efficiency and effectiveness as a renewable fuel. *Critical Review of Microbiology*, 31: 19-31.
- Proctor, L.M., 1997. Nitrogen-fixing, photosynthetic, anaerobic bacteria associated with pelagic copepods. *Aquatic Microbial Ecology*, 12: 105-113.

- Qian, D.J., Nakamura, C., Wenk, S.O., Ishikawa, H., Zorin, N. & Miyake, J., 2002. A hydrogen biosensor made of clay, poly (butylviologen), and hydrogenase sandwiched on a glass carbon electrode. *Biosensors and Bioelectronics*, 17: 789-796.
- Ramachandran, R., & Menon, P. K., 1998. An overview of industrial uses of hydrogen. *International Journal of hydrogen energy*, 23: 593-8.
- Rey, F.E., Heiniger, E.K. & Harwood, C.S., 2007. Redirection of Metabolism for biological hydrogen production. *Applied and Environmental Microbiology*, 73(5): 1665-1671.
- Robert, L.U. & Wolfe, R.S., 1970. Anaerobic growth of purple non sulfur bacteria under dark conditions. *Journal of Bacteriology*, 104(1): 462-472.
- Rocha, J.S., Barbosa, M.J. & Wijffels, R.H., 2001. Hydrogen production by photosynthetic bacteria: culture media, yields and efficiencies. In: *Biohydrogen II: An approach to environmentally acceptable technology* (eds, Miyake, J., Matsunaga, T., San Pietro, A.), Pergamon, London, p 3-32.
- Rodrigues, R.C.L.B., Felipe, M.G.A., Silva, J.B.A., Vitolo, M. & Gomez, P.V., 2001. The influence of pH, temperature and hydrolyzate concentration on the removal of volatile and nonvolatile compounds from sugarcane bagasse hemicellulosic hydrolyzate treated with activated charcoal before or after vacuum evaporation. *Braz. J. Chem. Eng.*, 18: [Epub ahead of print].
- Rodriguez, H. & Gallardo, R., 1993. Single cell protein from bagasse pith by a mixed bacterial culture. *Acta Biotechnologica*, 13: 141-149.
- Rodriguez, H., Alvarez, R. & Enriquez, A., 1993. Evaluation of different alkali treatments of bagasse pith for cultivation of *Cellulomonas* sp. *World Journal of Microbiology and Biotechnology*, 9: 213-215.
- Rosen, M. A. & Scott, D. S., 1998. Comparative efficiency assessments for a range of hydrogen production processes. *International Journal of Hydrogen Energy*, 23: 653-9.
- Saeed, A.A.W.S., 2005. Microbiological conversion of waste fruits and vegetables into ethanol. *Department of Zoology, University of the Punjab, Lahore*.
- Sahlstrom, L., 2003. A review of survival of pathogenic bacteria in organic waste used in biogas plants. *Bioresource Technology*, 87(2): 161-166.
- Sasaki, K. & Nagai, S., 1979. The optimum pH and temperature for the aerobic growth of *Rhodospseudomonas gelatinosa*, and vitamin B₁₂ and ubiquinone formation on a starch medium. *Journal of Fermentation Technology*, 57: 383-386.
- Sasaki, M., Adschiri, T. & Arai, K., 2003. Fractionation of sugarcane bagasse by hydrothermal treatment. *Bioresour. Technol.*, 86: 301-304.
- Sasikala, C. & Ramana, C. V., 1995. Biotechnological potentials of anoxygenic phototrophic bacteria. 1. Production of single-cell protein, vitamins, ubiquinones, hormones, and enzymes and use in waste treatment. *Advances in Applied Microbiology*, 41: 173-226.
- Sasikala, K., Ramana C., Rao, P.R. & Kovacs, K.L., 1993. Anoxygenic phototrophic bacteria: physiology and advances in hydrogen production technology. *Advance Applied Microbiology*, 38: 211-295.
- Sastri, M. V. C., 1989. India' hydrogen energy program- a status report. *International Journal of Hydrogen Energy*, 14: 507-13.
- Schachman, H.K., Padree, A.B. & Stanier, R.Y., 1952. Studies on the macromolecular organization of microbial cells. *Archives of Biochemistry and Biophysics*, 38: 245-260.

- Sedlak, M. and Ho, N.W., 2004. Characterization of the effectiveness of hexose transporters for transporting xylose during glucose and xylose co-fermentation by a recombinant *Saccharomyces* yeast. *Yeast*, 21:671-84.
- Segers, L. & Verstraete, W., 1983. Conversion of organic acids to hydrogen by *Rhodospirillaceae* growth with glutamate or dinitrogen as nitrogen source. *Biotech. Bioeng.*, 25: 2843-2853.
- Shi, X. Y. & Yu, H. Q., 2005. Response surface analysis on the effect of cell concentration and light intensity on hydrogen production by *Rhodopseudomonas capsulate*. *Process Biochemistry*, 40: 2475-81.
- Shin, H.S., Youn, J.H. & Kim, S.H., 2005. Hydrogen production from food waste in anaerobic mesophilic and thermophilic acidogenesis. *International Journal of Hydrogen Energy*, 29: 1355-1363.
- Sindhu, M.S. & Sandhu, D.K., 1980. Single-cell protein production by *trichoderma longibrachiatum* on treated sugarcane bagasse. *Biotechnol. Bioeng.*, 22: 689-692.
- Singleton, P. & Sainbury, D., 2001. *Dictionary of microbiology and molecular biology*. John Wiley and Sons Ltd., Baffins Lane, Chichester, West Sussex PO19 1UD, UK.
- Slapack, G.E., Russell, I. & Stewart, G.G., 1987. Thermophilic microbes in ethanol production. *CRC press, Inc. Boca Raton, Florida*, 129-134.
- Smith, J.E., 1996. *Biotechnology*, Cambridge University Press, Cambridge.
- Sojka, G. A. & Gest, H., 1968. Integration of energy conversion and biosynthesis in the photosynthetic bacterium *Rhodopseudomonas capsulate*. *Proc. Nat. Acad. Sci. (Wash.)* 61: 1486-1493.
- Sonderegger, M., Jeppsson, M., Larsson, C., Grauslund, C.M.F., Boles, E., Olsson, L., Martins, S.I., Hagerdal, H.B. & Sauer, U., 2004. Fermentation performance of engineered and evolved xylose-fermenting *Saccharomyces cerevisiae* strains. *Biotechnol. Bioeng.*, 1: 90-98.
- Sree, K., Sridhar, M., Rao, L.V. & Pandey, A., 1999. Ethanol production in solid substrate fermentation using thermotolerant yeast. *Proc. Biochem.*, 34: 115-119.
- Stabnikova, O., Wang, J.Y., Ding, H.B. & Tay, J.H., 2005. Biotransformation of vegetable and fruit processing waste with yeast biomass enriched with selenium. *Bioresour. Technol.*, 96: 747-751.
- Stenberg, K., Bollok, M., Reczey, K., Galbe, M. & Zacchi, G., 2000. Effect of substrate and cellulase concentration on simultaneous saccharification and fermentation of steam-pretreated softwood for ethanol production. *Biotechnol. Bioeng.*, 68: 204-210.
- Stryer, L., 1995. *Biochemistry*. W.H. Freeman Co. New York.
- Sun, Y. & Cheng, J., 2002. Hydrolysis of lignocellulosic materials for ethanol production: a review. *Bioresour. Technol.*, 83:1 – 11.
- Sunita, M. & Mitra, C.K., 1993. Photoproduction of hydrogen by photosynthetic bacteria from sewage and wastewater. *Journal of Biosciences*, 18 (1): 155-160.
- Suzuki, Y. 1982. On hydrogen as fuel gas. *International Journal of Hydrogen Energy*, 7: 227-30.
- Swoagar, W. C. & Linderstrom, E. S., 1971. Isolation and counting of *Athiorhodaceae* with membrane filters. *Applied journal of Microbiology*, 22 683-687.
- Taguchi, F., Mikukami, N., Saito-Taki, T. & Hasegawa, K., 1995. Hydrogen production from continuous fermentation of xylose during growth of *Clostridium* sp. Strain No. 2. *Canadian Journal of Microbiology*, 41: 536-540.

- Taherzadeh, M. J. & Karimi, K., 2007. Acid-based hydrolysis processes for ethanol from lignocellulosic materials: a review. *Bioethanol review. Bioresources*, 2: 472-499.
- Takabatake, H., Suzuki, K., Ko, I. B. & Noike, T., 2004. Characteristics of anaerobic ammonia removal by mixed culture of hydrogen producing photosynthetic bacteria. *Bioresource Technology*, 95:151-8.
- Tanisho, S. & Ishiwata, Y., 1995. Continuous hydrogen production from molasses by fermentation using urethane foam as a support of flocks. *International Journal of Hydrogen Energy*, 20: 541-544.
- Tanisho, S., Wakao, N. & Kokakov, Y., 1983. Biological hydrogen production by *Enterobacter aerogenes*. *Journal of Chemical Engineering, Japan*, 16: 529-530.
- Teixeira, L.C., Linden, J.C. & Schroeder, H.A., 2000. Simultaneous saccharification and co-fermentation of peracetic acid pretreated biomass. *Appl. Biochem. Biotechnol.*, 84-86: 111-127.
- Thomas, K.N.G., Bassat, A.B. & Zeikus, J.G., 1981. Ethanol production by thermophilic bacteria: fermentation of cellulosic substrates by co-cultures of *Clostridium thermocellum* and *Clostridium thermohydrosulfuricum*. *Appl. Environ. Microbiol.*, 41: 1337-1343.
- Toivari, M.H., Aristidou, A., Ruohonene, L. & Penttila, M., 2001. Conversion of xylose to ethanol by recombinant *Sacchromyces cerevisiae*: importance of xylulokinase (XKSI) and oxygen availability. *Metab. Eng.*3: 236-249.
- Tsygankov, A. A., Fedorov, A. S., Laurinavichene, T. V., Gogotov, I. N., Rao, N. N. & Hall, D. O., 1998. Actual and potential rates of hydrogen photoproduction by continuous culture of the purple non-sulfur bacterium *Rhodobacter capsulatus*. *Applied Journal of Microbial Biotechnology*, 49: 102-107.
- Ueno, R., Urano, N. & Kimura S., 2002. effect of temperature and cell density on ethanol fermentation by a thermotolerant aquatic yeast strain isolated from a hot spring environment. *Fisheries Sci.*, 68: 571-578.
- Ueno, Y., Haruta, S., Ishii, M. & Igarashi, Y., 2001b. Microbial community in anaerobic hydrogen-producing microflora enriched from sludge compost. *Applied Microbiology and Biotechnology*, 57: 555-562.
- Ueno, Y., Otsuka, S. & Morimoto, M., 1995. Hydrogen production from industrial wastewater by anaerobic microflora in chemostat culture. *Journal of Fermentation and Bioengineering*, 79: 395-397.
- Valdez-Vazquez, I., Rios-Leal, E., Esparza-Garcia, F., Cecchi, F. & Poggi-Varaldo, H.M., 2005. Semi-continuous solid substrate anaerobic reactors for H₂ production from organic waste: Mesophilic versus thermophilic regime. *International Journal of Hydrogen Energy*, 30: 1383-1391.
- Van Ginkel, S. & Sung, S., 2001. Biohydrogen production as a Function of pH and Substrate Concentration. *Journal of Environmental Science and Technology*, 35: 4726-4730.
- Van Groenestijn, J., Hazewinkel, O. & Bakker, R., 2006. Pretreatment of lignocellulose with biological acid recycling (Biosulfurol process). *Zuckerindustrie*, 131: 639-641.
- Van Haandel, A.C., 2005. Integrated energy production and reduction of the environmental impact at alcohol distillery plants. *Water Sci. Technol.*, 52: 49-57.
- Van Niel, C.B., 1929. Photosynthesis of bacteria. In: contributions to marine biology, Stanford Univ. Press, 161-169.

- Van Niel, C.B., 1931. On the morphology and physiology of the purple and green sulphur bacteria. *Archives of Microbiology*, 3: 1-112.
- Van Niel, C.B., 1944. The culture, general physiology, morphology, and classification of the non-sulfur purple and brown bacteria. *Microbiology and Molecular Biology Reviews*, 8(1):1-120.
- Van Niel, E., Claassen, P. & Stams, A., 2003. Substrate and product inhibition of hydrogen production by the extreme thermophile, *Caldicellulosiruptor saccharolyticus*. *Biotechnology and Bioengineering*, 81(3): 255-262.
- Voet, D., Voet, J.G. & Pratt, C.W., 1999. *Fundamentals of Biochemistry*. John Wiley and sons, Inc. New York, USA.
- Von, S.M., Zacchi, G., Olsson, L. & Hahn-Hagerdal, B., 1994. Cost analysis of ethanol production from willow using recombinant *Escherichia coli*. *Biotechnol. Prog.*, 10: 555-560.
- Wang, C.H., Lu, W. B. & Chang, J.S., 2007. Feasibility study on fermentative conversion of raw and hydrolyzed starch to hydrogen using anaerobic mixed microflora. *International Journal of Hydrogen Energy*, 32: 3849-3859.
- Watanabe, T., Kim, J.S., Ito, K., Buranakarl, L., Kampee, T. & Takahashi, H., 1979. Production of hydrogen by photosynthetic bacteria isolated from Thailand. *Microbial Utilization of Renewable Resources*, 1: 181-185.
- Weaver, P.F., Lien, S. & Seibert, M., 1979. *Improved hydrogen photoproduction from photosynthetic bacteria and green algae*. Solar Energy Research Institute 21 pp.; NREL Report No. TP-332-409 Colorado, U.S.
- Weaver, P.F., Wall, J.D. & Gest, H., 1975. Characterization of *Rhodospseudomonas capsulata*. *Archives of Microbiology*, 105: 207-216.
- Weissman, J.C. & Benemann, J.R., 1977. Hydrogen production by nitrogen-fixing cultures of *Anabaena cylindrica*. *Applied Environmental Microbiology*, 33: 123-131.
- Wheals, A.E., Basso, L.C., Alves, D.M. & Amorim, H.V., 1999. Fuel ethanol after 25 years. *Trends biotechnol.*, 17: 482-487.
- Wilke, C., Yang, R., Sciamanna, A. & Friedas, R., 1981. Raw material evaluation and process development studies for conversion of biomass to sugars and ethanol. *Biotechnol. Bioeng.*, 23: 163-183.
- Wolfrum, E.J. & Watt, A., 2002. Bioreactor design studies for a hydrogen producing bacterium. *Applied Biochemistry and Biotechnology*, 98(100): 611-625.
- Wolk, C.P., Ernst, A. & Elhai, J., 1994. Heterocyst metabolism and development, p. 769-823. In: *The molecular biology of cyanobacteria* (ed. Bryant, D.A.). Kluwer Academic Publishers, Dordrecht.
- Woodward, J., Orr, M., Cordray, K. & Greenbaum, E., 1996. Enzymatic production of biohydrogen. *Nature*, 405: 1014-1015.
- Wu, M., Wu, Y. & Wang, M., 2006. Energy and emission benefits of alternative transportation liquid fuels derived from switchgrass: a fuel life cycle assessment. *Biotechnol. Prog.*, 22: 1012-1024.
- Wu, S.Y., Hung, C.H., Lin, C.N., Chen, H.W., Lee, A.S. & Chang, J.S., 2006. Fermentative hydrogen production and bacterial community structure in high-rate anaerobic bioreactors containing silicone-immobilized and self-flocculated sludge. *Biotechnology and Bioengineering*, 93(5): 934-946.

- Yamagishi, K., 1995. *Interim Evaluation Report of Development of Environmentally Friendly Technology for the Production of Hydrogen*. New Energy and Industrial Technology Development Organization, Japan.
- Yang, B., Lu, Y., Gao, K. & Deng, Z., 1997. Study on the hydrolyzate of sugarcane bagasse to ethanol by fermentation. *Chin. J. Biotechnol.*, 13: 253-261.
- Yang, H. & Shen, J., 2006. Effect of ferrous iron concentration on anaerobic bio-hydrogen production from starch. *International Journal of Hydrogen Energy*, 31: 2137-2146.
- Yasa, I., Cadirci, B.H., Kocyigit, A. & Öztürk, T., 2006. Enrichment and isolation of anoxygenic phototrophic bacteria in Winogradsky Column. *E.U. Journal of Fisheries & Aquatic Science*, 23(1-2): 71-73.
- Yetis, M., Gunduz, U., & Eroglu, I., Yucel, M. and Turker, L., 2000. Photoproduction of hydrogen from sugar refinery wastewater by *Rhodobacter sphaeroides* O. U. 001 grown in the wastewater of a sugar refinery. *International Journal of Hydrogen Energy*, 25: 1035-41.
- Yetis, M., Gunduz, U., Eroglu, I., Yucel, M. and Turker, L., 1998. Photoproduction of hydrogen from wastewater of a sugar refinery by *Rhodobacter sphaeroides* O.U.001. Paper to be presented in *Marine Bioprocess Engineering*, Noord-wijkerhout, The Netherlands.
- Yigit, D.O., Gunduz, U. Turker, L. Yucel, M. & Eroglu, I., 1999. Identification of by-products in hydrogen producing bacteria , *Rhodobacter sphaeroides* O. U. 001 grown in the wastewater of sugar refinery. *Journal of Biotechnology*, 70: 125-131.
- Yoch, D.C. & Gotto, J.W., 1982. Effect of light intensity and inhibitors of nitrogen assimilation on NH^{++} inhibition of nitrogenase activity in *Rhodospirillum rubrum* and *Anabaena* sp. *J. Bacteriol.*, 151: 800-806.
- Yokoi, H., Saitsu, A., Uchita, H., Hirose, J., Hayashi, S. & Takasaki, Y., 2001. Microbial hydrogen production from sweet potato starch residue. *Journal of Bioscience and Bioengineering*, 91(1): 58-63.
- Yokoi, H., Tokushige, T., Hirose, J., Hayashi, S. & Takasai, Y., 1998. H_2 production form starch by a mixed culture of *Clostridium butyricum* and *Enterobacter aerogenes*. *Biotechnology Letters*, 20(2): 143-147.
- Yokoi, H., Tokushige, T., Hirose, J., Hayashi, S. & Takasaki, Y., 1997. Hydrogen production by immobilized cells of aciduric *Enterobacter aerogenes* strain HO-39. *Journal of Fermentation and Bioengineering* , 83: 484-491.
- Yokoyama, H., Moriya, N., Ohmori, H., Waki, M., Ogino, A. & Tanaka, Y., 2007. Community analysis of hydrogen-production extreme thermophilic anerobic microflora enriched from cow manure with five substrates. *Applied Microbiology and Biotechnology*, 77: 213-222.
- Younesi, H., Najafpour, G., Ismail, K.S.K., Mohamed, A.R. & Kamaruddin, A.H., 2008. Biohydrogen production in a continuous stirred tank bioreactor from synthesis gas by anaerobic photosynthetic bacterium: *Rhodospirillum rubrum*. *Bioresource Technology*, 99: 2612-2619.
- Zaborsky, O.R., 1998. Biohydrogen: *Plenum*, New York.1-552.
- Zanin, G.M., Santana, C.C., Bon, E.P., Giordano, R.C., de Moraes, F.F., Andrietta, S.R., De Carvalho, Neto. C.C., Macedo, I.C., Ramos, L.P.O. & Fontana, J.D., 2000. Brazilian bioethanol program. *Appl. Biochem. Biotechnol.*, 84-86: 1147-61.

- Zhang, T., Liu, H. and &, H., 2003. Biohydrogen production from starch in wastewater under thermophilic condition. *Journal of Environmental Management*, 69(2): 149-156.
- Zhang, Y. & Shen, J., 2006. Effect of temperature and iron concentration on the growth and hydrogen production of mixed bacteria. *International Journal of Hydrogen Energy*, 31(4): 441-446.
- Zhang, Z., Show, K., Tay, J., Liang, D. & Lee, D., 2008. Biohydrogen production with anaerobic fluidized bed reactors—a comparison of biofilm-based and granule-based systems. *International Journal of Hydrogen Energy*, 33(5): 1559-1564.
- Zheng, C., Lei, Y., Yu, Q., Lui, X. & Huan, K., 2002. Enzymatic hydrolysis of waste sugarcane bagasse in water media. *Environ. Technol.*, 23(9): 1009-1016.
- Zhu, H., Ueda, S., Asada, Y. & Miyake, J., 2002. Hydrogen production as a novel process of wastewater treatment-studies on tofu wastewater with entrapped *R.sphaeroides* and mutagenesis. *International Journal of Hydrogen Energy*, 27: 1349-57
- Zhu, H., Suzuki, T., Tsygankov, A.A., Asada, Y. & Miyake, J., 1999. Hydrogen production from tofu wastewater by *Rhodobacter sphaeroides* immobilized in agar gels. *International Journal of Hydrogen Energy*, 24: 305-10.
- Zhu, H., Wakayama, T., Asada, Y. & Miyake, J., 2001. Hydrogen production by four cultures with participation by anoxygenic photosynthetic bacterium and anaerobic bacterium in the presence of NH_4^+ . *International Journal of Hydrogen Energy*, 26: 1149-1154.
- Zhu, H.G., Shi, J.L. & Xu, Y.T., 1995. Highly concentrated alcohol waste water treatment by photosynthetic bacteria method. *Environmental Science Shanghai*, 14: 8-10.
- Zurrer, H. & Bachofen, R., 1979. Hydrogen Production by the Photosynthetic Bacterium *Rhodospirillum rubrum*. *Applied and Environmental Microbiology*, 37: 78.

IntechOpen

Biofuel Production-Recent Developments and Prospects

Edited by Dr. Marco Aurelio Dos Santos Bernardes

ISBN 978-953-307-478-8

Hard cover, 596 pages

Publisher InTech

Published online 15, September, 2011

Published in print edition September, 2011

This book aspires to be a comprehensive summary of current biofuels issues and thereby contribute to the understanding of this important topic. Readers will find themes including biofuels development efforts, their implications for the food industry, current and future biofuels crops, the successful Brazilian ethanol program, insights of the first, second, third and fourth biofuel generations, advanced biofuel production techniques, related waste treatment, emissions and environmental impacts, water consumption, produced allergens and toxins. Additionally, the biofuel policy discussion is expected to be continuing in the foreseeable future and the reading of the biofuels features dealt with in this book, are recommended for anyone interested in understanding this diverse and developing theme.

How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Javed Iqbal Qazi, Naureen Chaudhary and Saima Shahzad Mirza (2011). Biofuel From Cellulosic Mass with Incentive for Feed Industry Employing Thermophilic Microbes, Biofuel Production-Recent Developments and Prospects, Dr. Marco Aurelio Dos Santos Bernardes (Ed.), ISBN: 978-953-307-478-8, InTech, Available from: <http://www.intechopen.com/books/biofuel-production-recent-developments-and-prospects/biofuel-from-cellulosic-mass-with-incentive-for-feed-industry-employing-thermophilic-microbes>

INTECH
open science | open minds

InTech Europe

University Campus STeP Ri
Slavka Krautzeka 83/A
51000 Rijeka, Croatia
Phone: +385 (51) 770 447
Fax: +385 (51) 686 166
www.intechopen.com

InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai
No.65, Yan An Road (West), Shanghai, 200040, China
中国上海市延安西路65号上海国际贵都大饭店办公楼405单元
Phone: +86-21-62489820
Fax: +86-21-62489821

© 2011 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the [Creative Commons Attribution-NonCommercial-ShareAlike-3.0 License](https://creativecommons.org/licenses/by-nc-sa/3.0/), which permits use, distribution and reproduction for non-commercial purposes, provided the original is properly cited and derivative works building on this content are distributed under the same license.

IntechOpen

IntechOpen