We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists



186,000

200M



Our authors are among the

TOP 1% most cited scientists





WEB OF SCIENCE

Selection of our books indexed in the Book Citation Index in Web of Science™ Core Collection (BKCI)

## Interested in publishing with us? Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected. For more information visit www.intechopen.com



### Leak Tightness of Underground Carbon Dioxide Storage Sites and Safety of Underground CO<sub>2</sub> Storage by Example of the Upper Silesian Coal Basin (Poland)

Eleonora Solik-Heliasz Central Mining Institute Poland

#### 1. Introduction

The region of the Upper Silesian Coal Basin (USCB, southern Poland) was a subject of investigations referring to possibilities of underground storage of carbon dioxide. It is an industrial region characterized by high density of industrial infrastructure on the surface of the ground and underground as well as considerable emission of  $CO_2$  into the atmosphere. Among significant objects one should mention the presence of 53 mines of hard coal (Fig. 1). In these mines, there is or was conducted in previous years exploitation of coal deposit to the depth of about 1000 m below the terrain surface level. Location of underground storage sites within a small distance from an industrial emitter of  $CO_2$  might positively influence the cost-effectiveness of underground storage – if only by reducing costs of gas transport. However, with the current infrastructure, a selection of a proper site for storage necessitated conducting additional investigations, mainly detailed, multi-stage analysis of  $CO_2$  injection safety. Below, there are presented outcomes obtained in the years 2007-2010 in the framework of the research project the Technological Initiative I, entitled: "*Study of safe carbon dioxide storage by example of the Silesian agglomeration*", and dedicated researches carried out because of commissions received from concerned economic entities.

#### 2. Selection of CO<sub>2</sub> storage location

Selection of suitable location of underground storage is a prerequisite for successful process of CCS (*carbon capture storage*). Prospective site for storage must be market out by advantageous reservoir parameters, which was earlier mentioned by numerous researchers (Bachu et al., 2007; Bruining et al., 2004; Chadwick et al., 2008; Kumar et el., 2005; Obdam et al., 2003; Solik-Heliasz, 2010a). Both, safety of storage and effectiveness of  $CO_2$  injection must be also ensured. In the course of conducted examinations it was found out that in the region of USCB, underground storage sites must be located only beyond areas of active and liquidated mines but also outside areas of urban agglomeration and huge industrial plants. It is so because it has been ascertained that areas of underground mining are potentially seismic regions. Rock mass parted with mine workings can be a source of vibrations, which in unfavourable hydrogeological conditions might activate new paths of underground water

migration as well as injected gas and lead to their unforeseen dislocation. Also areas of cities and large plants have been excluded from  $CO_2$  storage – even at the deepest depths. In this case it does not, however, stem from some real threat but from a lack of sense of security which can concern the local community. In the investigated region it has also turned out to be crucial that prospective storage sites do not influence other undertakings of utilitarian character existing and planned in the vicinity of their borders. It can refer to both, workings of underground mines as well as water intakes, geothermal boreholes etc. Owing to the importance of the problem in question it became a subject of detailed investigations.

Having in mind the selected factors, the sandy and water-bearing horizon of the Dębowiec layers in the region of Skoczów-Zebrzydowice (Fig. 1) has been indicated for the injection of carbon dioxide. This horizon occurs in the forefield of USCB, beyond mines area, in overburden of coal series. Additionally, initially for the injection were qualified hard coal seams no. 405 and 510, deposited in the area of reserve mine field Pawłowice, at the depth of 1100-1500 m, as well as workings of hard coal mines Krupiński, Silesia and Brzeszcze – after their previous liquidation (Solik-Heliasz, 2010b).

The issue of safety of  $CO_2$  injection was considered with reference to the area of the Skoczów-Zebrzydowice storage site. Nevertheless, the addressed problems can also refer to the remaining storage sites.



Fig. 1. Location of planned carbon dioxide storage sites in the region of USCB (Poland).

55

#### 3. Examination of storage site leak tightness

Rock formations of the Skoczów-Zebrzydowice storage site are connected with Neogenic rock formations of the Dębowiec layers. They occur within the limits of regional structure of the Carpathian Foredeep, which stretches at the length of over 200 km along the southern border of Poland. The layers, deposited on morphologically diversified surface of carbon roof, are covered with thick complex of the Miocene claystones (Fig. 2). The existing hydrogeological conditions as well as parameters of reservoir rock formations, which are presented in Table 1, create favourable conditions for CO<sub>2</sub> storage. Nevertheless, the decisive role in the final selection of a site for injection played the analysis of storage site leak tightness and its potential influence on other underground objects in its vicinity. Leak tightness has been documented on the basis of geological cartography methods (maps, cross-sections), results of laboratory and *in situ* tests on hydro-geological and strength parameters of rocks, analyses of water chemical mechanism, results of geophysical tests and modelling.



Fig. 2. Geological cross-section of the region of the Skoczów-Zebrzydowice storage site.

Rock parameters	Parameters values	
Porosity of the Dębowiec layers rock formations [%]	8-15	
Permeability of the Dębowiec layers rock formations [mD]	13-103	
Compressive strength / tensile strength, R <sub>c</sub> /R <sub>r</sub> [MPa]:		
<ul> <li>rocks in overlay of the storage site</li> </ul>	5.0-39.9/-	
- storage site rock formations	4.0-56.0 / 0.1-2.4	
- rocks in storage floor	26.9-44.7/1.8-3.8	
Thickness of storage rock formations [m]	70-250	
Thickness of isolation rock formations in storage roof [m]	720-1030	
Effective CO <sub>2</sub> storage capacity [Mg · 10 <sup>6</sup> ]	24.1	

Table 1. Values of selected parameters of the Dębowiec layers in the area of the Skoczów-Zebrzydowice storage site.

The devised static model of the Dębowiec layers has shown that clay slates occurring in the overburden and in the floor of  $CO_2$  reservoir are impenetrable. Leak tightness was also confirmed by chemical analyses of waters, their hydro-chemical indicators and isotopic composition of oxygen,  $\delta^{18}O$ . At the horizon of the Dębowiec layers, paleoinfiltrational waters have been found of Cl-Na and Cl-Na-Ca type, and mineralization up to 98 g/dm<sup>3</sup>. They indicate lack of connection between the hydraulic reservoir with the terrain surface.

Hindrance in a selection of storage site location turned out to be the neighbourhood of a large fault zone with 400-600 m displacement (Fig. 3). Results of hydro-geological investigations conducted in the workings of nearby hard coal mines have admittedly shown that this zone is not water filled. However, in case of carbon dioxide injection under pressure higher than primary hydrostatic pressure, its clearing cannot be excluded. As a result of this, the border of the storage site has been mapped out within a safe distance from the fault. A significant challenge turned out also a fact that water-bearing layer in the area of storage yard is not "closed" in its side part. Lack of "closing up" of storage site is a problem referring to many storage sites occurring in water-bearing horizons of regional character. In case of the storage site under examination, however, the knowledge of the height difference of the floor of the Dębowiec layers was applied. The storage site has been located in the area of storage site was in considerable part contoured by natural geological frontiers, which should influence safety of  $CO_2$  injection.

On the leak tightness of storage site will also have influence adopted parameters of carbon dioxide injection. A threat can particularly result from the adopted pressure of  $CO_2$  injection. Too high pressure might lead to fracturing of reservoir rocks and/or neighbouring rocks. It is even more dangerous as rock formations of the Dębowiec layers display not too high values of strength parameters (Table 1). Fracturing of reservoir rocks is generally treated as a factor posing threat for storage safety. However – an opinion may be expressed here – that for reservoir rocks of medium and average values of hydro-geological parameters, controlled fracturing, limiting injection boreholes to the region can improve absorbing power of reservoir rock formations. In dynamic models of  $CO_2$  propagation in the horizon of the Dębowiec layers, developed with the use of numerical programme TOUGH-2 (Pruess, 1991), effects of injection were analysed: 100 000, 300 000 and 500 000 Mg  $CO_2$ /year during the period of 30 years. As a result of  $CO_2$  injection a repression cone will arise. It has

Leak Tightness of Underground Carbon Dioxide Storage Sites and Safety of Underground CO<sub>2</sub> Storage by Example of the Upper Silesian Coal Basin (Poland)



Fig. 3. Location of the Skoczów-Zebrzydowice storage site and major environmental features.

been ascertained that the optimum amount which can be injected through two injection boreholes amounts to  $2x150\ 000 = 300\ 000\ Mg/year$ . Injection of CO<sub>2</sub> into the floor part of the Dębowiec layers (Fig. 4a) will cause rapid increase of the pressure of water-gas medium in both holes from the initial value of 10.75 MPa to 12.6 MPa. During a short period of time maximum pressure in the region of injection boreholes can be similar to the pressure of rock fracturing. However, in the roof part of the Dębowiec layers the increase of pressure will mark itself much less clearly (Fig. 4b). On the other hand, saturation of water-bearing horizon with carbon dioxide will demonstrate unlike dynamics. During carbon dioxide injection (period of 0-30 years) CO<sub>2</sub> will be mainly accumulated in floor part of the Dębowiec layers (Fig. 5b). Results of analytical calculations confirmed that after 5 years of CO<sub>2</sub> injection, the radius of formed repression cone will amount to 11.8 km and encompass in its range both, storage site area as well as an area adjacent to it (Fig. 3).



Fig. 4a,b. Pressure changes of water in the Dębowiec layers as a result of  $CO_2$  injection in the amount of 300 000 Mg/year (according to Solik-Heliasz, on the basis of data obtained from Chećko, 2010).



Fig. 5a,b. Distribution of CO<sub>2</sub> saturation in the Dębowiec layers (according to Solik-Heliasz, on the basis of data obtained from Chećko, 2010).

#### 4. Analysis of storage site impact

Hitherto in Europe and in the world, locations of carbon dioxide storage sites are planned mainly in water-bearing horizons not utilized economically. This can however be subject to change due to building new underground objects. Then, a problem may arise connected with their interaction and a necessity to determine a safe distance between them. This problem has especially occurred in the examined region of USCB, especially with reference to workings of hard coal mines. From the conducted research works it follows that the approval of storage sites locations in industrialized regions or regions adjacent to them,

requires carrying out a detailed analysis of possible interactions. A two-stage analysis was performed. In the initial stage it covered determination of possible impact of storage site on other present and planned underground objects in its vicinity. In the subsequent stage an extreme scenario, in which consequences of possible penetration of  $CO_2$  in the direction of other underground objects were analysed.

With reference to the Skoczów-Zebrzydowice storage site, it was examined how the storage site influences the following (Fig. 3):

- 1. planned geothermal water intake in the Dębowiec layers;
- 2. water-bearing horizon of the Dębowiec layers in the overburden of mines Morcinek and Bzie.

These objects are situated beyond the storage site area, thus a source of threat can come mainly from overpressure created in the horizon of the Dębowiec layers. In connection with this, it turned out justifiable to provide the answer to possible physical effects of overpressure. The results of preliminary analyses of simulations have shown that it can be (apart from rock formations fracturing mentioned before) the increase of water flow velocity in the horizon of the Dębowiec layers. With reference to the planned geothermal waters intake - the speed increase can cause increased water inflow to the intake and at the same time improve its effectiveness. On the other hand, with reference to the planned mine Bzie in case of drainage of the Dębowiec layers in its area, which is to serve the increase of security of conducting mining exploitation - the increase of water flow might lead to increase of intakes to future drainage wellbores and as a result influence sooner attainment of the assumed depression of water level. The drainage process must be accurately monitored. It has been estimated that because of security reasons, arising cone of depression must not cross a border of protection zones established around the storage site (it will be developed in the further part of the work). In the extreme scenario, in contrast, the following were analysed:

- 1. results of possible penetration of CO<sub>2</sub> from the storage site to lower deposited workings in liquidated mine Morcinek;
- 2. threat to the stability of protecting pillar existing between workings of Polish mine Morcinek as well as active Czech mine ČSM.

Poor water leading of rock formations in the floor of storage site confirmed the results of *in situ* observations carried out during the functioning of mine Morcinek. Moreover, the dynamic model of the storage site area has not confirmed a possibility of carbon dioxide penetration into the foundation as well as its horizontal migration in the direction of mine workings. Despite that, the obtained results were treated with due caution. The numerical model requires designing a scheme of boundary conditions, whereas rock formations of storage site foundation constitute numerous interbedding of clay slates, mudstones and subordinately sandstones with coal seams. In spite of appropriate recognition of their parameters – general assessment of conductivity of this part is surely not sufficient. Thus, it turned out necessary to utilize the results of mining recognition as well as calculation methods applied in this field.

Workings of coal mine Morcinek are deposited at the depth of 750-1100 m below the terrain surface level. They are submerged and form huge reservoirs of underground waters. Their water capacity has been determined on the basis of calculation method by Rogoż (Rogoż,

2007) to be in total 2,3 10<sup>6</sup> m<sup>3</sup> (Solik-Heliasz, ed., 2009). What is more, in side walls of a long network of mine workings: longwall, heading and drifts, occur remainders of hard coal deposits which can even amount to several dozen million tonnes. Results of laboratory analyses have shown that hard coal has substantial sorption capacity of carbon dioxide (Ceglarska-Stefańska et al., 2008). Table 2 presents CO<sub>2</sub> storage capacity in workings of selected mines, Krupiński and Silesia, in case of creating low-pressure reservoirs in them, of pressure p<0.6 MPa. These mines are situated in comparable geological conditions to mine Morcinek.

Parameters	Silesia Mine	Krupiński Mine
Volume of mine workings: longwall, passageway and caving fractures [m <sup>3</sup> · 10 <sup>6</sup> ]	25.08	5.80
Mass of left hard coal [Mg · 106]	78.75	43.56
Total amount of CO <sub>2</sub> possible to be stored in mine workings and in coal reminders [Mg · 10 <sup>6</sup> ]	2.9-6.7	0.9-1.9

Table 2. CO<sub>2</sub> storage capacity in workings and coal reminders in mines Silesia and Krupiński in GZW (Solik-Heliasz, 2010b).

The presented results show that workings of mine Morcinek are capable to absorb substantial amount of  $CO_2$  in case of its potential migration from the Skoczów-Zebrzydowice storage site. Separate issue is a threat which can create the increase of watergas medium in mine workings of mine Morcinek, on the stability of protecting pillar separating workings of this mine from workings of active mine ČSM (Fig. 3). The stability of the pillar has been verified on the basis of calculation methods utilized in underground mining. It turned out helpful to adopt i.a. the *Slesariew*'s formula (Frolik, 1998), enabling to determine a safe pillar width:

$$D_{\min} = g \sqrt{60 p} \tag{1}$$

where: D<sub>min</sub> - minimum width of protecting pillar, m

*g* - average thickness of reservoir series, m

*p* - target pressure in the reservoir, MPa.

Increase of pressure in abandoned working of mine Morcinek even by 50% in comparison to the primary hydrostatic pressure amounting to 7.8 MPa, will not threaten the stability of the existing pillar. Its present width which is 100 m will be sufficient.

Conducted examinations have shown that the process of the storage site exploitation does not encounter difficulties which could lead to its premature closure.

#### 5. Will carbon dioxide storage sites require protection?

In EU Directive concerning underground storage of carbon dioxide (Directive, 2009) it is recommended that underground storage ought to be safe and injected carbon dioxide permanently bound with reservoir rock formations in the period of several hundred years and more. On the basis of its guidelines as well as experiences gained so far (i.a. Chadwick

www.intechopen.com

et.al., 2008, Frolik et al., 2006), the ranges of storage sites in the area of USCB were established. Does it however mean that in the direct vicinity of storage sites – which theoretically should be safe - other utilitarian enterprises, e.g. water intakes, storage yards etc. can be located with complete confidence?

The rock formations of the Dębowiec layers mentioned above are characterised by changeability of hydro-geological parameters. Similar Carboniferous rock formations deposited in their floor, which additionally demonstrate high lithological diversification. Rocks of these two geological series are a subject of research conducted since the end of the 60's of the 20<sup>th</sup> century. Despite that, the diversification, which has been mentioned, can become a potential source of threat for safe storage of  $CO_2$ . Having that in consideration, it has been proposed to establish protection zones around  $CO_2$  storage sites in USCB. They would constitute additional protection of storage sites against the influence of other utilitarian enterprises as well as other underground objects against storage site impact. Cap rock is a typical example of protection zones. Nonetheless, zones of this type should be also established in the side regions of the storage sites are presented in Figures 6a-c.



Fig. 6a-c. Concept of location of protection zones for carbon dioxide storage sites.

Methodology of delineation of protection zones width ought to become a subject of further research. Preliminary calculations made on the basis of the formula (1), with the assumption that  $CO_2$  carrier after its injection into reservoir rock formations will be the flow of underground waters, have shown that the width of protection zones can be diversified. Appropriate values are presented in Table 3.

Location of protection zones for CO <sub>2</sub> storage sites situated in:	Minimum width of protection zones in reservoir rock formations m	Notice
Water-bearing horizon		High-pressure
- in the region of $CO_2$ storage site	2540-2920	CO <sub>2</sub> reservoir;
Skoczów-Zebrzydowice		p≥10.75 MPa
Hard coal seams 405 and 510		High-pressure
- in the area of $CO_2$ storage site	147-196	CO <sub>2</sub> reservoir;
Pawłowice		р=10 МРа
Workings of hard coal mines		Low-pressure
Krupiński and Silesia – after their	1800-2400	CO <sub>2</sub> reservoirs;
liquidation		p< 0.6 MPa

Table 3. Minimum width of protection zones around underground carbon dioxide storage sites in the area of USCB (Poland).

Delineation of protection zones around carbon dioxide storage sites can have, however, economical aspect, as it requires exclusion of additional parts of rock mass from economic activity. Nevertheless, the growing number of utilitarian enterprises in water filled rock series causes that they may require introduction of additional protection measures for them.

#### 6. Conclusions

There is a possibility to create carbon dioxide storage site in the region adjacent to highly industrialised area of USCB. However, approval of its location took place only after conducting tests on storage site leak tightness and two-stage analyses of its potential impact on other underground objects located in the vicinity (workings of hard coal mines, water intakes). For the assessment of carbon dioxide storage safety, results of model research have been used which were supplemented with results of mining recognition (hydrodynamic regime in the area of the surrounding mine workings of the abandoned hard coal mine) using the calculation methods utilized in this field (connected with water capacity of mine workings, minimum width of the protecting pillars and their stability). The Skoczów-Zebrzydowice storage site will not negatively influence other underground objects in its vicinity. However, due to the fact that their number can increase in the future, it has been proposed to establish protection zone around storage site. It will constitute additional protection and determine intransgressible influence boundary of other underground objects planned to be built nearby.

#### 7. References

Bachu, S., Bonijoly, J., Burruss, R., Christensen, N.P., Holloway, S. & Mathiassen, O.M. (2007). Estimation of CO<sub>2</sub> Storage Capacity in Geological Media – Phase 2, *Prepared* 

Leak Tightness of Underground Carbon Dioxide Storage Sites and Safety of Underground CO<sub>2</sub> Storage by Example of the Upper Silesian Coal Basin (Poland) 63

*by the Task Force on CO*<sub>2</sub> *Storage Estimation for the Technical Group (TG) of the Carbon sequestration Leaderskie Forum,* February 12, version 1.5. URL:

http://www.cslforum.org/documents/PhaseIII/ReportStorageCapacityMeasurem entTask, Force.pdf.

- Bruining H., Bossie-Codreanu, D., Busch, A., Choi, X., de Schmedt, G., Frobel, J., Gale, J., Grabowski, D., Hadro, J., Hurtevent, D., Jura, B., Kretchmar, H., Krooss, B., Krzystolik, P., Mazumder, S., Muller, G., Pagnier, H., Reeves, S., Skiba, J., Stevens, S., van Bergen, F., van der Meer, B., Wenting, P., Winthaegen, P. & Wolf, K. (2004). Recopol field experiment of ECBM-CO<sub>2</sub> in the Upper Silesian Basin of Poland, *7th International Conference on Greenhouse Gas Control Technologies*, Vancouver, Canada.
- Ceglarska-Stefańska, G., Zarębska, K. & Wolszczak, J. (2008). Sorption of pure components and mixtures CO<sub>2</sub> and CH<sub>4</sub> on hard coals, *Mineral Resources Management* Vol. 24(4/1), pp.123-131.
- Chadwick, A., Arts, R., Bernstone, C., May, F., Thibeau, S. & Zweigel, P. (2008). *Best practice for the storage of CO<sub>2</sub> in saline aquifers. Observations and guidelines from the SACS and CO<sub>2</sub>STORE projects, Keyworth, Nottingham British Geological Survey.*
- Chećko, J. (2010). Modelling of underground reservoir for CO<sub>2</sub> storage in brine-bearing formations, *in* Wachowicz, J. (ed.), *Study of safe carbon dioxide storage by exemple of Silesian agglomeration*, Wyd. GIG, Katowice, pp. 52-75 (in Polish).
- *Dyrektywa Unii Europejskiej i Rady* 2009/31/WE *z dnia* 23.04.2009, dotycząca podziemnego składowania CO<sub>2</sub>.
- Frolik, A. (1998). Ocena szczelności przeciwwodnych filarów bezpieczeństwa. Prace GIG. VII Konferencja: Problemy geologii w ekologii i górnictwie podziemnym, Szczyrk, Poland, pp. 231-240.
- Frolik, A., Kidybiński, A., Marcak, H., Nierobisz, A., Rychlicki, S. & Solik-Heliasz, E. (2006). Assessment methods of possibilities of hydrocarbons storage in underground mine workings, *in* Kidybiński, A., Siemek, J. (eds.), *Underground repositories of gas in abandoned hard coal mines*, Wyd. GIG, Katowice, pp. 59-95 (in Polish).
- Kumar, A., Noh, M.H., Sepehrnoori, K., Bryant, S.L. & Lake, L.W. (2005). *Simulating* CO<sub>2</sub> storage in deep saline aquifers, in Carbon Dioxide Capture for Storage in Deep Geologic Formations – Results from the CO<sub>2</sub> Capture Project, Elsevier, London Vol. 2.
- Obdam, A., van der Meer, L.G.H., Kervevac, C., Bech, N. & Wildenborg, A. (2003). Effective CO<sub>2</sub> storage capacity in aquifers, gas fields, oil fields, and coal fields, *Proceedings of the* 6<sup>th</sup> International Conference on Greenhouse Gas Control Technologies, Gale and Y. Kaya, 1-4, October 2002, Kyoto, Japan, Pergamon.
- Pruess, K. (1991). TOUGH2 A General-Purpose Numerical Simulator for Multiphase Fluid and Heat Flow. *Earth Science Division*, Lawrence Berkeley Laboratory, University of California, Berkeley, CA 94720, Report LBL-29400.
- Rogoż, M. (2007). Dynamika wód podziemnych, Wyd. GIG, Katowice.
- Solik-Heliasz, E. (ed.) (2009). Atlas of geothermal energy resources in the Upper Silesian Region – the Neogene, Carboniferous and Devonian formations, Wyd. GIG, Katowice (in Polish).
- Solik-Heliasz, E. (2010a). Development of potential capacity of CO<sub>2</sub> storage in deeply located brine-bearing formations in the region of Silesian agglomeration, *in* Wachowicz, J.

(ed.), *Study of safe carbon dioxide storage by exemple of Silesian agglomeration*, Wyd. GIG, Katowice, pp. 15-51 (in Polish).

Solik-Heliasz, E. (2010b). Possibilities of underground CO<sub>2</sub> storage in the Upper Silesian region, *Mineral Resources Management* Vol. 26 (3), pp. 53-65.







Mining Methods Edited by Prof. Turgay Onargan

ISBN 978-953-51-0289-2 Hard cover, 64 pages Publisher InTech Published online 09, March, 2012 Published in print edition March, 2012

An economic viability of a modern day mine is highly dependent upon careful planning and management. Declining trends in average ore grades, increasing mining costs and environmental considerations will ensure that this situation will remain in the foreseeable future. This book describes mining methods for the surface and underground mineral deposits. The methods are generalized and focus on typical applications from different mining areas around the world, keeping in mind, however, that every mineral deposit, with its geology, grade, shape, and volume, is unique. The book will serve as a useful resource for researchers, engineers and managers working in the mining industry, as well as for universities, non-governmental organizations, legal organizations, financial institutions and students and lecturers in mining engineering.

#### How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Eleonora Solik-Heliasz (2012). Leak Tightness of Underground Carbon Dioxide Storage Sites and Safety of Underground CO2 Storage by Example of the Upper Silesian Coal Basin (Poland), Mining Methods, Prof. Turgay Onargan (Ed.), ISBN: 978-953-51-0289-2, InTech, Available from:

http://www.intechopen.com/books/mining-methods/tightness-of-underground-carbon-dioxide-storage-sitesand-safety-of-underground-co2-



#### InTech Europe

University Campus STeP Ri Slavka Krautzeka 83/A 51000 Rijeka, Croatia Phone: +385 (51) 770 447 Fax: +385 (51) 686 166 www.intechopen.com

#### InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai No.65, Yan An Road (West), Shanghai, 200040, China 中国上海市延安西路65号上海国际贵都大饭店办公楼405单元 Phone: +86-21-62489820 Fax: +86-21-62489821 © 2012 The Author(s). Licensee IntechOpen. This is an open access article distributed under the terms of the <u>Creative Commons Attribution 3.0</u> <u>License</u>, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

# IntechOpen

## IntechOpen