We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists

6,300

Open access books available

172,000

International authors and editors

190M

Downloads

Our authors are among the

154

Countries delivered to

TOP 1%

most cited scientists

12.2%

Contributors from top 500 universities

WEB OF SCIENCE™

Selection of our books indexed in the Book Citation Index
in Web of Science™ Core Collection (BKCI)

Interested in publishing with us?
Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected.
For more information visit www.intechopen.com

Unsupervised Classification of Aerial Images Based on the Otsu's Method

Antonia Macedo-Cruz¹, I. Villegas-Romero³,
M. Santos-Peñas² and G. Pajares-Martinsanz²

¹*Hidrociencias, Campus Montecillo,
Colegio de Postgraduados, Montecillo, Estado de México,*
²*Facultad de Informática, Universidad Complutense de Madrid,*

³*Universidad Autónoma Chapingo,*
^{1,3}*México*

²*España*

1. Introduction

Remote-sensing research focusing on image classification has long attracted the attention of the remote-sensing community because classification results are the basis for many environmental and socioeconomic applications. However, classifying remotely sensed data into a thematic map remains a challenge because many factors, such as the complexity of the landscape in a study area, selected remotely sensed data, and image-processing and classification approaches, may affect the success of a classification [1].

In forest management, a number of activities are oriented towards wood production or forest inventories with the aims of controlling parameters of interest such as diameter of trees, height, crown height, bark thickness, canopy, humidity, illumination, CO₂ transformation among others, always with the goal of environmental sustainability with high social impact. The unsupervised classification of aerial image offer solutions for monitoring production in forest trees while the same time costs are minimized. Also with Unmanned Aerial Vehicles (UAV) equipped with an appropriate image classification system, have become powerful tools for early fire forest detection and posterior monitoring. This technology has also been applied for crop monitoring under wireless sensor network architecture.

Clustering is the task of categorizing objects having several attributes into different classes so that the objects belonging to the same class are similar, and those that are broken down into different classes are not. Clustering is the subject of active research in several fields such as statistics, pattern recognition, machine learning, data mining, information science, agriculture technology and spatial databases. A wide variety of clustering algorithms have been proposed for different applications [1], [2].

Classification and segmentation in agriculture and forest management is an interesting topic but not new. There are many classification approaches that are oriented toward the identification of textures in agricultural and forest images. Most of them can be grouped as follows.

- Currently, many of the agriculture, livestock and forestry are planned using spatial analysis tools, seeking different specific objectives [3]. In this sense, the images acquired by remote sensors provide the necessary spatial resolution to obtain information about objects, areas, or phenomena on the earth's surface, at different scales. These sensors measure the intensity of the energy emitted or reflected by the objects by means of the electromagnetic spectrum [1].
- There are many segmentation techniques reported in the literature [4, 5]. Most color image segmentation techniques are usually derived from methods designed for graylevel images. Processing each channel individually by directly applying graylevel where the channels are assumed independent and only their intra-spatial interactions are considered [6]. Another option is decomposing the image into luminance and chromatic channel: after transforming the image data into the desired (usually application dependent) color space, texture features are extracted from the luminance channel while chromatic features are extracted from the chromatic channels, each in a specific manner [7]. Reference [8] and [9] show combining spatial interaction within each channel and interaction between spectral channels and gray level texture analysis techniques are applied in each channel, while pixel interactions between different channels are also taken into account.

Based on the presented considerations and in order to tackle the classification problem addressed in this paper, we have designed a new automatic strategy based on the thresholding Otsu's method is proposed. The first step consists in the thresholding of each R, G and B channels into two parts based on within-class and between-class variances suggested by Otsu [10]. This allows to classify each pixel to one part of each channel, so that conveniently combined the a pixel should be classified as belonging to one of the eight possible classes. Although in this paper we only use eight classes, the method can be easily extended to more classes, as described in section 2.2.2, even we can achieve until twenty seven. This makes the main contribution of this paper.

Additionally, one major advantage of this algorithm is that it does not need to know how many classes are required to be clustered in advance, as it is required for most supervised clustering processes. The termination criterion is established based on the within-class variance, according to the Otsu's method.

The proposed method is compared against the well-known Fuzzy c-means clustering [11], [12]. The prediction of the correct number of clusters is a fundamental problem in unsupervised classification problems. Many clustering algorithms require the definition of the number of clusters beforehand. To overcome this problem, various cluster validity indices have been proposed to assess the quality of a clustering partition [13]-[16]. Five cluster validation indices have been used in our tests, they are: Dunn's [15]-[19], Davies-Bouldin [15], [19]-[21], Calinski-Harabasz [15], [21]-[24], Krzanowski and Lai [22], [25]; and Hartigan [21], [22], [26]. We have used five because there is not relevant conclusions in the literature about their performance, depending on the application their behavior could vary considerably. Based on the above indices we have verified the best performance of our approach against the MS method, particularly in the images where water bodies are present.

The remainder of the paper is organized as follows. In Section 2, materials and methods; two issues will be addressed, unsupervised classification of color images and five of cluster validation indexes. Section 3, result and discussions; Conclusions are presented in Section 4.

2. Materials and methods

2.1 Study area

In the present investigation 16 color aerial photographs in digital format were used, owned by the Institute of Geography of the Autonomous University of Mexico, taken in October 1997. The photographs correspond to the catchments of the river La Sabana, Guerrero, with spatial resolution of 1:19500, and three-band spectral resolution visible and radiometric resolution RGB from 0 to 255 levels. As an example, Fig. 1 displays a representative image of the set of images analyzed in this work. As we can see it contains several textures which must be classified as belonging to a cluster.

Fig. 1. Land cover images in RGB color model

2.2 Classifier based on the theory of the Otsu's method

2.2.1 Brief description of the Otsu's method

Otsu's method [10], one of the most widely used thresholding techniques in image analysis, has showed great success in image enhancement and segmentation. As mentioned before, it is an automatic thresholding strategy; we exploit the automatic capability for designing the unsupervised classification strategy justifying its choice.

This research sought the optimal threshold (single or multiple) for each of the spectral bands of the color image by applying the algorithm modified [27, 28]:

The number of pixels with gray level i is denoted f_i giving a probability of gray level i in an image of

$$p_i = \frac{f_i}{N} \quad (1)$$

Then, the probability distributions for each class is

$$w_k = \sum_{i \in C_k} p_i \quad (2)$$

The w_k is regarded as the zeroth-order cumulative moment of the k th class C_k . and the means for classes is

$$u_k = \sum_{i \in C_k} \frac{i \cdot p_i}{w_k} \quad (3)$$

In the case of bi-level thresholding, Otsu defined the between-class variance of the thresholded image as:

Where

$$\sigma_B^{2*} = w_1(u_1 - u_T)^2 + w_2(u_2 - u_T)^2 \quad (4)$$

$$\mu_T = \sum_{k=1}^M w_k \mu_k \quad (5)$$

And

$$\sum_{k=1}^M w_k = 1 \quad (6)$$

Assuming that there are $M-1$ thresholds, $\{t_1, t_2, \dots, t_{M-1}\}$, which divide the original image into M classes: C_1 for $[1, \dots, t_1]$, C_2 for $[t_1+1, \dots, t_2]$, ..., C_i for $[t_{i-1}+1, \dots, t_i]$, ..., and C_M for $[t_{M-1}+1, \dots, L]$, the optimal thresholds $\{t_1^*, t_2^*, \dots, t_{M-1}^*\}$ are chosen by maximizing σ_B^2 as follows

$$\{t_1^*, t_2^*, \dots, t_{M-1}^*\} = \arg \max \{\sigma_B^2(t_1, t_2, \dots, t_{M-1})\} \quad (7)$$

$$1 \leq t_1 < \dots < t_{M-1} < L$$

then

$$(\sigma_B^2) = \sum_{k=1}^M w_k u_k^2 - u_T^2 = \sum_{k=1}^M w_k u_k^2 \quad (8)$$

A threshold value t_{Otsu} developed by Otsu is the one that maximizes $\text{var}^t_{\text{between-class}}$, or equivalently minimizes $\text{var}^t_{\text{within-class}}$.

$$\begin{aligned} t_{Otsu} &= \arg \left\{ \min_{1 \leq t \leq L} (\text{Var}^t_{\text{within-class}}) \right\} \\ t_{Otsu} &= \arg \left\{ \max_{1 \leq t \leq L} (\text{Var}^t_{\text{between-class}}) \right\} \end{aligned} \quad (9)$$

where L is the number of gray levels in each band, in our images L is 256 because each pixel is represented with eight bits.

2.2.2 Unsupervised classification strategy by within-class and between-classes spectral variances

There are three steps in the proposed classification strategy. First, the assignment process, that consists in assigning one of the possible classes to each pixel. Second, the codification of each cluster, which is identified by a label. Finally, a regrouping process so that very similar classes are merged into one.

2.2.2.1 Assignment process

Given a pixel i located at (x, y) in the original RGB image. Its three spectral components in this space are obtained, namely $R(x, y) = i_r$, $G(x, y) = i_g$ and $B(x, y) = i_b$.

As already mentioned, the thresholding methods split the histogram into two regions. As there are three spectral components, six sub-regions are obtained. If necessary, successive thresholding can be applied to each spectral channel. The second thresholding produces three partitions per channel. If a third thresholding is applied, four regions per component are obtained and so on. Therefore, assuming that eventually the number of thresholds per channel is M , there will be $t_{R1}, t_{R2}, \dots, t_{RM}$, thresholds for channel R , and in the same way, $t_{G1}, t_{G2}, \dots, t_{GM}$ for component G , and $t_{B1}, t_{B2}, \dots, t_{BM}$, for component B . Based on this, each pixel i can be coded as $\tilde{i}_s$ according to its spectral components by Equation (10):

$$\tilde{i}_s = \begin{cases} 0 & \text{if } i_s \leq t_{s1} \\ 1 & \text{if } t_{s1} < i_s \leq t_{s2} \\ 2 & \text{if } t_{s2} < i_s \leq t_{s3} \\ \vdots & \\ M & \text{if } i_s > t_{sM} \end{cases} \quad (10)$$

where s denotes the spectral component, i.e., $s = R, G$ or B , and t_{si} are the consecutive thresholds.

For example, it is known that in the RGB colour space values are in the range $[0, 255]$. So, considering the spectral component R with two thresholds, $t_{R1} = 120$ and $t_{R2} = 199$, a pixel will be coded as 0, 1, or 2, if its spectral value R is smaller than 120, between 120 and 199, or greater than 199, respectively.

2.2.2.2 Cluster labelling

Once the whole image has been coded, the next step is the labelling of the existing classes. If M thresholds haven been obtained, there are $n = M + 1$ histogram partitions per channel, and therefore the number of possible combinations is n^d , where d is the number of spectral components, i.e., $d = 3$ in the RGB colour space. This number of combinations represents the number of classes. Each cluster is identified by its label. Every pixel is assigned its corresponding label according to Equation (11). So, given the pixel $i \equiv (x, y)$ with codes $\tilde{i}_R$, $\tilde{i}_G$, and $\tilde{i}_B$, its label will be given by $\tilde{p}_i$ as follows:

$$\tilde{p}_i = n^2 \tilde{i}_R + n \tilde{i}_G + \tilde{i}_B \quad (11)$$

2.2.2.3 Merging process

Let C_k be the number of clusters obtained by the classification procedure, where k identifies a class between 1 and n^d , each class containing N_k pixels of the original image. It could be

said that each class is defined by a tri-dimensional vector ($d = 3$). The elements of that vector are the spectral components of the pixels according to the *RGB* colour model, i.e., $i_R \equiv (i_R^k, i_G^k, i_B^k)$ for the pixel $i \equiv (x, y)$, if the pixel and its spectral components belong to class C_k . For each class, the average value of the membership degrees to that class is calculated by Equation (12):

$$\mu_k \equiv (\mu_R^k, \mu_G^k, \mu_B^k) = \frac{1}{N_k} \sum_{i_k \in C_k} i_k \quad (12)$$

Based on the potential of Otsu's method, it is possible to estimate the within-class and the between-classes spectral variances, denoted by σ_k and σ_{kh} respectively, according to Equations (1) and (16). Obviously, σ_k is only related to class C_k and, as expected, σ_{kh} involves the two classes C_k and C_h , $k \neq h$:

$$\sigma_k = \frac{1}{d \cdot N_k} \sum_{i_k \in C_k} \left[(i_R^k - \mu_R^k)^2 + (i_G^k - \mu_G^k)^2 + (i_B^k - \mu_B^k)^2 \right]^{1/2} \quad (13)$$

$$\sigma_{kh} = \frac{1}{d} \left[(\mu_R^k - \mu_R^h)^2 + (\mu_G^k - \mu_G^h)^2 + (\mu_B^k - \mu_B^h)^2 \right] \quad (14)$$

Based on those variances, some classes can be fused due to their spectral similarities. The similarity is a concept defined as follows. Given the clusters C_k and C_h , for $k \neq h$, they are merged if $\sigma_k \geq \sigma_{kh}$ and $\sigma_h \geq \sigma_{kh}$. This is based on the hypothesis that if a good partition is already achieved, the classes obtained are properly separated, without overlapping, and then no further fusion is required. On the contrary, if classes overlap, the between-class variance σ_{kh} is greater than the individual within-class variances, σ_k and σ_h . This re-clustering process is repeated until all the between-class variances are greater than their corresponding within-class variances. Without loss of generality, if two classes are merged, the resulting fused class will be re-labelled with the name of the class with the smaller variance value. This does not affect the classification process because only labels are modified.

After the fusion process, it must be checked if more clusters are necessary. This is carried out on the basis that if after the combination process no class has been fused, it means that more clusters are needed. A new clustering process starts again with the number of thresholds increased by one. This is repeated until a fusion occurs.

2.3 Fuzzy C-Means clustering

Fuzzy c-means clustering (FCM) is a data clustering technique wherein each data point belongs to a cluster to some degree that is specified by a membership grade. This technique was originally introduced by Jim Bezdek [11], as an improvement on earlier clustering methods.

The FCM algorithm attempts to partition a finite collection of elements $X = \{x_1, x_2, \dots, x_n\}$ into a collection of c fuzzy clusters with respect to some given criterion.

The FCM algorithm, processes n vectors in p -space as data input, and uses them, in conjunction with first order necessary conditions for minimizing the FCM objective functional, to obtain estimates for two sets of unknowns.

The unknowns in FCM clustering are:

1. A fuzzy c -partition of the data, which is a $c \times n$ membership matrix $U = \{\mu_{ik}\} \in V_{cn}$ with c rows and n columns. The values in row i give the membership of all n input data in cluster i for $k=1$ to n ; the k -th column of U gives the membership p of vector k (which represents some object k) in all c clusters for $i=1$ to c . Each of the entries in U lies in $[0,1]$; each row sum is greater than zero; and each column sum equals 1.
2. The other set of unknowns in the FCM model is a set of c cluster centers or prototypes, arrayed as the c columns of a $p \times c$ matrix V . These prototypes are vectors (points) in the input space of p -tuples. Pairs (U, V) of coupled estimates are found by alternating optimization through the first order necessary conditions for U and V . The objective function minimized in the original version measured distances between data points and prototypes in any inner product norm, and memberships were weighted with an exponent $m > 1$.

That is:

As $X = \{x_1, x_2, \dots, x_n\}$ and the set all V_{cn} real matrices of dimension $c \times n$, with $2 \leq c < n$. Can be obtained a matrix representing the partition follow $U = \{\mu_{ik}\} \in V_{cn}$. The basic definition FCM for $m > 1$ is to minimize the following objective function:

$$\min z_m(U; v) = \sum_{k=1}^n \sum_{i=1}^c \mu_{ik}^m \|x_k - v_i\|_G^2 \quad (15)$$

G is a matrix of dimension $p \times p$ symmetric positive definite

$$\|x_k - v_i\|_G^2 = (x_k - v_i)^t G (x_k - v_i) \quad (16)$$

Where

$$v_i = \frac{1}{\sum_{k=1}^n (\mu_{ik})^m} \sum_{k=1}^n (\mu_{ik})^m x_k \quad i = 1, \dots, c \quad (17)$$

$$\mu_{ik} = \frac{\left(\frac{1}{\|x_k - v_i\|_G^2} \right)^{2/m-1}}{\sum_{j=1}^c \left(\frac{1}{\|x_k - v_j\|_G^2} \right)^{2/m-1}} \quad i = 1, \dots, c; k = 1, \dots, n \quad (18)$$

The exponent m is known as exponential weight and reduces the influence of noise when getting the centers of the clusters. The higher the $m > 1$, the greater this influence. More details on fuzzy c -means clustering [11, 12].

2.4 Methods for cluster validation

Evaluation of clustering results (or cluster validation) is an important and necessary step in cluster analysis, but it is often time-consuming and complicated work [16].

The procedure of evaluating the results of a clustering algorithm is known under the term cluster validity. In reference [15] two kinds of validity indices are showed: external indices and internal indices. A third is added in reference [29], based on relative criteria. The first is based on external criteria. This implies that we evaluate the results of a clustering algorithm based on a pre-specified structure, which is imposed on a data set and reflects our intuition about the clustering structure of the data set. The second approach is based on internal criteria. We may evaluate the results of a clustering algorithm in terms of quantities that involve the vectors of the data set themselves. The third approach of clustering validity is based on relative criteria. Here the basic idea is the evaluation of a clustering structure by comparing it to other clustering schemes, resulting by the same algorithm but with different parameter values.

To evaluate the proposed classification method, five cluster validation techniques are applied, based on internal criteria. These indices are used to measure the "goodness" of the result of the grouping; comparing the proposed classification method against the old pattern recognition procedure called Fuzzy c-means clustering.

2.4.1 Dunn's index

This index identifies sets of clusters that are compact and well separated. For any partition $U \leftrightarrow X: X_1 \cup \dots \cup X_c$ where X_i represents the i^{th} cluster of such partition, the Dunn's validation index, D , is defined as:

$$D(U) = \min_{1 \leq i \leq c} \left\{ \min_{\substack{1 \leq j \leq c \\ j \neq i}} \left\{ \frac{\delta(X_i, X_j)}{\max_{1 \leq k \leq c} \{\Delta(X_k)\}} \right\} \right\} \quad (19)$$

where $\delta(X_i, X_j)$ defines the distance between clusters X_i and X_j (intercluster distance); $\Delta(X_k)$ represents the intraccluster distance of cluster X_k , and c is the number of clusters of partition U . The main goal of this measure is to maximize intercluster distances whilst minimizing intraccluster distances. Thus large values of D correspond to good clusters. Therefore, the number of clusters that maximizes D is taken as the optimal number of clusters, c .

2.4.2 Davies-Bouldin index

As the Dunn's index, the Davies-Bouldin index aims at identifying sets of clusters that are compact and well separated. The Davies-Bouldin validation index, DB , is defined as:

$$DB(U) = \frac{1}{c} \sum_{i=1}^c \max \left\{ \frac{\Delta(X_i) + \Delta(X_j)}{\delta(X_i, X_j)} \right\} \quad (20)$$

where U , $\delta(X_i, X_j)$, $\Delta(X_i)$, $\Delta(X_j)$ and c are defined as in equation (20). Small values of DB correspond to clusters that are compact, and whose centers are far away from each other. Therefore, the cluster configuration that minimizes DB is taken as the optimal number of clusters, c .

2.4.3 Calinski and Harabasz index

The index of Calinski and Harabasz is defined by:

$$CH(k) = \frac{B_k / (k - 1)}{W_k / (n - k)} \quad (21)$$

where k denotes the number of clusters, and B_k and W_k denote the between and within cluster sums of squares of the partition, respectively. Therefore an optimal number of clusters is then defined as a value of k that maximizes $CH(k)$.

2.4.4 Krzanowski and Lai index

The index of Krzanowski and Lai is defined by:

where;

$$KL(k) = \left| \frac{diff_k}{diff_{k+1}} \right| \quad (22)$$

$$diff_k = (K - 1)^{2/p} W_{k-1} - k^{2/p} W_k \quad (23)$$

and p denotes the number of features in the data set. Therefore a value of k is optimal if it maximizes $KL(k)$.

2.4.5 Hartigan index

The index of Hartigan is defined by:

$$Han(k) = \log \left(\frac{B_k}{W_k} \right) \quad (24)$$

where, B_k and W_k denote the between and within cluster sums of squares of the partition, respectively. Therefore a value of k is optimal if it minimizes $Han(k)$.

3. Results and discussion

In accordance with the objectives and methodology used in this research encouraging results were obtained regarding the proposal to adopt the criterion used in Otsu's method to the process of clustering and unsupervised classification of colour images, and the application of cluster validity methods by five cluster validation indices, compare the results with those generated by the old pattern recognition procedure, Fuzzy c-means clustering.

In the present paper three issues are addressed. First, our proposed RGB unsupervised classification method. Secondly, to compare results we apply an old pattern recognition procedure, the Fuzzy c-means clustering. Third, five of cluster validation indices will be proposed to evaluate the quality of clusterings. To demonstrate the effectiveness of our proposed RGB unsupervised classification method, using 16 digital images from colour aerial photographs in which they can observe different land cover objects such as buildings,

streets, roads, tree crop plots, temporary plots of crops, pastures, water bodies etc.. Due to limited space, only the results of one experiment are included.

3.1 Unsupervised classification method by theory of the Otsu's method (results)

The proposed methodology is based on the method of Otsu. First a single thresholding of each of the bands of the RGB image, creating two classes per band as RGB in forming our startup account with eight classes. However, not all are representative, so that once segmented in this way the image is inserted through a sorting process exhaustive analysis of the variation between classes and within classes.

According to the characteristics of land cover images, which must be considered objects with different heterogeneous properties in size, shape and spectral behavior, we make the classification of the image labeled and grouped by simple thresholding, using the comprehensive analysis of variances between classes and within classes, to group and classify objects in the image.

Fig. 2. Image classified by the proposed classification Otsu method, where the optimal number of class is five.

As a result of this process, the classifier automatically grouped the different objects of the landscape into five classes, generating the classified image showed in Fig. 2, and the number of pixels per class, you can see in Table 1. With size of 1 542 288 pixels per band, where 53.1% of the surface of the image contains vegetation cover, the image represented by the blue color, and 14.8% contains bodies of water identified by the gray color. The 8.3% contain natural green grass, identified by the red color, 11.7% contains dry natural grass in the image identified by the yellow color, 12% contain areas without vegetation identified by the cyan color. Among the latter the accumulated deposits on the river bank, the effect of Hurricane Pauline, as well as streets and buildings are considered.

Classes	Pixels	Color
Plant Coverage	818,893	Blue
Water Bodies	228,830	Gray
Natural green grass	128,199	Red
Dry natural grass	180,696	Yellow
Area without vegetation coverage	185,670	Cyan
TOTAL	1,542,288	

Table 1. distribution of the classification of Fig. 2

3.2 The Fuzzy c-means clustering (results)

As a result of this process, the classifier automatically grouped the different objects of the landscape into three classes, generating the classified image showed in Fig. 3, and the number of pixels per class you can see in Table 2. With size of 1 542 288 pixels per band, where 23% of the surface of the image contains plant coverage, identified by the green colour; 36% of the surface of the image contains trees, identified by the blue colour; 28% of the surface of the image contains natural green grass, identified by the red colour; 9% of the surface of the image contains dry natural grass, identified by the yellow colour; and 4% of the surface of the image contains the accumulated deposits on the river bank, the effect of hurricane Pauline, the image represented by the cyan colour.

Fig. 3. Image classified by Fuzzy c-means clustering; where the optimal number of class by DB is five.

As showed in visual analysis (Fig. 2 and 3), our proposal clearly identifies the water bodies, whereas by Fuzzy c-means clustering classifier water bodies with grass coverage are confused.

Classes	Pixels	Color
Plant Coverage	358,176	green
Trees	549,978	Blue
Natural green grass	424,131	Red
Dry natural grass	143,474	Yellow
Area without vegetation coverage	66,529	Cyan
TOTAL	1,542,288	

Table 2. Distribution of the classification of Fig. 3

Fig. 4. Image classified by Fuzzy c-means clustering; where the optimal number of class is seven, by CH and Han, in (a); and two by Dunn and KL, in (b).

3.3 Quantitative results to validate the optimal number of clusters

Since clustering is an unsupervised method and there is no a priori indication for the actual number of clusters presented in a data set, there is a need of some kind of clustering result validation.

The results of the classification of colour images from aerial photographs by the proposed Otsu’s method, and the method known as Fuzzy c-means clustering are evaluated using five levels of validation. These indices are detailed in Section 2.3. Since the results of the Fuzzy c-means clustering algorithm, requires as input, the number of clusters, so it runs for 2,3, ..., 6; Fig. 3 corresponds to the optimal number of groups according to DB, who is the same as the proposed method.

No. Class	2	3	4	5	6	7	Optimo
DB	0.660	0.597	0.576	0.535*	0.605	0.584	<i>minimum</i>
CH	2.222	3.018	3.317	3.600	3.810	3.891*	<i>maximum</i>
Dunn	2.374*	1.417	1.199	1.154	1.020	0.926	<i>maximum</i>
KL	57.660*	37.527	29.976	25.080	21.922	20.104	<i>maximum</i>
Han	36.324	18.041	11.896	8.577	6.639	5.494*	<i>minimum</i>

* optimal

Table 3. Results obtained from 5 internal indices to validate the optimal number of clusters generated by Fuzzy c-means clustering.

Davies-Bouldin Index says: the cluster configuration that minimizes DB is taken as the optimal number of clusters, therefore for this methodology, the optimal number of clusters is 5.

Calinski and Harabasz Index says: an optimal number of clusters is then defined as a value of k that maximizes CH(k), therefore for this methodology, the optimal number of clusters is 7.

The Dunn’s Index says: the value that maximizes D is taken as the optimal number of clusters, therefore for this methodology, the optimal number of clusters is 2.

Krzanowski and Lai index says: a value of k is optimal if it maximizes KL(k), therefore for this methodology, the optimal number of clusters is 2

Hartigan index says: a value of k is optimal if it minimizes Han(k). therefore for this methodology, the optimal number of clusters is 7.

With the executed validation indices for Fuzzy c-means clustering, we want to find a match on the number of clusters of the new classification proposed. This was achieved with the Davies Bouldin index. Therefore, it indicates that the number of classes generated by the new classifier is optimal.

4. Conclusions

Otsu's method improved and changes implemented in this research can get the optimal threshold value as a basis for segmenting and classifying images in RGB color model, using a method of unsupervised classification.

Under the principle of the concept of within-class and between-class variances as suggested by Otsu; the algorithm automatically regrouped and merged different values of the groups obtained from the image in RGB colour domain and once the within-class variance is less than the between-class variance for each clustered class, the algorithm is finished.

Since this algorithm does not need to know how many classes are required to be clustered, five cluster validity indices have been proposed to validate if the number of clusters classified by Otsu is suitable. Davies Bouldin index indicates that the number of classes generated by the new classifier is optimal.

Also the classification made by the proposed method is better than that Fuzzy c-means clustering, as showed in Fig. 2, our method properly classified water bodies, whereas Fuzzy c-means clustering confuses the water bodies with vegetation.

This method unsupervised of image classification, can be widely used as support in decision-making in aspects of the environment by diagnosing areas of interest such as the loss of tree cover due to deforestation or fires, crop areas, Water Bodies, etc.. by virtue the proposed methodology to classify areas of different coverage density including areas where the soil surface has been exposed to erosion.

5. Acknowledgment

The authors would like to thank the World Bank from the Robert S. McNamara Fellowships Program (RSM) to support this research on: "Técnicas Inteligentes de Reconocimiento Aplicadas a la Clasificación del Uso del Suelo".

The Carolina Foundation and SRE_Mexico by co-financing for doctoral studies.

The "Colegio de Postgraduados", Mexico, for permission to join the Teachers' Training Sub-Investigators.

The UNAM by providing the aerial images, which is essential material for this investigation.

6. References

- [1] D. Lu, and Q. Weng. 2007. A survey of image classification methods and techniques for improving classification performance, *Int. J. Remote Sensing* 28(5):823-870.
- [2] A. K. Jain, M. N. Murty and P. J. Flynn. 1999. Data clustering: a review, *ACM Computing Surveys*, Vol. 31 (3):264-323.
- [3] E.R. Hunt; Cavigelli, M.; Daughtry, C.T.; McMurtrey, J.; Walthall, S.L. Evaluation of digital photography from model aircraft for remote sensing of crop biomass. *Precision Agriculture* 2005, 6 (4), 359-378.
- [4] X. Xie, and Majid Mirmehdi. 2007. Colour Image Segmentation using Texems, *Annals of the British Machine Vision Association*, (6):1-10.
- [5] X. Xie, 2008. A Review of Recent Advances in Surface Defect Detection using Texture Analysis Techniques, *Electronic Letters on Computer Vision and Image Analysis*, Special Issue on Quality Control by Artificial Vision, vol. 7(3): 1 -25.
- [6] M. Haindl, and V. Havlicek. 2002. A simple multispectral multiresolution Markov texture model. In *International Workshop on Texture Analysis and Synthesis*, pp: 63-66.
- [7] M. Dubuisson-Jolly, and A. Gupta. 2000. Color and texture fusion: Application to aerial image segmentation and GIS updating. *Image and Vision Computing*, 18:823-832.
- [8] C. Palm, 2004. Color texture classification by integrative co-occurrence matrices. *Pattern Recognition*, 37(5):965-976

- [9] M. Mirmehdi, and M. Petrou. 2000. Segmentation of color textures. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 22(2):142-159.
- [10] N. Otsu, 1979. A threshold selection method from gray-level histogram. *IEEE Transactions on System Man Cybernetics* 9(1):62-66.
- [11] J. C. Bezdek, 1981. *Pattern Recognition with Fuzzy Objective Function Algorithms*. Plenum Press, New York, NY, USA .
- [12] J. C. Bezdek , J. Keller, R. Krisnapuram, N. Pal. 2005. *Fuzzy Models and Algorithms for Pattern Recognition and Image Processing (The Handbooks of Fuzzy Sets)*. Springer, 776 pp.
- [13] M. Halkidi, Y. Batistakis and M. Vazirgiannis. 2002a. Cluster validity methods: part I, *SIGMOD Rec.*, Vol. 31(2):40-45.
- [14] M. Halkidi, Y. Batistakis and M. Vazirgiannis. 2002b. Cluster validity methods: part II, *SIGMOD Rec.*, Vol. 31, (3). 19-27.
- [15] K. Wang, B. Wang, and L. Peng. 2009. CVAP: Validation for Cluster Analyses. *Data Science. Journal* 8(20), 88-93
- [16] M. Halkidi, Y. Batistakis, and M. Vazirgiannis. 2001. On Clustering Validation Techniques. *Intelligent Information Systems Journal*, 17 (2-3): 107-145.
- [17] J. Dunn. 1974. Well separated clusters and optimal fuzzy partitions. *J.Cybernetics*, Vol. 4, pp. 95-104
- [18] J.C. Bezdek, and N.R. Pal. 1998 .Some new indexes of cluster validity, *IEEE Transactions on Systems, Man and Cybernetics*, Vol. 28 (B):301-315
- [19] N. Bolshakova, and F. Azuaje. 2003 Cluster validation techniques for genome expression data. *Signal Processing*, 83(4): 825-833.
- [20] D.L. Davies, and D.W. Bouldin. 1979. A cluster separation measure. *IEEE Transactions on Pattern Recognition and Machine Intelligence*, Vol. 1(2):224-227
- [21] E. Dimitriadou, S. Dolnicar, and A. Weingessel. 2002 An examination of indexes for determining the Number of Cluster in binary data sets. *Psychometrika*, 67(1): 137-160.
- [22] S. Dudoit, and J. Fridlyand. 2002. A prediction-based resampling method for estimating the number of clusters in a dataset. *Genome Biology*, 3(7): 0036.1-21.
- [23] G. Shu, B. Zeng, Y. P Chen, and O. H. Smith. (2003) Performance assessment of kernel density clustering for gene expression profile data. *Comparative and Functional Genomics*, 4(3): 287-299.
- [24] R. Calinski, and J. Harabasz. 1974. A dendrite method for cluster analysis. *Commun Statistics* 3:1-27.
- [25] W. Krzanowski, and Y. Lai. 1985. A criterion for determining the number of groups in a dataset using sum of squares clustering. *Biometrics*. 44:23-34.
- [26] J.A. Hartigan. 1985. Statistical theory in clustering. *J Classification.*, 2:63-76.
- [27] Macedo, A.; Pajares, G.; Santos, M. Unsupervised classification with ground color cover images. *Agrociencia* 2010, 44, 711-722.
- [28] Macedo-Cruz, A.; Pajares, G.; Santos, M.; Villegas-Romero, I. Digital image sensor-based assessment of the status of Oat (*Avena sativa* L.) Crops after frost damage. *Sensors* 2011, 11, 6015-6036.

- [29] F. Kovács, C. Legány, and A. Babos. 2005. Cluster validity measurement techniques. Proceedings of the 6th International Symposium of Hungarian Researchers on Computational Intelligence, Budapest, Nov. 2005, 18-19.

IntechOpen

IntechOpen

Deforestation Around the World

Edited by Dr. Paulo Moutinho

ISBN 978-953-51-0417-9

Hard cover, 372 pages

Publisher InTech

Published online 30, March, 2012

Published in print edition March, 2012

Deforestation and forest degradation represent a significant fraction of the annual worldwide human-induced emission of greenhouse gases to the atmosphere, the main source of biodiversity losses and the destruction of millions of people's homes. Despite local/regional causes, its consequences are global. This book provides a general view about deforestation dynamics around the world, incorporating analyses of its causes, impacts and actions to prevent it. Its 17 Chapters, organized in three sections, refer to deforestation impacts on climate, soil, biodiversity and human population, but also describe several initiatives to prevent it. A special emphasis is given to different remote-sensing and mapping techniques that could be used as a source for decision-makers and society to promote forest conservation and control deforestation.

How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Antonia Macedo-Cruz, I. Villegas-Romero, M. Santos-Peñas and G. Pajares-Martinsanz (2012). Unsupervised Classification of Aerial Images Based on the Otsu's Method, Deforestation Around the World, Dr. Paulo Moutinho (Ed.), ISBN: 978-953-51-0417-9, InTech, Available from:
<http://www.intechopen.com/books/deforestation-around-the-world/unsupervised-classification-of-aerial-images-based-on-the-otsu-s-method>

INTech
open science | open minds

InTech Europe

University Campus STeP Ri
Slavka Krautzeka 83/A
51000 Rijeka, Croatia
Phone: +385 (51) 770 447
Fax: +385 (51) 686 166
www.intechopen.com

InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai
No.65, Yan An Road (West), Shanghai, 200040, China
中国上海市延安西路65号上海国际贵都大饭店办公楼405单元
Phone: +86-21-62489820
Fax: +86-21-62489821

© 2012 The Author(s). Licensee IntechOpen. This is an open access article distributed under the terms of the [Creative Commons Attribution 3.0 License](https://creativecommons.org/licenses/by/3.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

IntechOpen

IntechOpen