

We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists

6,900

Open access books available

186,000

International authors and editors

200M

Downloads

Our authors are among the

154

Countries delivered to

TOP 1%

most cited scientists

12.2%

Contributors from top 500 universities



WEB OF SCIENCE™

Selection of our books indexed in the Book Citation Index
in Web of Science™ Core Collection (BKCI)

Interested in publishing with us?
Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected.
For more information visit www.intechopen.com



Desalination with Renewable Energy: A 24 Hours Operation Solution

*Muhammad Wakil Shahzad, Muhammad Burhan,
Doskhan Ybyraiymkul and Kim Choon Ng*

Abstract

The inevitable escalation in economic development has serious implications on energy and environment nexus. The International Energy Outlook 2016 (IEO2016) predicted that the Non Organization for Economic Cooperation and Development (non-OECD) countries will lead with 71% rise in energy demand in contrast with only 18% in developed countries from 2012 to 2040. In Gulf Cooperation Council countries (GCC) countries, about 50% of primary energy is consumed for cogeneration based power and desalination plants. The desalination capacities are expected to increase fivefold by 2050 and renewable energy application can be one of the solution for sustainable water production. The major bottleneck in commercialization of renewable energy sources is its intermittent nature of supplies specially wind and solar. We proposed solar thermal energy storage to operate desalination system around the clock. Magnesium oxide (MgO) can be utilized as an efficient energy storage system to store solar thermal energy for off period operation. The heat generated by regeneration processes at day time and exothermic adsorption at night can operate desalination cycle 24 h. The operational temperature ranges from 120 to 140°C and energy storage 41–81 kJ/mol. It was successfully demonstrated by experimentation that MgO operated hybrid desalination cycle can achieve highest performance and lowest carbon emission. The proposed cycle can achieve sustainable water production goals.

Keywords: renewable energy, hybrid desalination, low emission desalination, sustainable desalination, energy storage

1. Introduction

The energy demand in Gulf Cooperation Council (GCC) countries is almost doubled in a decades, from 300 TWh in 2000 to 600 TWh in 2012. In GCC countries, the residential and commercial sector energy demand has grown rapidly. The residential sector consumes over 50% due to improved living standards. In GCC countries, per capita primary energy consumption is the highest as compared to other countries in the world as shown in the **Figure 1** [1–3].

The GCC countries also produce substantial amount of CO₂ and it was estimated as 1.2 billion tons of CO₂-equivalent in 2012. The major part of CO₂ emission is related to energy and water production. The GCC countries are the most water




Figure 1.
Per capita oil consumption in different parts of the world.

| Country | 2010 consumption | 2050 consumption | 2050 shortage |
|--------------|------------------|------------------|---------------|
| Bahrain | 227 | 400 | 380 |
| Kuwait | 509 | 1220 | 850 |
| Oman | 760 | 1700 | 1150 |
| Qatar | 328 | 400 | 175 |
| Saudi Arabia | 20,480 | 27,000 | 20,100 |
| UAE | 3375 | 3500 | 3250 |
| Total | | | |

Table 1.
Water consumption and estimated shortage in 2050 in GCC countries.

scariest in the world due to dry environmental conditions and recently it became even worst due to population increase and GDP growth. It is estimated that by 2050, the shortage of water supply can be as high as 77%. **Table 1** shows the water consumption and shortage in million cubic meter per year scenario in all GCC countries by 2050. It can be noticed the large gap in water demand and supply cannot be filled by renewable and ground water sources. The non-renewable such as desalination is the only source for future water supplies in GCC countries [1–3].

Today, all desalination processes are energy intensive and consume primary energy in the range of 6–10 kWh/m³. The inefficiency of desalination processes, 10–13% of thermodynamic limit, requires not only more energy but they also emit enormous CO₂ [4–7]. For future sustainability, one feasible option is to utilize renewable energy such as wind and solar. The renewable technologies have drastically developed and their economics are greatly improved in recent years, and GCC countries have great potential to exploit the renewable energies potential such as solar and wind. The GCC countries government announced mega investment plans to invest in renewable energy sectors to meet the increasing demand of electricity as shown in **Figure 2** [8].

The resettlement of energy mix in GCC countries needs a comprehensive plan for contractor as well as operator companies. One of the major challenges in renewable energies development is its intermittent nature. Currently they are only employed to cope the peak load typically during office hours. The one of the solution to overcome intermittent supply is the energy storage and there are two methods namely, battery storage and thermal heat storage. In terms of battery storage, the efficiency is very low, typically 8–10% in field operation due to




Figure 2.
GCC countries renewable energy development plan by 2030.

| Materials | Heat storage method | | Heat storage density (GJ/m ³) | Heat charging temperature (°C) |
|--------------------------------|--------------------------------|------------------|---|--------------------------------|
| Co ₃ O ₄ | Thermochemical materials (TCM) | Inorganic oxides | 5.0 | 925 |
| CaO | | | 4.5 | 550 |
| MgO | | | 3.4 | 350 |
| MgSO ₄ | Phase change materials | Anhydrate | 2.6 | 125 |
| Silica gel | | Adsorbate | 0.8 | 85 |
| Zeolite | | | 0.6 | 220 |
| Paraffin | Phase change materials | | 0.2 | 60 |
| Water | Sensible | | 0.2 | 0–100 |

Table 2.
Comparison of different thermal energy storage materials.

efficiencies involved from one form to other form conversions. On the other hand, direct thermal storage and utilization efficiency is significantly high due to same form of energy utilization without conversion into different forms. There are three major technologies utilize different methods to store solar energy. The comparison of different heat storage materials is summarized in **Table 2** [9–11].

2. Solar thermal energy storage and desalination application

Thermochemical materials (TCM) have many advantages over the other materials such as high heat storage density and low heat leak. Once the reactant leave the thermochemical materials, the enthalpy remains same and it help to achieve the state of energy charging. Subsequently, the discharged energy is utilized while the material remains stable. In the past, a lot of studies were carried out on heat pump using different TCM materials [12–14]. The selection of TCM materials for different application is based on many elements such as (i) heat storage temperature, (ii) heat releasing temperature,




Figure 3.
MgO thermal energy storage system operation.

(iii) heat storage density, and (iv) material stability. The magnesium oxide (MgO) is most suitable for thermal heat storage as compared to other materials due to its high density and stability. Many researchers published data on MgO thermal heat storage and its performance improvement [15, 16].

The dry MgO reacts with water (hydration) to become hydrated Mg(OH)₂. The hydration is an exothermic reaction and generates 81 kJ/mol. During dehydration of Mg(OH)₂ it becomes MgO through a reverse process at 350–500°C from solar collectors and high temperature vapor are utilized as a heat source. It can be noticed that MgO as an energy storage material produce heat during day as well as night time. The hydration process at night and dehydration process at day with solar energy can produce sufficient heat energy to operate the desalination cycle.

The principle of this heat pump is shown in **Figure 3**. The heat pump consists of a magnesium oxide reactor and a water reservoir. In heat storage mode magnesium hydroxide (Mg(OH)₂) is dehydrated by surplus heat (Q_d) at T_d from sun. The generated vapors are condensed at the reservoir at T_C and the condensation heat (Q_d) of the vapor is used for desalination cycle at day time. The hydration of magnesium oxide proceeds in the reactor by introducing the vapor, and a hydration heat output (Q_h) at T_h is generated to operate desalination cycle at night. Thermal drivability, which does not require mechanical work, is one of the advantages of the heat pump. The environmentally friendly and economical nature of the reactants is also advantageous. This type of heat pump is able to store heat at around 350°C through Mg(OH)₂ dehydration and to transfer stored heat at temperatures between 110 and 150°C through MgO hydration. The solar thermal energy storage and 24 h delivery around 100°C is best suitable for sustainable desalination processes [17–19].

The renewable energy (RE) driven desalination processes are already commercialized but at low scale due to some operational complexity. **Table 3** summarized

| Plant name | Location | Technology | Capacity | Energy source | Cost* (US\$/m ³) |
|-----------------|--------------|--------------|----------|---------------|------------------------------|
| Kimolos | Greece | MED | 2000 | Geothermal | 2.5–3 |
| Keio university | Japan | MED | 100 | Solar thermal | |
| PSA | Spain | MED | 72 | CSP | |
| Ydriada | Greece | RO | 80 | Wind | 2–6 |
| Morocco | Morocco | RO | 20 | PV | 2–5 |
| Oyster | Scotland | RO | — | Wave energy | 3–5 |
| KAUST** | Saudi Arabia | MEDAD hybrid | 10 | Solar thermal | 0.5 |

*Cost is estimated based on plant capacity more than 1000 m³/day [20].

**Refs. [21–29].

Table 3.
RE driven desalination technologies and water cost.

the major renewable desalination plants operated in the world and estimated cost of water production.

It can be noticed that thermal desalination processes are most favorable option with solar thermal energy operation. The most efficient thermally driven multi effect desalination (MED) system recently investigated to overcome its conventional operational limitations. The numbers of stages in a MED is controlled by top brine temperature (TBT) and lower brine temperature (LBT). The TBT typically 70°C is restricted by soft scaling components in the feed water and the LBT is controlled by ambient condition due to water cooled condenser to condense the last stage vapors. The MED system can be more efficient if these two limitations can be removed to increase number of recoveries. Researchers found that TBT can be increased to 125°C by inducing nano-filtration (NF) prior to introduction the feed into the system. This NF process helps to remove soft scaling components and prevent scaling and fouling on the tubes of evaporators. The inter stage temperature and the last stage operating temperature limitations can be overcome by hybridization with adsorption cycle. AD cycle can operate below ambient conditions typically as low as 5°C due high affinity of water vapors of adsorbent (silica gel). MED last stage temperature can be lower down to 5°C by introducing the AD at downstream. The proposed hybrid MEDAD system with TES will be the best choice for sustainable water supplies.

3. Proposed system operation

The detailed schematic of TES driven hybrid MEDAD desalination cycle is shown in **Figure 4**. During day time operation, solar heat is supplied to the hydrated $\text{Mg}(\text{OH})_2$ at 300–400°C and regenerated vapor condensation heat at 120–150°C is utilized to operate desalination cycle. At night time, the hydration of MgO generates sufficient heat due to exothermic reaction that is supplied to the desalination cycle to continue the operation. It can be noticed that with MgO energy storage system, thermal desalination can be operated for 24 h using solar energy.




Figure 4.
Proposed TES driven hybrid MEDAD desalination cycle.

4. Experimentation

An experimental system was designed and installed to test workability of proposed concept. **Figure 5** shows the temperature profiles of MEDAD effects at heat source of 45°C. The pilot was tested at different temperatures to investigate the performance. **Figure 6** shows the hybrid MEDAD system effects temperatures at different heat source temperatures. The system performed well as per designed 3–4°C inter-effect temperature difference. Similarly, **Figure 7** shows the corresponding saturation pressures.

Figure 8 shows the water production profiles of MED effects, AD condenser and total production at 45°C heat source temperature. The summary of water production presented in **Figure 9** at different heat source temperatures. It can be seen that at higher temperature the water production is also higher and it drop due to drop in heat capacity. The system is designed for 45°C operational temperature but it performed well at off-design conditions. It shows the robustness of the thermally driven desalination systems.

The thermal energy consumed is shown in **Figure 10**. It can be noticed that at higher heat input temperature the energy consumed by the system is also higher. It is mainly due to the higher temperature difference between heat inlet and out




Figure 5.
Hybrid MEDAD temperature profiles at 45°C heat source.




Figure 6.
Hybrid MEDAD inter-effect temperatures at different heat source (reproduce with author’s permission [30]).




Figure 7.
Hybrid MEDAD inter-effect pressures at different heat source (reproduce with author’s permission [30]).




Figure 8.
Hybrid MEDAD water production profiles at 45°C heat source (reproduce with author’s permission [30]).




Figure 9.
Hybrid MEDAD water production at different heat source temperature (reproduce with author’s permission [30]).




Figure 10. Hybrid MEDAD thermal energy input at different heat source temperature (reproduce with author’s permission [30]).

temperatures. The interesting trend was noticed at below 25°C where heat input showed negative value. It is because the heat was scavenged from the ambient. The system was operating below ambient conditions due to adsorption cycle hybridization that allows last effects to operate as low as 5°C.

The successful experimentation of hybrid MEDAD cycle proved the workability of TES + MEDAD system for future sustainable water supplies.

5. Conclusion

Thermal energy storage based hybrid desalination system is proposed for 24 h operation. MgO has high energy density and stability for long term operation. The proposed TES + MEDAD hybrid cycle has highest performance. The superiority of MEDAD cycle has been successfully demonstrated pilot as compared to conventional MED system by improving water production to twofold as same heat source temperature. The proposed combination is estimated to have highest performance to achieve sustainability goals. These innovative solutions will help to save energy and protect environment.

Acknowledgements

Authors would like to thanks to KAUT and NUS for this study. The data is reproduced by PI and the author’s permission [30].

Nomenclature

| | |
|------|---|
| OECD | Organization for Economic Cooperation and Development |
| GCC | Gulf Cooperation Council |
| GDP | gross domestic product |
| UAE | United Arab Emirates |
| TCM | thermochemical materials |
| RE | renewable energy |
| MED | multi effect desalination |

| | |
|------|---------------------------------|
| MSF | multi stage flash |
| SWRO | seawater reverse osmosis |
| AD | adsorption |
| TES | thermal energy storage |
| CSP | concentrated solar photovoltaic |
| TBT | top brine temperature |
| LBT | lower brine temperature |
| LPM | liter per minute |

Author details

Muhammad Wakil Shahzad*, Muhammad Burhan, Doskhan Ybyraiymkul and Kim Choon Ng
Water Desalination and Reuse Centre (WDRC), Biological and Environmental Science and Engineering (BESE), King Abdullah University of Science and Technology, Saudi Arabia

*Address all correspondence to: muhammad.shahzad@kaust.edu.sa

IntechOpen

© 2019 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/3.0>), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited. 

References

- [1] Energy Use (kg of Oil Equivalent Per Capita). World Bank Data. Available from: <https://data.worldbank.org/indicator/EG.USE.PCAP.KG.OE> [Accessed: Jan 02 2019]
- [2] Renewable Energy Market Analysis. The GCC region. The International Renewable Energy Agency (IRENA) Report 2016
- [3] Parmigiani L. Water and Energy in the GCC: Securing Scarce Water in Oil-Rich Countries. The Institut français des relations internationales (Ifri) Report 2015. ISBN: 978-2-36567-442-3
- [4] Shahzad MW, Burhan M, Ng KC. A standard primary energy approach for comparing desalination processes. *Nature Clean Water*. 2019;**1**:1-7
- [5] Shahzad MW, Burhan M, Ybyraimkul D, Ng KC. Desalination processes efficiency and future roadmap. *Entropy*. 2019;**21**(1):84
- [6] Shahzad MW, Burhan M, Son HS, Seung Jin O, Ng KC. Desalination processes evaluation at common platform: A universal performance ratio (UPR) method. *Applied Thermal Engineering*. 2018;**134**:62-67
- [7] Ng KC, Shahzad MW, Son HS, Hamed OA. An exergy approach to efficiency evaluation of desalination. *Applied Physics Letters*. 2017;**110**:184101. DOI: 10.1063/1.4982628
- [8] Partner, Kearney AT. Why oil-rich gulf countries need to invest in renewable energy. World Economic Forum. Available from: <https://www.weforum.org/agenda/2017/05/why-oil-rich-gulf-countries-need-to-invest-in-renewable-energy/> [Accessed: Jan 15 2019]
- [9] Yim T, Kim HS, Lee JY. Cyclic assessment of magnesium oxide with additives as a thermochemical material to improve the mechanical strength and chemical reaction. *Energies*. 2018;**11**:2366
- [10] Singh A, Tescari S, Lantin G, Agrafiotis C, Roeb M, Sattler C. Solar thermochemical heat storage via the $\text{Co}_3\text{O}/\text{CoO}$ looping cycle: Storage reactor modelling and experimental validation. *Solar Energy*. 2017;**144**:453-465
- [11] Fernandes MS, Brites GJV, Costa JJ, Gaspar AR, Costa VAF. Modeling and parametric analysis of an adsorber unit for thermal energy storage. *Energy*. 2016;**102**:83-94
- [12] Cabeza LF, Martorell I, Miró L, Fernández AI, Barreneche C. *Advances in Thermal Energy Storage Systems: Methods and Applications, Advances in Thermal Energy Storage Systems*. Woodhead Publishing. ISBN: 978-1-78242-088-0
- [13] Alva G, Lin Y, Fang G. An overview of thermal energy storage systems. *Energy*. 2018;**144**:341-378
- [14] Thomas JJ, Musso S, Prestini I. Kinetics and activation energy of magnesium oxide hydration. *The American Ceramic Society Journal*. 2014;**97**:275-282
- [15] Mastronardo E, Kato Y, Bonaccorsi L, Piperopoulos E, Milone C. Thermochemical storage of middle temperature wasted heat by functionalized C/Mg(OH) hybrid materials. *Energies*. 2017;**10**:70
- [16] Mastronardo E, Kato Y, Bonaccorsi L. *Piperopoulos elpida*, efficiency improvement of heat storage materials for $\text{MgO}/\text{H}_2\text{O}/\text{Mg}(\text{OH})_2$ chemical heat pumps. *Applied Energy*. 2016;**162**:31-39
- [17] Kato Y, Takahashi F, Sekiguchi T, Ryu J. Study on medium temperature chemical

heat storage using mixed hydroxides. *International Journal of Refrigeration*. 2009;**32**:661-666

[18] Kato Y, Nakahata J, Yoshizawa Y. Durability characteristics of the hydration magnesium oxide under repetitive reaction. *Journal of Material Sciences*. 1999;**34**:475-480

[19] Kato Y, Yamashita N, Kobayashi K, Yoshizawa Y. Kinetic study of the hydration of magnesium oxide for a chemical heat pump. *Applied Thermal Engineering*. 1996;**16**:853-862

[20] Alkaisi A, Mossad R, Sharifian-Barforoush A. A review of the water desalination systems integrated with renewable energy. *Energy Procedia*. 2017;**110**:268-274

[21] Shahzad MW, Burhan M, Ang L, Ng KC. Energy-water-environment nexus underpinning future desalination sustainability. *Desalination*. 2017;**413**:52-64

[22] Shahzad MW, Ng KC. An improved multi-evaporator adsorption desalination cycle for GCC countries. *Energy Technology*. 2017. DOI: 10.1002/ente.201700061

[23] Shahzad MW, Ng KC, Thu K. Future sustainable desalination using waste heat: Kudos to thermodynamic synergy. *Environmental Science: Water Research & Technology*. 2016;**2**:206-212

[24] Thu K, Kim Y-D, Shahzad MW, Saththasivam J, Ng KC. Performance investigation of an advanced multi-effect adsorption desalination (MEAD) cycle. *Applied Energy*. 2015;**159**:469-477

[25] Shahzad MW, Thu K, Kim Y-d, Ng KC. An experimental investigation on MEDAD hybrid desalination cycle. *Applied Energy*. 2015;**148**:273-281

[26] Ng KC, Thu K, Oh SJ, Ang L, Shahzad MW, Ismail AB. Recent

developments in thermally-driven seawater desalination: Energy efficiency improvement by hybridization of the MED and AD cycles. *Desalination*. 2015;**356**:255-270

[27] Shahzad MW, Ng KC, Thu K, Saha BB, Chun WG. Multi effect desalination and adsorption desalination (MEDAD): A hybrid desalination method. *Applied Thermal Engineering*. 2014;**72**:289-297

[28] Ng KC, Thu K, Shahzad MW, Gee CW. Progress of adsorption cycle and its hybrids with conventional multi-effect desalination processes. *IDA Journal of Desalination and Water Reuse*. 2016;**6**:1, 44-56

[29] Shahzad MW, Thu K, Saha BB, Ng KC. An emerging hybrid multi-effect adsorption desalination system. *Evergreen Joint Journal of Novel Carbon Resource Sciences & Green Asia Strategy*. 2014;**01**:02, 30-36

[30] Muhammad Wakil Shahzad, The hybrid multi-effect desalination (MED) and the adsorption (AD) cycle for desalination, Doctoral Thesis, National University of Singapore. 2013