We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists



186,000

200M



Our authors are among the

TOP 1% most cited scientists





WEB OF SCIENCE

Selection of our books indexed in the Book Citation Index in Web of Science™ Core Collection (BKCI)

## Interested in publishing with us? Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected. For more information visit www.intechopen.com



## Optimal Filtering for Linear States over Polynomial Observations

Joel Perez<sup>1</sup>, Jose P. Perez<sup>1</sup> and Rogelio Soto<sup>2</sup> <sup>1</sup> Department of Physical and Mathematical Sciences, Autonomous University of Nuevo <sup>2</sup> Mechatronics and Automation Department, Monterrey Institute of Technology and Higher Education Mexico

## 1. Introduction

Although the general optimal solution of the filtering problem for nonlinear state and observation equations confused with white Gaussian noises is given by the equation for the conditional density of an unobserved state with respect to observations (see (1–6)), there are a very few known examples of nonlinear systems where that equation can be reduced to a finite-dimensional closed system of filtering equations for a certain number of lower conditional moments (see (7–10) for more details). Some relevant results on filtering for nonlinear stochastic systems can be found in (11–14). There also exists a considerable bibliography on robust filtering for the "general situation" systems (see, for example, (15–23)). Apart form the "general situation," the optimal finite-dimensional filters have recently been designed for certain classes of polynomial system states over linear observations with invertible ((24; 25; 27; 28)) or non-invertible ((26; 29)) observation matrix. However, the cited papers never consider filtering problems with nonlinear, in particular, polynomial observations.

This work presents the optimal finite-dimensional filter for linear system states over polynomial observations, continuing the research in the area of the optimal filtering for polynomial systems, which has been initiated in ((24–27; 29)). Designing the optimal filter over polynomial observations presents a significant advantage in the filtering theory and practice, since it enables one to address some filtering problems with observation nonlinearities, such as the optimal cubic sensor problem (30). The optimal filtering problem is treated proceeding from the general expression for the stochastic Ito differential of the optimal estimate and the error variance (31). As the first result, the Ito differentials for the optimal estimate and error variance corresponding to the stated filtering problem are derived. It is then proved that a closed finite-dimensional system of the optimal filtering equations with respect to a finite number of filtering variables can be obtained for a polynomial observation equation, additionally assuming a conditionally Gaussian initial condition for the higher degree states. This assumption is quite admissible in the filtering framework, since the real distribution of the entire state vector is actually unknown. In this case, the corresponding procedure for designing the optimal filtering equations is established.

As an illustrative example, the closed system of the optimal filtering equations with respect to two variables, the optimal estimate and the error variance, is derived in the explicit form for the particular case of the third degree polynomial observations. This filtering problem generalizes the optimal cubic sensor problem stated in (30), where nonexistence of a closed-form solution is indicated for the "general situation" case, without any assumptions for the third order state distribution. In our paper, taking into account that the real distributions of the first and third degree states are unknown, a conditionally Gaussian initial condition is additionally assumed for the third degree state. The resulting filter yields a reliable and rapidly converging estimate, in spite of a significant difference in the initial conditions between the state and estimate and very noisy observations, in the situation where the unmeasured state itself is a time-shifted Wiener process and the extended Kalman filter (EKF) approach fails.

## 2. Filtering Problem for Linear States over Polynomial Observations

Let  $(\Omega, F, P)$  be a complete probability space with an increasing right-continuous family of  $\sigma$ -algebras  $F_t$ ,  $t \ge t_0$ , and let  $(W_1(t), F_t, t \ge t_0)$  and  $(W_2(t), F_t, t \ge t_0)$  be independent Wiener processes. The  $F_t$ -measurable random process (x(t), y(t)) is described by a linear differential equation for the system state

$$dx(t) = (a_0(t) + a(t)x(t))dt + b(t)dW_1(t), \quad x(t_0) = x_0,$$
(1)

and a nonlinear polynomial differential equation for the observation process

$$dy(t) = h(x,t)dt + B(t)dW_2(t).$$
 (2)

Here,  $x(t) \in \mathbb{R}^n$  is the state vector and  $y(t) \in \mathbb{R}^m$  is the observation vector. The initial condition  $x_0 \in \mathbb{R}^n$  is a Gaussian vector such that  $x_0$ ,  $W_1(t)$ , and  $W_2(t)$  are independent. It is assumed that  $B(t)B^T(t)$  is a positive definite matrix. All coefficients in (1)–(2) are deterministic functions of time of appropriate dimensions. The nonlinear function h(x, t) forms the drift in the observation equation (2).

The nonlinear function h(x, t) is considered a polynomial of n variables, components of the state vector  $x(t) \in \mathbb{R}^n$ , with time-dependent coefficients. Since  $x(t) \in \mathbb{R}^n$  is a vector, this requires a special definition of the polynomial for n > 1. In accordance with (27), a p-degree polynomial of a vector  $x(t) \in \mathbb{R}^n$  is regarded as a p-linear form of n components of x(t)

$$h(x,t) = \alpha_0(t) + \alpha_1(t)x + \alpha_2(t)xx^T + \ldots + \alpha_p(t)x \dots_{p \text{ times}} \dots x,$$
(3)

where  $\alpha_0(t)$  is a vector of dimension n,  $\alpha_1$  is a matrix of dimension  $n \times n$ ,  $\alpha_2$  is a 3D tensor of dimension  $n \times n \times n$ ,  $\alpha_p$  is an (p+1)D tensor of dimension  $n \times \ldots_{(p+1) \text{ times}} \ldots \times n$ , and  $x \times \ldots_{p \text{ times}} \ldots \times x$  is a *p*D tensor of dimension  $n \times \ldots_{p \text{ times}} \ldots \times n$  obtained by *p* times spatial multiplication of the vector x(t) by itself (see (27) for more definition). Such a polynomial can also be expressed in the summation form

$$h_k(x,t) = \alpha_{0\ k}(t) + \sum_i \alpha_{1\ ki}(t)x_i(t) + \sum_{ij} \alpha_{2\ kij}(t)x_i(t)x_j(t) + \dots + \sum_{i_1\dots i_p} \alpha_{p\ ki_1\dots i_p}(t)x_{i_1}(t)\dots x_{i_p}(t), \quad k, i, j, i_1, \dots, i_p = 1, \dots, n.$$

The estimation problem is to find the optimal estimate  $\hat{x}(t)$  of the system state x(t), based on the observation process  $Y(t) = \{y(s), 0 \le s \le t\}$ , that minimizes the Euclidean 2-norm

$$J = E[(x(t) - \hat{x}(t))^T (x(t) - \hat{x}(t)) \mid F_t^Y]$$

at every time moment *t*. Here,  $E[\xi(t) | F_t^Y]$  means the conditional expectation of a stochastic process  $\xi(t) = (x(t) - \hat{x}(t))^T (x(t) - \hat{x}(t))$  with respect to the  $\sigma$  - algebra  $F_t^Y$  generated by the observation process Y(t) in the interval  $[t_0, t]$ . As known (31), this optimal estimate is given by the conditional expectation

$$\hat{x}(t) = m_x(t) = E(x(t) \mid F_t^Y)$$

of the system state x(t) with respect to the  $\sigma$  - algebra  $F_t^Y$  generated by the observation process Y(t) in the interval  $[t_0, t]$ . As usual, the matrix function

$$P(t) = E[(x(t) - m_x(t))(x(t) - m_x(t))^T | F_t^Y]$$

is the estimation error variance.

The proposed solution to this optimal filtering problem is based on the formulas for the Ito differential of the optimal estimate and the estimation error variance (cited after (31)) and given in the following section.

### 3. Optimal Filter for Linear States over Polynomial Observations

Let us reformulate the problem, introducing the stochastic process z(t) = h(x, t). Using the Ito formula (see (31)) for the stochastic differential of the nonlinear function h(x, t), where x(t) satisfies the equation (1), the following equation is obtained for z(t)

$$dz(t) = \frac{\partial h(x,t)}{\partial x} (a_0(t) + a(t)x(t))dt + \frac{\partial h(x,t)}{\partial t}dt +$$

$$\frac{1}{2} \frac{\partial^2 h(x,t)}{\partial x^2} b(t)b^T(t)dt + \frac{\partial h(x,t)}{\partial x}b(t)dW_1(t), \quad z(0) = z_0.$$
(4)

Note that the addition  $\frac{1}{2} \frac{\partial^2 h(x,t)}{\partial x^2} b(t) b^T(t) dt$  appears in view of the second derivative in x in the Ito formula.

The initial condition  $z_0 \in \mathbb{R}^n$  is considered a conditionally Gaussian random vector with respect to observations. This assumption is quite admissible in the filtering framework, since the real distributions of x(t) and z(t) are actually unknown. Indeed, as follows from (32), if only two lower conditional moments, expectation  $m_0$  and variance  $P_0$ , of a random vector  $[z_0, x_0]$ are available, the Gaussian distribution with the same parameters,  $N(m_0, P_0)$ , is the best approximation for the unknown conditional distribution of  $[z_0, x_0]$  with respect to observations. This fact is also a corollary of the central limit theorem (33) in the probability theory.

A key point for further derivations is that the right-hand side of the equation (4) is a polynomial in *x*. Indeed, since h(x, t) is a polynomial in *x*, the functions  $\frac{\partial h(x,t)}{\partial x}$ ,  $\frac{\partial h(x,t)}{\partial x}x(t)$ ,  $\frac{\partial h(x,t)}{\partial t}$ , and  $\frac{\partial^2 h(x,t)}{\partial x^2}$  are also polynomial in *x*. Thus, the equation (4) is a polynomial state equation with a polynomial multiplicative noise. It can be written in the compact form

$$dz(t) = f(x,t)dt + g(x,t)dW_1(t), \quad z(t_0) = z_0,$$
(5)

where

$$f(x,t) = \frac{\partial h(x,t)}{\partial x} (a_0(t) + a(t)x(t)) + \frac{\partial h(x,t)}{\partial t} + \frac{1}{2} \frac{\partial^2 h(x,t)}{\partial x^2} b(t)b^T(t), \quad g(x,t) = \frac{\partial h(x,t)}{\partial x} b(t).$$

In terms of the process z(t), the observation equation (2) takes the form

$$dy(t) = z(t)dt + B(t)dW_2(t).$$
 (6)

The reformulated estimation problem is now to find the optimal estimate  $[m_z(t), m_x(t)]$  of the system state [z(t), x(t)], based on the observation process  $Y(t) = \{y(s), 0 \le s \le t\}$ . This optimal estimate is given by the conditional expectation

$$m(t) = [m_z(t), m_x(t)] = [E(z(t) | F_t^Y), E(x(t) | F_t^Y)]$$

of the system state [z(t), x(t)] with respect to the  $\sigma$  - algebra  $F_t^Y$  generated by the observation process Y(t) in the interval  $[t_0, t]$ . The matrix function

$$P(t) = E[([z(t), x(t)] - [m_z(t), m_x(t)]) \times ([z(t), x(t)] - [m_z(t), m_x(t)])^T | F_t^Y]$$

is the estimation error variance for this reformulated problem.

The obtained filtering system includes two equations, (4) (or (5)) and (1), for the partially measured state [z(t), x(t)] and an equation (6) for the observations y(t), where z(t) is a measured polynomial state with polynomial multiplicative noise, x(t) is an unmeasured linear state, and y(t) is a linear observation process directly measuring the state z(t). Hence, the optimal filter for the polynomial system states with unmeasured linear part and polynomial multiplicative noise over linear observations, obtained in (29), can be applied to solving this problem. Indeed, as follows from the general optimal filtering theory (see (31)), the optimal filtering equations take the following particular form for the system (5), (1), (6)

$$dm(t) = E(\bar{f}(x,t) \mid F_t^Y)dt +$$
(7)

$$P(t)[I,0]^{T}(B(t)B^{T}(t))^{-1}(dy(t) - m_{z}(t)dt),$$

$$dP(t) = (E(([z(t), x(t)] - m(t))(\bar{f}(x, t))^{T} | F_{t}^{Y}) + E(\bar{f}(x, t)([z(t), x(t)] - m(t))^{T}) | F_{t}^{Y}) + E(\bar{g}(x, t)\bar{g}^{T}(x, t) | F_{t}^{Y}) - P(t)[I,0]^{T}(B(t)B^{T}(t))^{-1}[I,0]P(t))dt + E(((([z(t), x(t)] - m(t))([z(t), x(t)] - m(t)) \times ([z(t), x(t)] - m(t))^{T} | F_{t}^{Y}) \times [I,0]^{T}(B(t)B^{T}(t))^{-1}(dy(t) - m_{z}(t)dt),$$

$$(8)$$

where  $\bar{f}(x,t) = [f(x,t), a_0(t) + a(t)x(t)]$  is the polynomial drift term and  $\bar{g}(x,t) = [g(x,t), b(t)]$  is the polynomial diffusion (multiplicative noise) term in the entire system of the state equations (4), (1), and the last term should be understood as a 3D tensor (under the expectation sign) convoluted with a vector, which yields a matrix. The matrix [I,0] is the  $m \times (n+m)$  matrix composed of the  $m \times m$ -dimensional identity matrix and  $m \times n$ -dimensional zero matrix. The equations (7), (8) should be complemented with the initial conditions  $m(t_0) = [m_z(t_0), m_x(t_0)] = E([z_0, x_0] | F_{t_0}^Y)$  and  $P(t_0) = E[([z_0, x_0] - m(t_0)([z_0, x_0] - m(t_0))]$ 

The result given in (27; 29) claims that a closed system of the filtering equations can be obtained for the state [z(t), x(t)] over the observations y(t), in view of the polynomial properties

of the functions in the right-hand side of the equation (4). Indeed, since the observation matrix in (6) is the identity one, i.e., invertible, and the initial condition  $z_0$  is assumed conditionally Gaussian with respect to observations, the random variable  $z(t) - m_z(t)$  is conditionally Gaussian with respect to the observation process y(t) for any  $t \ge t_0$  ((27; 29)). Moreover, the random variable  $x(t) - m_x(t)$  is also conditionally Gaussian with respect to the observation process y(t) for any  $t \ge t_0$  (depends only on z(t), in view of (6), and the assumed conditional Gaussianity of the initial random vector  $z_0$  ((26; 29)). Hence, the entire random vector [z(t), x(t)] - m(t) is conditionally Gaussian with respect to the observation process y(t) for any  $t \ge t_0$ , and the assumed conditional Gaussianity of the initial random vector  $z_0$  ((26; 29)). Hence, the entire random vector [z(t), x(t)] - m(t) is conditionally Gaussian with respect to the observation process y(t) for any  $t \ge t_0$ , and the assumed conditional Gaussianity of the initial random vector  $z_0$  ((26; 29)). Hence, the entire random vector [z(t), x(t)] - m(t) is conditionally Gaussian with respect to the observation process y(t) for any  $t \ge t_0$ , and the following considerations outlined in (26; 27; 29) are applicable.

First, since the random variable x(t) - m(t) is conditionally Gaussian, the conditional third moment  $E((([z(t), x(t)] - m(t))([z(t), x(t)] - m(t))([z(t), x(t)] - m(t))^T | F_t^Y)$  with respect to observations, which stands in the last term of the equation (8), is equal to zero, because the process [z(t), x(t)] - m(t) is conditionally Gaussian. Thus, the entire last term in (8) is vanished and the following variance equation is obtained

$$dP(t) = (E(([z(t), x(t)] - m(t))(\bar{f}(x, t))^{T} | F_{t}^{Y}) + E(\bar{f}(x, t)([z(t), x(t)] - m(t))^{T}) | F_{t}^{Y}) + E(\bar{g}(x, t)\bar{g}^{T}(x, t) | F_{t}^{Y}) - P(t)[I, 0]^{T}(\bar{B}(t)\bar{B}^{T}(t))^{-1}[I, 0]P(t))dt,$$
(9)

with the initial condition  $P(t_0) = E[([z_0, x_0] - m(t_0)([z_0, x_0] - m(t_0)^T | F_{t_0}^Y]]$ . Second, if the functions  $\overline{f}(x,t)$  and  $\overline{g}(x,t)$  are polynomial functions of the state x with timedependent coefficients, the expressions of the terms  $E(\bar{f}(x,t) | F_t^Y)$  in (4) and E(([z(t), x(t)]  $m(t))\bar{f}^T(x,t)$  |  $F_t^Y$  and  $E(\bar{g}(x,t)\bar{g}^T(x,t) | F_t^Y)$ , which should be calculated to obtain a closed system of filtering equations (see (31)), would also include only polynomial terms of x. Then, those polynomial terms can be represented as functions of m(t) and P(t) using the following property of Gaussian random variable [z(t), x(t)] - m(t): all its odd conditional moments,  $m_1 = E[([z(t), x(t)] - m(t)) | Y(t)], m_3 = E[([z(t), x(t)] - m(t))^3 |$  $Y(t)], m_5 = E[([z(t), x(t)] - m(t))^5 | Y(t)], ... are equal to 0, and all its even conditional mo ments <math>m_2 = E[([z(t), x(t)] - m(t))^2 | Y(t)], m_4 = E[([z(t), x(t)] - m(t))^4 | Y(t)], ... can be$ represented as functions of the variance P(t). For example,  $m_2 = P$ ,  $m_4 = 3P^2$ ,  $m_6 = 15P^3$ , ... etc. After representing all polynomial terms in (7) and (9), that are generated upon expressing  $E(\bar{f}(x,t) | F_t^Y), E(([z(t), x(t)] - m(t))\bar{f}^T(x,t)) | F_t^Y), \text{ and } E(\bar{g}(x,t)\bar{g}^T(x,t) | F_t^Y), \text{ as func-}$ tions of m(t) and P(t), a closed form of the filtering equations would be obtained. The corresponding representations of  $E(f(x,t) | F_t^Y)$ ,  $E(([z(t), x(t)] - m(t))(f(x,t))^T | F_t^Y)$  and  $E(\bar{g}(x,t)\bar{g}^T(x,t) | F_t^Y)$  have been derived in (24–27; 29) for certain polynomial functions f(x,t)and g(x, t).

In the next example section, a closed form of the filtering equations will be obtained for a particular case of a scalar third degree polynomial function h(x, t) in the equation (2). It should be noted, however, that application of the same procedure would result in designing a closed system of the filtering equations for any polynomial function  $h(x, t) \in \mathbb{R}^n$  in (2).

### 4. Example: Third Degree Sensor Filtering Problem

This section presents an example of designing the optimal filter for a linear state over third degree polynomial observations, reducing it to the optimal filtering problem for a second degree polynomial state with partially measured linear part and second degree polynomial multiplicative noise over linear observations, where a conditionally Gaussian state initial condition is additionally assumed.

Let the unmeasured scalar state x(t) satisfy the trivial linear equation

$$dx(t) = dt + dw_1(t), \quad x(0) = x_0, \tag{10}$$

and the observation process be given by the scalar third degree sensor equation

$$dy(t) = (x^{3}(t) + x(t))dt + dw_{2}(t),$$
(11)

where  $w_1(t)$  and  $w_2(t)$  are standard Wiener processes independent of each other and of a Gaussian random variable  $x_0$  serving as the initial condition in (10). The filtering problem is to find the optimal estimate for the linear state (10), using the third degree sensor observations (11).

Let us reformulate the problem, introducing the stochastic process  $z(t) = h(x,t) = x^3(t) + x(t)$ . Using the Ito formula (see (31)) for the stochastic differential of the cubic function  $h(x,t) = x^3(t) + x(t)$ , where x(t) satisfies the equation (10), the following equation is obtained for z(t)

$$dz(t) = (1 + 3x(t) + 3x^{2}(t))dt + (3x^{2}(t) + 1)dw_{1}(t), \ z(0) = z_{0}.$$
 (12)

Here,  $\frac{\partial h(x,t)}{\partial x} = 3x^2(t) + 1$ ,  $\frac{1}{2} \frac{\partial^2 h(x,t)}{\partial x^2} = 3x(t)$ , and  $\frac{\partial h(x,t)}{\partial t} = 0$ ; therefore,  $f(x,t) = 1 + 3x(t) + 3x^2(t)$  and  $g(x,t) = 3x^2(t) + 1$ . The initial condition  $z_0 \in R$  is considered a conditionally Gaussian random vector with respect to observations (see the paragraph following (4) for details). This assumption is quite admissible in the filtering framework, since the real distributions of x(t) and z(t) are unknown. In terms of the process z(t), the observation equation (11) takes the form

$$dy(t) = z(t)dt + dw_2(t).$$
 (13)

The obtained filtering system includes two equations, (12) and (10), for the partially measured state [z(t), x(t)] and an equation (13) for the observations y(t), where z(t) is a completely measured quadratic state with multiplicative quadratic noise, x(t) is an unmeasured linear state, and y(t) is a linear observation process directly measuring the state z(t). Hence, the designed optimal filter can be applied for solving this problem. The filtering equations (7),(9) take the following particular form for the system (12),(10),(13)

$$dm_1(t) = (1 + 3m_2(t) + 3m_2^2(t) + 3P_{22}(t))dt +$$
(14)

$$P_{11}(t)[dy(t) - m_1(t)dt],$$

$$dm_2(t) = 1 + P_{12}(t)[dy(t) - m_1(t)dt],$$
(15)

with the initial conditions  $m_1(0) = E(x_0 | y(0)) = m_{10}$  and  $m_2(0) = E(x_0^3 | y(0)) = m_{20}$ ,

$$\dot{P}_{11}(t) = 12(P_{12}(t)m_2(t)) + 6P_{12}(t) + 27P_{22}^2(t) +$$
(16)

$$54P_{22}(t)m_2^2(t) + 9m_2^4(t) + 6P_{22}(t) + 6m_2^2 + 1 - P_{11}^2(t),$$
  

$$\dot{P}_{12}(t) = 6(P_{22}(t)m_2(t)) + 3P_{22}(t) + 3P_{22}(t) + 3(m_2^2(t) + P_{22}(t)) + 1 - P_{11}(t)P_{12}(t),$$
(17)

$$\dot{P}_{22}(t) = 1 - P_{12}^2(t), \tag{18}$$

with the initial condition  $P(0) = E(([x_0, z_0]^T - m(0))([x_0, z_0]^T - m(0))^T | y(0)) = P_0$ . Here,  $m_1(t)$  is the optimal estimate for the state  $z(t) = x^3(t) + x(t)$  and  $m_2(t)$  is the optimal estimate for the state x(t).

Numerical simulation results are obtained solving the systems of filtering equations (14)–(18). The obtained values of the state estimate  $m_2(t)$  satisfying the equation (15) are compared to the real values of the state variable x(t) in (10).

For the filter (14)–(18) and the reference system (12),(10),(13) involved in simulation, the following initial values are assigned:  $x_0 = z_0 = 0$ ,  $m_2(0) = 10$ ,  $m_1(0) = 1000$ ,  $P_{11}(0) = 15$ ,  $P_{12}(0) = 3$ ,  $P_{22}(0) = 1$ . Gaussian disturbances  $dw_1(t)$  and  $dw_2(t)$  are realized using the built-in MatLab white noise functions. The simulation interval is [0, 0.05].




Fig. 1. Above. Graph of the observation process y(t) in the interval [0, 0.05]. Below. Graphs of the real state x(t) (solid line) and its optimal estimate  $m_2(t)$  (dashed line) in the interval [0, 0.05].

Figure 1 shows the graphs of the reference state variable x(t) (10) and its optimal estimate  $m_2(t)$  (15), as well as the observation process y(t) (11), in the entire simulation interval from  $t_0 = 0$  to T = 0.05. It can be observed that the optimal estimate given by (14)–(18) converges to the real state (10) very rapidly, in spite of a considerable error in the initial conditions,  $m_2(0) - x_0 = 10$ ,  $m_1(0) - z_0 = 1000$ , and very noisy observations which do not even reproduce the shape of  $z(t) = x^3(t) + x(t)$ . Moreover, the estimated signal x(t) itself is a time-shifted Wiener process, i.e., the integral of a white Gaussian noise, which makes the filtering problem even more difficult. It should also be noted that the extended Kalman filter (EKF) approach fails for the system (10),(11), since the linearized value  $\partial z/\partial x = 3x^2(t) + 1$  at zero is the unit-valued constant, therefore, the observation process would consist of pure noise.

Thus, it can be concluded that the obtained optimal filter (14)–(18) solves the optimal third degree sensor filtering problem for the system (10),(11) and yields a really good estimate of the unmeasured state in presence of quite complicated observation conditions. Subsequent discussion of the obtained results can be found in Conclusions.

## 5. Conclusions

This paper presents the optimal filter for linear system states over nonlinear polynomial observations. It is shown that the optimal filter can be obtained in a closed form for any polynomial function in the observation equation. Based on the optimal filter for a bilinear state, the optimal solution is obtained for the optimal third degree sensor filtering problem, assuming a conditionally Gaussian initial condition for the third degree state. This assumption is quite admissible in the filtering framework, since the real distributions of the first and third degree states are unknown. The resulting filter yields a reliable and rapidly converging estimate, in spite of a significant difference in the initial conditions between the state and estimate and very noisy observations, in the situation where the unmeasured state itself is a time-shifted Wiener process and the extended Kalman filter (EKF) approach fails. Although this conclusion follows from the developed theory, the numerical simulation serves as a convincing illustration.


## 6. References

- [1] Kushner HJ. On differential equations satisfied by conditional probability densities of Markov processes. *SIAM J. Control* 1964; **12**:106-119.
- [2] Duncan TE. *Probability densities for diffusion processes with applications to nonlinear filtering theory*. Technical report, PhD thesis, Standford, CA, USA, 1967.
- [3] Mortensen RE. *Optimal control of continuous-time stochastic systems*. Technical report, PhD thesis, University of California, Berkeley, CA, USA, 1966.
- [4] Zakai M. On the optimal filtering of diffusion processes. *Zeitschrift für Wahrscheinlichkeitstheorie und verwandte Gebiete* 1969; **11**: 230Ű243.
- [5] Liptser RS, Shiryayev AN. Statistics of Random Processes. Vol. I: General Theory. Springer, 2000 (1st. Ed., 1974).
- [6] Kallianpur G. Stochastic Filtering Theory. Springer, 1980.
- [7] Kalman RE, Bucy RS. New results in linear filtering and prediction theory. *ASME Trans.*, *Part D (J. of Basic Engineering)* 1961; 83: 95-108.
- [8] Wonham WM. Some applications of stochastic differential equations to nonlinear filtering. *SIAM J. Control* 1965; **2**: 347-369.
- [9] Benes VE. Exact finite-dimensional filters for certain diffusions with nonlinear drift. *Stochastics* 1981; **5**: 65-92.
- [10] Yau SST. Finite-dimensional filters with nonlinear drift I: a class of filters including both Kalman-Bucy and Benes filters. *J. Math. Systems, Estimation, and Control* 1994; **4**: 181-203.
- [11] Germani A, Manes P, Palumbo P. Linear filtering for bilinear stochastic differential systems with unknown inputs, *IEEE Transactions on Automatic Control* 2002; **47**: 1726-1730.
- [12] Shin DR, Verriest E. Optimal access control of simple integrated networks with incomplete observations, *Proc. American Control Conf.* 1994; Baltimore, MD, USA, 3487-3488.
- [13] Zhang WH, Chen BS, Tseng CS. Robust  $H_{\infty}$  filtering for nonlinear stochastic systems, *IEEE Transactions on Signal Processing* 2005; **53**: 589–598.

- [14] Wang Z. Filtering on nonlinear time-delay stochastic systems, Automatica 2003, 39: 101-109.
- [15] Shi P. Filtering on sampled-data systems with parametric uncertainty, *IEEE Transactions* on Automatic Control 1998; **43**: 1022-1027.
- [16] Xu S., van Dooren PV. Robust  $H_{\infty}$ -filtering for a class of nonlinear systems with state delay and parameter uncertainty, *Int. J. Control*, 2002; **75**: 766–774.
- [17] Mahmoud M, Shi P. Robust Kalman filtering for continuous time-lag systems with Markovian jump parameters. *IEEE Transactions on Circuits and Systems* 2003; **50**: 98-105.
- [18] Sheng J, Chen T, Shah SL. Optimal filtering for multirate systems. *IEEE Transactions on Circuits and Systems* 2005; **52**: 228-232.
- [19] Sheng J. Optimal filtering for multirate systems based on lifted models. *Proc. American Control Conf.* 2005; Portland, OR, USA, 3459-3461.
- [20] Gao H, Lam J, Xie L, Wang C. New approach to mixed  $H_2/H_{\infty}$ -filltering for polytopic discrete-time systems. *IEEE Transactions on Signal Processing* 2005; **53**: 3183–3192.
- [21] Boukas EK. Stabilization of stochastic nonlinear hybrid systems, *International Journal of Innovative Computing, Information and Control* 2005; **1**: 131Ű-141.
- [22] Zhang H, Basin MV, Skliar M. Optimal state estimation for continuous, stochastic, statespace system with hybrid measurements, *International Journal of Innovative Computing*, *Information and Control* 2006; **2**: 863–874.
- [23] Jeong CS, Yaz E, Bahakeem A, Yaz Y. Nonlinear observer design with general criteria, *International Journal of Innovative Computing, Information and Control* 2006; **2**: 693Ű-704.
- [24] Basin MV. On Optimal filtering for polynomial system states. *ASME Trans. J. Dynamic Systems, Measurement, and Control* 2003; **125**: 123-125.
- [25] Basin MV, Alcorta-Garcia MA. Optimal filtering and control for third degree polynomial systems. *Dynamics of Continuous, Discrete, and Impulsive Systems* 2003; **10B**: 663-680.
- [26] Basin MV, Skliar M. Optimal filtering for partially measured polynomial system states. *Proc. American Control Conf.* 2005; Portland, OR, USA, 4022-4027.
- [27] Basin MV, Perez J, Skliar M. Optimal filtering for polynomial system states with polynomial multiplicative noise, *International J. Robust and Nonlinear Control* 2006; **16**: 287-298.
- [28] Basin MV, Perez J, Martinez-Zuniga R. Optimal filtering for nonlinear polynomial systems over linear observations with delay, *International Journal of Innovative Computing*, *Information and Control* 2006; **2**: 357–370.
- [29] Basin MV, Perez J, Skliar M. Optimal filtering for polynomial systems with patially measured states and multiplicative noises, *Proc. 45th IEEE Conf. on Decision and Control* 2006; San Diego, CA, USA, 4169-4174.
- [30] Hazewinkel M, Marcus SI, Sussmann HJ. Nonexistence of exact finite-dimensional filters for conditional statistics of the cubic sensor problem, *Systems and Control Letters* 1983; 5: 331-340.
- [31] Pugachev VS, Sinitsyn IN. *Stochastic Systems: Theory and Applications*. World Scientific, 2001.
- [32] Pugachev VS. Probability Theory and Mathematical Statistics for Engineers. Pergamon, 1984.
- [33] Tucker HG. A Graduate Course in Probability. Academic Press, 1967.

# IntechOpen

## IntechOpen



Stochastic Control Edited by Chris Myers

ISBN 978-953-307-121-3 Hard cover, 650 pages Publisher Sciyo Published online 17, August, 2010 Published in print edition August, 2010

Uncertainty presents significant challenges in the reasoning about and controlling of complex dynamical systems. To address this challenge, numerous researchers are developing improved methods for stochastic analysis. This book presents a diverse collection of some of the latest research in this important area. In particular, this book gives an overview of some of the theoretical methods and tools for stochastic analysis, and it presents the applications of these methods to problems in systems theory, science, and economics.

## How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Joel Perez Padron, Jose Paz Perez Padron and Rogelio Soto (2010). Optimal Filtering for Linear States over Polynomial Observations, Stochastic Control, Chris Myers (Ed.), ISBN: 978-953-307-121-3, InTech, Available from: http://www.intechopen.com/books/stochastic-control/optimal-filtering-for-linear-states-over-polynomial-observations-

## Open science | open minds

## InTech Europe

University Campus STeP Ri Slavka Krautzeka 83/A 51000 Rijeka, Croatia Phone: +385 (51) 770 447 Fax: +385 (51) 686 166 www.intechopen.com

## InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai No.65, Yan An Road (West), Shanghai, 200040, China 中国上海市延安西路65号上海国际贵都大饭店办公楼405单元 Phone: +86-21-62489820 Fax: +86-21-62489821 © 2010 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the <u>Creative Commons Attribution-NonCommercial-ShareAlike-3.0 License</u>, which permits use, distribution and reproduction for non-commercial purposes, provided the original is properly cited and derivative works building on this content are distributed under the same license.



# IntechOpen