We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists

6.900

186,000

Our authors are among the

most cited scientists

12.2%



WEB OF SCIENCE

Selection of our books indexed in the Book Citation Index in Web of Science™ Core Collection (BKCI)

Interested in publishing with us? Contact book.department@intechopen.com

> Numbers displayed above are based on latest data collected. For more information visit www.intechopen.com



Stochastic Decision Support Models and Optimal Stopping Rules in a New Product Lifetime Testing

Nicholas A. Nechval and Maris Purgailis *University of Latvia Latvia*

1. Introduction

The theory of stopping rules has its roots in the study of the optimality properties of the sequential probability ratio test of Wald and Wolfowitz (1948) and Arrow, Blackwell and Girshick (1949). The essential idea in both of these papers was to create a formal Bayes problem.

The formal Bayes problem is what we would now call an optimal stopping problem. A decision maker observes an adapted sequence $\{R_n, f_n, n \ge I\}$, with $E\{|R_n|\} < \infty$ for all n, where f_n denotes the σ -algebra generated by a sequence of rewards $R_1, ..., R_n$. At each time n a choice is to be made, to stop sampling and collect the currently available reward, R_n , or continue sampling in the expectation of collecting a larger reward in the future. An optimal stopping rule N is one that maximizes the expected reward, $E\{R_n\}$. The key to finding an optimal or close to optimal stopping rule is the family of equations

$$Z_n = \max (R_n, E\{Z_{n+1} | f_n\}), \quad n = 1, 2, ...$$
 (1)

The informal interpretation of Z_n , is that it is the most one can expect to win if one has already reached stage n; and equations (1) say that this quantity is the maximum of what one can win by stopping at the nth stage and what one can expect to win by taking at least one more observation and proceeding optimally thereafter. The plausible candidate for an optimal rule is to stop with

$$N = \min\{ n : R_n \ge E\{Z_{n+1} \mid F_n\} \}, \tag{2}$$

that is, stop as soon as the current reward is at least as large as the most that one can expect to win by continuing. Equations (1) show that $\{Z_{n},f_n\}$ is a supermartingale, while $\{Z_{\min(N,n)},f_n\}$, is a martingale. The equations do not have a unique solution, but in the case where the index n is bounded, say $1 \le n \le m$ for some given value of m, the solution of interest satisfies Z_m , = R_m . Hence (1) can be solved and the optimal stopping rule can be found by "backward induction". The general strategy of optimal stopping theory is to

approximate the case where no bound m exists by first imposing such a bound, solving the bounded problem and then letting m $\rightarrow \infty$. For reviews of the many variations on this problem and the extensive related literature, see Freeman (1983), Petrucelli (1988) and Samuels (1991).

For illustration of the stopping problem, consider the Bayesian sequential estimation problem of a binomial parameter under quadratic loss and constant observation cost. Suppose that the unknown binomial parameter p is assigned a beta prior distribution with integer parameters (a,b) so that

$$\pi(p \mid a, b) = \frac{(b-1)!}{(a-1)!(b-a-1)!} p^{a-1} (1-p)^{b-a-1}, \quad 0 (3)$$

The posterior distribution of p having observed s successes in n trials is simply $\pi(p;s+a,n+b)$ (Raiffa and Schlaifer, 1968); hence the result of sampling may be represented as a plot of s+a against n+b which stops when the stopping boundary is reached. If a=1, b=2, the uniform prior, is taken as the origin, sample paths for any other proper prior will start at the point (a-1,b-2). Consequently stopping boundaries will be obtained using the uniform prior. Suppose that the loss in estimating p by d is $9(p-d)^2$ where 9 is a constant giving loss in terms of cost. Then the Bayes estimator is the current prior mean (s+l)/(n+2) and the Bayes risk is

$$B(s,n) = \frac{9(s+1)(n-s+1)}{(n+2)^2(n+3)}.$$
 (4)

At a point (s,n) let D(s,n) be the risk of taking one further observation at a cost c and M(s,n) be the minimum risk, then the dynamic programming equations giving the partition of the (s,n) plane into stopping and continuation points are

$$M(s,n) = min\{B(s,n),D(s,n)\},$$
 (5)

where

$$D(s,n) = c + \frac{s+1}{n+2}M(s+1,n+1) + \frac{n-s+1}{n+2}M(s,n+1).$$
 (6)

The equations are similar to those of Lindley and Barnett (1965) and Freeman (1970, 1972, 1973). The optimal decision at each point is obtained by working back from a maximum sample size, which is approximately $[(1/2)\sqrt{9/c}]-2$. A suboptimal stopping point (s,n) is defined as a first stopping point for fixed s if (s,n-1) is a continuation point, in this case

$$D(s, n-1) = c + \frac{s+1}{n+1}M(s+1, n) + \frac{n-s}{n+1}B(s, n)$$

$$\leq c + \frac{s+1}{n+1}B(s+1,n) + \frac{n-s}{n+1}B(s,n) = D^{\bullet}(s,n-1). \tag{7}$$

A lower bound for the sample size n above may now be found from (7) by setting $B(s,n-1) \ge D^{\bullet}(s,n-1)$. This leads to

$$[(n+2)(n+1)]^2 \le (9/c)(s+1)(n-s). \tag{8}$$

The optimal stopping boundary starts at s = 0 and n, and from (8) it may be shown that this sample size is at least $[(9/c)^{1/3}]-3$.

The approximate design obtained by (8) will be termed a one step ahead design. Both designs will obviously stop at the same maximum number of observations N, and will give the same decision after (N–1) observations. The one step ahead design gives stopping boundaries, which will lie inside those of the optimal. The one step ahead design is similar to the modified Bayes rule of Amster (1963) and has been used by El-Sayyad and Freeman (1973) to estimate a Poisson process rate.

The present research investigates the frequentist (non-Bayesian) stopping rules. In this paper, stopping rules in fixed-sample testing as well as in sequential-sample testing are discussed.

2. Assumptions and Cost Functions in Fixed-Sample Testing

Let c_1 be the cost per hour of conducting the test, c_2 be the total cost of redesign (including the time required to implement it). The cost of redesign c_2 is undoubtedly the most difficult to estimate. This cost is to include whatever redesigns are necessary to make the probability of failure on rerun negligible. To simplify the mathematics, it is assumed that unnecessary design changes, caused by incorrectly abandoning the test, will also have a beneficial effect on performance. This assumption appears warranted for many electronic and mechanical systems, where the introduction of redundancies, higher-quality components, etc., can always be expected to improve reliability.

It will be assumed in this section that the times of interest to the decision maker are restricted to those where a failure has just occurred.

Let $X_1 \le X_2 \le ... \le X_r$ be the first r ordered past observations with lifetime distribution $f(x \mid \theta)$ from a sample of size n. Let $\widehat{\theta}$ be the maximum-likelihood estimate of θ based upon the first r order statistics $(X_1, ..., X_r) \equiv X^r$. Let $g(x_1, x_2, ..., x_r \mid \theta)$ be the joint density of the r observations, $g(x_1, x_2, ..., x_r, x_s \mid \theta)$ be the joint density of the first r and sth order statistics (s > r) and $f(x_s \mid x^r, \theta)$ be the conditional density of the sth order statistic. If τ_0 is the life specified as acceptable and the product will be accepted if a random sample of n items shows (s-1) or fewer failures in performance testing, then the probability of passing the test after x_r has been observed may be estimated as

$$\widehat{p}_{pas} = \int_{\tau_0}^{\infty} f(x_s \mid x^r, \widehat{\theta}) dx_s, \tag{9}$$

where

$$f(x_{s} \mid x^{r}, \widehat{\theta}) = \frac{g(x_{1}, ..., x_{r}, x_{s} \mid \widehat{\theta})}{g(x_{1}, ..., x_{r} \mid \widehat{\theta})}.$$
 (10)

The cost of abandoning the test is

$$c_{\text{abandoning}} = c_1 \tau_0 + c_2 \tag{11}$$

The estimated cost of continuation of the test is given by

$$\widehat{c}_{\text{continuing}} = \int_{x_r}^{\tau_0} [c_1(x_s - x_r) + c_1\tau_0 + c_2] f(x_s \mid x^r, \widehat{\theta}) dx_s + \int_{\tau_0}^{\infty} c_1(\tau_0 - x_r) f(x_s \mid x^r, \widehat{\theta}) dx_s$$

$$= c_1 \int_{x_r}^{\tau_0} x_s f(x_s \mid x^r, \widehat{\theta}) dx_s + (1 - \widehat{p}_{pas}) [c_1(\tau_0 - x_r) + c_2] + \widehat{p}_{pas} [c_1(\tau_0 - x_r)]$$

$$=c_{1}\int_{x_{r}}^{\tau_{0}}x_{s}f(x_{s}\mid x^{r},\widehat{\theta})dx_{s}+c_{1}\tau_{0}+c_{2}-c_{1}x_{r}-\widehat{p}_{pas}c_{2}. \tag{12}$$

3. Stopping Rule in Fixed-Sample Testing

The decision rule will be based on the relative magnitude of $\,c_{abandoning}\,$ and $\,\widehat{c}_{continuing}\,$. The simplest rule would be:

If $\hat{c}_{continuing} < c_{abandoning}$, i.e., if

$$\int_{x_{r}}^{\tau_{0}} x_{s} f(x_{s} \mid x^{r}, \widehat{\theta}) dx_{s} < x_{r} + \widehat{p}_{pas} \frac{c_{2}}{c_{1}},$$
(13)

continue the present test;

If $\hat{c}_{continuing} \ge c_{abandoning}$, i.e., if

$$\int_{x_r}^{\tau_0} x_s f(x_s \mid x^r, \widehat{\theta}) dx_s \ge x_r + \widehat{p}_{pas} \frac{c_2}{c_1}, \tag{14}$$

abandon the present test and initiate a redesign.

4. Estimation of the Probability of Passing the Fixed-sample Test

Evaluation of the cost functions for the lifetime-testing model requires, even for relatively simple probability distributions, the evaluation of some complicated integrals that cannot always be obtained in closed form. For example, using the one-parameter exponential model for lifetime distribution, we have

$$f(x \mid \sigma) = \frac{1}{\sigma} \exp\left(-\frac{x}{\sigma}\right), \quad x \ge 0, \tag{15}$$

$$F(x \mid \sigma) = 1 - \exp\left(-\frac{x}{\sigma}\right). \tag{16}$$

Therefore,

$$g(x_1, ..., x_r \mid \sigma) = \frac{n!}{(n-k)!} \frac{1}{\sigma^r} \exp\left(-\sum_{i=1}^r \frac{x_i}{\sigma}\right) \left[\exp\left(-\frac{x_r}{\sigma}\right)\right]^{n-r};$$
(17)

$$g(x_1, ..., x_r, x_s \mid \sigma) = \frac{n!}{(s-r-1)!(n-s)!} \frac{1}{\sigma^{r+1}} \left[exp\left(-\frac{x_r}{\sigma}\right) - exp\left(-\frac{x_s}{\sigma}\right) \right]^{s-r-1}$$

$$\times \exp\left(-\sum_{i=1}^{r} \frac{x_i}{\sigma}\right) \left[\exp\left(-\frac{x_s}{\sigma}\right)\right]^{n-s+1}.$$
 (18)

The maximum likelihood estimate for σ is

$$\widehat{\sigma} = \frac{\sum_{i=1}^{r} x_i + (n-r)x_r}{r}.$$
(19)

Replacing σ by $\hat{\sigma}$ in the density functions and simplifying, we obtain

$$\hat{p}_{pas} = \int_{\tau_0}^{\infty} \frac{(n-r)!}{(s-r-1)!(n-s)!} \frac{\left[exp\left(-\frac{x_r}{\hat{\sigma}}\right) - exp\left(-\frac{x_s}{\hat{\sigma}}\right)\right]^{s-r-1}}{\left[exp\left(-\frac{x_r}{\hat{\sigma}}\right)\right]^{n-r}} \frac{1}{\hat{\sigma}} \left[exp\left(-\frac{x_s}{\hat{\sigma}}\right)\right]^{n-s+1} dx_s. \quad (20)$$

If we write

$$\left[\exp\left(-\frac{x_{r}}{\widehat{\sigma}}\right)\right]^{n-r} = \left[\exp\left(-\frac{x_{r}}{\widehat{\sigma}}\right)\right]^{s-r-1} \left[\exp\left(-\frac{x_{r}}{\widehat{\sigma}}\right)\right]^{n-s+1}, \tag{21}$$

then it is clear that

$$\widehat{p}_{pas} = \int_{\tau_0}^{\infty} \frac{(n-r)!}{(s-r-1)!(n-s)!} \frac{1}{\widehat{\sigma}} \left[1 - \frac{\exp\left(-\frac{x_s}{\widehat{\sigma}}\right)}{\exp\left(-\frac{x_r}{\widehat{\sigma}}\right)} \right]^{s-r-1} \left[\frac{\exp\left(-\frac{x_s}{\widehat{\sigma}}\right)}{\exp\left(-\frac{x_r}{\widehat{\sigma}}\right)} \right]^{n-s+1} dx_s.$$
 (22)

The change of variable

$$v = \frac{\exp\left(-\frac{x_s}{\hat{\sigma}}\right)}{\exp\left(-\frac{x_r}{\hat{\sigma}}\right)}$$
 (23)

leads to

$$\widehat{p}_{pas} = \int_{0}^{\exp\left(-\frac{\tau_{0} - x_{r}}{\widehat{\sigma}}\right)} \frac{(n-r)!}{(s-r-1)!(n-s)!} v^{n-s} (1-v)^{s-r-1} dv.$$
 (24)

Thus, \hat{p}_{pas} is equivalent to the cumulative beta distribution with parameters (n–s+1, s–r). The situation for the Weibull distribution,

$$f(x \mid \sigma, \delta) = \frac{\delta}{\sigma} x^{\delta - 1} \exp\left(-\frac{x^{\delta}}{\sigma}\right), \quad x \ge 0; \quad F(x \mid \sigma, \delta) = 1 - \exp\left(-\frac{x^{\delta}}{\sigma}\right), \tag{25}$$

is much the same, except that we make the change of variable

$$v = \frac{\exp\left(-\frac{x_s^{\hat{\delta}}}{\hat{\sigma}}\right)}{\exp\left(-\frac{x_r^{\hat{\delta}}}{\hat{\sigma}}\right)}.$$
 (26)

The maximum likelihood estimates $\hat{\sigma}$ and $\hat{\delta}$ of the parameters σ and δ , respectively, required in (26), can only be obtained by iterative methods. The appropriate likelihood equations for $X_1, ..., X_r$ are

$$\frac{\partial L}{\partial \sigma} = 0 = -\frac{r}{\sigma} + \frac{1}{\sigma^2} \left[\sum_{i=1}^r x_i^{\delta} + (n-r) x_r^{\delta} \right], \tag{27}$$

$$\frac{\partial L}{\partial \delta} = 0 = \frac{r}{\delta} + \sum_{i=1}^{r} x_i - \frac{1}{\sigma} \left[\sum_{i=1}^{r} x_i^{\delta} \ln x_i + (n-r) x_r^{\delta} \ln x_r \right]. \tag{28}$$

Now $\hat{\sigma}$ and $\hat{\delta}$ can be found from solution of

$$\widehat{\sigma} = \frac{\sum_{i=1}^{r} x_i^{\widehat{\delta}} + (n-r) x_r^{\widehat{\delta}}}{r}$$
(29)

and

$$\hat{\delta} = \left[\left(\sum_{i=1}^{r} x_i^{\hat{\delta}} \ln x_i + (n-r) x_r^{\hat{\delta}} \ln x_r \right) \left(\sum_{i=1}^{r} x_i^{\hat{\delta}} + (n-r) x_r^{\hat{\delta}} \right)^{-1} - \frac{1}{r} \sum_{i=1}^{r} \ln x_i \right]^{-1}.$$
 (30)

The method described above is quite general and works well for all closed-form or tabulated cumulative distribution functions, so that numerical integration techniques are not needed for calculating \hat{p}_{pas} . It is easy to see that the general case would involve a change of variable

$$v = \frac{1 - F(x_s \mid \hat{\theta})}{1 - F(x_r \mid \hat{\theta})},$$
(31)

where, of course, x_r is a constant.

4.1 Statistical Inferences for Future Order Statistics in the Same Sample

If we deal with small size n of the fixed sample for testing and wish to find the conditional distribution of the sth order statistic to obtain the probability of passing the test after x_r has been observed, then it may be suitable the following results.

$$\widetilde{f}(x_s \mid x_r) = \frac{1}{B(s-r,n-s+1)B(r,n-r+1)} \sum_{j=0}^{s-r-1} \sum_{i=0}^{r-1} (-1)^{i+j} \binom{s-r-1}{j} \binom{r-1}{i}$$

$$\times \frac{1}{[w_{s}(n-s+1+j)+(n-r+1+i)]^{2}} \frac{1}{x_{r}}, \quad w_{s} > 0,$$
(32)

where

$$W_{\rm s} = \frac{X_{\rm s} - X_{\rm r}}{X_{\rm r}}.\tag{33}$$

Proof. It follows readily from standard theory of order statistics (see, for example, Kendall and Stuart (1969)) that the joint distribution of X_r , X_s (s > r) is given by

$$f(x_r, x_s \mid \sigma) dx_r dx_s = \frac{1}{B(r, s - r)B(s, n - s + 1)}$$

$$\times [F(x_{r} \mid \sigma)]^{r-1} [F(x_{s} \mid \sigma) - F(x_{r} \mid \sigma)]^{s-r-1} [1 - F(x_{s} \mid \sigma)]^{n-s} dF(x_{r} \mid \sigma) dF(x_{s} \mid \sigma), \tag{34}$$

Making the transformation $z = x_s - x_r$, $x_r = x_r$, and integrating out x_r , we find the density of z as the beta density

$$f(z \mid \sigma) = \frac{1}{B(s-r, n-s+1)} [\exp(-z/\sigma)]^{n-s+1} [1 - \exp(-z/\sigma)]^{s-r-1} \frac{1}{\sigma}.$$
 (35)

The distribution of X_r is

$$f(x_r \mid \sigma)dx_r = \frac{1}{B(r, n-r+1)} [F(x_r \mid \sigma)]^{r-1} [1 - F(x_r \mid \sigma)]^{n-r} dF(x_r \mid \sigma), \tag{36}$$

and since Z, X_r are independent, we have the joint density of Z and X_r as

$$f(z, x_r \mid \sigma) = \frac{1}{B(r, s - r)B(s, n - s + 1)} [\exp(-z/\sigma)]^{n - s + 1} [1 - \exp(-z/\sigma)]^{s - r - 1}$$

$$\times [1 - \exp(-x_r/\sigma)]^{r - 1} [\exp(-x_r/\sigma)]^{n - r + 1} \frac{1}{\sigma^2}.$$
(37)

Making the transformation $w_s = z/x_r$, $x_r = x_r$, we find the joint density of W_s and X_r as

$$f(w_{s}, x_{r} \mid \sigma) = \frac{1}{B(r, s - r)B(s, n - s + 1)} [\exp(-w_{s}x_{r} / \sigma)]^{n - s + 1} [1 - \exp(-w_{s}x_{r} / \sigma)]^{s - r - 1}$$

$$\times [1 - \exp(-x_{r} / \sigma)]^{r - 1} [\exp(-x_{r} / \sigma)]^{n - r + 1} x_{r} \frac{1}{\sigma^{2}}.$$
(38)

It is then straightforward to integrate out x_r , leaving the density of W_s as

$$f(w_s) = \frac{1}{B(s-r,n-s+1)B(r,n-r+1)} \sum_{j=0}^{s-r-1} \sum_{i=0}^{r-1} (-1)^{i+j} \binom{s-r-1}{j} \binom{r-1}{i}$$

$$\times \frac{1}{\left[w_{s}(n-s+1+j)+(n-r+1+i)\right]^{2}}, \quad w_{s} > 0.$$
 (39)

It will be noted that the technique of invariant embedding (Nechval, 1982, 1984, 1986, 1988a, 1988b; Nechval et al., 1999, 2000, 2001, 2003a, 2003b, 2004, 2008, 2009) allows one to obtain (39) directly from (34). This ends the proof.

Corollary 1.1.

$$Pr\{W_s \le w_s\} = \frac{1}{B(s-r,n-s+1)B(r,n-r+1)} \sum_{j=0}^{s-r-1} \sum_{i=0}^{r-1} (-1)^{i+j} \binom{s-r-1}{j} \binom{r-1}{i}$$

$$\times \left(\frac{1}{n-r+1+i} - \frac{1}{w_{s}(n-s+1+j) + (n-r+1+i)}\right) \frac{1}{(n-s+1+j)}$$

$$= 1 - \frac{1}{B(s-r,n-s+1)B(r,n-r+1)} \sum_{j=0}^{s-r-1} (-1)^{j} {s-r-1 \choose j} \left[r(n-s+1+j) {w_{s}(n-s+1+j) + n \choose r} \right]^{-1}.$$
(40)

For a specified probability level α , w_s can be obtained such that

$$\Pr\{W_{s} \le W_{s} \mid X_{r} = X_{r}\} = \Pr\left\{\frac{X_{s} - X_{r}}{X_{r}} \le W_{s}\right\} = \Pr\{X_{s} \le (W_{s} + 1)X_{r}\} = \alpha.$$
(41)

Hence, with confidence α , one could predict X_s to be less than or equal to $(w_s+1)x_r$.

Consider, for instance, the case where n=6 simultaneously tested items have life times following the exponential distribution (15). Two items (r = 2) fail at times 75 and 90 hours. Suppose, say, we are predicting the 4th failure time (s = 4). Using (40), (41), and α = 0.95, we get w_s=10, which yields a predicted value for X_s of 990 hours.

Theorem 2 (*Predictive distribution of the sth order statistic* X_s *on the basis of the past observations* $X_1 \le X_2 \le ... \le X_r$ *from the exponential distribution of the same sample*). Under conditions of Theorem 1, the predictive probability density function of the sth order statistic X_s ($r < s \le n$) may be obtained on the basis of the past observations ($X_1 \le X_2 \le ... \le X_r$) from the same sample as

$$\widetilde{f}(x_{s} | x^{r}) = \frac{r}{B(s-r,n-s+1)} \sum_{j=0}^{s-r-1} (-1)^{j} {s-r-1 \choose j} \frac{1}{[1+w_{s}(n-s+1+j)]^{r+1}} \frac{1}{q_{r}}, \quad w_{s} > 0, \quad (42)$$

where

$$W_{\rm s} = \frac{X_{\rm s} - X_{\rm r}}{Q_{\rm r}},\tag{43}$$

$$Q_{r} = \sum_{i=1}^{r} X_{i} + (n-r)X_{r}.$$
 (44)

Proof. The joint probability density function of $X_1, X_2, ..., X_r, X_s$ is given by

$$f(x_1, x_2, ..., x_r, x_s \mid \sigma) = \frac{n!}{(s-r-1)!(n-s)!}$$

$$\times [F(x_{s} \mid \sigma) - F(x_{r} \mid \sigma)]^{s-r-1} [1 - F(x_{s} \mid \sigma)]^{n-s} \prod_{i=1}^{r} f(x_{i} \mid \sigma) f(x_{s} \mid \sigma)$$

$$=\frac{n!}{(s-r-1)!(n-s)!}\frac{1}{\sigma^{r+1}}\exp\left(-\frac{\sum_{i=1}^{r}x_{i}+(n-r)x_{r}}{\sigma}\right)$$

$$\times \left[1 - \exp\left(-\frac{x_{s} - x_{r}}{\sigma}\right)\right]^{s - r - 1} \left[\exp\left(-\frac{x_{s} - x_{r}}{\sigma}\right)\right]^{n - s + 1}.$$
(45)

Let

$$V = \frac{Q_r}{\sigma} = \frac{\sum_{i=1}^{r} X_i + (n-r)X_r}{\sigma}$$
(46)

and

$$W_{s} = \frac{X_{s} - X_{r}}{Q_{r}} = \frac{X_{s} - X_{r}}{\sum_{i=1}^{r} X_{i} + (n-r)X_{r}}.$$
(47)

Using the invariant embedding technique (Nechval, 1982, 1984, 1986, 1988a, 1988b; Nechval et al., 1999, 2000, 2001, 2003a, 2003b, 2004, 2008, 2009), we then find in a straightforward manner that the joint density of V, W_s conditional on fixed $x^r = (x_1, x_2, ..., x_r)$, is

$$f(w_s, v | x^r) = 9(x^r) \sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^j v^r \exp(-v[1+w_s(n-s+1+j)]),$$

$$\mathbf{w}_{s} \in (0, \infty), \quad \mathbf{v} \in (0, \infty),$$
 (48)

where

$$\vartheta(x^{r}) = \left(\int_{0}^{\infty} \int_{0}^{\infty} \frac{1}{\vartheta(x^{r})} f(w_{s}, v \mid x^{r}) dw_{s} dv\right)^{-1} = \frac{1}{B(s - r, n - s + 1)\Gamma(r)}$$
(49)

is the normalizing constant, which does not depend on x^r . Now v can be integrated out of (48) in a straightforward way to give

$$f(w_s \mid x^r) = \frac{r}{B(s-r,n-s+1)} \sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^j \frac{1}{[1+w_s(n-s+1+j)]^{r+1}}.$$
 (50)

Then (42) follows from (50). This completes the proof.

Corollary 2.1.

$$\Pr\{W_{s} \le w_{s}\} = 1 - \frac{1}{B(s-r,n-s+1)} \sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^{j} \frac{1}{(n-s+1+j)[1+w_{s}(n-s+1+j)]^{r}}. \quad (51)$$

For a specified probability level α, w_s can be obtained such that

$$\Pr\{W_{s} \le w_{s} \mid X_{r} = x_{r}, Q_{r} = q_{r}\} = \Pr\left\{\frac{X_{s} - x_{r}}{q_{r}} \le w_{s}\right\} = \Pr\{X_{s} \le x_{r} + q_{r}w_{s}\} = \alpha.$$
 (52)

Hence, with confidence α , one could predict X_s to be less than or equal to $x_r + q_r w_s$. Consider a life-testing situation similar to that in the above example of Theorem 1, where n = 6 simultaneously tested items have life times following the exponential distribution (15). Two items (r = 2) fail at times 75 and 90 hours. Suppose, say, we are predicting the 4th

Two items (r = 2) fail at times 75 and 90 hours. Suppose, say, we are predicting the 4th failure time (s = 4). Using (44), (45), (46), and α = 0.95, we get q_r = 525 and w_s = 1.855, which yield a predicted value for X_s of 1064 hours.

We make two additional remarks concerning evaluation of the above probability (51):

(i) In the important case where s = n, expression (51) simplifies to

$$\Pr\{W_{s} \le W_{s}\} = \sum_{j=0}^{n-r} {n-r \choose j} (-1)^{j} \frac{1}{(1+jW_{s})^{r}}.$$
 (53)

(ii) In the special case where r = s-1, we note that $(s-1)(n-s+1)(X_s-X_{s-1})/Q_{s-1}$ is an F variate with (2, 2s-2) degrees of freedom, so that appropriate probability statements can be read from standard tables of the F distribution.

Theorem 3 (*Predictive distribution of the sth order statistic* X_s *on the basis of the past order statistics* X_r *and* X_1 *from the two-parameter exponential distribution of the same sample*). Let $X_1 \le X_2 \le ... \le X_r$ be the first r ordered past observations from a sample of size n from the exponential distribution with the PDF

$$f(x \mid \sigma) = \frac{1}{\sigma} \exp[-(x - \mu) / \sigma], \quad (\sigma > 0, -\infty < \mu < \infty, x \ge \mu), \tag{54}$$

which is characterized by the scale parameter σ and the shift parameter μ . It is assumed that these parameters are unknown. Then the predictive PDF of the sth order statistic X_s (s>r) from the same sample may be obtained as

$$\widetilde{f}\left(x_{s} \mid x_{1}, x_{r}\right) = \frac{1}{B(s-r, n-s+1)B(r-1, n-r+1)} \sum_{j=0}^{s-r-1} \sum_{i=0}^{r-2} (-1)^{i+j} \binom{s-r-1}{j} \binom{r-2}{i}$$

$$\times \frac{1}{\left[w_{s}(n-s+1+j)+(n-r+1+i)\right]^{2}} \frac{1}{x_{r}-x_{1}}, \quad w_{s} > 0, \tag{55}$$

where

$$W_{s} = \frac{X_{s} - X_{r}}{X_{r} - X_{1}}. (56)$$

Proof. It is carried out in the similar way as the proof of Theorem 1. Corollary 3.1.

$$\Pr\{W_{s} \leq w_{s}\} = \frac{1}{B(s-r,n-s+1)B(r-1,n-r+1)} \sum_{j=0}^{s-r-1} \sum_{i=0}^{r-2} (-1)^{i+j} \binom{s-r-1}{j} \binom{r-2}{i}$$

$$\times \left(\frac{1}{n-r+1+i} - \frac{1}{w_{s}(n-s+1+j) + (n-r+1+i)}\right) \frac{1}{(n-s+1+j)}$$

$$= 1 - \frac{1}{B(s-r,n-s+1)B(r-1,n-r+1)} \sum_{j=0}^{s-r-1} \binom{s-r-1}{j} (-1)^{j} \frac{[(r-1)(n-s+1+j)]^{-1}}{\binom{w_{s}(n-s+1+j) + n}{r-1}}$$
(57)

For a specified probability level α , w_s can be obtained such that

$$\Pr\{W_{s} \le w_{s} \mid X_{r} = x_{r}, X_{1} = x_{1}\} = \Pr\left\{\frac{X_{s} - x_{r}}{x_{r} - x_{1}} \le w_{s}\right\}$$

$$= \Pr\{X_{s} \le x_{r} + w_{s}(x_{r} - x_{1})\} = \alpha. \tag{58}$$

Hence, with confidence α , one could predict X_s to be less than or equal to $x_r+w_s(x_r-x_1)$. **Theorem 4** (*Predictive distribution of the sth order statistic* X_s *on the basis of the past order statistics* $X_1 \le X_2 \le ... \le X_r$ *from the two-parameter exponential distribution of the same sample*). Under conditions of Theorem 3, the predictive probability density function of the sth order statistic X_s (s>r) from the same sample may be obtained as

$$\widetilde{f}(x_{s} \mid x^{r}) = \frac{r-1}{B(s-r,n-s+1)} \sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^{j} \frac{1}{[1+w_{s}(n-s+1+j)]^{r}} \frac{1}{q}, \quad w_{s} > 0, \quad (59)$$

where

$$W_{\rm s} = \frac{X_{\rm s} - X_{\rm r}}{O},\tag{60}$$

$$Q = \sum_{i=1}^{r} (X_i - X_1) + (n-r)(X_r - X_1).$$
 (61)

Proof. The proof is carried out in the similar way as the proof of Theorem 2. Corollary 4.1.

$$\Pr\{W_{s} \le w_{s}\} = 1 - \frac{1}{B(s-r,n-s+1)} \sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^{j} \frac{1}{(n-s+1+j)[1+w_{s}(n-s+1+j)]^{r-1}}$$

$$=1-\frac{1}{B(s-r,n-s+1)}\sum_{j=r+1}^{s}\binom{s-r-1}{s-j}(-1)^{s-j}\frac{1}{(n+1-j)[1+w_{s}(n+1-j)]^{r-1}}.$$
 (62)

For a specified probability level α , w_s can be obtained such that

$$\Pr\{W_{s} \le W_{s} \mid X_{r} = X_{r}, Q = q\} = \Pr\left\{\frac{X_{s} - X_{r}}{q} \le W_{s}\right\} = \Pr\{X_{s} \le X_{r} + qW_{s}\} = \alpha.$$
 (63)

Hence, with confidence α , one could predict X_s to be less than or equal to x_r+qw_s .

Suppose, for instance, that n = 8 items are put on test simultaneously and that the first r = 4 items have the lifetimes 62, 84, 106 and 144 hours. Let the lifetimes of all n items be distributed according to the two-parameter exponential distribution (47) with the same parameters σ and μ . We wish to find a 95% prediction interval of the type (56) for s=8. We obtain from (55) and (56) that $\Pr\{X_s \le 1408.8\} = 0.95$. Thus, we can be 95% confident that the total elapsed time will not exceed 1409 hours.

Theorem 5 (*Predictive distribution of the sth order statistic* X_s *on the basis of the past order statistics* $X_1 \le X_2 \le ... \le X_r$ *from the two-parameter Weibull distribution of the same sample*). Let $X_1 \le X_2 \le ... \le X_r$ be the first r ordered past observations from a sample of size n from the two-parameter Weibull distribution given by

$$f(x \mid \beta, \delta) = \frac{\delta}{\beta} \left(\frac{x}{\beta} \right)^{\delta - 1} \exp \left[-\left(\frac{x}{\beta} \right)^{\delta} \right] \quad (x > 0), \tag{64}$$

where δ >0 and β >0 are the shape and scale parameters, respectively, which are unknown. Then the predictive PDF of the sth order statistic X_s (s>r) from the same sample may be obtained as

$$\tilde{f}(x_s, v | z)$$

$$= \left(\sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^{s-r-1-j} \frac{rv^{r-2}e^{v\tilde{\delta}\sum\limits_{i=1}^{r}\ln\left(x_{i}\,/\,\hat{\beta}\right)}ve^{v\left[w_{s}+\tilde{\delta}\ln\left(x_{r}\,/\,\hat{\beta}\right)\right]}}{\left((n-r-j)e^{v\left[w_{s}+\tilde{\delta}\ln\left(x_{r}\,/\,\hat{\beta}\right)\right]}+je^{v\tilde{\delta}\ln\left(x_{r}\,/\,\hat{\beta}\right)}+\sum_{i=1}^{r}e^{v\tilde{\delta}\ln\left(x_{i}\,/\,\hat{\beta}\right)}\right)^{r+1}} \frac{\tilde{\delta}}{x_{s}}\right)} \\ \times \left(\sum_{j=0}^{s-r-1} \left(s-r-1\right)(-1)^{s-r-1-j} \int\limits_{0}^{\infty} \frac{v^{r-2}e^{v\tilde{\delta}\sum\limits_{i=1}^{r}\ln\left(x_{i}\,/\,\hat{\beta}\right)}}{(n-r-j)\left(\sum\limits_{i=1}^{r}e^{v\tilde{\delta}\ln\left(x_{i}\,/\,\hat{\beta}\right)}+(n-r)e^{v\tilde{\delta}\ln\left(x_{r}\,/\,\hat{\beta}\right)}\right)^{r}}dv\right)^{-1},$$

$$W_s \in (-\infty, \infty), \quad v \in (0, \infty).$$
 (65)

where $\hat{\beta}$ and $\hat{\delta}$ are the maximum likelihood estimators of β and δ based on the first r ordered past observations $(X_1, ..., X_r)$ from a sample of size n from the Weibull distribution, which can be found from solution of

$$\widehat{\beta} = \left(\frac{\sum_{i=1}^{r} x_i^{\widehat{\delta}} + (n-r) x_r^{\widehat{\delta}}}{r}\right)^{1/\widehat{\delta}},$$
(66)

and

$$\hat{\delta} = \left[\left(\sum_{i=1}^{r} x_i^{\hat{\delta}} \ln x_i + (n-r) x_r^{\hat{\delta}} \ln x_r \right) \left(\sum_{i=1}^{r} x_i^{\hat{\delta}} + (n-r) x_r^{\hat{\delta}} \right)^{-1} - \frac{1}{r} \sum_{i=1}^{r} \ln x_i \right]^{-1},$$
(67)

$$\mathbf{z} = (\mathbf{z}_1, \mathbf{z}_2, ..., \mathbf{z}_r), \tag{68}$$

$$\mathbf{z} = (z_1, z_2, ..., z_r),$$

$$Z_i = \hat{\delta} \ln \left(\frac{X_i}{\hat{\beta}} \right), \quad i = 1, ..., r,$$
(68)

$$W_{\rm s} = \widehat{\delta} \ln \left(\frac{X_{\rm s}}{X_{\rm r}} \right). \tag{70}$$

Proof. The joint density of $Y_1=ln(X_1)$, ..., $Y_r=ln(X_r)$, $Y_s=ln(X_s)$ is given by

$$f(y_1, ..., y_r, y_s \mid \mu, \sigma) = \frac{n!}{(s-r-1)!(n-s)!} \prod_{i=1}^r f(y_i \mid \mu, \sigma) [F(y_s \mid \mu, \sigma) - F(y_r \mid \mu, \sigma)]^{s-r-1}$$

$$\times f(\mathbf{y}_{s} \mid \boldsymbol{\mu}, \boldsymbol{\sigma}) [1 - F(\mathbf{y}_{s} \mid \boldsymbol{\mu}, \boldsymbol{\sigma})]^{n-s}, \tag{71}$$

where

$$f(y \mid \mu, \sigma) = \frac{1}{\sigma} \exp \left[\frac{y - \mu}{\sigma} - \exp \left(\frac{y - \mu}{\sigma} \right) \right], \tag{72}$$

$$F(y \mid \mu, \sigma) = 1 - \exp\left[-\exp\left(\frac{y - \mu}{\sigma}\right)\right],\tag{73}$$

$$\mu = \ln \beta, \ \sigma = 1/\delta.$$
 (74)

Let $\hat{\mu}$, $\hat{\sigma}$ be the maximum likelihood estimators (estimates) of μ , σ based on Y_1 , ..., Y_r and let

$$V_1 = \frac{\widehat{\mu} - \mu}{\widehat{\sigma}},\tag{75}$$

$$V = \frac{\hat{\sigma}}{\sigma},\tag{76}$$

$$W_{\rm s} = \frac{Y_{\rm s} - Y_{\rm r}}{\widehat{G}},\tag{77}$$

and

$$Z_{i} = \frac{Y_{i} - \widehat{\mu}}{\widehat{\sigma}}, \quad i = 1(1)r.$$
 (78)

Parameters μ and σ in (64) are location and scale parameters, respectively, and it is well known that if $\hat{\mu}$ and $\hat{\sigma}$ are estimates of μ and σ , possessing certain invariance properties, then the quantities V_1 and V_2 are parameter-free. Most, if not all, proposed estimates of μ and σ possess the necessary properties; these include the maximum likelihood estimates and various linear estimates. Z_{ir} , i=1(1)r, are ancillary statistics, any r-2 of which form a functionally independent set. For notational convenience we include all of z_1 , ..., z_r in (68); z_{r-1} and z_r can be expressed as function of z_1 , ..., z_r only.

Using the invariant embedding technique (Nechval, 1982, 1984, 1986, 1988a, 1988b; Nechval et al., 1999, 2000, 2001, 2003a, 2003b, 2004, 2008, 2009), we then find in a straightforward manner that the joint density of V_1 , V, W_s conditional on fixed $\mathbf{z} = (z_1, z_2, ..., z_r)$, is

$$f(w_s, v, v_1 | \mathbf{z}) = \vartheta(\mathbf{z})v^{r-1} \exp\left(v[\sum_{i=1}^r z_i + z_r + w_s] + (r+1)v_1\right)$$

$$\times \sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^{s-r-1-j} \exp \left[-e^{v_1} \left((n-r-j)e^{v(z_r + w_s)} + je^{vz_r} + \sum_{i=1}^r e^{vz_i} \right) \right],$$

$$w_s \in (0, \infty), \quad v \in (0, \infty), \quad v_1 \in (-\infty, \infty),$$

$$(79)$$

where

$$\vartheta(\mathbf{z}) = \left(\int_{-\infty}^{\infty} \int_{0}^{\infty} \int_{0}^{\infty} \frac{1}{\vartheta(\mathbf{z})} f(\mathbf{w}_{s}, \mathbf{v}_{1}, \mathbf{v} \mid \mathbf{z}) d\mathbf{w}_{s} d\mathbf{v} d\mathbf{v}_{1}\right)^{-1}$$

$$\times \left(\sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^{s-r-1-j} \int_{0}^{\infty} \frac{v^{r-2} \exp \left(v \sum_{i=1}^{r} z_{i} \right)}{(n-r-j) \left(\sum_{i=1}^{r} \exp[v z_{i}] + (n-r) \exp[v z_{r}] \right)^{r}} dv \right)^{-1}$$

$$(80)$$

is the normalizing constant.

Now v₁ can be integrated out of (79) in a straightforward way to give

$$f(\mathbf{w}_{s}, \mathbf{v} \mid \mathbf{z})$$

$$= \left(\sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^{s-r-1-j} \frac{rv^{r-2} \exp\left(v \sum_{i=1}^{r} z_{i}\right) v \exp[v(w_{s} + z_{r})]}{\left((n-r-j) \exp[v(w_{s} + z_{r})] + j \exp[vz_{r}] + \sum_{i=1}^{r} \exp[vz_{i}]\right)^{r+1}}\right)$$

$$\times \left(\sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^{s-r-1-j} \int_{0}^{\infty} \frac{v^{r-2} \exp\left(v \sum_{i=1}^{r} z_{i}\right)}{(n-r-j) \left(\sum_{i=1}^{r} \exp[vz_{i}] + (n-r) \exp[vz_{r}]\right)^{r}} dv\right)^{-1}$$
(81)

Then (65) follows from (81). This completes the proof.

Corollary 5.1. A lower one-sided conditional $(1-\alpha)$ prediction limit h on the sth order statistic X_s (s>r) from the same sample may be obtained from (73) as

$$Pr\left\{X_{s} \geq h \mid \mathbf{z}\right\} = Pr\left\{\widehat{\delta} ln\left(\frac{X_{s}}{\widehat{\beta}}\right) \geq \widehat{\delta} ln\left(\frac{h}{\widehat{\beta}}\right) \mid \mathbf{z}\right\} = Pr\left\{W_{s} \geq w_{h} \mid \mathbf{z}\right\}$$

(82)

$$= \left(\sum_{j=0}^{s-r-1} {s-r-1 \choose j} (-1)^{s-r-1-j} \int\limits_0^\infty \frac{(n-r-j)^{-1} \, v^{r-2} e^{v\hat{\delta} \sum\limits_{i=1}^r \ln\left(x_i \, / \, \hat{\beta}\right)}}{\left((n-r-j) e^{v\left[w_h + \hat{\delta} \ln\left(x_r \, / \, \hat{\beta}\right)\right]} + j e^{v\hat{\delta} \ln\left(x_r \, / \, \hat{\beta}\right)} + \sum_{i=1}^r e^{v\hat{\delta} \ln\left(x_i \, / \, \hat{\beta}\right)}\right)^r} \, dv \right)$$

$$\times \left(\sum_{j=0}^{s-r-1} \left(s-r-1\right) (-1)^{s-r-1-j} \int\limits_0^\infty \frac{v^{r-2} e^{v\hat{\delta} \sum\limits_{i=1}^r \ln\left(x_i \, / \, \hat{\beta}\right)}}{(n-r-j) \left(\sum\limits_{i=1}^r e^{v\hat{\delta} \ln\left(x_i \, / \, \hat{\beta}\right)} + (n-r) e^{v\hat{\delta} \ln\left(x_r \, / \, \hat{\beta}\right)}\right)^r} \, dv \right)^{-1}$$

Let $X_1 \le X_2 \le ... \le X_n$ denote the order statistics in a sample of size n from a continuous parent distribution whose cumulative distribution function $F(x \mid \theta)$ is a strictly increasing function of x, where θ is an unknown parameter. A number of authors have considered the prediction problem for the future observation X_s based on the observed values $X_1 \le ... \le X_r$, $1 \le r \le s \le n$. Prediction intervals have been treated by Hewitt (1968), Lawless (1971), Lingappaiah (1973), Likes (1974), and Kaminsky (1977).

 $=1-\alpha$.

Consider, in this section, the case when the parameter θ is known. It can be shown that the predictive distribution of X_n , given $X_i = x_i$ for all $i \le r$, is the same as the predictive distribution of X_n , given only $X_r = x_r$, which is given by

$$\Pr\{X_{n} \le h \mid \theta, X_{r} = x_{r}\} = \left[\frac{F(h \mid \theta) - F(x_{r} \mid \theta)}{1 - F(x_{r} \mid \theta)}\right]^{n - r}$$
(83)

for $h \ge x_r$. We remark also at this point that

$$\Pr\{X_{r+1} \le h \mid \theta, X_r = x_r\} = 1 - \left[1 - \frac{F(h \mid \theta) - F(x_r \mid \theta)}{1 - F(x_r \mid \theta)}\right]^{n-r} = 1 - \left[\frac{1 - F(h \mid \theta)}{1 - F(x_r \mid \theta)}\right]^{n-r}$$
(84)
for $h \ge x_r$.

4.2 Statistical Inferences for Order Statistics in the Future Sample

Theorem 6 (*Predictive distribution of the lth order statistic* Y_l *from a set of m future ordered observations* $Y_1 \le ... \le Y_l \le ... \le Y_m$ *on the basis of the past sample from the left-truncated Weibull distribution*). Let $X_1 \le X_2 \le ... \le X_r$ be the first r ordered past observations from a sample of size n from the left-truncated Weibull distribution with pdf

$$f(x \mid a, b, \delta) = \frac{\delta}{\sigma} x^{\delta - 1} \exp\left[-\left(x^{\delta} - \mu\right)/\sigma\right], \quad (x^{\delta} \ge \mu, \sigma, \delta > 0), \tag{85}$$

which is characterized by being three-parameter (μ, σ, δ) where δ is termed the shape parameter, σ is the scale parameter, and μ is the truncation parameter. It is assumed that the parameter δ is known. Then the non-unbiased predictive density function of the lth order statistic Y_1 from a set of m future ordered observations $Y_1 \leq ... \leq Y_1 \leq ... \leq Y_m$ is given by

$$\widetilde{f}(y_{1}|x^{n}) = \begin{cases} n(r-1)l \binom{m}{l} \sum_{i=0}^{l-1} \frac{\binom{l-1}{i}(-1)^{i} \left[1 + w_{1}(m-l+i+1)\right]^{-r}}{n+m-l+i+1} \frac{\delta}{s} y_{1}^{\delta-1}, & \text{if } y_{1} \geq x_{1}, \\ n(r-1) \frac{m!(n+m-l)!}{(m-l)!(n+m)!} (1-nw_{1})^{-r} \frac{\delta}{s} y_{1}^{\delta-1}, & \text{if } y_{1} \leq x_{1}, \end{cases}$$
(86)

where

$$W_1 = \left(Y_1^{\delta} - X_1^{\delta}\right) / S, \tag{87}$$

$$S = \sum_{i=1}^{r} (X_i^{\delta} - X_1^{\delta}) + (n-r)(X_r^{\delta} - X_1^{\delta}).$$
 (88)

Proof. It can be justified by using the factorization theorem that (X_1^{δ}, S) is a sufficient statistic for (μ, σ) . We wish, on the basis of the sufficient statistic (X_1^{δ}, S) for (μ, σ) , to construct the non-unbiased predictive density function of the lth order statistic Y_1 from a set of m future ordered observations $Y_1 \le ... \le Y_1 \le ... \le Y_m$.

By using the technique of invariant embedding (Nechval, 1982, 1984, 1986, 1988a, 1988b; Nechval et al., 1999, 2000, 2001, 2003a, 2003b, 2004, 2008, 2009) of (X_1^δ, S) , if $X_1 \le Y_1$, or (Y_1^δ, S) , if $X_1 \ge Y_1$, into a pivotal quantity $(Y_1^\delta - \mu)/\sigma$ or $(X_1^\delta - \mu)/\sigma$, respectively, we obtain an ancillary statistic $W_1 = (Y_1^\delta - X_1^\delta)/S$, whose distribution does not depend on any unknown parameter, and the pdf of W_1 given by

$$f(w_{1}) = \begin{cases} n(r-1)l \binom{m}{l} \sum_{i=0}^{l-1} \frac{\binom{l-1}{i}(-1)^{i} [1+w_{1}(m-l+i+1)]^{-r}}{n+m-l+i+1}, & \text{if } w_{1} \geq 0, \\ n(r-1) \frac{m!(n+m-l)!}{(m-l)!(n+m)!} (1-nw_{1})^{-r}, & \text{if } w_{1} \leq 0. \end{cases}$$

$$(89)$$

This ends the proof.

Corollary 6.1. A lower one-sided $(1-\alpha)$ prediction limit h on the lth order statistic Y_1 from a set of m future ordered observations $Y_1 \le ... \le Y_1 \le ... \le Y_m$ ($Pr\{Y_1 \ge h \mid x^n\} = 1-\alpha$) may be obtained from (89) as

$$h = \left(x_1^{\delta} + w_h s\right)^{1/\delta},\tag{90}$$

where

$$w_{h} = \begin{cases} \arg\left(nl\binom{m}{l}\sum_{i=0}^{l-1}\frac{\binom{l-1}{i}(-1)^{i}[1+w_{h}(m-l+i+1)]^{-(r-1)}}{(n+m-l+i+1)(m-l+i+1)} = 1-\alpha \right), & \text{if } \alpha \ge \frac{m!(n+m-l)!}{(m-l)!(n+m)!}, \\ \arg\left(1-\frac{m!(m+n-l)!}{(m-l)!(m+n)!}(1-nw_{h})^{-(r-1)} = 1-\alpha \right), & \text{if } \alpha \le \frac{m!(n+m-l)!}{(m-l)!(n+m)!}. \end{cases}$$

$$(91)$$

(Observe that an upper one-sided conditional α prediction limit h on the lth order statistic Y_1 may be obtained from a lower one-sided $(1-\alpha)$ prediction limit by replacing $1-\alpha$ by α .) Corollary 6.2. If l=1, then a lower one-sided $(1-\alpha)$ prediction limit h on the minimum Y_1 of a set of m future ordered observations $Y_1 \leq ... \leq Y_m$ is given by

$$h = \begin{cases} \left(x_1^{\delta} + \frac{s}{m} \left[\left(\frac{n}{(1-\alpha)(n+m)}\right)^{\frac{1}{r-1}} - 1 \right] \right)^{1/\delta}, & \alpha \ge \frac{m}{n+m}, \\ \left(x_1^{\delta} - \frac{s}{n} \left[\left(\frac{m}{\alpha(n+m)}\right)^{\frac{1}{r-1}} - 1 \right] \right)^{1/\delta}, & \alpha \le \frac{m}{n+m}. \end{cases}$$

$$(92)$$

Consider, for instance, an industrial firm which has the policy to replace a certain device, used at several locations in its plant, at the end of 24-month intervals. It doesn't want too many of these items to fail before being replaced. Shipments of a lot of devices are made to each of three firms. Each firm selects a random sample of 5 items and accepts his shipment if no failures occur before a specified lifetime has accumulated. The manufacturer wishes to take a random sample and to calculate the lower prediction limit so that all shipments will be accepted with a probability of 0.95. The resulting lifetimes (rounded off to the nearest month) of an initial sample of size 15 from a population of such devices are given in Table 1.

Observations															
\mathbf{x}_1	\mathbf{x}_2	X 3	X 4	X 5	x ₆	X 7	x ₈	X 9	x ₁₀	X ₁₁	X ₁₂	X ₁₃	X ₁₄	X 15	
8	9	10	12	14	17	20	25	29	30	35	40	47	54	62	
	Lifetime (in number of month intervals)														

Table 1. The data of resulting lifetimes

Goodness-of-fit testing. It is assumed that

$$X_{i} \sim f(x \mid a, b, \delta) = \frac{\delta}{\sigma} x^{\delta - 1} \exp\left[-\left(x^{\delta} - \mu\right)/\sigma\right], \quad (x \ge \mu, \sigma, \delta > 0), \quad i = 1(1)15, \tag{93}$$

where the parameters μ and σ are unknown; (δ =0.87). Thus, for this example, r = n = 15, k = 3, m = 5, 1– α = 0.95, X_1^{δ} = 6.1, and S = 170.8. It can be shown that the

$$U_{j} = 1 - \left(\frac{\sum_{i=2}^{j+1} (n-i+1)(X_{i}^{\delta} - X_{i-1}^{\delta})}{\sum_{i=2}^{j+2} (n-i+1)(X_{i}^{\delta} - X_{i-1}^{\delta})} \right), \quad j = 1(1)n-2,$$
(94)

are i.i.d. U(0,1) rv's (Nechval et al., 1998). We assess the statistical significance of departures from the left-truncated Weibull model by performing the Kolmogorov-Smirnov goodness-of-fit test. We use the $_{\bullet}K$ statistic (Muller et al., 1979). The rejection region for the α level of significance is $\{_{\bullet}K >_{\bullet}K_{n;\alpha}\}$. The percentage points for $_{\bullet}K_{n;\alpha}$ were given by Muller et al. (1979). For this example,

$$_{\bullet}$$
K = 0.220 < $_{\bullet}$ K_{n=13; α =0.05} = 0.361. (95)

Thus, there is not evidence to rule out the left-truncated Weibull model. It follows from (92), for

$$\alpha = 0.05 < \frac{km}{n + km} = 0.5,$$
(96)

that

$$h = \left(x_1^{\delta} - \frac{s}{n} \left[\left(\frac{km}{\alpha(n+km)} \right)^{\frac{1}{n-1}} - 1 \right] \right)^{1/\delta} = \left(6.1 - \frac{170.8}{15} \left[\left(\frac{15}{0.05(15+15)} \right)^{\frac{1}{14}} - 1 \right] \right)^{1/0.87} = 5. \quad (97)$$

Thus, the manufacturer has 95% assurance that no failures will occur in each shipment before h = 5 month intervals.

5. Examples

5.1 Example 1

An electronic component is required to pass a performance test of 500 hours. The specification is that 20 randomly selected items shall be placed on test simultaneously, and 5 failures or less shall occur during 500 hours. The cost of performing the test is \$105 per hour. The cost of redesign is \$5000. Assume that the failure distribution follows the one-parameter

exponential model (15). Three failures are observed at 80, 220, and 310 hours. Should the test be continued?

We have from (19) and (20)

$$\hat{\theta} = \frac{80 + 220 + 310 + 17 \times 310}{3} = 1960 \text{ hours};$$
 (98)

$$\hat{p}_{pas} = \int_{500}^{\infty} \frac{17!}{2! \, 14!} \frac{\left[\exp\left(-\frac{310}{1960}\right) - \exp\left(-\frac{x_6}{1960}\right) \right]^2}{\left[\exp\left(-\frac{310}{1960}\right) \right]^{17}} \frac{1}{1960} \left[\exp\left(-\frac{x_6}{1960}\right) \right]^{15} dx_6 = 0.79665; \quad (99)$$

Since

$$\int_{x_r}^{\tau_0} x_s f(x_s \mid x^r, \widehat{\sigma}) dx_s = 430.05 \text{ hours} > x_k + \widehat{p}_{pas} \frac{c_2}{c_1} = 310 + 0.79665 \frac{5000}{105} = 347.94 \text{ hours}, \quad (100)$$

abandon the present test and initiate a redesign.

5.2 Example 2

Consider the following problem. A specification for an automotive hood latch is that, of 30 items placed on test simultaneously, ten or fewer shall fall during 3000 cycles of operation. The cost of performing the test is \$2.50 per cycle. The cost of redesign is \$8500. Seven failures, which follow the Weibull distribution with the probability density function (25), are observed at 48, 300, 315, 492, 913, 1108, and 1480 cycles. Shall the test be continued beyond the 1480th cycle?

It follows from (29) and (30) that $\hat{\sigma}$ = 2766.6 and $\hat{\delta}$ = 0.9043. In turn, these estimates yield \hat{p}_{pas} =0.25098. Since

$$\int_{x_{\rm r}}^{\tau_0} x_{\rm s} f(x_{\rm s} \mid x^{\rm r}, \hat{\sigma}) dx_{\rm s} = 1877.6 \text{ hours} < x_{\rm k} + \hat{p}_{\rm pas} \frac{c_2}{c_1} = 1480 + 0.25098 \frac{8500}{2.5} = 2333.33 \text{ hours,}$$
(101)

continue the present test.

6. Stopping Rule in Sequential-Sample Testing

At the planning stage of a statistical investigation the question of sample size (n) is critical. For such an important issue, there is a surprisingly small amount of published literature. Engineers who conduct reliability tests need to choose the sample size when designing a test plan. The model parameters and quantiles are the typical quantities of interest. The large-sample procedure relies on the property that the distribution of the t-like quantities is close to the standard normal in large samples. To estimate these quantities the maximum

likelihood method is often used. The large-sample procedure to obtain the sample size relies on the property that the distribution of the above quantities is close to standard normal in large samples. The normal approximation is only first order accurate in general. When sample size is not large enough or when there is censoring, the normal approximation is not an accurate way to obtain the confidence intervals. Thus sample size determined by such procedure is dubious.

Sampling is both expensive and time consuming. Hence, there are situations where it is more efficient to take samples sequentially, as opposed to all at one time, and to define a stopping rule to terminate the sampling process. The case where the entire sample is drawn at one instance is known as "fixed sampling". The case where samples are taken in successive stages, according to the results obtained from the previous samplings, is known as "sequential sampling".

Taking samples sequentially and assessing their results at each stage allows the possibility of stopping the process and reaching an early decision. If the situation is clearly favorable or unfavorable (for example, if the sample shows that a widget's quality is definitely good or poor), then terminating the process early saves time and resources. Only in the case where the data is ambiguous do we continue sampling. Only then do we require additional information to take a better decision.

In this section, the following optimal stopping rule for determining the efficient sample size sequentially under assigning warranty period is proposed.

6.1 Stopping Rule on the Basis of the Expected Beneficial Effect

Suppose the random variables X_1 , X_2 , ..., all from the same population, are observed sequentially and follow the two-parameter Weibull fatigue-crack initiation lifetime distribution (64). After the nth observation ($n \ge n_0$, where n_0 is the initial sample size needful to estimate the unknown parameters of the underlying probability model for the data) the experimenter can stop and receive the beneficial effect on performance,

$$c_1 h_{(1:m);\alpha}^{PL} - cn,$$
 (102)

where c_1 is the unit value of the lower conditional $(1-\alpha)$ prediction limit (warranty period) $h_{(1:m);\alpha}^{PL} \equiv h_{(1:m);\alpha}^{PL}(x^n)$ (Nechval et al., 2007a, 2007b), $x^n = (x_1, ..., x_n)$, and c is the sampling cost

Below a rule is given to determine if the experimenter should stop in the nth observation, x_n , or if he should continue until the (n+l)st observation, X_{n+1} , at which time he is faced with this decision all over again.

Consider $h_{(1:m);\alpha}^{PL}(X_{n+1},x^n)$ as a function of the random variable X_{n+1} , when x_1 , ..., x_n are known, then it can be found its expected value

$$E\left\{h_{(1:m);\alpha}^{PL}(X_{n+1},x^n) \mid x^n\right\} = \int_{0}^{\infty} \int_{0}^{\infty} h_{(1:m);\alpha}^{PL}(x_{n+1},x^n) f(x_{n+1},v \mid x^n) dx_{n+1} dv.$$
 (103)

where

$$f(x_{n+1}, v \mid x^n) = \frac{nv^{n-2}e^{v\hat{\delta}\sum\limits_{i=1}^n\ln\left(\frac{x_i}{\hat{\beta}}\right)}ve^{v\hat{\delta}\ln\left(\frac{x_{n+1}}{\hat{\beta}}\right)}\hat{\delta}x_{n+1}^{-1}}{\int\limits_{0}^{\infty}v^{n-2}e^{v\hat{\delta}\sum\limits_{i=1}^n\ln\left(\frac{x_i}{\hat{\beta}}\right)}\left(\sum\limits_{i=1}^n e^{v\hat{\delta}\ln\left(\frac{x_i}{\hat{\beta}}\right)}\right)^{-n}dv} \left(e^{v\hat{\delta}\ln\left(\frac{x_{n+1}}{\hat{\beta}}\right)} + \sum_{i=1}^n e^{v\hat{\delta}\ln\left(\frac{x_i}{\hat{\beta}}\right)}\right)^{-(n+1)}, \quad (104)$$

the maximum likelihood estimates $\hat{\beta}$ and $\hat{\delta}$ of β and δ , respectively, are determined from the equations (66) and (67), $\int\limits_0^\infty f(x_{n+1},v\,|\,x^n) dv$ is the predictive probability density function

Now the optimal stopping rule is to determine the expected beneficial effect on performance for continuing

$$c_{1}E\left\{h_{(1:m);\alpha}^{PL}(X_{n+1},x^{n}) \mid x^{n}\right\} - c(n+1)$$
(105)

and compare this with (102).

If

$$c_1 \Big(E \Big\{ h_{(1:m);\alpha}^{PL} (X_{n+1}, x^n) \mid x^n \Big\} - h_{(1:m);\alpha}^{PL} (x^n) \Big) > c, \tag{106}$$

it is profitable to continue;

Ιf

$$c_1 \Big(E \Big\{ h_{(1:m);\alpha}^{PL}(X_{n+1}, x^n) \mid x^n \Big\} - h_{(1:m);\alpha}^{PL}(x^n) \Big) \le c, \tag{107}$$

the experimenter should stop.

7. Conclusions

Determining when to stop a statistical test is an important management decision. Several stopping criteria have been proposed, including criteria based on statistical similarity, the probability that the system has a desired reliability, and the expected cost of remaining faults. This paper presents a new stopping rule in fixed-sample testing based on the statistical estimation of total costs involved in the decision to continue beyond an early failure as well as a stopping rule in sequential-sample testing to determine when testing should be stopped.

The paper considers the problem that can be stated as follows. A new product is submitted for lifetime testing. The product will be accepted if a random sample of n items shows less than s failures in performance testing. We want to know whether to stop the test before it is completed if the results of the early observations are unfavorable. A suitable stopping decision saves the cost of the waiting time for completion. On the other hand, an incorrect stopping decision causes an unnecessary design change and a complete rerun of the test. It

is assumed that the redesign would improve the product to such an extent that it would definitely be accepted in a new lifetime testing. The paper presents a stopping rule based on the statistical estimation of total costs involved in the decision to continue beyond an early failure. Sampling is both expensive and time consuming. The cost of sampling plays a fundamental role and since there are many practical situations where there is a time cost and an event cost, a sampling cost per observed event and a cost per unit time are both included. Hence, there are situations where it is more efficient to take samples sequentially, as opposed to all at one time, and to define a stopping rule to terminate the sampling process. One of these situations is considered in the paper. The practical applications of the stopping rules are illustrated with examples.

8. Acknowledgments

This research was supported in part by Grant No. 06.1936, Grant No. 07.2036, Grant No. 09.1014, and Grant No. 09.1544 from the Latvian Council of Science.

9. References


- Amster, S. J. (1963). A modified bayes stopping rule. *The Annals of Mathematical Statistics*, Vol. 34, pp. 1404-1413
- Arrow, K. J.; Blackwell, D. & Girshick, M. A., (1949). Bayes and minimax solutions of sequential decision problems. *Econometrica*, Vol. 17, pp. 213-244
- El-Sayyad, G. M. & Freeman, P. R. (1973). Bayesian sequential estimation of a Poisson process rate. *Biometrika*, Vol. 60, pp. 289-296
- Freeman, P. R. (1970). Optimal bayesian sequential estimation of the median effective dose. *Biometrika*, Vol. 57, pp. 79-89
- Freeman, P. R. (1972). Sequential estimation of the size of a population. *Biometrika*, Vol. 59, pp. 9-17
- Freeman, P. R. (1973). Sequential recapture. Biometrika, Vol. 60, pp. 141-153
- Freeman, P. R. (1983). The secretary problem and its extensions: a review. *International Statistical Review*, Vol. 51, pp. 189-206
- Hewitt, J.E. (1968). A note on prediction intervals based on partial observations in certain life test experiments. *Technometrics*, Vol. 10, pp. 850-853
- Kaminsky, K.S. (1977). Comparison of prediction intervals for failure times when life is exponential. *Technometrics*, Vol. 19, pp. 83-86
- Kendall, M. G. & Stuart, A. S. (1969). *The Advanced Theory of Statistics*, Vol. 1 (3rd edition), Charles Griffin and Co. Ltd, London
- Lawless, J.F. (1971). A prediction problem concerning samples from the exponential distribution with applications in life testing. *Technometrics*, Vol. 13, pp. 725-730
- Likes, J. (1974). Prediction of sth ordered observation for the two-parameter exponential distribution. *Technometrics*, Vol. 16, pp. 241-244
- Lindley, D. V. & Barnett, B.N. (1965). Sequential sampling: two decision problems with linear losses for binomial and normal random variables. *Biometrika*, Vol. 52, pp. 507-532
- Lingappaiah, G.S. (1973). Prediction in exponential life testing. *Canadian Journal of Statistics*, Vol. 1, pp. 113-117 Muller, P.H.; Neumann, P. & Storm, R. (1979). *Tables of Mathematical Statistics*, VEB Fachbuchverlag, Leipzig

- Nechval, N. A. (1982). Modern Statistical Methods of Operations Research, RCAEI, Riga
- Nechval, N. A. (1984). Theory and Methods of Adaptive Control of Stochastic Processes, RCAEI, Riga
- Nechval, N.A. (1986). Effective invariant embedding technique for designing the new or improved statistical procedures of detection and estimation in signal processing systems, In: *Signal Processing III: Theories and Applications*, Young, I. T. et al. (Eds.), pp. 1051-1054, Elsevier Science Publishers B.V., North-Holland
- Nechval, N. A. (1988a). A general method for constructing automated procedures for testing quickest detection of a change in quality control. *Computers in Industry*, Vol. 10, pp. 177-183
- Nechval, N. A. (1988b). A new efficient approach to constructing the minimum risk estimators of state of stochastic systems from the statistical data of small samples, In: *Preprint of the 8th IFAC Symposium on Identification and System Parameter Estimation*, pp. 71-76, Beijing, P.R. China
- Nechval, N.A. & Nechval, K.N. (1998). Characterization theorems for selecting the type of underlying distribution, In: *Proceedings of the 7th Vilnius Conference on Probability Theory and 22nd European Meeting of Statisticians*, pp. 352-353, TEV, Vilnius
- Nechval, N. A. & Nechval, K. N. (1999). Invariant embedding technique and its statistical applications, In: *Conference Volume of Contributed Papers of the 52nd Session of the International Statistical Institute*, Finland, pp. 1-2, ISI International Statistical Institute, Helsinki, http://www.stat.fi/isi99/proceedings/arkisto/varasto/nech09 02.pdf
- Nechval, N. A. & Nechval, K. N. (2000). State estimation of stochastic systems via invariant embedding technique, In: *Cybernetics and Systems* 2000, Trappl, R. (Ed.), Vol. 1, pp. 96-101, Austrian Society for Cybernetic Studies, Vienna
- Nechval, N. A.; Nechval, K. N. & Vasermanis, E. K. (2001). Optimization of interval estimators via invariant embedding technique. *IJCAS (An International Journal of Computing Anticipatory Systems)*, Vol. 9, pp. 241-255
- Nechval, K. N.; Nechval N. A. & Vasermanis, E. K. (2003a). Adaptive dual control in one biomedical problem. *Kybernetes (The International Journal of Systems & Cybernetics)*, Vol. 32, pp. 658-665
- Nechval, N. A.; Nechval, K. N. & Vasermanis, E. K. (2003b). Effective state estimation of stochastic systems. *Kybernetes (The International Journal of Systems & Cybernetics)*, Vol. 32, pp. 666-678
- Nechval, N. A. & Vasermanis, E. K. (2004). *Improved Decisions in Statistics*, SIA "Izglitibas soli", Riga
- Nechval, K. N.; Nechval, N. A.; Berzins, G. & Purgailis, M. (2007a). Planning inspections in service of fatigue-sensitive aircraft structure components for initial crack detection. *Maintenance and Reliability*, Vol. 35, pp. 76-80
- Nechval, K. N.; Nechval, N. A.; Berzins, G. & Purgailis, M. (2007b). Planning inspections in service of fatigue-sensitive aircraft structure components under crack propagation. *Maintenance and Reliability*, Vol. 36, pp. 3-8
- Nechval, N. A.; Berzins, G.; Purgailis, M. & Nechval, K. N. (2008). Improved estimation of state of stochastic systems via invariant embedding technique. *WSEAS Transactions on Mathematics*, Vol. 7, pp. 141-159

Nechval, N. A.; Berzins, G.; Purgailis, M.; Nechval, K.N. & Zolova, N. (2009). Improved adaptive control of stochastic systems. *Advances In Systems Science and Applications*, Vol. 9, pp. 11-20

- Petrucelli, J. D. (1988) Secretary Problem, In: *Encyclopedia of Statistical Sciences*, Kotz, S. & Johnson, N. (Eds.), Vol. 8, pp. 326-329, Wiley, New York
- Raiffa, H. & Schlaifer, R. (1968). *Applied Statistical Decision Theory*, Institute of Technology Press, Massachusetts
- Samuels, S. M. (1991). Secretary Problems, In: *Handbook of Sequential Analysis*, Ghosh, B. K. & Sen, P. K. (Eds.), pp. 35-60, Dekker, New York
- Wald, A. & Wolfowitz, J. (1948). Optimum character of the sequential probability ratio test. *The Annals of Mathematical Statistics*, Vol. 19, pp. 326-339





Edited by Chris Myers

ISBN 978-953-307-121-3
Hard cover, 650 pages
Publisher Sciyo
Published online 17, August, 2010
Published in print edition August, 2010

Uncertainty presents significant challenges in the reasoning about and controlling of complex dynamical systems. To address this challenge, numerous researchers are developing improved methods for stochastic analysis. This book presents a diverse collection of some of the latest research in this important area. In particular, this book gives an overview of some of the theoretical methods and tools for stochastic analysis, and it presents the applications of these methods to problems in systems theory, science, and economics.

How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Nicholas A. Nechval and Maris Purgailis (2010). Stochastic Decision Support Models and Optimal Stopping Rules in a New Product Lifetime Testing, Stochastic Control, Chris Myers (Ed.), ISBN: 978-953-307-121-3, InTech, Available from: http://www.intechopen.com/books/stochastic-control/stochastic-decision-support-models-and-optimal-stopping-rules-in-a-new-product-lifetime-testing-

INTECH open science | open minds

InTech Europe

University Campus STeP Ri Slavka Krautzeka 83/A 51000 Rijeka, Croatia Phone: +385 (51) 770 447

Fax: +385 (51) 686 166 www.intechopen.com

InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai No.65, Yan An Road (West), Shanghai, 200040, China 中国上海市延安西路65号上海国际贵都大饭店办公楼405单元

Phone: +86-21-62489820 Fax: +86-21-62489821 © 2010 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the <u>Creative Commons Attribution-NonCommercial-ShareAlike-3.0 License</u>, which permits use, distribution and reproduction for non-commercial purposes, provided the original is properly cited and derivative works building on this content are distributed under the same license.



