We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists



186,000

200M



Our authors are among the

TOP 1% most cited scientists





WEB OF SCIENCE

Selection of our books indexed in the Book Citation Index in Web of Science™ Core Collection (BKCI)

### Interested in publishing with us? Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected. For more information visit www.intechopen.com



### Segmentation of Brain MRI

Rong Xu<sup>1</sup>, Limin Luo<sup>2</sup> and Jun Ohya<sup>1</sup> <sup>1</sup>Waseda University, <sup>2</sup>Southeast University, <sup>1</sup>Japan, <sup>2</sup>China

#### 1. Introduction

Effective, precise and consistent brain cortical tissue segmentation from magnetic resonance (MR) images is one of the most prominent issues in many applications of medical image processing. These applications include surgical planning (Kikinis et al., 1996), surgery navigation (Grimson et al., 1997), multimodality image registration (Saeed, 1998), abnormality detection (Rusinek et al., 1991), multiple sclerosis lesion quantification (Udupa et al., 1997), brain tumour detection (Vaidyanathan et al., 1997), functional mapping (Roland et al., 1993), etc. Traditionally, the purpose of segmentation is to partition the image into non-overlapping, constituent regions (or called classes, clusters, subsets or sub-regions) that are homogeneous with respect to intensity and texture (Gonzalez & Woods, 1992). If the domain of the image is given by  $\Omega$ , then the segmentation problem is to determine the sets  $S_k \subset \Omega$ , whose union is the entire domain  $\Omega$ . Thus, the sets that make up a segmentation must satisfy

$$\Omega = \bigcup_{k=1}^{K} S_k \tag{1}$$

where  $S_k \cap S_j = \emptyset$  for  $k \neq j$ , and each  $S_k$  is connected. Ideally, a segmentation method is to find those sets that correspond to distinct anatomical structures or regions of interest in the image (Pham et al., 2000).

For brain MR image segmentation, some studies aim to identify the entire image into subregions such as white matter (WM), grey matter (GM), and cerebrospinal fluid spaces (CSF) of the brain (Lim & Pfefferbaum, 1989), whereas others aim to extract one specific structure, for instance, brain tumour (M.C. Clark et al., 1998), multiple sclerosis lesions (Mortazavi et al., 2011), or subcortical structures (Babalola et al., 2008). Due to varying complications in segmenting human cerebral cortex, the manual methods for brain tissues segmentation might easily lead to errors both in accuracy and reproducibility (operator bias), and are exceedingly time-consuming, we thus need fast, accurate and robust semi-automatic (i.e., supervised classification explicitly needs user interaction) or completely automatic (i.e., nonsupervised classification) techniques (Suri, Singh, et al., 2002b).

#### 1.1 MR imaging (MRI)

MR imaging (MRI), invented by Raymond V. Damadian in 1969, and was firstly done on a human body in 1977 (Damadian et al., 1977). MR imaging is a popular medical imaging technique used in radiology to visualize detailed internal structures. It provides good contrast between different soft tissues of the body, which makes it especially useful in imaging the brain, muscles, the heart and cancers when compared with other medical imaging techniques, such as computed tomography (CT) or X-rays (Novelline & Squire, 2004). According to different magnetic signal weighting with particular values of the echo time ( $T_E$ ) and the repetition time ( $T_R$ ), three different images can be achieved from the same body:  $T_1$ -weighted,  $T_2$ -weighted, and PD-weighted (proton density).

In the clinical diagnosis, one patient's head is examined from 3 planes showed in Fig.1 (a), and they are axial plane, sagittal plane and coronal plane. The  $T_1$ -weighted brain MR images from different planes are respectively showed in Fig.1 (b), (c), and (d).





Fig.1. Brain MR images from (b) axial plane, (c) sagittal plane and (d) coronal plane.

#### 1.2 Difficulties in segmentation of brain MRI

Even though cortical segmentation has developed for many years in medical research, it is not regarded as an automated, reliable, and high speed technique because of magnetic field inhomogeneities:

- 1. Noise: random noise associated with the MR imaging system, which is known to have a Rician distribution (Prima et al., 2001);
- 2. Intensity inhomogeneity (also called bias field, or shading artefact): the non-uniformity in the radio frequency (RF) field during data acquisition, resulting in the shading of effect (X. Li et al., 2003);
- 3. Partial volume effect: more than one type of class or tissue occupies one pixel or voxel of an image, which are called partial volume effect. These pixels or voxels are usually called mixels (Ruan et al., 2000).

#### 1.3 Evaluation of segmentation techniques

The evaluation of brain tissue classification also is a complex issue in medical image processing. Visual inspection and comparison with manual segmentation are very strenuous and are not reliable since the amount of data to be processed is usually large. Tissue classification methods can also be validated by using synthetic data and real brain MR images. The simulated brain MR data with different noise levels and different levels of intensity inhomogeneity, have been provided by Brainweb simulated brain phantom (Collins et al., 1998; Kwan et al., 1999) (http://www.bic.mni.mcgill.ca/brainweb/), and the ground truth for both the classification and partial volumes within the images is also available to estimate different methods quantitatively. The real brain MRI datasets with expert segmentations can be obtained from Internet Brain Segmentation Repository (IBSR) (http://www.cma.mgh.harvard.edu/ibsr/). A few surveys on this topic have been provided in (H. Zhang et al., 2008; Y.J. Zhang, 1996, 2001). Here, we depict three different measures for quantitatively evaluating segmentation results.

(1) The misclassification rate (MCR) is the percentage of misclassified pixels and is computed as (background pixels were ignored in the MCR computation) (Bankman, 2000)

$$MCR = \frac{number \ of \ misclassified \ pixels}{total \ number \ of \ all \ pixels} \times 100\%$$
(2)

(2) The root mean squared error (RMSE) is to quantify the difference between the true partial volumes and the algorithm estimations. The RMSE of an estimator  $\hat{\theta}$  with respect to the estimated parameter  $\theta$  is defined as (Bankman, 2000):

$$RMSE(\hat{\theta}) = \sqrt{MSE(\hat{\theta})} = \sqrt{E[(\hat{\theta} - \theta)^2]}$$
(3)

(3) Let  $N_{fp}$  be the number of pixels that do not belong to a cluster and are segmented into the cluster,  $N_{fn}$  be the number of pixels that belong to a cluster and are not segmented into the cluster,  $N_p$  be the number of all pixels that belong to a cluster, and  $N_n$  be the total number of pixels that do not belong to a cluster. Three parameters in this evaluation system may now be defined as follows (Shen et al., 2005).

- Under segmentation (*UnS*):  $UnS = N_{fp}/N_n$ , representing the percentage of negative false segmentation;
- Over segmentation (*OvS*):  $0vS = N_{fn}/N_p$ , representing the percentage of positive false segmentation;

145

• Incorrect segmentation (*InC*):  $InC = (N_{fp} + N_{fn})/N$ , representing the total percentage of false segmentation.

The purpose of this chapter is to render a review about existing segmentation techniques and the work we have done in the segmentation of brain MR images. The rest of this chapter is organized as follows: In Section 2, existing techniques for human cerebral cortical segmentation and their applications are reviewed. In Section 3, a new non-homogeneous Markov random field model based on fuzzy membership is proposed for brain MR image segmentation. In Section 4, image pre-processing, such as de-noising, the correction of intensity inhomogeneity and the estimation of partial volume effect are summarized. In Section 5, the conclusion of this chapter is given.

#### 2. Image segmentation methods

A wide variety of segmentation techniques have been reviewed in (Balafar et al., 2010; Bankman, 2000; Bezdek et al., 1993; Clarke et al., 1995; Dubey et al., 2010; Pal & Pal, 1993; Pham et al., 2000; Saeed, 1998; Suri, Singh, et al., 2002b, 2002a; Zijdenbos & Dawant, 1994). We separate these techniques into 9 categories based on the classification scheme in (Pham et al., 2000): (1) thresholding, (2) region growing, (3) edge detection, (4) classifiers, (5) clustering, (6) statistical models, (7) artificial neural networks, (8) deformable models, and (9) atlas-guided approaches. Other notable methods that do not belong to any of these categories are described at the end of this section. Though each technique is presented separately, multiple techniques are often used in conjunction to solve various applications.

#### 2.1 Thresholding

The simplest operation in this category is image thresholding (Pal & Pal, 1993). In this technique a threshold is selected, and an image is divided into groups of pixels having value less than the threshold and groups of pixels with values greater or equal to the threshold. There are several thresholding methods: global thresholding, adaptive thresholding, optimal global and adaptive thresholding, local thresholding, and thresholds based on several variables (Bankman, 2000). Thresholding is a very simple, fast and easily implemented procedure that works reasonably well for images with very good contrast between distinctive sub-regions. A typical example is to separate CSF from highly T2-weighted brain images (Saeed, 1998). However, the distribution of intensities in brain MR images is usually very complex, and determining a threshold is difficult. In most cases, thresholding is combined with other methods (Brummer et al., 1993; Suzuki & Toriwaki, 1991).

#### 2.2 Region growing

Region growing (or region merging) is a procedure that looks for groups of pixels with similar intensities. It starts with a pixel or a group of pixels (called seeds) that belong to the structure of interest. Subsequently the neighbouring pixels with the same properties as seeds (or based on a homogeneity criteria) are appended gradually to the growing region until no more pixels can be added (Dubey et al., 2010). The object is then represented by all pixels that have been accepted during the growing procedure. The advantage of region growing is that it is capable of correctly segmenting regions that have the same properties

and are spatially separated, and also it generates connected regions (Bankman, 2000). Instead of region merging, it is possible to start with some initial segmentation and subdivide the regions that do not satisfy a given uniformity test. This technique is called splitting (Haralick & Shapiro, 1985). A combination of splitting and merging adds together the advantages of both approaches (Zucker, 1976). However, the results of region growing depend strongly on the selection of homogeneity criterion. Another problem is that different starting points may not grow into identical regions (Bankman, 2000). Region growing has been exploited in many clinical applications (Cline et al., 1987; Tang et al., 2000).

147

#### 2.3 Edge detection techniques

In edge detection techniques, the resulting segmented image is described in terms of the edges (boundaries) between different regions. Edges are formed at intersection of two regions where there are abrupt changes in grey level intensity values. Edge detection works well on images with good contrast between regions. A large number of different edge operators can be used for edge detection. These operations are generally named after their inventors. The most popular ones are the Marr-Hildreth or LoG (Laplacian-of-Gaussian), Sobel, Roberts, Prewitt, and Canny operators. Binary mathematical morphology and Watershed algorithm are often used for edge detection purposed in the segmentation of brain MR images (Dogdas et al., 2002; Grau et al., 2004). However, the major drawbacks of these methods are over-segmentation, sensitivity to noise, poor detection of significant areas with low contrast boundaries, and poor detection of thin structures, etc. (Grau et al., 2004).

#### 2.4 Classifiers

Classifier methods are known as supervised methods in pattern recognition, which seek to partition the image by using training data with known labels as references. The simplest classifier is nearest-neighbour classifier (NNC), in which each pixel is classified in the same class as the training datum with closest intensity (Boudraa & Zaidi, 2006). Other examples of classifiers are *k*-nearest neighbour (*k*-NN) (Duda & Hart, 1973; Fukunaga, 1990), Parzen window (Hamamoto et al., 1996), Bayes classifier or maximum likelihood (ML) estimation (Duda & Hart, 1973), Fisher's linear discriminant (FLD) (Fisher, 1936), the nearest mean classifier (NMC) (Skurichina & Duin, 1996), support vector machine (SVM) (Vapnik, 1998). The weakness of classifiers is that they generally do not perform any spatial modelling. This weakness has been addressed in recent work extending classifier methods to segment images corrupted by intensity in-homogeneities (Wells III et al., 1996). Neighbourhood and geometric information was also incorporated into a classifier approach in (Kapur et al., 1998). In addition, it requires manual interaction to obtain training data. Training sets for each image can be time consuming and laborious (Pham et al., 2000).

#### 2.5 Clustering

Clustering is the process of organizing objects into groups whose members are similar in certain ways, whose goal is to recognize structures or clusters presented in a collection of unlabelled data. It is a method of unsupervised learning, and a common technique for statistical data analysis used in many fields.

#### 2.5.1 K-means clustering

K-means clustering (or Hard C-means clustering, HCM) (MacQueen, 1967) is one of the simplest unsupervised clustering method, aiming to partition N samples into K clusters by minimizing an objective function so that the within-cluster sum of squares is minimized. It starts with defined initial K cluster centers and keeps reassigning the samples to clusters based on the similarity between the sample and the cluster centers until a convergence criterion is met. Given a set of samples ( $x_1, x_2, ..., x_N$ ), where each sample is a M-dimensional real vector,  $N_k$  is the num of samples in cluster k denoted by  $\Gamma_k$ ,  $v_k$  is the mean value of these samples, and then the objective function is defined as:

$$J_m = \sum_{k=1}^{K} \sum_{i=1}^{N} ||x_i - v_k||^2$$
(4)

$$v_k = \frac{1}{N_k} \sum_{x_i \in \Gamma_k} x_i \tag{5}$$

where  $||x_i - v_k||$  is a distance measure between point  $x_i$  and the cluter center  $v_k$ . The common distance measures are Euclidean distance, chessboard distance, city block distance, Mahalanobis distance, or Hamming distance. The K-means algorithm has been used widely in brain MR image segmentation (Abras & Ballarin, 2005; Vemuri et al., 1995), because of its easy implementation and simple time complexity. A major problem of this algorithm is that it is sensitive to the selection of *K* cluster centers, and may converge to a local minimum of the criterion function value (Jain et al., 1999). Dozens of optimal solutions have been proposed for selecting better initial *K* cluster centers to find the global minimum value (Bradley & Fayyad, 1998; Khan & Ahmad, 2004).

#### 2.5.2 Fuzzy c-means clustering (FCM)

Fuzzy c-means clustering (FCM) (Bezdek, 1981; Dunn, 1973) is based on the same idea of finding cluster centers by iteratively adjusting their positions and minimizing an objective function as K-means algorithm. Meanwhile it allows more flexibility by introducing multiple fuzzy membership grades to multiple clusters. The objective function is defined as:

$$J_m = \sum_{k=1}^{K} \sum_{i=1}^{N} u_{ik}^m ||x_i - v_k||^2, 1 \le m < \infty$$
(6)

where *m* is constant to control clustering fuzziness, generally m = 2.  $u_{ik}$  is the fuzzy membership of  $x_i$  in the cluster *k* and satisfying ①  $0 \le u_{ik} \le 1$ , ②  $\sum_{k=1}^{K} u_{ik} = 1$ .  $x_i$  is the *i*-th sample in measured data.  $v_k$  is the cluster center, and  $\|*\|$  is a distance measure. Fuzzy partitioning is carried out through an iterative optimization of the objective function shown above, with the update of membership  $u_{ik}$  and cluster centers  $v_k$  by:

$$u_{ik} = \frac{1}{\sum_{l=1}^{K} \left(\frac{|x_i - v_k||}{|x_i - v_l||}\right)^{2/(m-1)}}$$
(7)

$$v_{k} = \frac{\sum_{i=1}^{N} u_{ik}^{m} x_{i}}{\sum_{i=1}^{N} u_{ik}^{m}}$$
(8)

This iteration will stop when  $max \left\{ \left| u_{ik}^{(p)} - u_{ik}^{(p-1)} \right| \right\} \le \varepsilon$ ,  $\varepsilon$  is a termination criterion between 0 and 1, and *p* is the iteration step (Kannan et al., 2010). Although clustering algorithms do not require training data, they do require an initial segmentation (or equivalently, initial parameters). Clustering algorithms do not directly incorporate spatial modeling and can therefore be sensitive to noise and intensity inhomogeneities. This lack of spatial modeling, however, can provide significant advantages for fast computation (Hebert, 1997). Some work on improving the robustness of clustering algorithms to intensity inhomogeneities in MR images have been carried out (Pham & Prince, 1999). Robustness to noise can be incorporated with spatial correlations in an image based on k-nearest neighbor model (R. Xu & Ohya, 2010) or Markov random field (MRF) modeling (Liu et al., 2005).

#### 2.6 Statistical models

Statistical classification methods usually solve the segmentation problem by either assigning a class label to a pixel or by estimating the relative amounts of the various tissue types within a pixel (Noe et al., 2001). Statistical inference enables us to make statements about which element(s) of this set are likely to be the true ones.

#### 2.6.1 Expectation maximization (EM)

Expectation maximization (EM) algorithm (Dempster et al., 1977) is a method for finding the maximum likelihood or maximum a posteriori (MAP) estimator of a hidden parameter  $\theta$  with a probability distribution. EM is an iterative method which alternates between performing an expectation (E) step, in which each pixel is classified into one cluster according to the current estimates of the posterior distributions over hidden variables, and a maximization (M) step, in which the hidden parameters are re-estimated by maximizing the likelihood function, according to the current classification. These parameter-estimates are then used to determine the distribution over hidden variables in the next E step. Convergence is assured since the increase of likelihood after each iteration (Zaidi et al., 2006). The underlying model in EM algorithm can be specified according the specific requirements of the given task (Wells III et al., 1996; Y. Zhang et al., 2001). In spite of these achievements, they have a few deficiencies: a good prior distribution and the known number of classes are required, and it has extensive computations.

#### 2.6.2 Markov random field model (MRF)

Markov random field (S.Z. Li, 1995) model is a statistical model that can be used within segmentation methods. MRFs model spatial interactions among neighboring or nearby pixels. In medical imaging, they are typically used because most pixels belong to the same class as their neighboring pixels (Pham et al., 2000). Let a finite lattice *I* as a 2D image,  $i \in I$  is the pixel *i* in this image, which is denoted by  $Y = \{Y_i, i \in I\}$ , where  $Y_i$  is the gray value of pixel *i*. For each pixel, the region-type (or pixel class) that the pixel belongs to is specified by

a class label  $X = \{X_i, i \in I\}$  (i.e., image segmentation results).  $X_i \in \Lambda$ ,  $\Lambda = \{1, 2, ..., K\}$  is a set of labels and K is the number of classes. So X (label filed) and Y (gray field) will be random fields in lattice I and the purpose of MRF model is to establish the relationship between X and Y, then the image model is defined as:

$$Y_i = v_{X_i} + e_i, i \in I \tag{9}$$

where  $v_{X_i}$  is the gray mean value of class  $X_i$ , and  $e_i$  is a random variable meeting Gaussian distribution. If  $X_i = k, k \in \Lambda$ ,  $e_i - N(0, \sigma_k^2)$ , in which  $\sigma_k^2$  is the variance of  $e_i$  for k, then the conditional probability density is defined as:

$$P(Y_i = y_i \mid X_i = k) = \frac{1}{\sqrt{2\pi\sigma_k^2}} \exp[-\frac{(y_i - v_k)^2}{2\sigma_k^2}]$$
(10)

Subsequently,  $X = \{X_i, i \in I\}$ , the priori model of image segmentation results is a 2D MRF. According to Hammersley-Clifford theorem in (Hammersley & Clifford, 1971), the priori probability of MRF meets Gibbs distribution, and so the priori model is defined as:

$$P(X = x) = \frac{1}{Z} \exp[-\sum_{c \in C} V_c(x)]$$
(11)

where  $Z = \sum_{x \in \Lambda} \exp[-\sum_{c \in C} V_c(x)]$  is a normalizing constant called *partition function* and  $V_c(x)$  denotes the potential function of clique  $c \in C$ , which only depends on  $\delta(i)$ ,  $i \in c$ . *C* is the set of second order cliques (i.e. doubletons), and  $\delta(i)$  indicates the neighborhood of pixel *i*. If multi-level logistic (MLL) model is adopted and the second order neighborhood system and the dual potential function are only considered, energy function is defined as:

$$U(x) = \sum_{i \in I} \sum_{j \in \delta(i)} V(x_i, x_j)$$
(12)

$$V(x_i, x_j) = \begin{cases} -\beta, & \text{if } x_i = x_j \\ \beta, & \text{if } x_i \neq x_j \end{cases}$$
(13)

Note that the energies of singletons (i.e. pixel  $i \in I$ ) directly reflect the probabilistic modeling of labels without context, while doubleton clique potentials express relationship between neighboring pixel label. On the basis of maximum a posteriori (MAP) estimation (Geman & Geman, 1993) and Bayes' theorem, the optimal solution  $X = X^*$  is defined as:

$$X^{*} = \arg \max_{X} P(X \mid Y)$$
  
=  $\arg \max_{X} P(Y \mid X) P(X)$  (14)

In order to facilitate the solution, the objective function takes natural logarithm to be

$$X^* = \arg\min_{x \in \Lambda} \{ U(y \mid x; \theta) + U(x) \}$$
(15)

$$U(y \mid x; \theta) = \sum_{i \in I} U(y_i \mid x_i) = \sum_{i \in I} \left[ \frac{(y_i - v_k)}{2\sigma_k^2} + \frac{1}{2} \log(\sigma_k^2) \right]$$
(16)

$$\theta = \{ v_k, \sigma_k \mid k \in \Lambda \}$$
(17)

In this way, the segmentation problem in MRF model is reduced to the minimization of the above energy function, which is usually computed by iterated conditional modes (ICM) algorithm (Besag, 1986). The ICM method uses the 'greedy' strategy in the iterative local minimization and convergence is guaranteed after only a few iterations (Boudraa & Zaidi, 2006). By importing spatial relations among pixels, non-supervised and nonparametric MRF model can effectively decrease the influence of image noise, and undertake fine stable and satisfied segmentation results for low SNR images. This model has been widely applied in human cerebral cortical segmentation (Held et al., 1997; Y. Zhang et al., 2001). Contrarily a difficulty associated with MRF models is proper selection of the parameters controlling the strength of spatial interaction (S.Z. Li, 1995). A setting that is too high can result in an excessively smooth segmentation and a loss of important structural details. Some researchers have proposed several schemes for the estimation of MRF parameters (Descombes et al., 1999; Salzenstein & Pieczynski, 1997; R. Xu & Luo, 2009). In addition, MRF methods usually require computationally intensive algorithms (Pham et al., 2000).

#### 2.7 Artificial neural networks (ANNs)

Artificial neural networks (ANNs) are parallel networks of processing elements or nodes to simulate biological neural networks. Each node in an ANN is capable of performing elementary computations. Learning is achieved through the adaptation of weights assigned to the connections between nodes. The massive connectionist architecture usually makes the system robust while the parallel processing enables the system to produce output in real time. To simulate biological neural network, the neurons and connections in ANNs model comprise the following components and variables in Fig. 2 (Kriesel, 2007). A thorough treatment of ANNs can be found in (J.W. Clark, 1991).





The most widely application in medical imaging is as a classifier (Gelenbe et al., 1996; Hall et al., 1992), in which the weights are determined by training data and the ANN is then used to segment new data. ANNs can also be used in an unsupervised fashion as a clustering method (Bezdek et al., 1993; Reddick et al., 1997), as well as for deformable models (Vilarino et al., 1998). Because of the many interconnections used in a neural network, spatial information can be easily incorporated into its classification procedures (Pham et al., 2000). However, the major disadvantage of the artificial neural networks (ANNs) is that it requires training data. For large neural networks, it also requires high processing time because its processing is usually simulated on a standard serial computer.

#### 2.8 Deformable models

Deformable models are physically motivated, model-based techniques for detecting region boundaries by using closed parametric curves or surfaces that deform under the influence of internal and external forces. To delineate an object boundary in an image, a closed curve or surface must first be placed near the desired boundary and then be allowed to undergo an iterative relaxation process. Internal forces are computed from within the curve or surface to keep it smooth throughout the deformation. External forces are usually derived from the image to drive the curve or surface toward the desired feature of interest (Pham et al., 2000). The original deformable, called *snake* model, was introduced in (Kass et al., 1988), in which the contour deforms to minimize the contour energy that includes the internal energy from the contour and the external energy from the image. A number of improvements have also been proposed, such as snake variations (Cohen, 1991; McInerney & Terzopoulos, 2000; C. Xu & Prince, 1998). *Level set* is another important deformable contour method and it was firstly proposed for image segmentation in (Malladi et al., 1995). Some researchers applied level set formulation with a contour energy minimization for obtaining a better convergence (Siddiqi et al., 1998; Wang et al., 2004).

Deformable models are quite helpful for cerebral cortical segmentation in MR images (Davatzikos & Bryan, 1996; C. Xu et al., 1998). The advantages are that they are capable of generating closed parametric curves or surfaces from images and incorporating a smoothness constraint that provides robustness to noise and spurious edges. The disadvantage is that they require manual interaction to place an initial model and choose appropriate parameters. The successes in reducing sensitivity to initialization have been made in (Cohen, 1991; Malladi et al., 1995; C. Xu & Prince, 1998). Standard deformable models can also exhibit poor convergence to concave boundaries. This difficulty can be alleviated somewhat through the use of pressure forces (Cohen, 1991) and other modified external-force models (C. Xu & Prince, 1998). Another important extension of deformable models is the adaptivity of model topology by using an implicit representation rather than an explicit parameterization (Malladi et al., 1995; McInerney & Terzopoulos, 1995). Several general reviews on deformable models in medical image analysis can be found in (He et al., 2008; Heimann & Meinzer, 2009; McInerney & Terzopoulos, 1996; Suri, Liu, et al., 2002).

#### 2.9 Atlas-guided approaches

Atlas-guided approaches are a powerful tool for medical image segmentation when a standard atlas or template is available. The whole idea of using the brain atlas was to provide a priori knowledge, which can help in grouping the segments into anatomical

152

structures. This helps to obtain fully automatic cortical segmentation procedures. The standard atlas-guided approach treats segmentation as a registration problem. It first finds a one-to-one transformation that maps a pre-segmented atlas image to the target image. This process is often referred to as 'atlas warping'. The warping can be performed with linear transformations (Talairach & Tournoux, 1988), or nonlinear transformations (Collins et al., 1995; Davatzikos, 1996). Atlas-guided approaches have been applied mainly in brain MRI segmentation (Collins et al., 1995), as well as in extracting the brain volume from head scans (Aboutanos & Dawant, 1997). One advantage is that labels as well as the segmentation are transferred. They also provide a standard system for studying morphometric properties (Thompson & Toga, 1997). Atlas-guided approaches are generally better suited for segmentation of structures that are stable over the population of study. One method that helps model anatomical variability is to use probabilistic atlases (Thompson & Toga, 1997), but these require additional time and interaction to accumulate data. Another method is to use manually selected landmarks (Davatzikos, 1996) to constrain transformation.

#### 2.10 Other techniques

*Texture segmentation* is to segment an image into regions according to the textures of the regions. It was in the late 1970s when Haralick et al (Haralick et al., 1973) published an extensive paper on texture. Later, Peleg et al (Peleg et al., 1984) and Cross et al (Cross & Jain, 1983) also published work in texture analysis applied to computer vision images. Application of texture in brain segmentation started in the early 1990s, when Lachmann et al (Lachmann & Barillot, 1992) developed a method for the classification of WM, GM and CSF. This method, however, did not discuss the validation schemes, and it was hard to judge the performance of such a segmentation algorithm. Besides, it seemed sensitive to initial textural properties, and no such discussion was carried out in the paper (Suri, Singh, et al., 2002b).

*Self-organizing maps* (SOM), introduced by Kohonen in early 1981 (Kohonen, 1990), is a type of artificial neural network, whose precursor is *learning vector quantization* (LVQ) invented by T. Kohonen (Kohonen, 1997). It is able to convert complex, nonlinear statistical relationships between high-dimensional data items into simple geometric relationships on a low-dimensional display via using unsupervised learning. The applications of SOM method can be found in (Y. Li & Chi, 2005; Tian & Fan, 2007). However, SOM algorithms are, firstly, highly dependent on the training data representatives and the initialization of the connection weights. Secondly, they are very computationally expensive if the dimensions of the data increases (Y. Li & Chi, 2005).

*Wavelet transform*, adventured in medical imaging research in 1991 (Weaver et al., 1991), is a tool that cuts up data or functions or operators into different frequency components, and then studies each component with a resolution matched to its scale (Daubechies, 2004). Modern wavelet analysis was considered to be proposed by Grossmann and Morlet in their milestone paper (Morlet & Grossman, 1984). In medical image segmentation, wavelet transforms have been employed to combine texture analysis, edge detection, classifiers, statistical models, and deformable models, etc. Many works benefit through using image features within a spatial-frequency domain after wavelet transform to assist the segmentation (Barra & Boire, 2000; Bello, 1994).

*Multispectral segmentation* is a method for differentiating tissue classes having similar characteristics in a single imaging modality by using several independent images of the same anatomical slice in different modalities (e.g., T1, T2, proton density, etc.). As a consequence of different responses of the tissues to particular pulse sequences, this increases the capability of discrimination between different tissues (Fletcher et al., 1993; Vannier et al., 1985). The most common approach for multispectral MR image segmentation is pattern recognition (Bezdek et al., 1993; Suri, Singh, et al., 2002b). These techniques generally appear to be successful particularly for brain MR images (Reddick et al., 1997; Taxt & Lundervold, 1994), but much work remains in the area of validation.

#### 3. A new non-homogeneous Markov random field model

As we introduced in Section 2.6.2, Markov random field (MRF) theory (S.Z. Li, 1995) has been widely used in the field of medical image processing with the advantages, including non-supervision, fine stability and satisfied segmentation effect for the image with low SNR. MRF theory provides a convenient and consistent way for modeling context among image pixels. This is achieved through characterizing mutual influences among such entities using conditional MRF distributions. The practical use of MRF models is largely ascribed to the equivalence between MRF and Gibbs distributions established by Hamersley and Clifford (Hammersley & Clifford, 1971) and is further developed by Besag (Besag, 1974) for the joint distribution of MRF. This enables us to model vision problems by a mathematically sound yet tractable means for image segmentation in Bayesian framework (Geman & Geman, 1993; Grenander, 1983).

In traditional MRF model, Gibbs random field (GRF) uses the parameter  $\beta$  to determine spatial correlation among dependent image pixels. The greater the parameter  $\beta$  is, the stronger the spatial correlation would be; the smaller the parameter  $\beta$  is, the weaker the spatial correlation would be. Generally, MRF model is assumed to be homogeneous, which means the parameter  $\beta$  is constant. Plenty of previous researches have offered a series of methods to accurately estimate this parameter, which advance the effect of image segmentation (Deng & Clausi, 2004; Descombes et al., 1999). Due to its own features of medical image, homogeneous MRF model often leads to over-segmentation and induces higher misclassification rate. In this section, we propose a new non-homogeneous MRF model (called Modified-MRF or M-MRF model) using fuzzy membership to accurately estimate the parameter  $\beta$  and the experimental results show our model effectively reduces over-segmentation and enhances segmentation precision (R. Xu & Luo, 2009).

#### 3.1 Fuzzy sets

Fuzzy sets are sets whose elements have degrees of membership, which firstly were proposed by L.A. Zedeh in 1965 (Zadeh, 1965) as an extension of the classical notion of set. Classical set theory only describes precise phenomenon, because an element belonging to a classic set contains only two cases: yes or no. By contrast, fuzzy set theory permits the gradual assessment of the membership of elements in a set; this is described with the aid of a membership function valued in the real unit interval [0, 1]. Fuzzy sets generalize classical sets, since the indicator functions of classical sets are special cases of the membership functions of fuzzy sets, if the latter only take values 0 or 1 (DuBois & Prade, 1980).

154

The fuzzy set is defined as: Given a domain *X*, *x* denotes its element, the mapping  $u_F$  is defined as  $u_F : X \to [0,1]$ ,  $x \to u_F(x)$ , which means  $u_F$  confirms a fuzzy set *F* in domain *X*,  $u_F$  is called *F*'s membership function and  $u_F(x)$  is *x*'s membership for *F*. The greater the membership, the greater the degree of one element pertaining to one fuzzy set. As a consequence, *F* is a subset in domain *X*, which does not have undefined border.

#### 3.2 Modified non-homogeneous MRF model

In terms of the features in brain MR images, the spatial correlation of adjacent pixels varies with the positions of image space, which indicates the parameter  $\beta$  should be a variable changing with space site. Consequently, the corresponding MRF model should be considered as non-homogeneous.

#### 3.2.1 The $\beta$ Function based on fuzzy membership

Let *y* be the gray value of pixels, and *x* be the classification of pixels in image I. If pixel *i* is marked by class *k* ( $v_k$  is the clustering center of class *k*, k = 1, ..., K), the parameter  $\beta$  will be a decreasing function of  $u_{ik}$ , which denotes the membership of pixel *i* belonging to class *k*. The smaller the  $u_{ik}$  is, the less the degree of pixel *i* in class *k* would be, which implies the attribute of pixel *i* should be decided by the state of neighborhood. The larger the  $u_{ik}$  is, the larger the degree of pixel *i* in class *k* would be, which implies the attribute of pixel *i* in class *k* would be, which implies the larger the degree of pixel *i*. Thus, the  $\beta$  function is defined as:

$$\beta_i = 1 - 0.8 \cdot u_{ik} \tag{18}$$

#### 3.2.2 The modified MRF model (M-MRF model)

In traditional MRF model (see Section 2.6.2), the parameter  $\beta$  is used to calculate the *energy function* U(x) and *clique potentials*  $V_c(x)$  over all possible cliques  $c \in C$ , which only depends on the neighborhood of pixel *i*:  $\delta(i), i \in c$ . According to the  $\beta$  function, the energy function and clique potentials through considering multi-level logistic (MLL) model, second-order neighborhood system and dual potential function, can be modified as

$$U(x) = \sum_{i \in I} \sum_{j \in \delta(i)} V_c(x_i, x_j)$$

$$V(x_i, x_j) = \begin{cases} -\beta_i, & \text{if } x_i = x_j \\ \beta_i, & \text{if } x_i \neq x_j \end{cases}$$
(19)
$$(19)$$

And the new non-homogeneous MRF (M-MRF) model has been improved into

$$U(y \mid x) = \sum_{i \in I} U(y_i \mid x_i) = \sum_{i \in I} \left[ \frac{(y_i - v_k)^2}{2\sigma_k^2} + \frac{1}{2} \log(\sigma_k^2) \right]$$
(21)

Therefore, the segmentation problem is reduced to minimize the above energy function, which is generally solved by iterated conditional modes (ICM) algorithm (Besag, 1986). The algorithm of M-MRF model for image segmentation is designed as follows:

- 1. Initialize the number of class *K*, the clustering center  $v_k$ , the smallest error  $\varepsilon$ , and p = 0;
- 2. Get the initial segmentation results via KFCM algorithm (L. Zhang et al., 2002), and estimate the parameter  $\beta$  by Eq.(18);
- 3. Segment the initial image based on maximum-likelihood criterion and M-MRF model, and calculate the global energy *E* of whole image;
- 4. Calculate local conditional energy of every pixel for all possible classification by Eq.(19) and Eq.(21), and update the classification of every pixel following the principle of minimizing local conditional energy.
- 5. Calculate the global energy E of whole image again by the new classification of every pixel, p = p + 1;
- 6. if  $\max[|E^{(p)} E^{(p-1)}|] \le \varepsilon$ , then go to (7), else return (4);
- 7. Output image segmentation results and stop.

#### 3.2.3 Smoothing of image

Owing to complexity of brain MR images and their own reasons of segmentation algorithms, segmentation results are often accompanied by burrings, stains, rugged edges, etc. By smoothing, isolated burrings and stains of image can be removed, edges of regions can be smoothed and holes of areal objects can be filled. Sequentially, the quality of segmentation results can be further improved. In the processing of image smoothing, matrix template of  $n \times n(n)$  is customarily assigned by  $3\sim5$ ) is currently employed to march image via lines and columns. If the image matches successfully, the segmentation results around this pixel.

#### 3.2.3.1 Deburring

The 3 × 3 deburring matrix in (a) is frequently betaken, where  $a, b, x \in L, a \neq b(L \text{ is the set of labels})$  and 'x' is arbitrary which figures the segmentation results of x's sites can be left out of account. When the image segmentation results in 3 × 3 matrix march the deburring matrix in Fig. 3 (a), 'b' in the center of matrix will become 'a'.



Fig. 3. The matrix for deburring and smoothing. (a) the deburring matrices; (b) the matrix of smoothing of lines.

#### 3.2.3.2 Smoothing of lines and filling of holes

The methods of smoothing of lines and filling of holes are the same as that of deburring, just the matrices are different. The  $3 \times 3$  matrix of smoothing of lines in Fig. 3 (b) is utilized as a rule. In the same way, When the image segmentation results in  $3 \times 3$  matrix march the  $3 \times 3$  matrix in Fig. 3 (b), *'b'* in the center of matrix will become *'a'*.

#### 3.3 Experimental results

In order to verify the effect of M-MRF model in image segmentation, KFCM algorithm (L. Zhang et al., 2002), traditional MRF model (S.Z. Li, 1995) and M-MRF model are applied in the segmentation of simulated brain MR images. During the experiments, brain MR images are divided into four regions: gray matter (GM), white matter (WM), cerebrospinal fluid (CSF) and background (BG). All experiments are operated by VS.Net 2003 in PC of Intel® Core<sup>™</sup>2 CPU 6600 @ 2.40GHZ with 2GB memory.

The simulated brain MR images from Brainweb (http://www.bic.mni.mcgill.ca/brainweb/) are applied in the experiments, and we call them gold standard of image segmentation. Each data set is composed of  $258 \times 258$  pixels, thickness of layer is 1mm,  $T_1$  weighted. Herein, the lay images used in experiments are the Z = 16.5mm's ones of image sequences. Fig. 4 is a comparison of the segmentation results of several algorithms for a simulated brain MRI superposed 9% noise. The experimental results demonstrate that, even for images of lower signal-to-noise ratio (SNR), M-MRF model also achieves more satisfied segmentation results.







(b)











Fig. 4. A comparison of the segmentation results for several algorithms. (a) a simulated brain MR image; (b) a simulated brain MR image superposed 9% noise; (c) ground truth; (d) the results of KFCM method; (e) the results of MRF model; (f) the results of M-MRF model.

Table 1 presents MCRs of several algorithms for simulated brain MRIs superposed noise of distinct intensity in image segmentation (see the definition of MCR in Section 1.3), whose data are average segmentation results of 20 images. From table 1, MCRs of M-MRF model for all simulated brain MRIs are lower than other algorithms. In addition, segmentation effect of M-MRF model for simulated brain MRI superposed 7% and 9% noise is obviously better than other algorithms, while segmentation effect of M-MRF model for simulated brain MRI superposed 3% and 5% noise only has slight ascendancy compared with other algorithms. For this reason, the stronger the intensity of noise in image is, the better the segmentation performance of M-MRF model would be.

The intensity of noise(%)	3%	5%	7%	9%
MCRs of KFCM(%)	4.88	5.65	6.64	8.19
MCRs of MRF(%)	4.21	5.24	6.30	7.64
MCRs of M-MRF(%)	4.06	5.00	5.80	6.67

Table 1. MCRs (%) of images superposed noise of distinct intensity

In consideration of its own traits of brain MRIs, a new non-homogeneous MRF model (M-MRF model) is put forward for reducing over-segmentation, where the parameter  $\beta$  is estimated to an inch by fuzzy membership, so that the spatial relativities among each pixel will be reasonably set up. The experimental results prove our model not only inherits the superiorities of traditional MRF model, e.g., non-supervision, fine stability and satisfied robustness for image of low signal-to-noise ratio (SNR), but also significantly enhance the accuracy of image segmentation. Meanwhile, the algorithm of this new model is also simple and feasible and it is easy to be applied into clinical application by fusing de-bias field model.

#### 4. Image pre-processing

Due to the inherent technical limitations of the MR image process, uncertainties are inserted into MR images, including random noise, intensity inhomogeneity, and partial volume effect, etc. A more complete and comprehensive coverage of the contributing sources of error inherent in MR images can be found in (Plante & Turkstra, 1991). The image preprocessing techniques reviewed here mainly focus on reducing the detrimental effects of the artifacts mentioned for the purpose of applying segmentation methods.

It is difficult to remove noise from MR images, which is known to have a *Rician distribution* (Prima et al., 2001), and state-of-art methods in removing noise are substantial. Methods vary from standard filters to more advanced filters, from general methods to specific MR image de-noising methods, such as linear filtering, nonlinear filtering, adaptive filtering, anisotropic diffusion filtering, wavelet analysis, total variation regularization, bilateral filter, trilateral filtering, and non-local means models (NL-means), etc. A worthy survey of image de-noising algorithms can be seen in (Buades et al., 2006).

Intensity inhomogeneity (also called bias field, or shading artefact) in MRI, which arises from the imperfections of the image acquisition process, manifests itself as a smooth intensity variation across the image (Fig. 5). Because of this phenomenon, the intensity of the same tissue varies with the location of the tissue within the image. Although intensity inhomogeneity is usually hardly noticeable to a human observer, many medical image analysis methods, such as segmentation and registration, are highly sensitive to the spurious variations of image intensities. This is why a large number of methods for the correction of intensity inhomogeneity in MR images have been proposed in the past (Vovk et al., 2007). Early publications on MRI intensity inhomogeneity correction date back to 1986 (Haselgrove & Prammer, 1986; McVeigh et al., 1986). Since then, sources of intensity inhomogeneity in MRI have been studied extensively (Alecci et al., 2001; Keiper et al., 1998; Liang & Lauterbur, 2000; Simmons et al., 1994) and can be generally divided into two groups: prospective methods and retrospective methods. According to the classification proposed by U. Vovk (Vovk et al., 2007), we may further classify the prospective methods into those that are based on phantoms, multi-coils, and special sequences. The retrospective methods are further classified into filtering, surface fitting, segmentation-based, and histogram-based, etc. Additionally, several valuable reviews about this topic can be found in (Arnold et al., 2001; Belaroussi et al., 2006; Hou, 2006; Sled et al., 1997; Velthuizen et al., 1998; Vovk et al., 2007).



Fig. 5. Intensity inhomogeneity in MR brain image (Images provided courtesy of U. Vovk).

Partial volume effect (PVE) means artefacts that occur where multiple tissue types contribute to a single pixel, resulting in a blurring of intensity across boundaries, which is common in medical images, particularly for 3D MRI data. Fig. 6 illustrates how the sampling process can result in PVE, leading to ambiguities in structural definitions. In Fig. 6 (Right), it is difficult to precisely determine the boundaries of the two objects. The most common approach to addressing partial volume effect is to produce segmentations that allow regions or classes to overlap, called soft segmentations. Standard approaches use 'hard segmentations' that enforce a binary decision on whether a pixel is inside or outside the object. Soft segmentations, on the other hand, retain more information from the original image by allowing for uncertainty (such as membership for every pixel) in the location of object boundaries. Generally, membership functions can be derived by fuzzy clustering and classifier algorithms (Herndon et al., 1996; Pham & Prince, 1999) or statistical algorithms, in which case the membership functions are probability functions (Wells III et al., 1996), or can be computed as estimates of partial volume fractions (Choi et al., 1991). Soft segmentations based on membership functions can be easily converted to hard segmentations by assigning a pixel to its class with the highest membership value (Pham et al., 2000). The growing attention have been given to estimate partial volume effect in the last decade (Choi et al., 1991; Gage et al., 1992; Gonzalez Ballester et al., 2002; Roll et al., 1994; Soltanian-Zadeh et al., 1993; Thacker et al., 1998; Tohka et al., 2004).



Fig. 6. Illustration of partial volume effect. (Left) Ideal image; (Right) Acquired image (Images provided courtesy of D.L. Pham).

#### 5. Conclusion

A great number of medical image segmentation techniques have been used for analysis of MRI data of human brain, whose performance is affected by the characteristics of MRI data, which include a number of artifacts, such as random noise, intensity inhomogeneity and partial volume effect, etc. On the other hand, the inherent multispectral character of MRI gives it a distinct advantage over other imaging techniques. Many of the approaches described here explore ways to correct the artifacts in MRI and to fully exploit the multispectral character of this imaging modality. In this chapter, we have given a brief introduction to the fundamental concepts of these techniques, and presented our work on brain MR image segmentation, as well as a descripted the pre-processings such as denoising, the correction of intensity inhomogeneity and the estimation of partial volume effect.

www.intechopen.com

160

The future researches in the segmentation of human brain MRI will focus upon improving the accuracy, precision, and execution speed of segmentation methods, as well as reducing the amount of manual interaction. Accuracy and precision can be improved by incorporating prior information from atlases and by the fusion of different methods. For the sake of advancing execution efficiency, multi-scale processing, graphic processing unit (GPU) technique and parallelizable methods such as neural networks can be used promisingly. In order to raise the current acceptance of routine clinical applications for segmentation methods, extensive efficient validation is required. Furthermore, one must be able to demonstrate some significant performance advantage (e.g. more accurate diagnosis or earlier detection of pathology) over traditional methods to guarantee the less cost of training and equipment. It is impossible that automated methods will replace the physicians, but they are likely to become crucial elements in medical image analysis.

#### 6. Acknowledgment

Special thanks to go the group of Ohya Laboratory, Global Information and Telecommunication Studies (GITS), Waseda University, Japan, and the group of the Laboratory of Image Science and Technology (LIST), School of Computer Science and Engineering, Southeast University, China, for their contribution and discussion on various aspects and projects associated with image segmentation. The authors would like to thank the reviewers for their valuable suggestions for improving this manuscript.

#### 7. References

- Aboutanos, G.B. & Dawant, B.M. (1997). Automatic Brain Segmentation and Validation: Image-Based Versus Atlas-Based Deformable Models, *Processings of SPIE*, Vol.3034, pp.299, DOI: 10.1117/12.274098.
- Abras, G.N. & Ballarin, V.L. (2005). A Weighted K-Means Algorithm Applied to Brain Tissue Classification. *Journal of Computer Science & Technology*, Vol.5, No.3, pp.121-126.
- Alecci, M., Collins, C.M., Smith, M.B. & Jezzard, P. (2001). Radio Frequency Magnetic Field Mapping of a 3 Tesla Birdcage Coil: Experimental and Theoretical Dependence on Sample Properties. *Magnetic Resonance in Medicine*, Vol.46, No.2, pp.379-385, ISSN: 1522-2594.
- Arnold, J.B., Liow, J.S., Schaper, K.A., Stern, J.J., Sled, J.G., Shattuck, D.W., Worth, A.J., Cohen, M.S., Leahy, R.M. & Mazziotta, J.C. (2001). Qualitative and Quantitative Evaluation of Six Algorithms for Correcting Intensity Nonuniformity Effects. *NeuroImage*, Vol.13, No.5, pp.931-943, ISSN: 1053-8119.
- Babalola, K., Patenaude, B., Aljabar, P., Schnabel, J., Kennedy, D., Crum, W., Smith, S., Cootes, T., Jenkinson, M. & Rueckert, D. (2008). Comparison and Evaluation of Segmentation Techniques for Subcortical Structures in Brain MRI, *Processings of Medical Image Computing and Computer-Assisted Intervention (MICCAI' 2008)*, Vol.5241, pp.409-416, DOI: 10.1007/978-3-540-85988-8\_49.
- Balafar, M.A., Ramli, A.R., Saripan, M.I. & Mashohor, S. (2010). Review of Brain MRI Image Segmentation Methods. *Artificial Intelligence Review*, Vol.33, No.3, pp.261-274, ISSN: 0269-2821.

- Bankman, I.N. (2000). *Handbook of Medical Imaging: Processing and Analysis*, Academic Press, ISBN 0120777908.
- Barra, V. & Boire, J.Y. (2000). Tissue Segmentation on MR Images of the Brain by Possibilistic Clustering on a 3D Wavelet Representation. *Journal of Magnetic Resonance Imaging*, Vol.11, No.3, pp.267-278, ISSN: 1522-2586.
- Belaroussi, B., Milles, J., Carme, S., Zhu, Y.M. & Benoit-Cattin, H. (2006). Intensity Non-Uniformity Correction in MRI: Existing Methods and Their Validation. *Medical Image Analysis*, Vol.10, No.2, pp.234-246, ISSN: 1361-8415.
- Bello, M.G. (1994). A Combined Markov Random Field and Wave-Packet Transform-Based Approach for Image Segmentation. *IEEE Transactions on Image Processing*, Vol.3, No.6, pp.834-846, ISSN: 1057-7149.
- Besag, J. (1974). Spatial Interaction and the Statistical Analysis of Lattice Systems. *Journal of the Royal Statistical Society. Series B (Methodological)*, Vol.36, No.2, pp.192-236, ISSN: 0035-9246.
- Besag, J. (1986). On the Statistical Analysis of Dirty Pictures. *Journal of the Royal Statistical Society. Series B (Methodological)*, Vol.48, No.3, pp.259-302, ISSN: 0035-9246.
- Bezdek, J.C. (1981). Pattern Recognition with Fuzzy Objective Function Algorithms, Kluwer Academic Publishers, ISBN 0306406713.
- Bezdek, J.C., Hall, L.O. & Clarke, L.P. (1993). Review of MR Image Segmentation Techniques Using Pattern Recognition. *Medical Physics*, Vol.20, No.4, pp.1033-1048, ISSN: 0094-2405.
- Boudraa, A.O. & Zaidi, H. (2006). Image Segmentation Techniques in Nuclear Medicine Imaging. *Quantitative Analysis in Nuclear Medicine Imaging*, pp.308-357.
- Bradley, P.S. & Fayyad, U.M. (1998). Refining Initial Points for K-Means Clustering, Processings of the 15th International Conference on Machine Learing (ICML' 98), pp.91-99, Morgan Kaufmann, San Francisco, 1998.
- Brummer, M.E., Mersereau, R.M., Eisner, R.L. & Lewine, R.R.J. (1993). Automatic Detection of Brain Contours in MRI Data Sets. *IEEE Transactions on Medical Imaging*, Vol.12, No.2, pp.153-166, ISSN: 0278-0062.
- Buades, A., Coll, B. & Morel, J.M. (2006). A Review of Image Denoising Algorithms, with a New One. *Multiscale Modeling and Simulation*, Vol.4, No.2, pp.490-530, ISSN: 1540-3459.
- Choi, H.S., Haynor, D.R. & Kim, Y. (1991). Partial Volume Tissue Classification of Multichannel Magnetic Resonance Images-A Mixel Model. *IEEE Transactions on Medical Imaging*, Vol.10, No.3, pp.395-407, ISSN: 0278-0062.
- Clark, J.W. (1991). Neural Network Modelling. *Physics in Medicine and Biology*, Vol.36, pp.1259.
- Clark, M.C., Hall, L.O., Goldgof, D.B., Velthuizen, R., Murtagh, F.R. & Silbiger, M.S. (1998). Automatic Tumor Segmentation Using Knowledge-Based Techniques. *IEEE Transactions on Medical Imaging*, Vol.17, No.2, pp.187-201, ISSN: 0278-0062.
- Clarke, L.P., Velthuizen, R.P., Camacho, M.A., Heine, J.J., Vaidyanathan, M., Hall, L.O., Thatcher, R.W. & Silbiger, M.L. (1995). MRI Segmentation: Methods and Applications. *Magnetic Resonance Imaging*, Vol.13, No.3, pp.343-368, ISSN: 0730-725X.

- Cline, H.E., Dumoulin, C.L., Hart Jr, H.R., Lorensen, W.E. & Ludke, S. (1987). 3D Reconstruction of the Brain from Magnetic Resonance Images Using a Connectivity Algorithm. *Magnetic Resonance Imaging*, Vol.5, No.5, pp.345-352, ISSN: 0730-725X.
- Cohen, L.D. (1991). On Active Contour Models and Balloons. *CVGIP: Image understanding*, Vol.53, No.2, pp.211-218, ISSN: 1049-9660.
- Collins, D.L., Holmes, C.J., Peters, T.M. & Evans, A.C. (1995). Automatic 3-D Model-Based Neuroanatomical Segmentation. *Human Brain Mapping*, Vol.3, No.3, pp.190-208, ISSN: 1097-0193.
- Collins, D.L., Zijdenbos, A.P., Kollokian, V., Sled, J.G., Kabani, N.J., Holmes, C.J. & Evans, A.C. (1998). Design and Construction of a Realistic Digital Brain Phantom. *IEEE Transactions on Medical Imaging*, Vol.17, No.3, pp.463-468, ISSN: 0278-0062.
- Cross, G.R. & Jain, A.K. (1983). Markov Random Field Texture Models. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol.PAMI-5, No.1, pp.25-39, ISSN: 0162-8828.
- Damadian, R., Goldsmith, M. & Minkoff, L. (1977). NMR in Cancer: XVI. FONAR Image of the Live Human Body. *Physiological Chemistry and Physics*, Vol.9, No.1, pp.97-100, ISSN: 0031-9325.
- Daubechies, I. (2004). *Ten Lectures on Wavelets*, Society for Industrial and Applied Mathematics, ISBN 0898712742.
- Davatzikos, C. (1996). Spatial Normalization of 3D Brain Images Using Deformable Models. *Journal of Computer Assisted Tomography*, Vol.20, No.4, pp.656-665, ISSN: 0363-8715.
- Davatzikos, C. & Bryan, N. (1996). Using a Deformable Surface Model to Obtain a Shape Representation of the Cortex. *IEEE Transactions on Medical Imaging*, Vol.15, No.6, pp.785-795, ISSN: 0278-0062.
- Dempster, A.P., Laird, N.M. & Rubin, D.B. (1977). Maximum Likelihood from Incomplete Data Via the EM Algorithm. *Journal of the Royal Statistical Society. Series B* (*Methodological*), Vol.39, No.1, pp.1-38, ISSN: 0035-9246.
- Deng, H. & Clausi, D.A. (2004). Unsupervised Image Segmentation Using a Simple MRF Model with a New Implementation Scheme. *Pattern Recognition*, Vol.37, No.12, pp.2323-2335, ISSN: 0031-3203.
- Descombes, X., Morris, R.D., Zerubia, J. & Berthod, M. (1999). Estimation of Markov Random Field Prior Parameters Using Markov Chain Monte Carlo Maximum Likelihood. *IEEE Transactions on Medical Imaging*, Vol.8, No.7, pp.954-963, ISSN: 1057-7149.
- Dogdas, B., Shattuck, D.W. & Leahy, R.M. (2002). Segmentation of the Skull in 3D Human MR Images Using Mathematical Morphology, *Processings of SPIE*, Vol.4684, pp.1553-1562.
- Dubey, R.B., Hanmandlu, M. & Gupta, S.K. (2010). The Brain MR Image Segmentation Techniques and Use of Diagnostic Packages. *Academic Radiology*, Vol.17, No.5, pp.658-671, ISSN: 1076-6332.
- DuBois, D. & Prade, H.M. (1980). Fuzzy Sets and Systems: Theory and Applications, Academic Press, ISBN 0122227506, New York.
- Duda, R.O. & Hart, P.E. (1973). Pattern Classification and Scene Analysis, New York: Wiley.
- Dunn, J.C. (1973). A Fuzzy Relative of the Isodata Process and Its Use in Detecting Compact Well-Separated Clusters. *Cybernetics and Systems*, Vol.3, No.3, pp.32-57, ISSN: 0196-9722.

- Fisher, R.A. (1936). The Use of Multiple Measurements in Taxonomic Problems. *Annals of Human Genetics*, Vol.7, No.2, pp.179-188, ISSN: 1469-1809.
- Fletcher, L.M., Barsotti, J.B. & Hornak, J.P. (1993). A Multispectral Analysis of Brain Tissues. *Magnetic Resonance in Medicine*, Vol.29, No.5, pp.623-630, ISSN: 1522-2594.
- Fukunaga, K. (1990). Introduction to Statistical Pattern Recognition, Academic Press Professional, ISBN 0122698517.
- Gage, H.D., Santago II, P. & Snyder, W.E. (1992). Quantification of Brain Tissue through Incorporation of Partial Volume Effects, *Processings of SPIE*, Vol.1652, pp.84, DOI: 10.1117/12.59414.
- Gelenbe, E., Feng, Y. & Krishnan, K.R.R. (1996). Neural Network Methods for Volumetric Magnetic Resonance Imaging of the Human Brain. *Proceedings of the IEEE 1996*, Vol.84, No.10, pp.1488-1496, ISSN: 0018-9219.
- Geman, S. & Geman, D. (1993). Stochastic Relaxation, Gibbs Distributions and the Bayesian Restoration of Images\*. *Journal of Applied Statistics*, Vol.20, No.5, pp.25-62, ISSN: 0266-4763.
- Gonzalez Ballester, M.A., Zisserman, A.P. & Brady, M. (2002). Estimation of the Partial Volume Effect in MRI. *Medical Image Analysis*, Vol.6, No.4, pp.389-405, ISSN: 1361-8415.
- Gonzalez, R.C. & Woods, R.E. (1992). Digital Image Processing, Addison Wisley.
- Grau, V., Mewes, A.U.J., Alcaniz, M., Kikinis, R. & Warfield, S.K. (2004). Improved Watershed Transform for Medical Image Segmentation Using Prior Information. *IEEE Transactions on Medical Imaging*, Vol.23, No.4, pp.447-458, ISSN: 0278-0062.
- Grenander, U. (1983). Tutorials in Pattern Synthesis. Brown University, Division of Applied Mathematics.
- Grimson, W.E.L., Ettinger, G.J., Kapur, T., Leventon, M.E., Wells, W.M. & Kikinis, R. (1997). Utilizing Segmented MRI Data in Image-Guided Surgery. *International Journal of Pattern Recognition and Artificial Intelligence*, Vol.11, No.8, pp.1367-1397.
- Hall, L.O., Bensaid, A.M., Clarke, L.P., Velthuizen, R.P., Silbiger, M.S. & Bezdek, J.C. (1992). A Comparison of Neural Network and Fuzzy Clustering Techniques in Segmenting Magnetic Resonance Images of the Brain. *IEEE Transactions on Neural Networks*, Vol.3, No.5, pp.672-682, ISSN: 1045-9227.
- Hamamoto, Y., Fujimoto, Y. & Tomita, S. (1996). On the Estimation of a Covariance Matrix in Designing Parzen Classifiers. *Pattern Recognition*, Vol.29, No.10, pp.1751-1759, ISSN: 0031-3203.
- Hammersley, J.M. & Clifford, P. (1971). Markov Field on Finite Graphs and Lattices. Unpublished.
- Haralick, R.M., Shanmugam, K. & Dinstein, I. (1973). Textural Features for Image Classification. *IEEE Transactions on Systems, Man and Cybernetics*, Vol.3, No.6, pp.610-621, ISSN: 0018-9472.
- Haralick, R.M. & Shapiro, L.G. (1985). Image Segmentation Techniques. *Computer Vision, Graphics, and Image Processing*, Vol.29, No.1, pp.100-132, ISSN: 0734-189X.
- Haselgrove, J. & Prammer, M. (1986). An Algorithm for Compensation of Surface-Coil Images for Sensitivity of the Surface Coil. *Magnetic Resonance Imaging*, Vol.4, No.6, pp.469-472, ISSN: 0730-725X.
- He, L., Peng, Z., Everding, B., Wang, X., Han, C.Y., Weiss, K.L. & Wee, W.G. (2008). A Comparative Study of Deformable Contour Methods on Medical Image

Segmentation. *Image and Vision Computing*, Vol.26, No.2, pp.141-163, ISSN: 0262-8856.

- Hebert, T.J. (1997). Fast Iterative Segmentation of High Resolution Medical Images. *IEEE Transactions on Nuclear Science*, Vol.44, No.3, pp.1362-1367, ISSN: 0018-9499.
- Heimann, T. & Meinzer, H.P. (2009). Statistical Shape Models for 3D Medical Image Segmentation: A Review. *Medical Image Analysis*, Vol.13, No.4, pp.543-563, ISSN: 1361-8415.
- Held, K., Kops, E.R., Krause, B.J., Wells III, W.M., Kikinis, R. & Muller-Gartner, H.W. (1997). Markov Random Field Segmentation of Brain MR Images. *IEEE Transactions on Medical Imaging*, Vol.16, No.6, pp.878-886, ISSN: 0278-0062.
- Herndon, R.C., Lancaster, J.L., Toga, A.W. & Fox, P.T. (1996). Quantification of White Matter and Gray Matter Volumes from T1 Parametric Images Using Fuzzy Classifiers. *Journal of Magnetic Resonance Imaging*, Vol.6, No.3, pp.425-435, ISSN: 1522-2586.
- Hou, Z. (2006). A Review on Mr Image Intensity Inhomogeneity Correction. International Journal of Biomedical Imaging, Vol.2006, pp.1-11.
- Jain, A.K., Murty, M.N. & Flynn, P.J. (1999). Data Clustering: A Review. ACM Computing Surveys (CSUR), Vol.31, No.3, pp.264-323, ISSN: 0360-0300.
- Kannan, S.R., Ramathilagam, S., Sathya, A. & Pandiyarajan, R. (2010). Effective Fuzzy C-Means Based Kernel Function in Segmenting Medical Images. *Computers in Biology* and Medicine, Vol.40, No.6, pp.572-579, ISSN: 0010-4825.
- Kapur, T., Grimson, W.E.L., Kikinis, R. & Wells, W.M. (1998). Enhanced Spatial Priors for Segmentation of Magnetic Resonance Imagery. *Medical Image Computing and Computer-Assisted Interventation (MICCAI' 98)*, pp.457.
- Kass, M., Witkin, A. & Terzopoulos, D. (1988). Snakes: Active Contour Models. *International Journal of Computer Vision*, Vol.1, No.4, pp.321-331, ISSN: 0920-5691.
- Keiper, M.D., Grossman, R.I., Hirsch, J.A., Bolinger, L., Ott, I.L., Mannon, L.J., Langlotz, C.P. & Kolson, D.L. (1998). MR Identification of White Matter Abnormalities in Multiple Sclerosis: A Comparison between 1.5 T and 4 T. American Journal of Neuroradiology, Vol.19, No.8, pp.1489-1493.
- Khan, S.S. & Ahmad, A. (2004). Cluster Center Initialization Algorithm for K-Means Clustering. *Pattern Recognition Letters*, Vol.25, No.11, pp.1293-1302, ISSN: 0167-8655.
- Kikinis, R., Shenton, M.E., Iosifescu, D.V., McCarley, R.W., Saiviroonporn, P., Hokama, H.H., Robatino, A., Metcalf, D., Wible, C.G. & Portas, C.M. (1996). A Digital Brain Atlas for Surgical Planning, Model-Driven Segmentation, and Teaching. *IEEE Transactions on Visualization and Computer Graphics*, Vol.2, No.3, pp.232-241, ISSN: 1077-2626.
- Kohonen, T. (1990). The Self-Organizing Map. *Proceedings of the IEEE*, Vol.78, No.9, pp.1464-1480, ISSN: 0018-9219.
- Kohonen, T. (1997). Self-Organizing Maps. Springer, Berlin.
- Kriesel, D.: A Brief Introduction to Neural Networks, 2007, Available from: <a href="http://www.dkriesel.com/en/science/neural\_networks">http://www.dkriesel.com/en/science/neural\_networks</a>>.
- Kwan, R.K.S., Evans, A.C. & Pike, G.B. (1999). MRI Simulation-Based Evaluation of Image-Processing and Classification Methods. *IEEE Transactions on Medical Imaging*, Vol.18, No.11, pp.1085-1097, ISSN: 0278-0062.
- Lachmann, F. & Barillot, C. (1992). Brain Tissue Classification from MRI Data by Means of Texture Analysis, *Processings of SPIE*, Vol.1652, pp.72, DOI: 10.1117/12.59413.

- Li, S.Z. (1995). Markov Random Field Modeling in Image Analysis, Springer-Verlag, ISBN 1848002785, New York.
- Li, X., Li, L., Lu, H., Chen, D. & Liang, Z. (2003). Inhomogeneity Correction for Magnetic Resonance Images with Fuzzy C-Mean Algorithm, *Processings of SPIE*, Vol.5032, 2003.
- Li, Y. & Chi, Z. (2005). MR Brain Image Segmentation Based on Self-Organizing Map Network. *International Journal of Information Technology*, Vol.11, No.8, pp.45-53.
- Liang, Z.P. & Lauterbur, P.C. (2000). Principles of Magnetic Resonance Imaging: A Signal Processing Perspective, Wiley: IEEE press, ISBN 0780347234.
- Lim, K.O. & Pfefferbaum, A. (1989). Segmentation of MR Brain Images into Cerebrospinal Fluid Spaces, White and Gray Matter. *Journal of Computer Assisted Tomography*, Vol.13, No.4, pp.588-593, ISSN: 0363-8715.
- Liu, S., Li, X. & Li, Z. (2005). A New Image Segmentation Algorithm Based the Fusion of Markov Random Field and Fuzzy C-Means Clustering, *Processings of IEEE International Symposium on Communications and Information Technology* 2005 (ISCIT' 2005), pp.144-147.
- MacQueen, J.B. (1967). Some Methods for Classification and Analysis of Multivariate Observations, *Processings of Proceedings of the 5th Berkeley Symposium on Mathematical Statistics and Probability*, Vol.1, pp.281-297, Berkeley.
- Malladi, R., Sethian, J.A. & Vemuri, B.C. (1995). Shape Modeling with Front Propagation: A Level Set Approach. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol.17, No.2, pp.158-175, ISSN: 0162-8828.
- McInerney, T. & Terzopoulos, D. (1995). Topologically Adaptable Snakes, *Processings of the* 5th International Conference on Computer Vision 1995, pp.840-845, Cambridge, MA, USA
- McInerney, T. & Terzopoulos, D. (1996). Deformable Models in Medical Image Analysis: A Survey. *Medical Image Analysis*, Vol.1, No.2, pp.91-108, ISSN: 1361-8415.
- McInerney, T. & Terzopoulos, D. (2000). T-Snakes: Topology Adaptive Snakes. *Medical Image Analysis*, Vol.4, No.2, pp.73-91, ISSN: 1361-8415.
- McVeigh, E.R., Bronskill, M.J. & Henkelman, R.M. (1986). Phase and Sensitivity of Receiver Coils in Magnetic Resonance Imaging. *Medical Physics*, Vol.13, No.6, pp.806-814.
- Morlet, J. & Grossman, A. (1984). Decomposition of Hardy Functions into Square Integrable Wavelets of Constant Shape. *SIAM Journal on Mathematical Analysis*, Vol.15, No.4, pp.723-736.
- Mortazavi, D., Kouzani, A.Z. & Soltanian-Zadeh, H. (2011). Segmentation of Multiple Sclerosis Lesions in MR Images: A Review. *Neuroradiology*, pp.1-22, ISSN: 0028-3940.
- Noe, A., Kovacic, S. & Gee, J.C. (2001). Segmentation of Cerebral Mri Scans Using a Partial Volume Model, Shading Correction and an Anatomical Prior, *Processings of SPIE*, pp.1466-1477.
- Novelline, R.A. & Squire, L.F. (2004). *Squire's Fundamentals of Radiology*, Harvard Univ Press, ISBN 0674012798.
- Pal, N.R. & Pal, S.K. (1993). A Review on Image Segmentation Techniques. *Pattern Recognition*, Vol.26, No.9, pp.1277-1294, ISSN: 0031-3203.

- Peleg, S., Naor, J., Hartley, R. & Avnir, D. (1984). Multiple Resolution Texture Analysis and Classification. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol.PAMI-6, No.4, pp.518-523, ISSN: 0162-8828.
- Pham, D.L. & Prince, J.L. (1999). An Adaptive Fuzzy C-Means Algorithm for Image Segmentation in the Presence of Intensity Inhomogeneities. *Pattern Recognition Letters*, Vol.20, No.1, pp.57-68, ISSN: 0167-8655.
- Pham, D.L., Xu, C. & Prince, J.L. (2000). Current Methods in Medical Image Segmentation. *Annual Review of Biomedical Engineering*, Vol.2, No.1, pp.315-337, ISSN: 1523-9829.
- Plante, E. & Turkstra, L. (1991). Sources of Error in the Quantitative Analysis of MRI Scans. *Magnetic Resonance Imaging*, Vol.9, No.4, pp.589-595, ISSN: 0730-725X.
- Prima, S., Ayache, N., Barrick, T. & Roberts, N. (2001). Maximum Likelihood Estimation of the Bias Field in MR Brain Images: Investigating Different Modelings of the Imaging Process, Processings of Medical Image Computing and Computer-Assisted Intervention (MICCAI' 2001), Vol.2208, pp.811-819, DOI: 10.1007/3-540-45468-3\_97.
- Reddick, W.E., Glass, J.O., Cook, E.N., Elkin, T.D. & Deaton, R.J. (1997). Automated Segmentation and Classification of Multispectral Magnetic Resonance Images of Brain Using Artificial Neural Networks. *IEEE Transactions on Medical Imaging*, Vol.16, No.6, pp.911-918, ISSN: 0278-0062.
- Roland, P.E., Graufelds, C.J., Wahlin, J., Ingelman, L., Andersson, M., Ledberg, A., Pedersen, J., Akerman, S., Dabringhaus, A. & Zilles, K. (1993). Human Brain Atlas: For High-Resolution Functional and Anatomical Mapping. *Human Brain Mapping*, Vol.1, No.3, pp.173-184, ISSN: 1097-0193.
- Roll, S.A., Colchester, A.C.F., Summers, P.E. & Griffin, L.D. (1994). Intensity-Based Object Extraction from 3D Medical Images Including a Correction for Partial Volume Errors, *Processings of the 5th British Machine Vision Conference (BMVC' 94)*, Vol.94, pp.205-214, Guildford, UK.
- Ruan, S., Jaggi, C., Xue, J., Fadili, J. & Bloyet, D. (2000). Brain Tissue Classification of Magnetic Resonance Images Using Partial Volume Modeling. *IEEE Transactions on Medical Imaging*, Vol.19, No.12, pp.1179-1187, ISSN: 0278-0062.
- Rusinek, H., De Leon, M.J., George, A.E., Stylopoulos, L.A., Chandra, R., Smith, G., Rand, T., Mourino, M. & Kowalski, H. (1991). Alzheimer Disease: Measuring Loss of Cerebral Gray Matter with MR Imaging. *Radiology*, Vol.178, No.1, pp.109-114, ISSN: 0033-8419.
- Saeed, N. (1998). Magnetic Resonance Image Segmentation Using Pattern Recognition, and Applied to Image Registration and Quantitation. NMR in Biomedicine, Vol.11, No.4-5, pp.157-167, ISSN: 1099-1492.
- Salzenstein, F. & Pieczynski, W. (1997). Parameter Estimation in Hidden Fuzzy Markov Random Fields and Image Segmentation. *Graphical Models and Image Processing*, Vol.59, No.4, pp.205-220, ISSN: 1077-3169.
- Shen, S., Sandham, W., Granat, M. & Sterr, A. (2005). MRI Fuzzy Segmentation of Brain Tissue Using Neighborhood Attraction with Neural-Network Optimization. *IEEE Transactions on Information Technology in Biomedicine*, Vol.9, No.3, pp.459-467, ISSN: 1089-7771.
- Siddiqi, K., Lauziere, Y.B., Tannenbaum, A. & Zucker, S.W. (1998). Area and Length Minimizing Flows for Shape Segmentation. *IEEE Transactions on Image Processing*, Vol.7, No.3, pp.433-443, ISSN: 1057-7149.

- Simmons, A., Tofts, P.S., Barker, G.J. & Arridge, S.R. (1994). Sources of Intensity Nonuniformity in Spin Echo Images at 1.5 T. *Magnetic Resonance in Medicine*, Vol.32, No.1, pp.121-128, ISSN: 1522-2594.
- Skurichina, M. & Duin, R.P.W. (1996). Stabilizing Classifiers for Very Small Sample Sizes, Processings of the 13th International Conference on Pattern Recognition, Vol.2, pp.891-896, 1996.
- Sled, J., Zijdenbos, A. & Evans, A. (1997). A Comparison of Retrospective Intensity Non-Uniformity Correction Methods for MRI, *Processings of Information Processing in Medical Imaging*, Vol.1230, pp.459-464, Springer, DOI: 10.1007/3-540-63046-5\_43.
- Soltanian-Zadeh, H., Windham, J.P. & Yagle, A.E. (1993). Optimal Transformation for Correcting Partial Volume Averaging Effects in Magnetic Resonance Imaging. *IEEE Transactions on Nuclear Science*, Vol.40, No.4, pp.1204-1212, ISSN: 0018-9499.
- Suri, J.S., Liu, K., Singh, S., Laxminarayan, S.N., Zeng, X. & Reden, L. (2002). Shape Recovery Algorithms Using Level Sets in 2-D/3-D Medical Imagery: A State-of-the-Art Review. *IEEE Transactions on Information Technology in Biomedicine*, Vol.6, No.1, pp.8-28, ISSN: 1089-7771.
- Suri, J.S., Singh, S. & Reden, L. (2002a). Fusion of Region and Boundary/Surface-Based Computer Vision and Pattern Recognition Techniques for 2-D and 3-D MR Cerebral Cortical Segmentation (Part-II): A State-of-the-Art Review. *Pattern Analysis* & Applications, Vol.5, No.1, pp.77-98, ISSN: 1433-7541.
- Suri, J.S., Singh, S. & Reden, L. (2002b). Computer Vision and Pattern Recognition Techniques for 2-D and 3-D Mr Cerebral Cortical Segmentation (Part I): A State-ofthe-Art Review. *Pattern Analysis & Applications*, Vol.5, No.1, pp.46-76, ISSN: 1433-7541.
- Suzuki, H. & Toriwaki, J. (1991). Automatic Segmentation of Head MRI Images by Knowledge Guided Thresholding. *Computerized Medical Imaging and Graphics*, Vol.15, No.4, pp.233-240, ISSN: 0895-6111.
- Talairach, J. & Tournoux, P. (1988). Co-Planar Stereotaxic Atlas of the Human Brain: 3-Dimensional Proportional System: An Approach to Cerebral Imaging, Thieme, ISBN 0865772932.
- Tang, H., Wu, E.X., Ma, Q.Y., Gallagher, D., Perera, G.M. & Zhuang, T. (2000). MRI Brain Image Segmentation by Multi-Resolution Edge Detection and Region Selection. *Computerized Medical Imaging and Graphics*, Vol.24, No.6, pp.349-357, ISSN: 0895-6111.
- Taxt, T. & Lundervold, A. (1994). Multispectral Analysis of the Brain Using Magnetic Resonance Imaging. *IEEE Transactions on Medical Imaging*, Vol.13, No.3, pp.470-481, ISSN: 0278-0062.
- Thacker, N., Jackson, A., Zhu, X.P. & Li, K.L. (1998). Accuracy of Tissue Volume Estimation in NMR Images, *Processings of MIUA*' 98, Leeds, UK.
- Thompson, P.M. & Toga, A.W. (1997). Detection, Visualization and Animation of Abnormal Anatomic Structure with a Deformable Probabilistic Brain Atlas Based on Random Vector Field Transformations. *Medical Image Analysis*, Vol.1, No.4, pp.271-294, ISSN: 1361-8415.
- Tian, D. & Fan, L. (2007). A Brain MR Images Segmentation Method Based on SOM Neural Network, *Processings of The 1st International Conference on ICBBE*' 2007, pp.686-689, Wuhan.

- Tohka, J., Zijdenbos, A. & Evans, A. (2004). Fast and Robust Parameter Estimation for Statistical Partial Volume Models in Brain MRI. *NeuroImage*, Vol.23, No.1, pp.84-97, ISSN: 1053-8119.
- Udupa, J.K., Wei, L., Samarasekera, S., Miki, Y., Van Buchem, M.A. & Grossman, R.I. (1997). Multiple Sclerosis Lesion Quantification Using Fuzzy-Connectedness Principles. *IEEE Transactions on Medical Imaging*, Vol.16, No.5, pp.598-609, ISSN: 0278-0062.
- Vaidyanathan, M., Clarke, L.P., Hall, L.O., Heidtman, C., Velthuizen, R., Gosche, K., Phuphanich, S., Wagner, H., Greenberg, H. & Silbiger, M.L. (1997). Monitoring Brain Tumor Response to Therapy Using MRI Segmentation. *Magnetic Resonance Imaging*, Vol.15, No.3, pp.323-334, ISSN: 0730-725X.
- Vannier, M.W., Butterfield, R.L., Jordan, D., Murphy, W.A., Levitt, R.G. & Gado, M. (1985). Multispectral Analysis of Magnetic Resonance Images. *Radiology*, Vol.154, No.1, pp.221-224, ISSN: 0033-8419.
- Vapnik, V.N. (1998). *Statistical Learning Theory*, Wiley-Interscience, ISBN 0471030031, New York.
- Velthuizen, R.P., Heine, J.J., Cantor, A.B., Lin, H., Fletcher, L.M. & Clarke, L.P. (1998). Review and Evaluation of MRI Nonuniformity Corrections for Brain Tumor Response Measurements. *Medical physics*, Vol.25, pp.1655.
- Vemuri, B., Rahman, S. & Li, J. (1995). Multiresolution Adaptive K-Means Algorithm for Segmentation of Brain MRI. *Image Analysis Applications and Computer Graphics*, Vol.1024, pp.347-354.
- Vilarino, D.L., Brea, V.M., Cabello, D. & Pardo, J.M. (1998). Discrete-Time CNN for Image Segmentation by Active Contours. *Pattern Recognition Letters*, Vol.19, No.8, pp.721-734, ISSN: 0167-8655.
- Vovk, U., Pernus, F. & Likar, B. (2007). A Review of Methods for Correction of Intensity Inhomogeneity in MRI. *IEEE Transactions on Medical Imaging*, Vol.26, No.3, pp.405-421, ISSN: 0278-0062.
- Wang, X., He, L. & Wee, W. (2004). Deformable Contour Method: A Constrained Optimization Approach. *International Journal of Computer Vision*, Vol.59, No.1, pp.87-108, ISSN: 0920-5691.
- Weaver, J.B., Xu, Y., Healy Jr, D.M. & Cromwell, L.D. (1991). Filtering Noise from Images with Wavelet Transforms. *Magnetic Resonance in Medicine*, Vol.21, No.2, pp.288-295, ISSN: 1522-2594.
- Wells III, W.M., Grimson, W.E.L., Kikinis, R. & Jolesz, F.A. (1996). Adaptive Segmentation of Mri Data. *IEEE Transactions on Medical Imaging*, Vol.15, No.4, pp.429-442, ISSN: 0278-0062.
- Xu, C., Pham, D.L., Prince, J.L., Etemad, M.E. & Yu, D.N. (1998). Reconstruction of the Central Layer of the Human Cerebral Cortex from MR Images, *Processings of Medical Image Computing and Computer-Assisted Interventation (MICCAI' 98)*, Vol.1496/1998, pp.481-488, DOI: 10.1007/BFb0056233.
- Xu, C. & Prince, J.L. (1998). Snakes, Shapes, and Gradient Vector Flow. *IEEE Transactions on Image Processing*, Vol.7, No.3, pp.359-369, ISSN: 1057-7149.
- Xu, R. & Luo, L.M. (2009). A New Nonhomogeneous Markov Random Field Model Based on Fuzzy Membership for Brain MRI Segmentation, *Processings of SPIE*, Vol.7497, pp.74972F, Yichang, China, DOI: 10.1117/12.832160.

- Xu, R. & Ohya, J. (2010). An Improved Kernel-Based Fuzzy C-Means Algorithm with Spatial Information for Brain MR Image Segmentation, Processings of 25th International Conference of Image and Vision Computing New Zealand (IVCNZ' 2010), Queenstown, New Zealand.
- Zadeh, L.A. (1965). Fuzzy Sets. Information and Control, Vol.8, No.3, pp.338-353, ISSN: 0019-9958.
- Zaidi, H., Ruest, T., Schoenahl, F. & Montandon, M.L. (2006). Comparative Assessment of Statistical Brain MR Image Segmentation Algorithms and Their Impact on Partial Volume Correction in PET. *NeuroImage*, Vol.32, No.4, pp.1591-1607, ISSN: 1053-8119.
- Zhang, H., Fritts, J.E. & Goldman, S.A. (2008). Image Segmentation Evaluation: A Survey of Unsupervised Methods. *Computer Vision and Image Understanding*, Vol.110, No.2, pp.260-280, ISSN: 1077-3142.
- Zhang, L., Zhou, W.D. & Jiao, L.C. (2002). Kernel Clustering Algorithm. *Chinese Journal of Computers*, Vol.25, No.6, pp.587-590, ISSN: 0254-4164.
- Zhang, Y., Brady, M. & Smith, S. (2001). Segmentation of Brain MR Images through a Hidden Markov Random Field Model and the Expectation-Maximization Algorithm. *IEEE Transactions on Medical Imaging*, Vol.20, No.1, pp.45-57, ISSN: 0278-0062.
- Zhang, Y.J. (1996). A Survey on Evaluation Methods for Image Segmentation. *Pattern Recognition*, Vol.29, No.8, pp.1335-1346, ISSN: 0031-3203.
- Zhang, Y.J. (2001). A Review of Recent Evaluation Methods for Image Segmentation, Processings of the Sixth International Symposium on Signal Processing and its Applications 2001, Vol.1, pp.148-151, Kuala Lumpur.
- Zijdenbos, A.P. & Dawant, B.M. (1994). Brain Segmentation and White Matter Lesion Detection in MR Images. *Critical Review in Biomedical Engineering*, Vol.22, No.5-6, pp.401-465.
- Zucker, S.W. (1976). Region Growing: Childhood and Adolescence. *Computer Graphics and Image Processing*, Vol.5, No.3, pp.382-399, ISSN: 0146-664X.





Advances in Brain Imaging Edited by Dr. Vikas Chaudhary

ISBN 978-953-307-955-4 Hard cover, 264 pages **Publisher** InTech **Published online** 01, February, 2012 **Published in print edition** February, 2012

Remarkable advances in medical diagnostic imaging have been made during the past few decades. The development of new imaging techniques and continuous improvements in the display of digital images have opened new horizons in the study of brain anatomy and pathology. The field of brain imaging has now become a fast-moving, demanding and exciting multidisciplinary activity. I hope that this textbook will be useful to students and clinicians in the field of neuroscience, in understanding the fundamentals of advances in brain imaging.

#### How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Rong Xu, Limin Luo and Jun Ohya (2012). Segmentation of Brain MRI, Advances in Brain Imaging, Dr. Vikas Chaudhary (Ed.), ISBN: 978-953-307-955-4, InTech, Available from: http://www.intechopen.com/books/advances-in-brain-imaging/segmentation-of-brain-mri

## Open science | open minds

#### InTech Europe

University Campus STeP Ri Slavka Krautzeka 83/A 51000 Rijeka, Croatia Phone: +385 (51) 770 447 Fax: +385 (51) 686 166 www.intechopen.com

#### InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai No.65, Yan An Road (West), Shanghai, 200040, China 中国上海市延安西路65号上海国际贵都大饭店办公楼405单元 Phone: +86-21-62489820 Fax: +86-21-62489821 © 2012 The Author(s). Licensee IntechOpen. This is an open access article distributed under the terms of the <u>Creative Commons Attribution 3.0</u> <u>License</u>, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

# IntechOpen

# IntechOpen