We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists



186,000

200M



Our authors are among the

TOP 1% most cited scientists





WEB OF SCIENCE

Selection of our books indexed in the Book Citation Index in Web of Science™ Core Collection (BKCI)

### Interested in publishing with us? Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected. For more information visit www.intechopen.com



Chapter

## CO<sub>2</sub> Capture for Industries by Algae

Vetrivel Anguselvi, Reginald Ebhin Masto, Ashis Mukherjee and Pradeep Kumar Singh

#### Abstract

The increased usage of fossil fuels has led to increase in the concentration of  $CO_2$ , which is a greenhouse gas responsible for global warming. Algae-based  $CO_2$ conversion is a cost-effective option for reducing carbon footprint. In addition, algae-based  $CO_2$  mitigation strategy has the potential to obtain valuable products at the end of the process. In the present study, freshwater algal species were isolated and identified for CO<sub>2</sub> capture, such as *Hydrodictyon*, *Spirogyra*, *Oscillatoria*, Oedogonium, and Chlorella. The algal strains were screened based on different parameters like fast growth rate, high rate of photosynthesis, strong tolerance to the trace constituents of other gases (gaseous hydrocarbons, NOx, SOx, etc.), high temperature tolerance, and possibility to produce high value products, etc. The study involves integrated methods for utilizing 90-99% CO<sub>2</sub> from a natural gas processing industry (GAIL India, Ltd.) as well as 13-15% of CO<sub>2</sub> from flue gas of thermal power plants (Chandrapura and Santaldih Thermal Power Station) as carbon nutrient source along with the additional nutritional supplements. A 400-ml and 25-l flat panel photo-bioreactor (PSI Photo-bioreactors) was used for CO<sub>2</sub> capture. After CO<sub>2</sub> capture, the algal biomass was used to extract value-added products such as amino acid rich feed, algal oil, algal pellets, etc.

**Keywords:** algae, CO<sub>2</sub>, flue gas, capture, petrochemical industries, thermal power station

#### 1. Introduction

Greenhouse gas emissions by industries and human activities make the planet warmer.  $CO_2$  emitting industries are contributing a major role in the increase of greenhouse gases in the atmosphere for several decades. The largest source of greenhouse gas emissions from human activities in the world is burning fossil fuels for electricity, heat, transportation, and domestic uses. Carbon sequestration, capturing, and storing carbon emitted from the global energy system could be a major tool for reducing atmospheric  $CO_2$  concentration. The conventional  $CO_2$  sequestration processes like geological sequestration are highly power intensive and therefore expensive. While chemical and physical means exist to capture  $CO_2$  from smoke stack emissions, the cost of utilizing these technologies would result in a significant increase in the cost of power. The need for  $CO_2$  management, in particular capture and storage, is currently an important technological, economical, and global issue and will continue to be so until alternative energy sources diminish the need for fossil fuels. As microalgae grow in aqueous environments, directly passing  $CO_2$ -rich gases through this medium is a very efficient way of capturing the  $CO_2$  in those streams.

Algae-based carbon di-oxide (CO<sub>2</sub>) sequestration has gained more interest due to its capability to utilize  $CO_2$  as carbon source, higher photosynthetic efficiency, high  $CO_2$  fixation capacities and optimal culture condition, higher growth rates than conventional crop plants and biomass produced can be used as a feedstock for other value added products such as biofuel and chemicals [1]. In recent years, cultivation of microalgae has received renewed attention on account of its possibility as a feasible CO<sub>2</sub> sequestration technology. Under phototrophic growth conditions, microalgae absorb solar energy, and assimilate CO<sub>2</sub> from air and nutrients from aquatic habitats. One kilogram of algal dry cell weight utilizes around 1.83 kg of CO<sub>2</sub>. As per the available literature, an area of 1 Acre ( $4000 \text{ m}^2$ ) shall be able to capture about 2.7 tons/day of  $CO_2$  [2]. Algae are receiving wide attention as a source of biomass protein for use in animal feeds and foods [3, 4]. In addition, algae-based CO<sub>2</sub> mitigation strategy has the potential to obtain valuable products from the algal biomass that can be used to generate revenues, thereby making this route feasible. This route could also provide solutions to another major problem viz. high dependency on fossil fuels.

As microalgae grow in aqueous environments, directly passing  $CO_2$ -rich gases through this medium is a very efficient way of capturing the  $CO_2$  in those streams. Algae-based  $CO_2$  conversion offers a cost-effective option toward reducing our carbon footprint. In addition, algae-based  $CO_2$  mitigation strategy has the potential to obtain valuable products at the end of the process. Thus, any value addition achieved through such route could also provide solutions to the other major problem viz. high dependency on fossil fuels. Microalgae utilize  $CO_2$  for photosynthesis. Algae-based  $CO_2$  capture is one of the viable options for anthropogenic  $CO_2$  conversion. While microalgal cultivation is expensive, microalgae biomass can be utilized to produce a variety of high value commercial products (algal fuel, protein-rich algal food, animal feed, algae-based medicines, etc.) that can be used to generate revenues, thereby making this route feasible.

At present, more number of researches work is in progress globally to develop and commercialize algae-based carbon conversion technology. Large companies of United States such as Duke Energy, the third largest electric power holding company, are working on various aspects of carbon conversion technology. Government policies, especially in the US and Europe, are also supporting the growth of algaebased carbon conversion technologies. If the challenges associated with algae-based carbon capture technology are addressed successfully, the technology will present a solution not only to the global warming problem, but also to reduce the fossil fuel demand.

### 2. Experimental study on CO<sub>2</sub> capture for petrochemical industry and thermal power plants

#### 2.1 Isolation, identification, and selection of the high CO<sub>2</sub>-tolerant algal strains

In the present study, freshwater algal species were isolated and identified for CO<sub>2</sub> capture, such as *Hydrodictyon*, *Spirogyra*, *Oscillatoria*, *Oedogonium* and *Chlorella* from freshwater taken from pond in the coal mining area of Dhanbad, Jharkhand, India. The blue-green microalgae, *Oscillatoria*, were used for CO<sub>2</sub> capture study. The stock culture and inoculum were grown in BG11 medium [3] in the required condition. The inoculum was pre-cultured aseptically in 500-ml Erlenmeyer flasks with 200 ml of



**Figure 1.** *Scanning electron micrograph of the filament of Oscillatoria.* 

BG11 medium. The flasks were placed in a 28°C illuminated incubator for 7 days under a 12-h light/12-h dark photoperiod and a light density of 40  $\mu$ E m<sup>-2</sup> s<sup>-1</sup>. The BG-11 medium was used for algal culture with the composition of (g/L): K<sub>2</sub>HPO<sub>4</sub>.3H<sub>2</sub>O 0.04, NaNO<sub>3</sub> 1.5, CaCl<sub>2</sub>.2H<sub>2</sub>O 0.036, MgSO<sub>4</sub>.7H<sub>2</sub>O 0.075, ferric ammonium citrate 0.006, Na<sub>2</sub>EDTA 0.001, citric acid 0.006, Na<sub>2</sub>CO<sub>3</sub> 0.02, pH 7.0. B The identification was done on the basis of the morphological characters of the algae (**Figure 1**).

#### 2.2 Optimization of process parameters for CO<sub>2</sub> conversion

After pre-cultivation, the algal inoculum reached exponential growth phase. One gram of the algal inoculum was collected using centrifugation (4000×g, 4°C, 15 min). The collected algal cells were washed twice with sterile distilled water, and then inoculated into the growth medium. Microalgae growth and composition are affected by several process parameters. Different process parameters were optimized such as pH, light and temperature, nutrient media, culture condition, inoculum volume, inoculum concentration, etc.

#### 2.3 CO<sub>2</sub> capture in photo-bioreactor

Exhaust gas from natural gas processing industry and thermal power plants were collected and analyzed for its composition (**Tables 1** and **2**) (Gas analyzer and GC). Selected species of microalgae were inoculated in a bioreactor and studied for  $CO_2$  capture. Further, a novel "fibrous matrix photo-bioreactor" designed and used for algal culture and  $CO_2$  capture. Novel bioreactor designed and used in the process is having in-built organic fibrous matrix for support of the filamentous algae growth, rapid proliferation, and easy recovery (**Figure 2**).

S. no	Test parameter	Unit	Result
1	Nitrogen	Mole %	0.20
2	Methane	Mole %	0.71
3	Ethane	Mole %	0.20
4	Hydrogen sulfide	ppm	60
5	Amine content	ppm	ND
6	Moisture content	Mole %	1.50
7	Carbon dioxide	Mole %	97.384

**Table 1.**Composition of exhaust gas from natural gas processing industry, GAIL (PATA).

Gas	Santaldih TPS	Chandrapura TPS
		Amount (%)
CO <sub>2</sub>	11.93	10–12
O <sub>2</sub>	3.96	4–6
SO <sub>2</sub>	0.99	Trace
NO <sub>2</sub>	0.99	Trace
N <sub>2</sub>	82.13	85

#### Table 2.

Composition of exhaust gas from thermal power plants.



**Figure 2.** *Light microscope photo of a filament of Oscillatoria.* 

CO<sub>2</sub> Capture for Industries by Algae DOI: http://dx.doi.org/10.5772/intechopen.81800



**Figure 3.** *CO*<sub>2</sub> capture and algal fuel production from lab to pilot scale: Facilities at CSIR-CIMFR.

Pigment estimation, protein content, and fatty acid determination were carried out at 5 days interval to determine the growth and subsequently to compare the tolerance of the algal species. The experiment was carried out in flat panel photo-bioreactor (**Figure 3**), which contained 15 l of algal media. Injection of CO<sub>2</sub> rich gas was carried out at a rate of 500 ml/30 min continuously for 48 h. Determination of pH was undertaken at 3 h interval and pigment estimation was carried out at 24, 36, and 48 h intervals.

#### 3. Results and discussion

*Oscillatoria* is a filamentous blue-green algae with uniserially arranged cells that are not constricted at the cross walls (**Figure 1**). The straight, unbranched, filaments are dark blue-green, covered with a thin hyaline sheath and is not attenuated or capitated at the end. This unbranched filamentous alga occurs singly or in tangled mats. Terminal cells are hemispherical with a slightly thickened membrane on the outer cell envelope (**Figure 4**, Geitler [5]). *Oscillatoria* is common in freshwater environments, including hot springs. It has more than 100 species.

The growth pattern showed that the lag phase of *Oscillatoria* was from 0 to 24 h, exponential phase from 24 to 36 h, the stationary phase from 36 to 60 h and then the decline phase (**Figure 5**).

Growth of algae, in general, depends upon the availability of nitrogen and phosphate (**Table 3**). The increased nutrients result in higher growth and higher biomass of cyanobacteria. Phosphorus was reported to be an essential element for pigment development. Algae are known to assimilate phosphorus in excess of their requirements. The algae (*Oscillatoria*) could not survive in water to which urea was added. Sodium and potassium containing salts along with orthophosphate



#### Figure 4.

 $CO_2$  capture system using filamentous cyanobacteria: 1—gas absorbed media inlet, 2—gaseous source for feed, 3—gas outlet valve, 4—gas regulator, 5—illumination source, 6—photo-reactor outer wall, 7—growth media, 8—pH control inlet tube, 9—acid source - pH control, 10—alkali source - pH control, 12—media outlet tube, 13—spent media container, 14—spent media exhaust, 15—media inlet tube, 16—media container, 17—media inlet valve, 18—photo-bioreactor vessel, 19—media exhaust tube, 20—fibrous matrix attachment, 21—photo-bioreactor lid, and 22—gas absorption container lid.





proved to be a good nutrient for the growth of *Oscillatoria*. Luxuriant growth of *Oscillatoria* was observed in  $KNO_3$  + sodium orthophosphate and  $NaNO_3$  + sodium orthophosphate.

#### CO2 Capture for Industries by Algae DOI: http://dx.doi.org/10.5772/intechopen.81800

Nutrient	Day 0	Day 10	Day 20	Day 30
Control	+	+	+	+
KNO <sub>3</sub> + NaHPO <sub>4</sub>	+	+++	+++	+++
NaNO <sub>3</sub> + NaHPO <sub>4</sub>	+	+++	+++	+++
Urea	+	+	+	+
Glucose	+	++	++	++

+++: luxuriant growth; ++: moderate growth; +: mild growth.

Та	ble	: 3.

Effect of nutrients on growth of Oscillatoria.

Metal ion				Days			
	0	5	10	15	20	25	30
Control	+	+	+	+	+	+	+
Ba⁺	+	-	+	+	+	+	+-
Ca <sup>++</sup>	+	+	++	++	++	++	+-
Co**	+	-	+	+	+	+	+
Cr***	+	+	+	+	+	+	+
Cu <sup>++</sup>	+	+	+	+	+	+	+
Fe <sup>+++</sup>	+	+	++	++	++	++	+
Fe <sup>++</sup>	+	-	-	+	+	+	+
Mn <sup>++</sup>	+	-	-	+	+	++	++
Mg <sup>++</sup>	+	+++	+++	+	+++	+++	++
Ni <sup>++</sup>	+	+	+	+	+	+	+
K <sup>+</sup>	+	++	++	+++	+++	+++	++
Na <sup>+</sup>	+	++	++	+++	+++	+++	++
Sn <sup>++</sup>	+	+	+	++	++	++	+
Zn <sup>++</sup>	+	+	+	+	+	+	+
Ag <sup>+</sup>	+	-	- /			-	
Hg⁺		(-)	$\overline{\mathbf{A}}$	+	+	+	+

#### Table 4.

Effect of metal ions on growth of Oscillatoria.

#### 3.1 Effect of metal ions on growth of Oscillatoria

Maximum growth was observed in salts containing Na<sup>+</sup>, Mg<sup>++</sup>, Ni<sup>++</sup>, Co<sup>++</sup>. A drastic increase in chlorophyll content was observed in salt containing Mg<sup>++</sup>, Mn<sup>+2</sup> ions. Growth was observed in 15 metal salts out of 16. The algae (*Oscillatoria*) died in salt containing Ag<sup>+</sup>. Since, nearly all algae possess chlorophyll and all are expected to carry out molecular phosphate transfers, magnesium is without doubt needed universally by algal species. Net synthesis of RNA may stop immediately following magnesium withdrawal. Potassium is a major cell electrolyte, used for balancing the ionic charge. Sodium plays a key role in maintaining turgor pressure within the organism (**Table 4**).

#### Algae

Vitamin	Day 0	Day 5	Day 10	Day 15
Control	+	+	+	+
Vitamin B12	+	+++	++	+
Vitamin B1	+	+++	+++	+++
Vitamin C	+	+++	+	+
11 1 .	.1 .1 1	.1		

+++: luxuriant growth; ++: moderate growth; +: mild growth.

#### Table 5.

owth of Oscillatoria in different vitamins.						
Hormones	Day 0	Day 10	Day 20	Day 30		
Control	+	+	+	+		
IAA <sup>*</sup>	+	+	++	++		
GA**	+	+	++	++		

++: moderate growth; +: mild growth. \*IAA: Indole-3-acetic acid; \*\*GA: Gibberellic acid.

#### Table 6.

Growth of Oscillatoria in different hormones.

Surfactants	Day 0	Day 5	Day 10	Day 15		
Control	+	+	+	+		
Triton X	+	+++	+++	+++		
Tween 20	+	+++	+++	+++		
Tween 80	+	+++	+++	+++		
SDS	+	+++	++	+		
+++: luxuriant growth; ++: moderate growth; +: mild growth.						

#### Table 7.

Growth of Oscillatoria in different surfactants.

#### 3.2 Effect of vitamins, growth hormones and surfactants on growth of Oscillatoria

Growth was observed in all the three vitamins (B<sub>1</sub>, B<sub>12</sub>, and C). An increase in the chlorophyll content was observed in all the three vitamins till the fifth day. Afterward, luxuriant growth was observed in Vitamin B<sub>1</sub>, good growth was observed in Vitamin B<sub>12</sub>, and moderate in Vitamin C. Vitamin B<sub>12</sub> acts as a growth factor for all algae as well as higher plants. A good growth was observed in Gibberellic acid as well as Indole-3-acetic acid. Gibberellic acid is a plant growth hormone that influences various developmental processes; while, cyanobacteria respond to IAA in a manner analogous to higher plants. Luxuriant growth was observed in all the four surfactants with increase in the pigment content of *Oscillatoria*. Almost equal growth was observed (visually) up to 7 days. At the tenth day, moderate growth was observed in SDS while luxuriant growth was observed in Triton-X, Tween-20, and Tween-80 (**Tables 5–7**).

#### 3.3 CO<sub>2</sub> capture by Oscillatoria in photo-bioreactor

Photo-bioreactors act as closed pond system that are used for microalgae cultivation, as they can reduce contamination risk from unwanted algae, mold, and bacteria; control temperature; minimize water evaporation; and reduce carbon CO<sub>2</sub> Capture for Industries by Algae DOI: http://dx.doi.org/10.5772/intechopen.81800



**Figure 6.**  $CO_2$  capture by Oscillatoria.

dioxide losses. Photo-bioreactor FMT 150 used in the present study consists of an algal-cultivation vessel with a sealable lid and a base box containing electronics circuitry, LED light panel, and other components essential for the optimal operation of the photo-bioreactor (**Figure 3**). The cultivation vessel is rectangular in shape and flat with a working volume capacity of 400 ml. Its front and back windows are made of glass plates. The bottom of the cultivation vessel is made of stainless steel and contains a thermal bridge that helps heat transfer between a Peltier cell in the instrument base and the culture suspension.

The culture vessel is fixed with the array of high-power light emitting diodes (LEDs). These LEDs produce a highly uniform light with the irradiance flux that can be controlled in the range of  $0-3000 \ \mu mol \ (photons)/m^{-}/s^{1}$  PAR. The irradiance of the LEDs can be dynamically modulated by the instrument control unit through external computer with software. The photo-bioreactor is equipped with semiconductor light sensor for measuring fluorescence emission and suspension optical density by attenuation of light that was emitting from the LEDs. The solenoid valves are used to switch off the gas supply to the culture (bubbling) during optical measurements. For the supply of fresh medium or buffer, the Peristaltic pumps are used in turbidostat and chemostat mode.

Higher  $CO_2$  capture capacity observed in *Oscillatoria* from 16 to 32 h (**Figure 6**). Higher  $CO_2$  capture efficiency, algal biomass productivity was observed in the selected strains of algae at optimum pH of 7–9 and temperature 25–30°C. The results indicate that the selected blue-green algae *Oscillatoria* can be used for  $CO_2$  capture and biomass production, freshwater algae are ideal candidates for  $CO_2$  capture, when treated with  $CO_2$ -rich gas.

#### 4. Conclusion

Developed process for the CO<sub>2</sub> capture will lead to environment-friendly alternatives to chemical CO<sub>2</sub> capture process. The study exclusively relates to integrated methods and systems for utilizing 99.9%  $CO_2$  as a nutrient carbon source along with modified growth media derived from coal mine water for filamentous cyanobacteria culture. The modified algal media was enriched with the addition of Fe, Mg, vitamins, and surfactants for higher photosynthetic efficiency of algae.

#### Acknowledgements

The authors would like to thank the GAIL (India) Ltd., and CSIR, Govt. of India, for its financial support (SSP 7219 and CSC 102). All the authors express their sincere thanks to Dr. P.K. Singh, Director, CSIR-CIMFR, for supporting the publication of this chapter.

# Author details

Vetrivel Anguselvi<sup>\*</sup>, Reginald Ebhin Masto, Ashis Mukherjee and Pradeep Kumar Singh Industrial Biotechnology and Waste Utilization, CSIR-Central Institute of Mining and Fuel Research, Dhanbad, India

\*Address all correspondence to: vaselvi@yahoo.com

#### **IntechOpen**

© 2019 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/3.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

CO<sub>2</sub> Capture for Industries by Algae DOI: http://dx.doi.org/10.5772/intechopen.81800

#### References

[1] Kassim MA, Meng TK. Carbon dioxide (CO<sub>2</sub>) biofixation by microalgae and its potential for biorefinery and biofuel production. Science of the Total Environment. 2017;**584-585**:1121-1129. DOI: 10.1016/j.scitotenv.2017.01.172

[2] Benemann JR, Van Olst JC, Massingill
MJ, Weissman JC, Brune DE. The controlled eutrophication process:
Using microalgae for CO<sub>2</sub> utilization and agricultural fertilizer recycling.
In: Proceedings of Conference on Greenhouse Gas Technologies; Kyoto, Japan; 2003

[3] Mituya A, Nyunoya T, Tamiya H. In: Burlew JS, editor. Algal cultures from laboratory to pilot plant. Washington: Carnegie Institute; 1953. p. 266

[4] Becker WE, Venkataraman LV. Algae for feed and food. In: A Manual on the Cultivation and Processing of Algae as a Source of Single Cell Protein. Mysore: Wesley Press; 1978

[5] Geitler L, Cyanophyceae L. 14. Band.In: Rabenhorst L, editor. Kryptogamen-Flora. Leipzig: AkademischeVerlagsgesellschaft; 1932. p. 1196

## Open

