We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists

6,300

Open access books available

172,000

International authors and editors

190M

Downloads

Our authors are among the

154

Countries delivered to

TOP 1%

most cited scientists

12.2%

Contributors from top 500 universities

WEB OF SCIENCE™

Selection of our books indexed in the Book Citation Index
in Web of Science™ Core Collection (BKCI)

Interested in publishing with us?
Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected.
For more information visit www.intechopen.com

Cold-Induced Aggregation Microextraction: A Novel Sample Preparation Technique Based on Ionic Liquids for Preconcentration of Cobalt Prior to Its Determination by Fiber Optic-Linear Array Detection Spectrophotometry in Real Water Samples

Maysam Gharehbaghi, Farzaneh Shemirani,
Malihe Davudabadi Farahani and Majid Baghdadi
*University of Tehran
Iran*

1. Introduction

Despite good development in modern analytical instruments, direct determination of trace analytes at low concentrations is often a problem for analytical chemists and, as a result, a sample-preparation step is required. The sample preparation in analytical process typically consists of an extraction-separation step, which offers not only the ability to isolate target analytes from the matrix solution, thus reducing or even eliminating originally present interferences but also the opportunity for these analytes to be preconcentrated and determined at very low levels. Liquid-liquid extraction (LLE), based on the partitioning of an analyte from one liquid phase to another immiscible liquid phase, is a still widely used traditional sample preparation technique. However, this method is time-consuming and tedious. Also large amounts of high purity solvents, which are expensive and toxic, are inevitable to be used. The continuous quest for novel sample preparation procedures has led to a development of new methods, which have main advantages like rapidity and reduction of solvents consumption, such as cloud point extraction (CPE), solid-phase microextraction (SPME), single drop microextraction (SDME), hollow fiber-liquid phase microextraction (HF-LPME), dispersive liquid-liquid microextraction (DLLME) and others.

Cloud point extraction is considered to be a green extraction method because the extraction is performed while using surfactants, which may exhibit lower toxicity, volatility and flammability compared with organic solvents used in other extraction techniques. This technique is widely used in extraction of metals (Bezerra et al., 2005; Dallali et al., 2009), organic compounds (Carabias-Martinez et al., 2000) and proteins (Saitoh & Hinze, 1995). Despite many benefits when using CPE, in rather high content of salt, background is increased since the enrichment phase is composed of a little aqueous sample. Also in the presence of more than 3 % of water-miscible organic solvents such as acetone the phase separation does not occur and the extraction system is destroyed (Manzoori & Karim-

Nezhad, 2003). In addition, the application of this technique is limited by the influence of temperature, pressure, pH, and selection of specified surfactants (Paleologos et al., 2005).

Solid-phase microextraction (SPME), a widely used sample preparation technique, is a solventless, simple and convenient method, which combines extraction, preconcentration and sample introduction in one step (Risticovic et al., 2009). However, it is expensive; its fiber is fragile and has a limited lifetime. Unfortunately, large amounts of eluents are used in this method. In addition, the carryover between extractions is also problematic when determining some analytes at very low concentrations.

Single-drop microextraction is a type of solvent microextraction (SME) technique that is performed by exposing a single drop of solvent to the headspace or directly into the matrix of the sample (Genfa & Dasgupta, 2000; He & Lee, 1997; Jeannot & Cantwell, 1996; Liu & Dasgupta, 1995). It was developed as a solvent-minimized sample preparation procedure, which is inexpensive and advantageous. Since very little amount of the solvent is used, there is a minimal exposure to toxic organic solvents (Ahmadi et al., 2006; Jeannot & Cantwell, 1997). In comparison with solid phase microextraction, it has advantages like wide choice of extraction solvents, cheaper devices and simpler operation and no analyte carryover occurs. However, relatively small volumes of extractant drop lead to lower sensitivity. In addition, it is time-consuming and at fast stirring rates, the organic drop is broken up and air bubbles are formed.

Hollow-fiber liquid-phase microextraction is a sample preparation technique, in which the analytes are extracted into an organic layer filled in pores of a suspended hollow fiber or further extracted back into an aqueous phase inside the fiber, depending on whether a two-phase or three-phase system is applied (Pedersen-Bjergaard & Rasmussen, 1999; Rasmussen & Pedersen-Bjergaard, 2004). Because of the larger contact area between the analyte aqueous solution and extraction phase, the extraction efficiency obtained with this method is higher than with SDME. However, the extraction procedure is tedious and in most cases, the extraction equilibrium is not attained during a short time. Moreover, carryover and contamination of the hollow fiber can be an outcome.

Dispersive liquid-liquid microextraction (DLLME), another type of SME which was developed in 2007, is simple, fast and inexpensive. However, the amount of used disperser solvent is relatively high, therefore it may lead to decrease of the extraction recovery of less hydrophobic species.

In recent years, room-temperature ionic liquids (RTILs) have attracted increasing interest and are applied more and more as the extraction solvent replacing the volatile solvent in sample preparation (Huddleston et al., 1998), due to their unique chemical and physical properties, such as negligible vapour pressure, non-flammability, good extractability for various organic compounds and metal ions as a neutral or charged complexes, as well as tunable viscosity and miscibility with water and organic solvents. However, most of them were conducted in the liquid-liquid extraction and as a result a large volume of ionic liquid was required (Smirnova et al., 2004; Xia et al., 2006), which is tedious and costly. Then the microextraction based on ILs was developed by Liu et al. (Liu et al., 2003). Subsequently, due to a combination of the viscosity and the expense of ionic liquids, we used an ionic liquid (IL) at the microscale for the analytical extraction and the determination of mercury ions in water samples by using spectrophotometric detection (Gharehbaghi et al., 2009).

In 2008 Baghdadi and Shemirani developed a new method called cold-induced aggregation microextraction (CIAME), which was based on the use of ILs in homogeneous liquid-liquid microextraction (HLLME) (Baghdadi & Shemirani, 2008). In this method, a very small

amount of hydrophobic IL as an extractant solvent is dissolved in the sample solution containing Triton X-114. Triton X-114 prevents IL from sticking onto the surface of a centrifuge tube wall, therefore we have named it “anti-sticking agent”. One should be aware that there is no interface between the water and the extractant phases; as a result mass transfer from aqueous phase into separated phase has no important effect on the extraction step. After dissolving, the solution is cooled in the ice bath, a cloudy solution is formed due to the solubility reduction of IL and fine droplets of it are formed. During the formation of fine droplets of the extractant phase, the hydrophobic species are collected by the extractant molecules and the extraction process is completed after the formation of the droplets. After centrifuging, the fine droplets of extractant phase settle to the bottom of the conical-bottom glass centrifuge tube.

This method is simple, rapid, safe and robust against high content of salt and water-miscible organic solvents. In comparison with CPE, background is too low in case of saline solutions, because of very low solubility of water in ILs. Also, owing to high viscosity of ILs, removal of bulk aqueous phase is easier. This method is more suitable for the extraction of heat-susceptible species in comparison with CPE. CIAME provides a high recovery and has a low toxicity since only very small amounts of IL as a “green extraction solvent” is used.

2. Importance

2.1 Cobalt; the occurrence, benefits and applications, exposure and toxicity and methods of determination

Cobalt is a natural element found throughout the environment, used in pigment manufacture and used to make superalloys (alloys that maintain their strength at high temperatures approaching their melting points). It can benefit or harm human health. Cobalt is an essential element in people's lives, as a constituent of vitamin B₁₂. It has also been used as a treatment for anemia, because it stimulates red blood cell production. The significance of cobalt as a transition metal in its wide spectrum of applications is covering many frontier areas of study, particularly in medicine. We can be exposed to low levels of cobalt by breathing air, eating food or drinking water. Food and drinking water are the largest sources of exposure to cobalt for general population.

Toxicological effects of large amounts of cobalt include vasodilatation, flushing and cardiomyopathy in men and animals (Yuzefovsky et al., 1994). Even though cobalt is not considered to be as toxic as most heavy metals, it is an equally harmful element. Hence owing to the importance of cobalt, its determination from associated elements by extractive spectrophotometry has been of a considerable importance.

A wide variety of chelating agents has been reported for the spectrophotometric determination of cobalt (Appadoo & Bhagwat, 1994; Carvalho et al., 1996; Chaudhari & Sawant, 1993; Dasilva & Martins, 1992; Kalika et al., 1993; Kamburova et al., 1994; Khambekar & Sawant, 1997; Lokhande et al., 1996; Maheshwari & Balasubramanian, 1995; More & Sawant, 1992; Pillai & Shinde, 1995; R.A. Chaudhari & A.D. Sawant, 1993; Reddy & Sarma, 1994; Sharma & Dave, 1997; Shen et al., 1995; Taher & Puri, 1995; Toral et al., 1993; Umebayashi & Ishiguro, 1996). However, these methods suffer from limitations such as critical pH (Dasilva et al., 1992; Maheshwari et al., 1995; Pillai et al., 1995), long color development time (Umebayashi et al., 1996) and interference with some ions (Chaudhari et al., 1993; Kalika et al., 1993; Lokhande et al., 1996; Maheshwari et al., 1995; More et al., 1992; Pillai et al., 1995; Reddy et al., 1994; Toral et al., 1993; Umebayashi et al., 1996).

In addition, the preconcentration and determination of cobalt (II) has been studied in various extraction methods such as: liquid-liquid extraction (LLE), flow injection extraction (FIE), cloud point extraction (CPE), solid phase extraction (SPE) and dispersive liquid-liquid microextraction (DLLME).

New LLE methods based on liquid membranes (Kakoi et al., 1998; Ribeiro et al., 2004) and hollow fiber contactors (Soldenhoff et al., 2005) were used for extraction and preconcentration of cobalt. However, it is time-consuming, tedious and uses large amounts of high purity solvents, which are expensive and toxic. The continuous quest for novel sample preparation procedures has led to a development of new methods, among which main advantages belong their speed and negligible volume of used solvents. Initial efforts to address the problem of large solvent consumption have led to a development of the FIE method. Some of these methods have been applied for cobalt extraction (Andac et al., 2001; Cao et al., 1999; Cassella et al., 2001; Dadfarnia & Jafarzadeh, 1999; Dzherayan et al., 2002; Fujimoto et al., 1999; Li et al., 2006a; Li et al., 2006b; Nogueira et al., 1998; Shabani et al., 2003; Song et al., 2006; Tsakovski et al., 2002). FIE has some advantages compared with LLE like low cost, high extraction speed and reduced solvent and sample consumption. However, the amount of used solvent is still in the order of several hundred micro liters per analysis.

Also preconcentration of cobalt in some CPE methods has been reported (Bezerra et al., 2007; Chen & Teo, 2001; Donati et al., 2006; Ghaedi et al., 2008; Gil et al., 2008; Nascentes & Arruda, 2003; Safavi et al., 2004; Shemirani & Shokoufi, 2006; Shokoufi et al., 2007b). Despite many benefits from the use of CPE, in high content of salt, background is increased since the enrichment phase is composed of a little aqueous sample and in very high content of salt, the density of the sample becomes equal or even higher than that of micelles, therefore they can not be settled. Also in the presence of more than 3 % of water-miscible organic solvents such as acetone phase separation does not occur.

Several SPE preconcentration procedures for cobalt have been reported using various sorbents (Blitz-Raith et al., 2007; Ghaedi et al., 2007; Praveen et al., 2005; Yang et al., 2002).

DLLME is a type of solvent microextraction (SME), which has been developed in 2007. A combined method including fiber optic-linear array detection spectrophotometry (FO-LADS) and DLLME was developed for preconcentration and determination of cobalt (Shokoufi et al., 2007a). In this method 1,2-dichlorobenzene (a harmful solvent) was used as an extractant. Another DLLME method, which was applied to preconcentrate trace levels of cobalt as a prior step to its determination by spectrophotometric detection, was reported (Gharehbaghi et al., 2008). This method is simple, fast and inexpensive. However, the amount of used disperser solvent is relatively high, therefore it may happen that recoveries of relatively less hydrophobic species decrease.

Homogeneous liquid-liquid microextraction (HLLME) utilizes the phase separation phenomenon from a homogeneous solution and the target solutes are extracted into a separated phase. However, HLLME has some problems; for instance, sometimes it is not compatible with some instrumental analysis and it also requires an addition of a reagent such as acid, base, salt, etc. As a result, some interesting compounds are probably destroyed; moreover, the addition of the reagent causes a release of heat during the extraction.

2.2 Vantage points of cold-induced aggregation microextraction method

In this research the performance of CIAME was investigated with the determination of cobalt in water samples using FO-LADS. The effects of various experimental parameters on

the extraction were investigated. This method is simple, rapid and viscosity independent for extraction and preconcentration of metal ions and organic compounds from water samples, and is robust against high content of salt and water-miscible organic solvents. Additionally, in comparison with the organic solvent extraction, it is much safer since only small amounts of surfactant and IL are used which are being considered as “green solvents” for various separation processes and in comparison with IL-based DLLME, the extraction recoveries of CIAME are relatively high (Gharehbaghi et al., 2009).

Another important capability of this method is that it can be operated in a continuous mode. If the solution is cooled during centrifuging, fine droplets of extractant phase are continuously formed and analytes are extracted and transferred to the bottom of the centrifuge tube. In order to have a good recovery in case of microextraction in which the volume of the extractant solvent is very small, a large distribution coefficient is necessary, unless the recovery is low and continuous microextraction is required. This project is currently being performed in our laboratory.

3. Experimental

3.1 Instrumentation

A UV-vis light source, optical fiber and spectrograph model 2048 were prepared from Avantes (Eerbeek, Netherlands) for FOLADS. A 50 μL quartz cylindrical micro-cell (Hellma, Mullheim, Germany) was used as a determination cell. A Universal 320R refrigerated centrifuge equipped with an angle rotor (6-place, 9000 rpm, Cat. No.1620A) and a Jeio Tech BW-05G water bath were obtained from Hettich (Kirchlengern, Germany).

3.2 Reagents

All used reagents were of analytical grade. Triply distilled water was used throughout the experiment. 1-(2-pyridylazo)-2-naphthol (PAN), acetone, ethanol, acetic acid, 1-hexyl-3-methylimidazolium hexafluorophosphate [Hmim][PF₆] and 1-hexyl-3-methylimidazolium bis (trifluoromethylsulfonyl) imide [Hmim][Tf₂N] and all used salts were obtained from Merck (Darmstadt, Germany). Triton X-100 and Triton X-114 were purchased from Fluka (Buchs, Switzerland). A stock solution of cobalt (II) (1000 mg L⁻¹) was prepared by dissolving appropriate amount of CoCl₂·6H₂O and working standard solutions were obtained by appropriate stepwise dilution of the stock standard solutions. All stock and working standard solutions were stored in plastic (polypropylene) bottles with leak proof screw cap, which were cleaned before being used by soaking in 10% nitric acid solution for at least 24 h and then rinsed thoroughly with triply distilled water. A 10⁻³ mol L⁻¹ PAN solution was prepared by dissolving the appropriate amount in absolute ethanol. The viscosity of ILs is high and their handling is difficult, therefore working solutions ([Hmim][PF₆], 0.8 mg μL^{-1} and [Hmim][Tf₂N], 0.5 mg μL^{-1}) were prepared in acetone.

3.3 Cold-induced aggregation microextraction procedure

The sample or standard solution containing Co(II) in the range of 1.5–65 ng mL⁻¹, PAN (2.5×10⁻⁵ mol L⁻¹), Triton X-114 (0.05 %, w/v), sodium nitrate (0.25 %, w/v), oxalate (4.0×10⁻³ mol L⁻¹) was poured in a 10 mL conical-bottom glass centrifuge tube. After 1 or 2 min, while greenish complex of cobalt was formed, pH of the solution was adjusted to 1 by concentrated HCl. [Hmim][PF₆] (64mg) and [Hmim][Tf₂N] (5 mg) were added and the volume of the solution was adjusted to 10.0 mL by triply distilled water. After that, tube was

kept in a thermostated bath at 35 °C for 4 min. After shaking, it was placed in an ice-water bath for 10 min and a cloudy solution was formed. Then, the mixture was centrifuged for 5 min at 5000 rpm. As a result, fine droplets of IL settled at the bottom of the centrifuge tube (about 8 μ L). The bulk aqueous phase was removed simply by inverting the tubes. The extraction steps are illustrated in Fig. 1. Afterwards, IL-phase was dissolved in 50 μ L of pure ethanol and transferred to quartz cylindrical micro-cell. The absorbance of the complex was measured at 578 nm.

4. Results and discussion

It is necessary to investigate the effect of all parameters that can probably influence the extraction performance. In this methodology these parameters are the kind and amount of IL and anti-sticking agent, ligand concentration, pH, salt concentration, temperature and centrifuge conditions, which were investigated and optimized in order to achieve a high recovery and enrichment factor. In all optimization steps concentration of cobalt was 30 ng mL⁻¹.

Fig. 1. Photography of different steps in CIAME: (a) after adding IL in the sample solution, (b) after shaking and dissolving the IL, (c) after cooling and phase separation, (d) after centrifuging and (e) after removing the bulk aqueous phase.

4.1 Selection of ionic liquid

For the selection of a suitable IL some considerations were recommended, which were mentioned in the previous work (Baghdadi et al., 2008). In this work, we focused on ILs containing imidazolium cation. Imidazolium-ILs containing PF₆⁻ as an anion are hydrophobe, relatively inexpensive and liquid in experimental conditions, therefore they are suitable for LLE. From [Bmim][PF₆], [Hmim][PF₆] and [Omim][PF₆] according to some physicochemical properties like density, viscosity and water solubility (Liu et al., 2005) and with regard to the point that the sample volume was 10 mL, [Hmim][PF₆] was chosen as an extractant. Thus, about 75 mg of this IL was solved in the aqueous sample solution.

4.2 Selection of anti-sticking agent

Like in the previous work, after centrifugation, it was observed that some of the IL-phase stick on the wall of the centrifuge tube. In order to overcome this problem, a non-ionic surfactant was added to the sample solution (Baghdadi et al., 2008). In the presence of non-ionic surfactant and during the phase separation, molecules of the surfactant surround the fine droplets of IL. Hence, interactions of IL with the wall of the centrifuge tube decrease and consequently, IL-phase does not stick on the wall of the centrifuge tube. The effects of two non-ionic surfactants (Triton X-114 and Triton X-100) were investigated and compared. In the presence of Triton X-100 absorbance decreased, while in the case of using Triton X-114 absorbance increased. Therefore, the Triton X-114 was chosen as the anti-sticking agent at the optimum concentration of 0.05 % (w/v).

4.3 Effect of pH and PAN concentration

In CIAME method pH plays a unique role in the metal-chelate formation and the subsequent extraction. The effect of pH on the extraction of cobalt from water samples was studied in the range of 0.5–6 after Co-PAN complex formation. Results reveal that the absorbance is slightly reduced by increasing pH. As well as at low pH, cations are less likely to precipitate; pH 1 seems a proper choice for extraction.

The effect of PAN concentration on the absorption is shown in Fig. 2. As it is well expected, in accordance with ML_2 stoichiometry of the complex the absorption is higher when increasing the PAN concentration. We investigated PAN concentration in the range of 1.5×10^{-7} to 4×10^{-5} mol L⁻¹. The maximum absorbance was obtained at a concentration of 2.5×10^{-5} mol L⁻¹ of the ligand and after that, the absorbance stays approximately constant.

Fig. 2. Effect of PAN concentration on the absorbance of complex. Utilized conditions: Cobalt 30 ng mL⁻¹, pH = 1, NaNO₃ 0.2 % (w/v), Triton X-114 0.05 % (w/v), [Hmim][PF₆] 60 mg, [Hmim][Tf₂N] 5 mg, diluting agent 50 μL.

4.4 Effect of IL amount

In the presence of high content of salt, the solubility of [Hmim][PF₆] increases and phase separation does not occur. But according to the common ion effect, solubility decreases in

the presence of IL with a common ion (such as [Hmim][Tf₂N]). This is one of the interesting properties of ILs. The effect of [Hmim][PF₆] in the presence and absence of [Hmim][Tf₂N] is shown in Fig. 3. In the presence of [Hmim][Tf₂N], lower amount of [Hmim][PF₆] was required for the phase separation. The optimum amount of [Hmim][PF₆] for the complete extraction was 70 and 60 mg in the absence and presence of [Hmim][Tf₂N], respectively.

Fig. 3. Effect of the amount of [Hmim][PF₆] on the absorbance of Co-PAN complex. Utilized conditions: Cobalt 30 ng mL⁻¹, PAN 2.5×10⁻⁵ mol L⁻¹, pH = 1, NaNO₃ 0.2 % (w/v), Triton X-114 0.05 % (w/v), [Hmim][Tf₂N] 5 mg, diluting agent 50 μL.

4.5 Effect of salt concentration and water-miscible organic solvents

NaNO₃ was chosen in order to study the salt effect in the range of 0–1 % (w/v). The absorbance slightly increased as a result of the salting out effect. A concentration of 0.2% (w/v) NaNO₃ was selected for subsequent experiments in order to increase recovery. Also to investigate the robustness of the method against salty solutions, various solutions with the concentration up to 10% were examined. As shown in Fig. 4, in the absence of [Hmim][Tf₂N], absorbance decreased by increasing the salt concentration as a result of increasing in solubility of [Hmim][PF₆], but in the presence of [Hmim][Tf₂N] phase separation occurred up to 10% NaNO₃.

Since acetone and ethanol were selected as the solvents for the IL and ligand, their effects were investigated, too. In the presence of acetone, the absorbance was nearly constant up to 10 % and afterwards, it decreased and in the presence of ethanol, the absorbance was almost constant up to 12 %. This is one of the advantages of CIAME compared to CPE. In case of CPE, the extraction system is destroyed in the presence of over 3% water-miscible organic solvents (Manzoori et al., 2003). Even in case of DLLME based on common organic solvents like chloroform, carbon tetrachloride, etc., the extraction efficiency was clearly reduced for solutions containing water-miscible organic solvents.

Fig. 4. Effect of NaNO₃ on the absorbance of Co-PAN complex in the range of 1-10 % (w/v). Utilized conditions: Cobalt 30 ng mL⁻¹, PAN 2.5×10⁻⁵ mol L⁻¹, pH = 1, Triton X-114 0.05 % (w/v), [Hmim][PF₆] 64 mg, [Hmim][Tf₂N] 5 mg, diluting agent 50 μL.

4.6 Effect of temperature

Before shaking the solutions containing IL, they were heated in the range of 20-60 °C. In this range the absorbance was constant; warming of the solution had no effect on the extraction process. This is another advantage of CIAME in comparison with CPE, especially if the species are heat-sensitive. Since ILs are dissolved more easily at the temperatures above 30 °C, a temperature of 35 °C was chosen for the heating step.

After dissolving of IL, samples were cooled in the temperature range of 0-25 °C. As the temperature decreased, the absorbance increased, as a result of decreasing IL solubility. Hence, a temperature of 0 °C was applied in all experiments by placing the centrifuge tubes in an ice bath for 10 min.

4.7 Effect of centrifuge conditions

The effect of centrifugation rate on the absorbance was studied in the range of 1000 - 7000 rpm. It was found, that over 4000 rpm IL-phase completely settled, therefore a rate of 5000 rpm was selected as the optimum point.

At the optimum rate, the absorbance was investigated as a function of the centrifugation time. Over 2 min, absorbance was constant, indicating complete transfer of IL-phase to the bottom of centrifuge tube. Therefore, the optimum centrifugation time was chosen as 3 min.

4.8 Effect of coexisting ions

The effects of coexisting ions in real water samples on the recovery of cobalt were also studied. In these experiments, 10mL solutions containing 30 ng mL⁻¹ of cobalt and various

amounts of interfering ions were treated. A given species was considered to interfere if it resulted in a $\pm 5\%$ variation of the absorbance. The obtained results are given in Table 1. Most of the examined cations and anions did not interfere with the extraction and determination of Co^{2+} . However, some of the tried species, such as Fe^{3+} , Cu^{2+} and Pd^{2+} interfered with the determination of Co^{2+} ion. These interferences were eliminated in the presence of proper masking agents, such as $1.5 \times 10^{-4} \text{ mol L}^{-1}$ acetylacetone for Pd^{2+} , $4.0 \times 10^{-3} \text{ mol L}^{-1}$ oxalate for Fe^{3+} (and Ca^{2+}) and $2.5 \times 10^{-3} \text{ mol L}^{-1}$ ascorbic acid and $4.0 \times 10^{-3} \text{ mol L}^{-1}$ iodide for Cu^{2+} . In the presence of the masking agents, no interference was observed for Ca^{2+} up to 1000, Fe^{3+} and Cu^{2+} up to 100 and Pd^{2+} up to 10 times relative to Co^{2+} concentration. Thus, a quantitative extraction of Co^{2+} was possible.

Interferent	Interferent/ Co(II) (weight ratio)	Recovery (%)	Interferent	Interferent/ Co(II) (weight ratio)	Recovery (%)
Ba^{2+}	1000	98	Cu^{2+}	100	- ^c
Mg^{2+}	1000	100		100	105 ^d
Mn^{2+}	1000	99	Hg^{2+}	100	92
Cr^{3+}	1000	104		50	99
Cd^{2+}	1000	100	Pd^{2+}	10	188
Zn^{2+}	1000	103		10	95 ^e
Ca^{2+}	1000	98 ^a	I^-	1000	100
Ag^+	500	97	SO_4^{2-}	1000	101
Pb^{2+}	500	101	NO_3^-	1000	98
Al^{3+}	500	102	PO_4^{3-}	1000	98
Fe^{3+}	100	165	CH_3COO^-	1000	100
	100	98 ^b	NO_2^-	1000	98

Table 1. Effect of interferents on the recovery of $30 \mu\text{g L}^{-1} \text{Co(II)}$ in water sample using CIAME

^a Ca^{2+} masked with $4.0 \times 10^{-3} \text{ mol L}^{-1}$ oxalate .

^b Fe^{3+} masked with $4.0 \times 10^{-3} \text{ mol L}^{-1}$ oxalate.

^cIn the presence of this interferent the shape of spectrum is changed completely.

^d Cu^{2+} masked with $2.8 \times 10^{-3} \text{ mol L}^{-1}$ ascorbic acid and $3.9 \times 10^{-3} \text{ mol L}^{-1}$ iodide.

^e Pd^{2+} masked with $1.9 \times 10^{-4} \text{ mol L}^{-1}$ acetylacetone.

4.9 Figures of merit

Table 2 summarizes analytical characteristics of the optimized method, including limit of detection, reproducibility and enhancement factor. The limit of detection ($\text{LOD} = 0.14 \text{ ng mL}^{-1}$) was calculated as $3 S_b/m$ (S_b : standard deviation of the blank signals; m : slope of calibration curve after the preconcentration). A good correlation coefficient ($r = 0.9997$) was obtained and only small deviations between sequential determinations ($\text{RSD} = 2.32 \%$) were found. The calibration curve was investigated up to 65 ng mL^{-1} which was linear. Enhancement factor ($\text{EF} = 165$) was obtained from the slope ratio of calibration curve after and before the preconcentration.

Parameter	Analytical Feature
Linear range (ng mL ⁻¹)	1.5-65
r ²	0.9995
Limit of detection (ng mL ⁻¹) (3σ, n = 5)	0.14
Repeatability (RSD ^a , %) (n = 5)	2.32
Enhancement factor ^b (EF)	165
Sample volume (mL)	10
Extraction time (min)	<20

Table 2. Analytical characteristics of CIAME for determination of Co(II)

^aRSD was obtained for 30 μg L⁻¹ concentration of Co(II) .

^bEnhancement factor is the slope ratio of calibration graph after and before extraction.

The equation of the calibration curve after the preconcentration procedure is given in Eq. (1). Also the equation of the calibration curve before the preconcentration procedure is given at below in Eq. (2). (These standard samples of cobalt were chosen up to 200 ng mL⁻¹ with excels PAN to measure their absorbance and obtain the equation of the calibration curve accurately).

$$A= 2.30 \times 10^{-2} C_{(Co)} + 0.0094 \quad (r^2 = 0.9995, r = 0.9997) \tag{1}$$

$$A= 1.39 \times 10^{-4} C_{(Co)} + 0.0323 \quad (r^2 = 0.9983, r = 0.9991) \tag{2}$$

4.10 Accuracy

For evaluating the accuracy of the method, a certified reference material (CRM) was analyzed. The Reference Standard “SCP-ES-L-1” (SCP SCIENCE Canada, ground water (Low level)) is a ground water that has been spiked with metals. The certified value and analytical results are presented in Table 3. The result indicates effectiveness and accuracy of the proposed method.

Certified reference material	Certified ^a (ng mL ⁻¹)	Found ^b (ng mL ⁻¹)	Found ^c (ng mL ⁻¹)	Recovery (%)
SCP-ES-L-1	51 ± 8	48.6 ± 0.2 ^d	49.5 ± 0.6 ^d	101.8

Table 3. Determination of cobalt in a standard reference material using DLLME

^aResults after dilution 1 : 500.

^bDetermined by GFAAS.

^cDetermined by CIAME/FO-LADS.

^dMean value ± standard deviation based on five replicate measurements.

4.11 Analysis of natural water

The proposed methodology was applied for the determination of cobalt in different water samples. Damavand mineral water, Tajan river water and Caspian Sea water samples were collected from the north of Iran and analyzed by CIAME as a prior step to its determination by FO-LADS. No concentration of cobalt in the tap and mineral water samples was detected. Moreover, the robustness of the proposed method was checked by performing recovery tests on a saline serum and a synthetic sample (containing Mn²⁺, Zn²⁺, Mg²⁺, Cd²⁺, Cr³⁺ of 1000 ng mL⁻¹ and Na⁺, K⁺ of 3000 ng mL⁻¹). Each type of water was spiked with variable

amounts of Co(II) to assess matrix effects. The results are shown in Table 4. The relative recoveries of cobalt from mentioned water samples at various spiking levels were between 96.0 and 103.0 %. These results demonstrated that matrices of these water samples, under presented conditions, had little effect on CIAME of cobalt.

Sample	Spiked (ng mL ⁻¹)	Found (ng mL ⁻¹) ^a	Recovery (%)
Mineral water	–	N.D ^b	–
	10	10.1 ± 0.15	101.0
	20	20.3 ± 0.32	101.5
Tap water ^c	–	N.D ^b	–
	10	10.2 ± 0.22	102.0
	15	14.7 ± 0.35	98.0
River water	–	4.3 ± 0.39	–
	10	13.9 ± 0.23	96.0
	25	28.5 ± 0.33	96.8
Sea water	–	1.7 ± 0.27	–
	10	12.0 ± 0.32	103.0
	25	27.1 ± 0.55	101.6
Saline Serum ^d	25	25.6 ± 0.2	102.4
	45	43.9 ± 0.4	97.6
Synthetic sample	10	10.1 ± 0.18	101.0
	15.0	14.9 ± 0.23	99.3

Table 4. Determination of cobalt in real and synthetic samples

^aMean ± S.D. (n = 5).

^bNot detected.

^cFrom drinking water system of Tehran, Iran.

^dProduced by Daru Paksh Company for injection.

4.12 Comparison of CIAME with other methods

A comparison of the represented method with other reported preconcentration methods is given in Table 5. In comparison with other reported methods, CIAME has low LOD (0.14 ng mL⁻¹), high enrichment factor (165) and relative short extraction procedure (less than 20 min). All these results indicate that CIAME is a reproducible, simple and low cost technique that can be used for the preconcentration of metal ions like cobalt from water samples.

5. Conclusions and future work

In this study, a new mode of HLLME based on IL, named cold-induced aggregation microextraction (CIAME), was developed for preconcentration of cobalt from water samples as a prior step to its determination by FO-LADS. Cobalt was employed as a test analyte and 1-(2-pyridylazo)-2-naphthol (PAN) as a complexing agent to assess the extraction procedure.

Method	LOD ^a (ng mL ⁻¹)	RSD. ^b (%)	Enhance- ment factor	Sample consumpt -ion (mL)	Calibration range (ng mL ⁻¹)	References
CPE/Spectrophotometry	7.5	2.2	10 ^c	10	20-200	(Safavi et al., 2004)
CPE/FAAS	1.06	5.41	28.5	12.5	25-200	(Nascentes et al., 2003)
CPE/FAAS	0.24	2.1	57 ^d	50	0-120	(Chen et al., 2001)
SPE/Spectrophotometry	10	2.23	100 ^e	250	10-400	(Yang et al., 2002)
DLLME/FO-LADS	0.2	<4	165	10	1-70	(Shokoufi et al., 2007a)
DLLME/Spectrophotometry	0.5	2.5	125	50	2-60	(Gharehbaghi et al., 2008)
CPE/FAAS	5	1.71	20 ^f	10	0-200	(Giokas et al., 2001)
SPE/ETAAS	0.004	4.5	87	11.5	0.01-0.25	(Sant'Ana et al., 2002)
CIAME/FO-LADS	0.14	2.32	165	10	1.5-65	This work

Table 5. Characteristic performance data obtained by using CIAME and other techniques for determination of cobalt

^aLimit of detection.

^bRelative standard deviation.

^cRatio of the aqueous phase to final volume of surfactant-rich phase.

^dThe enhancement factor, as the ratio of absorbance of preconcentrated sample to that obtained without preconcentration.

^eRatio of the aqueous phase to final volume of eluent phase.

^fPreconcentration factor.

This method is simple, rapid, safe and robust against high content of salt and water-miscible organic solvents. In comparison with CPE, background is too little in case of saline solutions, because of very low solubility of water in ILs. Also owing to high viscosity of ILs removing the bulk aqueous phase is easier. This method is more suitable for extraction of heat-susceptible species in comparison with CPE. CIAME provides high recovery and has low toxicity since only very small amounts of an IL as a “green extraction solvent” is used. In addition, the proposed method offers good sensitivity in comparison with other combination methods, which were used, FAAS or conventional UV-vis spectrophotometer as the detection technique.

Our research group is currently working on CIAME in a continuous mode and as a future work would like to develop a microextraction technique in which the volume of the extractant solvent is very small. In order to have a good recovery, in this case a large distribution coefficient is necessary unless a continuous microextraction, in which fine droplets of extractant phase are continuously formed and analytes are extracted and transferred to the bottom of the centrifuge tube, is applied.

Financial support from University of Tehran, as well as proofreading by Barbora Ehrlichová is gratefully acknowledged.

6. References

- Ahmadi, F.;Assadi, Y.;Hosseini, S., & Rezaee, M. (2006). Determination of organophosphorus pesticides in water samples by single drop microextraction and gas chromatography-flame photometric detector. *Journal of Chromatography A*, 1101(1-2), 307-312.
- Andac, M.;Asan, A.;Isildak, I., & Cesur, H. (2001). Flow-injection spectrophotometric determination of cobalt(II) at low $\mu\text{g l}^{-1}$ levels with 4-benzylpiperidinedithiocarbamate. *Analytica Chimica Acta*, 434(1), 143-147.
- Appadoo, C., & Bhagwat, V. W. (1994). Spectrophotometric determination of cobalt with m-(mercaptoacetamido) phenol. *Asian Journal of Chemistry*, 6, 703-705.
- Baghdadi, M., & Shemirani, F. (2008). Cold-induced aggregation microextraction: A novel sample preparation technique based on ionic liquids. *Analytica Chimica Acta*, 613(1), 56-63.
- Bezerra, M. A.;Maeda, S. M. D.;Oliveira, E. P.;de Carvalho, M. D. B., & Santelli, R. E. (2007). Internal standardization for the determination of cadmium, cobalt, chromium and manganese in saline produced water from petroleum industry by inductively coupled plasma optical emission spectrometry after cloud point extraction. *Spectrochimica Acta Part B-Atomic Spectroscopy*, 62(9), 985-991.
- Bezerra, M. D.;Arruda, M. A. Z., & Ferreira, S. L. C. (2005). Cloud point extraction as a procedure of separation and pre-concentration for metal determination using spectroanalytical techniques: A review. *Applied Spectroscopy Reviews*, 40(4), 269-299.
- Blitz-Raith, A. H.;Paimin, R.;Cattrall, R. W., & Kolev, S. D. (2007). Separation of cobalt(II) from nickel(II) by solid-phase extraction into Aliquat 336 chloride immobilized in poly(vinyl chloride). *Talanta*, 71(1), 419-423.
- Cao, Q. E.;Zhao, Y. K.;Cheng, X. G.;Hu, Z. D., & Xu, Q. H. (1999). Sequential fluorescent determination of copper(II) and cobalt(II) in food samples by flow injection analysis. *Food Chemistry*, 65(3), 405-409.
- Carabias-Martinez, R.;Rodriguez-Gonzalo, E.;Moreno-Cordero, B.;Perez-Pavon, J. L.;Garcia-Pinto, C., & Laespada, E. F. (2000). Surfactant cloud point extraction and preconcentration of organic compounds prior to chromatography and capillary electrophoresis. *Journal of Chromatography A*, 902(1), 251-265.
- Carvalho, M. S.;Fraga, I. C. S.;Neto, K. C. M., & Silva, E. Q. (1996). Selective determination of cobalt using polyurethane foam and 2-(2-benzothiazolylazo)-2-p-cresol as a spectrophotometric reagent. *Talanta*, 43(10), 1675-1680.
- Cassella, R. J.;Salim, V. A.;Jesuino, L. S.;Santelli, R. E.;Ferreira, S. L. C., & de Carvalho, M. S. (2001). Flow injection determination of cobalt after its sorption onto polyurethane foam loaded with 2-(2-thiazolylazo)-p-cresol (TAC). *Talanta*, 54(1), 61-67.

- Chaudhari, R. A., & Sawant, A. D. (1993). Extraction and spectrophotometric determination of cobalt. *Asian Journal of Chemistry*, 5, 1-5.
- Chen, J. R., & Teo, K. C. (2001). Determination of cobalt and nickel in water samples by flame atomic absorption spectrometry after cloud point extraction. *Analytica Chimica Acta*, 434(2), 325-330.
- Dadfarnia, S., & Jafarzadeh, M. H. (1999). Online trace enrichment and determination of cobalt ion as an anionic complex by flow injection atomic absorption spectrometry. *Microchemical Journal*, 63(2), 226-234.
- Dallali, N.;Zahedi, M. M.;Yamimi, Y., & Agrawal, Y. K. (2009). Simultaneous cloud point extraction and determination of zn, co, ni, and pb by flame atomic absorption spectrometry. *Reviews in Analytical Chemistry*, 28(2), 125-136.
- Dasilva, J. F., & Martins, W. (1992). Extraction of Fe(III), Cu(II), Co(II), Ni(II) and Pb(II) with thenoyltrifluoroacetone using the ternary solvent system water ethanol methylisobutylketone. *Talanta*, 39(10), 1307-1312.
- Donati, G. L.;Nascentes, C. C.;Nogueira, A. R. A.;Arruda, M. A. Z., & Nobrega, J. S. (2006). Acid extraction and cloud point preconcentration as sample preparation strategies for cobalt determination in biological materials by thermospray flame furnace atomic absorption spectrometry. *Microchemical Journal*, 82(2), 189-195.
- Dzherayan, T. G.;Shkinev, V. M.;Shpigun, L. K.;Kamilova, P. M., & Geckeler, K. E. (2002). Water-soluble polymers for spectrophotometric and flow injection determination of cobalt with nitroso-R-salt. *Talanta*, 57(1), 7-13.
- Fujimoto, T.;Teshima, N.;Kurihara, M.;Nakano, S., & Kawashima, T. (1999). Catalytic determination of cobalt at sub-nanogram levels using the oxidative coupling of 3-methyl-2-benzothiazolinone hydrazone with N-ethyl-N-(2-hydroxy-3-sulfopropyl)-3,5-dimethoxyaniline by manual and flow-injection methods. *Talanta*, 49(5), 1091-1098.
- Genfa, Z., & Dasgupta, P. K. (2000). A continuous film-recirculable drop gas-liquid equilibration device. Measurement of trace gaseous ammonia. *Analytical Chemistry*, 72(14), 3165-3170.
- Ghaedi, M.;Ahmadi, F., & Soylak, M. (2007). Preconcentration and separation of nickel, copper and cobalt using solid phase extraction and their determination in some real samples. *Journal of Hazardous Materials*, 147(1-2), 226-231.
- Ghaedi, M.;Shokrollahi, A.;Ahmadi, F.;Rajabi, H. R., & Soylak, M. (2008). Cloud point extraction for the determination of copper, nickel and cobalt ions in environmental samples by flame atomic absorption spectrometry. *Journal of Hazardous Materials*, 150(3), 533-540.
- Gharehbaghi, M.;Shemirani, F., & Baghdadi, M. (2008). Dispersive liquid-liquid microextraction and spectrophotometric determination of cobalt in water samples. *International Journal of Environmental Analytical Chemistry*, 88(7), 513-523.
- Gharehbaghi, M.;Shemirani, F., & Baghdadi, M. (2009). Dispersive liquid-liquid microextraction based on ionic liquid and spectrophotometric determination of mercury in water samples. *International Journal of Environmental Analytical Chemistry*, 89(1), 21-33.
- Gil, R. A.;Gasquez, J. A.;Olsina, R.;Martinez, L. D., & Cerutti, S. (2008). Cloud point extraction for cobalt preconcentration with on-line phase separation in a knotted reactor followed by ETAAS determination in drinking waters. *Talanta*, 76(3), 669-673.
- Giokas, D. L.;Paleologos, E. K.;Tzouwara-Karayanni, S. M., & Karayannis, M. I. (2001). Single-sample cloud point determination of iron, cobalt and nickel by flow injection

- analysis flame atomic absorption spectrometry - application to real samples and certified reference materials. *Journal of Analytical Atomic Spectrometry*, 16(5), 521-526.
- He, Y., & Lee, H. K. (1997). Liquid phase microextraction in a single drop of organic solvent by using a conventional microsyringe. *Analytical Chemistry*, 69(22), 4634-4640.
- Huddleston, J. G.;Willauer, H. D.;Swatloski, R. P.;Visser, A. E., & Rogers, R. D. (1998). Room temperature ionic liquids as novel media for 'clean' liquid-liquid extraction. *Chemical Communications*(16), 1765-1766.
- Jeannot, M. A., & Cantwell, F. F. (1996). Solvent microextraction into a single drop. *Analytical Chemistry*, 68(13), 2236-2240.
- Jeannot, M. A., & Cantwell, F. F. (1997). Mass transfer characteristics of solvent extraction into a single drop at the tip of a syringe needle. *Analytical Chemistry*, 69(2), 235-239.
- Kakoi, T.;Ura, T.;Kasaini, H.;Goto, M., & Nakashio, F. (1998). Separation of cobalt and nickel by liquid surfactant membranes containing a synthesized cationic surfactant. *Separation Science and Technology*, 33(8), 1163-1180.
- Kalika, K. C.;Kumar, A.;Rajeev, P., & Rajeev, S. (1993). Simultaneous spectrophotometric estimation of cobalt(II) and nickel(II) with phenylazobenzaldoxime. *Asian Journal of Chemistry*, 5, 559-562.
- Kamburova, M.;Alexandrov, A., & Trifonov, K. (1994). Extraction-spectrophotometric determination of cobalt in soils and plants using tetrazolium violet. *Chemia Analityczna*, 39(5), 639-643.
- Khambekar, A. M., & Sawant, A. D. (1997). Extractive and spectrophotometric determination of Co(II) using p-nitroisonitrosoacetophenone. *Indian Journal of Chemistry Section a-Inorganic Bio-Inorganic Physical Theoretical & Analytical Chemistry*, 36(5), 459-460.
- Li, B. X.;Wang, D. M.;Lv, H., & Zhang, Z. J. (2006a). Chemometrics-assisted simultaneous determination of cobalt(II) and chromium(III) with flow-injection chemiluminescence method. *Spectrochimica Acta Part a-Molecular and Biomolecular Spectroscopy*, 65(1), 67-72.
- Li, B. X.;Wang, D. M.;Lv, H. G., & Zhang, Z. J. (2006b). Flow-injection chemiluminescence simultaneous determination of cobalt(II) and copper(II) using partial least squares calibration. *Talanta*, 69(1), 160-165.
- Liu, J.;Jiang, G. B.;Chi, Y. G.;Cai, Y. Q.;Zhou, Q. X., & Hu, J. T. (2003). Use of ionic liquids for liquid-phase microextraction of polycyclic aromatic hydrocarbons. *Analytical Chemistry*, 75(21), 5870-5876.
- Liu, J. F.;Jonsson, J. A., & Jiang, G. B. (2005). Application of ionic liquids in analytical chemistry. *Trac-Trends in Analytical Chemistry*, 24(1), 20-27.
- Liu, S. R., & Dasgupta, P. K. (1995). Liquid droplet - a renewable gas sampling interface. *Analytical Chemistry*, 67(13), 2042-2049.
- Lokhande, R. S.;Jaywant, A. S., & Barhate, V. D. (1996). Extractive spectrophotometric determination of cobalt(II) with p-methylisonitrosoacetophenonehydrazone. *Asian Journal of Chemistry*, 8(4), 610-612.
- Maheshwari, V., & Balasubramanian, N. (1995). Spectrophotometric determination of cobalt with nitrosochromotropic acid. *Fresenius Journal of Analytical Chemistry*, 351, 333-335.
- Manzoori, J. L., & Karim-Nezhad, G. (2003). Selective cloud point extraction and preconcentration of trace amounts of silver as a dithizone complex prior to flame atomic absorption spectrometric determination. *Analytica Chimica Acta*, 484(2), 155-161.

- More, P. S., & Sawant, A. D. (1992). Extractive and spectrophotometric determination of Co(II) at trace levels using isonitroso-4-methyl-2-pentanone. *Indian Journal of Chemistry Section a-Inorganic Bio-Inorganic Physical Theoretical & Analytical Chemistry*, 31(12), 984-985.
- Nascentes, C. C., & Arruda, M. A. Z. (2003). Cloud point formation based on mixed micelles in the presence of electrolytes for cobalt extraction and preconcentration. *Talanta*, 61(6), 759-768.
- Nogueira, A. R. A.;Souza, G. B.;Batista, L. A. R.;Arruda, M. A. Z., & Miyazawa, M. (1998). Catalytic determination of cobalt by flow injection spectrophotometry: application in animal faeces analysis using hydrochloric acid as extracting solution. *Animal Feed Science and Technology*, 74(1), 79-84.
- Paleologos, E. K.;Giokas, D. L., & Karayannis, M. I. (2005). Micelle-mediated separation and cloud-point extraction. *Trac-Trends in Analytical Chemistry*, 24(5), 426-436.
- Pedersen-Bjergaard, S., & Rasmussen, K. E. (1999). Liquid-liquid-liquid microextraction for sample preparation of biological fluids prior to capillary electrophoresis. *Analytical Chemistry*, 71(14), 2650-2656.
- Pillai, V. P., & Shinde, V. M. (1995). Synergistic extraction of copper(II), cobalt(II) and nickel(II) with trifluoroacetylacetone and pyridine. *Indian Journal of Chemistry Section a-Inorganic Bio-Inorganic Physical Theoretical & Analytical Chemistry*, 34(5), 407-409.
- Praveen, R. S.;Daniel, S., & Rao, T. P. (2005). Solid phase extraction preconcentration of cobalt and nickel with 5,7-dichloroquinone-8-ol embedded styrene-ethylene glycol dimethacrylate polymer particles and determination by flame atomic absorption spectrometry (FAAS). *Talanta*, 66(2), 513-520.
- R.A. Chaudhari & A.D. Sawant (1993). Extraction and spectrophotometric determination of cobalt. *Asian Journal of Chemistry*, 5, 1-5.
- Rasmussen, K. E., & Pedersen-Bjergaard, S. (2004). Developments in hollow fibre-based, liquid-phase microextraction. *Trac-Trends in Analytical Chemistry*, 23(1), 1-10.
- Reddy, B. R., & Sarma, P. (1994). Extractive spectrophotometric determination of cobalt using cyanex-272. *Talanta*, 41(8), 1335-1339.
- Ribeiro, C. P.;Costa, A. O. S.;Lopes, I. P. B.;Campos, F. F.;Ferreira, A. A., & Salum, A. (2004). Cobalt extraction and cobalt-nickel separation from a simulated industrial leaching liquor by liquid surfactant membranes using Cyanex 302 as carrier. *Journal of Membrane Science*, 241(1), 45-54.
- Risticvic, S.;Niri, V. H.;Vuckovic, D., & Pawliszyn, J. (2009). Recent developments in solid-phase microextraction. *Analytical and Bioanalytical Chemistry*, 393(3), 781-795.
- Safavi, A.;Abdollahi, H.;Nezhad, M. R. H., & Kamali, R. (2004). Cloud point extraction, preconcentration and simultaneous spectrophotometric determination of nickel and cobalt in water samples. *Spectrochimica Acta Part a-Molecular and Biomolecular Spectroscopy*, 60(12), 2897-2901.
- Saitoh, T., & Hinze, W. L. (1995). Use of surfactant-mediated phase-separation (cloud point extraction) with affinity ligands for the extraction of hydrophilic proteins. *Talanta*, 42(1), 119-127.
- Sant'Ana, O. D.;Oliveira, L. G.;Jesuino, L. S.;Carvalho, M. S.;Domingues, M. D. F.;Cassella, R. J., & Santelli, R. E. (2002). A novel sampling strategy for cobalt determination by ETAAS using polyurethane foam. *Journal of Analytical Atomic Spectrometry*, 17(3), 258-262.
- Shabani, A. M. H.;Dadfarnia, S., & Dehghan, K. (2003). On-line preconcentration and determination of cobalt by chelating microcolumns and flow injection atomic spectrometry. *Talanta*, 59(4), 719-725.

- Sharma, R. R., & Dave, D. P. (1997). Solvent extraction and spectrophotometric determination of cobalt(II) with isonitrosopropiophenone. *Indian Journal of Chemistry Section a-Inorganic Bio-Inorganic Physical Theoretical & Analytical Chemistry*, 36(7), 629-630.
- Shemirani, F., & Shokoufi, N. (2006). Laser induced thermal lens spectrometry for cobalt determination after cloud point extraction. *Analytica Chimica Acta*, 577(2), 238-243.
- Shen, H. X.;Tang, Y. P.;Xiao, X. L.;Zhang, S. F., & Liu, R. X. (1995). Synthesis and studies on the analytical functions of a highly selective spectrophotometric reagent 2-(8-quinolylazo)-5-n,n'-dimethylaminobenzoic acid. *Analyst*, 120(5), 1599-1602.
- Shokoufi, N.;Shemirani, F., & Assadi, Y. (2007a). Fiber optic-linear array detection spectrophotometry in combination with dispersive liquid-liquid microextraction for simultaneous preconcentration and determination of palladium and cobalt. *Analytica Chimica Acta*, 597(2), 349-356.
- Shokoufi, N.;Shemirani, F., & Memarzadeh, E. (2007b). Fiber optic-linear array detection spectrophotometry in combination with cloud point extraction for simultaneous preconcentration and determination of cobalt and nickel. *Analytica Chimica Acta*, 601(2), 204-211.
- Smirnova, S. V.;Torocheshnikova, II;Formanovsky, A. A., & Pletnev, I. V. (2004). Solvent extraction of amino acids into a room temperature ionic liquid with dicyclohexano-18-crown-6. *Analytical and Bioanalytical Chemistry*, 378(5), 1369-1375.
- Soldenhoff, K.;Shamieh, M., & Manis, A. (2005). Liquid-liquid extraction of cobalt with hollow fiber contactor. *Journal of Membrane Science*, 252(1-2), 183-194.
- Song, Z. H.;Yue, Q. L., & Wang, C. N. (2006). Flow injection chemiluminescence determination of femtogram-level cobalt in egg yolk, fish tissue and human serum. *Food Chemistry*, 94(3), 457-463.
- Taher, M. A., & Puri, B. K. (1995). Column preconcentration of cobalt with the ion-pair of 2-nitroso-1-naphthol-4-sulfonic acid tetradecyldimethylbenzylammonium chloride supported on naphthalene using 2nd-derivative spectrophotometry. *Analyst*, 120(5), 1589-1592.
- Toral, M. I.;Richter, P.;Silva, L., & Salinas, A. (1993). Determination of mixtures of cobalt and iron by 1st derivative spectrophotometry. *Microchemical Journal*, 48(2), 221-228.
- Tsakovski, S.;Benkhedda, K.;Ivanova, E., & Adams, F. C. (2002). Comparative study of 8-hydroxyquinoline derivatives as chelating reagents for flow-injection preconcentration of cobalt in a knotted reactor. *Analytica Chimica Acta*, 453(1), 143-154.
- Umebayashi, Y., & Ishiguro, S. I. (1996). Spectrophotometric study of thiocyanato complexation of cobalt(II) and nickel(II) ions in micellar solutions of a nonionic surfactant Triton X-100. *Journal of Solution Chemistry*, 25(8), 731-746.
- Xia, Z.;Li, Z.;Rui, Y., & Liu, H. (2006). A novel room temperature ionic liquid extraction spectrophotometric determination of trace germanium in natural water with methybenzeneazosalicylfluorone. *Analytical Letters*, 39(4/6), 863-877.
- Yang, G. Y.;Huang, Z. J.;Hu, Q. F., & Yin, J. Y. (2002). Study on the solid phase extraction of Co(II)-QADEAB chelate with C-18 disk and its application to the determination of trace cobalt. *Talanta*, 58(3), 511-515.
- Yuzefovsky, A. I.;Lonardo, R. F.;Wang, M. H., & Michel, R. G. (1994). Determination of ultra-trace amounts of cobalt in ocean water by laser-excited atomic fluorescence spectrometry in a graphite electrothermal atomizer with semi online flow-injection preconcentration. *Journal of Analytical Atomic Spectrometry*, 9(11), 1195-1202.

Ionic Liquids: Applications and Perspectives

Edited by Prof. Alexander Kokorin

ISBN 978-953-307-248-7

Hard cover, 674 pages

Publisher InTech

Published online 21, February, 2011

Published in print edition February, 2011

This book is the second in the series of publications in this field by this publisher, and contains a number of latest research developments on ionic liquids (ILs). This promising new area has received a lot of attention during the last 20 years. Readers will find 30 chapters collected in 6 sections on recent applications of ILs in polymer sciences, material chemistry, catalysis, nanotechnology, biotechnology and electrochemical applications. The authors of each chapter are scientists and technologists from different countries with strong expertise in their respective fields. You will be able to perceive a trend analysis and examine recent developments in different areas of ILs chemistry and technologies. The book should help in systematization of knowledges in ILs science, creation of new approaches in this field and further promotion of ILs technologies for the future.

How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Maysam Gharehbaghi, Farzaneh Shemirani, Malihe Davudabadi Farahani and Majid Baghdadi (2011). Cold-Induced Aggregation Microextraction: A Novel Sample Preparation Technique Based on Ionic Liquids for Preconcentration of Cobalt Prior to Its Determination by Fiber Optic-Linear Array Detection Spectrophotometry in Real Water Samples, *Ionic Liquids: Applications and Perspectives*, Prof. Alexander Kokorin (Ed.), ISBN: 978-953-307-248-7, InTech, Available from: <http://www.intechopen.com/books/ionic-liquids-applications-and-perspectives/cold-induced-aggregation-microextraction-a-novel-sample-preparation-technique-based-on-ionic-liquids>

INTech
open science | open minds

InTech Europe

University Campus STeP Ri
Slavka Krautzeka 83/A
51000 Rijeka, Croatia
Phone: +385 (51) 770 447
Fax: +385 (51) 686 166
www.intechopen.com

InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai
No.65, Yan An Road (West), Shanghai, 200040, China
中国上海市延安西路65号上海国际贵都大饭店办公楼405单元
Phone: +86-21-62489820
Fax: +86-21-62489821

© 2011 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the [Creative Commons Attribution-NonCommercial-ShareAlike-3.0 License](https://creativecommons.org/licenses/by-nc-sa/3.0/), which permits use, distribution and reproduction for non-commercial purposes, provided the original is properly cited and derivative works building on this content are distributed under the same license.

IntechOpen

IntechOpen