We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists

6,300

Open access books available

172,000

International authors and editors

190M

Downloads

Our authors are among the

154

Countries delivered to

TOP 1%

most cited scientists

12.2%

Contributors from top 500 universities

WEB OF SCIENCE™

Selection of our books indexed in the Book Citation Index
in Web of Science™ Core Collection (BKCI)

Interested in publishing with us?
Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected.
For more information visit www.intechopen.com

Weibull Distribution for Estimating the Parameters

Paritosh Bhattacharya

*Department of Mathematics, College of Engineering & Management, Kolaghat
India*

1. Introduction

Today, most electrical energy is generated by burning huge fossil fuels and special weather conditions such as acid rain and snow, climate change, urban smog, regional haze, several tornados, etc., have happened around the whole world. It is now clear that the installation of a number of wind turbine generators can effectively reduce environmental pollution, fossil fuel consumption, and the costs of overall electricity generation. Although wind is only an intermittent source of energy, it represents a reliable energy resource from a long-term energy policy viewpoint. Among various renewable energy resources, wind power energy is one of the most popular and promising energy resources in the whole world today. At a specific wind farm, the available electricity generated by a wind power generation system depends on mean wind speed (MWS), standard deviation of wind speed, and the location of installation. Since year-to-year variation on annual MWS is hard to predict, wind speed variations during a year can be well characterized in terms of a probability distribution function (pdf). This paper also addresses the relations among MWS, its standard deviation, and two important parameters of Weibull distribution.

The wind resource varies with of the day and the season of the year and even some extent from year to year. Wind energy has inherent variances and hence it has been expressed by distribution functions. In this paper, we present some methods for estimating Weibull parameters, namely, shape parameter (k) and scale parameter (c). The Weibull distribution is an important distribution especially for reliability and maintainability analysis. The suitable values for both shape parameter and scale parameters of Weibull distribution are important for selecting locations of installing wind turbine generators. The scale parameter of Weibull distribution also important to determine whether a wind farm is good or not. The presented method is the analytical methods and computational experiments on the presented methods are reported.

2. Weibull distribution

The Weibull distribution is characterized by two parameters, one is the shape parameter k (dimensionless) and the other is the scale parameter c (m/s)

The cumulative distribution function is given by

$$F(v) = 1 - \exp \left[- \left(\frac{v}{c} \right)^k \right] \quad (1)$$

And the probability function is given by

$$f(v) = \frac{dF(v)}{dv} = \frac{k}{c} \left(\frac{v}{c} \right)^{k-1} \exp \left[- \left(\frac{v}{c} \right)^k \right] \quad (2)$$

The average wind speed can be expressed as

$$\bar{v} = \int_0^{\infty} v f(v) dv = \int_0^{\infty} \frac{vk}{c} \left[\left(\frac{v}{c} \right)^{k-1} \right] \exp \left[- \left(\frac{v}{c} \right)^k \right] dv \quad (3)$$

$$\text{Let } x = \left(\frac{v}{c} \right)^k, \quad x^{\frac{1}{k}} = \frac{v}{c} \quad \text{and} \quad dx = \frac{k}{c} \left(\frac{v}{c} \right)^{k-1} dv$$

Equation (3) can be simplified as

$$\bar{v} = c \int_0^{\infty} x^{\frac{1}{k}} \exp(-x) dx \quad (4)$$

By substituting a Gamma Function

$$\Gamma(n) = \int_0^{\infty} e^{-x} x^{n-1} dx \quad \text{into (4) and let } y = 1 + \frac{1}{k} \text{ then we have}$$

$$\bar{v} = c \Gamma \left(1 + \frac{1}{k} \right) \quad (5)$$

The standard deviation of wind speed v is given by

$$\sigma = \sqrt{\int_0^{\infty} (v - \bar{v})^2 f(v) dv} \quad (6)$$

i.e.

$$\begin{aligned} \sigma &= \sqrt{\int_0^{\infty} (v^2 - 2v\bar{v} + \bar{v}^2) f(v) dv} \\ &= \sqrt{\int_0^{\infty} v^2 f(v) dv - 2\bar{v} \int_0^{\infty} v f(v) dv + \bar{v}^2} \\ &= \sqrt{\int_0^{\infty} v^2 f(v) dv - 2\bar{v} \cdot \bar{v} + \bar{v}^2} \end{aligned} \quad (7)$$

Use

$$\int_0^{\infty} v^2 f(v) dv = \int_0^{\infty} v^2 \frac{k}{c} \left(\frac{v}{c}\right)^{k-1} dv = \int_0^{\infty} c^2 x^{\frac{2}{k}} \frac{k}{c} \left(\frac{v}{c}\right)^{k-1} dv = \int_0^{\infty} c^2 x^{\frac{2}{k}} \exp(-x) dx \quad (8)$$

And put $y = 1 + \frac{2}{k}$, then the following equation can be obtained

$$\int_0^{\infty} v^2 f(v) dv = c^2 \Gamma\left(1 + \frac{2}{k}\right) \quad (9)$$

Hence we get

$$\begin{aligned} \sigma &= \left[c^2 \Gamma\left(1 + \frac{2}{k}\right) - c^2 \Gamma^2\left(1 + \frac{1}{k}\right) \right]^{\frac{1}{2}} \\ &= c \sqrt{\Gamma\left(1 + \frac{2}{k}\right) - \Gamma^2\left(1 + \frac{1}{k}\right)} \end{aligned} \quad (10)$$

2.1 Linear Least Square Method (LLSM)

Least square method is used to calculate the parameter(s) in a formula when modeling an experiment of a phenomenon and it can give an estimation of the parameters. When using least square method, the sum of the squares of the deviations S which is defined as below, should be minimized.

$$S = \sum_{i=1}^n w_i^2 [y_i - g(x_i)]^2 \quad (11)$$

In the equation, x_i is the wind speed, y_i is the probability of the wind speed rank, so (x_i, y_i) mean the data plot, w_i is a weight value of the plot and n is a number of the data plot. The estimation technique we shall discuss is known as the Linear Least Square Method (LLSM), which is a computational approach to fitting a mathematical or statistical model to data. It is so commonly applied in engineering and mathematics problem that is often not thought of as an estimation problem. The linear least square method (LLSM) is a special case for the least square method with a formula which consists of some linear functions and it is easy to use. And in the more special case that the formula is line, the linear least square method is much easier. The Weibull distribution function is a non-linear function, which is

$$F(v) = 1 - \exp\left[-\left(\frac{v}{c}\right)^k\right] \quad (12)$$

i.e.

$$\frac{1}{1 - F(v)} = \exp\left[\left(\frac{v}{c}\right)^k\right] \quad (13)$$

i.e.

$$\ln\left\{\frac{1}{1 - F(v)}\right\} = \left[\left(\frac{v}{c}\right)^k\right] \quad (14)$$

But the cumulative Weibull distribution function is transformed to a linear function like below:

Again

$$\ln \ln \left\{ \frac{1}{1 - F(v)} \right\} = k \ln v - k \ln c \quad (15)$$

Equation (15) can be written as $Y = bX + a$ where

$$Y = \ln \ln \left\{ \frac{1}{1 - F(v)} \right\}, \quad X = \ln v, \quad a = -k \ln c, \quad b = k$$

By Linear regression formula

$$b = \frac{n \sum_{i=1}^n X_i Y_i - \sum_{i=1}^n X_i \sum_{i=1}^n Y_i}{n \sum_{i=1}^n X_i^2 - \left(\sum_{i=1}^n X_i \right)^2} \quad (16)$$

$$a = \frac{\sum_{i=1}^n X_i^2 \sum_{i=1}^n Y_i - \sum_{i=1}^n X_i \sum_{i=1}^n X_i Y_i}{n \sum_{i=1}^n X_i^2 - \left(\sum_{i=1}^n X_i \right)^2} \quad (17)$$

2.2 Maximum Likelihood Estimator(MLE)

The method of maximum likelihood (Harter and Moore (1965a), Harter and Moore (1965b), and Cohen (1965)) is a commonly used procedure because it has very desirable properties.

Let $x_1, x_2, \dots, x_n$ be a random sample of size n drawn from a probability density function $f(x, \theta)$ where θ is an unknown parameter. The likelihood function of this random sample is the joint density of the n random variables and is a function of the unknown parameter. Thus

$$L = \prod_{i=1}^n f_{X_i}(x_i, \theta) \quad (18)$$

is the Likelihood function. The Maximum Likelihood Estimator (MLE) of θ , say $\bar{\theta}$, is the value of θ , that maximizes L or, equivalently, the logarithm of L . Often, but not always, the MLE of θ is a solution of

$$\frac{d \log L}{d \theta} = 0 \quad (19)$$

Now, we apply the MLE to estimate the Weibull parameters, namely the shape parameter and the scale parameters. Consider the Weibull probability density function (pdf) given in (2), then likelihood function will be

$$L(x_1, x_2, \dots, x_n, k, c) = \prod_{i=1}^n \left(\frac{k}{c} \right) \left(\frac{x_i}{c} \right)^{k-1} e^{-\left(\frac{x_i}{c} \right)^k} \quad (20)$$

On taking the logarithms of (20), differentiating with respect to k and c in turn and equating to zero, we obtain the estimating equations

$$\frac{\partial \ln L}{\partial k} = \frac{n}{k} + \sum_{i=1}^n \ln x_i - \frac{1}{c} \sum_{i=1}^n x_i^k \ln x_i = 0 \quad (21)$$

$$\frac{\partial \ln L}{\partial c} = \frac{-n}{c} + \frac{1}{c^2} \sum_{i=1}^n x_i^k = 0 \quad (22)$$

On eliminating c between these two above equations and simplifying, we get

$$\frac{\sum_{i=1}^n x_i^k \ln x_i}{\sum_{i=1}^n x_i^k} - \frac{1}{k} - \frac{1}{n} \sum_{i=1}^n \ln x_i = 0 \quad (23)$$

which may be solved to get the estimate of k . This can be accomplished by Newton-Raphson method. Which can be written in the form

$$x_{n+1} = x_n - \frac{f(x_n)}{f'(x_n)} \quad (24)$$

Where

$$f(k) = \frac{\sum_{i=1}^n x_i^k \ln x_i}{\sum_{i=1}^n x_i^k} - \frac{1}{k} - \frac{1}{n} \sum_{i=1}^n \ln x_i \quad (25)$$

And

$$f'(k) = \sum_{i=1}^n x_i^k (\ln x_i)^2 - \frac{1}{k^2} \sum_{i=1}^n x_i^k (k \ln x_i - 1) - \left(\frac{1}{n} \sum_{i=1}^n \ln x_i \right) \left(\sum_{i=1}^n x_i^k \ln x_i \right) \quad (26)$$

Once k is determined, c can be estimated using equation (22) as

$$c = \frac{\sum_{i=1}^n x_i^k}{n} \quad (27)$$

2.3 Some results

When a location has $c=6$ the pdf under various values of k are shown in Fig. 1. A higher value of k such as 2.5 or 4 indicates that the variation of Mean Wind speed is small. A lower value of k such as 1.5 or 2 indicates a greater deviation away from Mean Wind speed.

Fig. 1. Weibull Distribution Density versus wind speed under a constant value of c and different values of k

When a location has $k=3$ the pdf under various values of c are shown in Fig.2. A higher value of c such as 12 indicates a greater deviation away from Mean Wind speed.

Fig. 2. Weibull Distribution Density versus wind speed under a constant value of $k=3$ and different values of c

Fig. 3 represents the characteristic curve of $\Gamma\left(1 + \frac{1}{k}\right)$ versus shape parameter k . The values of $\Gamma\left(1 + \frac{1}{k}\right)$ varies around .889 when k is between 1.9 to 2.6.

Fig.4 represents the characteristic curve of $\frac{c}{v}$ versus shape parameter k . Normally the wind speed data collected at a specified location are used to calculate Mean Wind speed. A good

estimate for parameter c can be obtained from Fig.4 as $c = 1.128\bar{v}$ where k ranges from 1.6 to 4. If the parameter k is less than unity , the ratio $\frac{c}{\bar{v}}$ decrease rapidly. Hence c is directly proportional to Mean Wind speed for $1.6 \leq k \leq 4$ and Mean Wind speed is mainly affected by c . The most good wind farms have k in this specified range and estimation of c in terms of $\bar{v}$ may have wide applications.

Fig. 3. Characteristic curve of $\Gamma(1+1/k)$ versus Shape parameter k

Fig. 4. Characteristic curve of $c/\bar{v}$ versus shape parameter k

March, 2009	Wind Speed (m/s)	March, 2009	Wind Speed (m/s)
1	0.56	17	0.28
2	0.28	18	0.83
3	0.56	19	1.39
4	0.56	20	1.11
5	1.11	21	1.11
6	0.83	22	0.83
7	1.11	23	0.56
8	1.94	24	0.83
9	1.11	25	1.67
10	0.83	26	1.94
11	1.11	27	1.39
12	1.39	28	0.83
13	0.28	29	2.22
14	0.56	30	1.67
15	0.28	31	2.22
16	0.28		

Example: Consider the following example where x_i represents the Average Monthly Wind Speed (m/s) at kolkata (from 1st March, 2009 to 31st March, 2009)

Also let $F(x_i) = \frac{i}{n+1}$ and using equations (16) and (17) we get $k = 1.013658$ and $c = 29.9931$

But if we apply maximum Likelihood Method we get $k = 1.912128$ and $c = 1.335916$. There is a huge difference in value of c by the above two methods. This is due to the mean rank of $F(x_i)$ and k value is tends to unity.

3. Conclusions

In this paper, we have presented two analytical methods for estimating the Weibull distribution parameters. The above results will help the scientists and the technocrats to select the location for Wind Turbine Generators.

4. Appendix

Those who are not familiar with the units or who have data given in units of other systems (For example wind speed in kmph), here is a short list with the conversion factors for the units that are most relevant for design of Wind Turbine Generators

Length	1m = 3.28 ft
Area	1m ² =10.76 ft ²
Volume	1m ³ = 35.31 ft ³ =264.2 gallons
Speed	1m/s=2.237mph 1knot=.5144 m/s=1.15 mph
Mass	1 kg=2.20 5lb
Force	1N=0.225 lbf=0.102 kgf
Torque	1Nm=.738 ft lbf
Energy	1J= 0.239 Calories= 0.27777*10 ⁻⁶ kWh= 1 Nm
Power	1 W=1Watt=1 J/s=0.738 ft lbf/s= 1Nm/s 1 hp = 0.7457 kW 1 pk = 0.7355 Kw

5. References

Mann, N. R., Schafer, R. E., and Singpurwalla, N. D., Methods for statistical analysis of reliability and life data, 1974, John Wiley and Sons, New York.

Engelhardt, M., "On simple estimation of the parameters of the Weibull or extreme-value distribution", Technometrics, Vol. 17, No. 3, August 1975.

Mann, N. R. and K. W. Fertig , "Simplified efficient point and interval estimators of the Weibull parameters", Technometrics, Vol. 17, No. 3, August 1975

Cohen, A. C., "Maximum likelihood estimation in the Weibull distribution based on complete and on censored samples", Technometrics, Vol. 7, No. 4, November 1965.

Harter, H. L. and A. H. Moore, "Point and interval estimators based on order statistics, for the scale parameter of a Weibull population with known shape parameter", Technometrics, Vol. 7, No. 3, August 1965a

Harter, H. L. and A. H. Moore, "Maximum likelihood estimation of the parameters of Gamma and Weibull populations from complete and from censored samples", Technometrics, Vol. 7, No. 4, November 1965b

Stone, G. C. and G. Van Heeswijk, "Parameter estimation for the Weibull distribution , IEEE Trans. On Elect Insul. VolEI-12, No-4, August, 1977.

P. Gray and L. Johnson, *Wind Energy System*. Upper Saddle River, NJ: Prentice-Hall, 1985.

W.A.M Jansen and P.T Smulders "Rotor Design for Horizontal Axis Windmills" Development Corporation Information Department, Netherlands, May 1977

IntechOpen

IntechOpen

Wind Energy Management

Edited by Dr Paritosh Bhattacharya

ISBN 978-953-307-336-1

Hard cover, 128 pages

Publisher InTech

Published online 22, September, 2011

Published in print edition September, 2011

The book "Wind Energy Management" is a required part of pursuing research work in the field of Renewable Energy at most universities. It provides in-depth knowledge to the subject for the beginners and stimulates further interest in the topic. The salient features of this book include: - Strong coverage of key topics - User friendly and accessible presentation to make learning interesting as much as possible - Its approach is explanatory and language is lucid and communicable - Recent research papers are incorporated

How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Paritosh Bhattacharya (2011). Weibull Distribution for Estimating the Parameters, Wind Energy Management, Dr Paritosh Bhattacharya (Ed.), ISBN: 978-953-307-336-1, InTech, Available from:
<http://www.intechopen.com/books/wind-energy-management/weibull-distribution-for-estimating-the-parameters>

INTECH
open science | open minds

InTech Europe

University Campus STeP Ri
Slavka Krautzeka 83/A
51000 Rijeka, Croatia
Phone: +385 (51) 770 447
Fax: +385 (51) 686 166
www.intechopen.com

InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai
No.65, Yan An Road (West), Shanghai, 200040, China
中国上海市延安西路65号上海国际贵都大饭店办公楼405单元
Phone: +86-21-62489820
Fax: +86-21-62489821

© 2011 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the [Creative Commons Attribution-NonCommercial-ShareAlike-3.0 License](https://creativecommons.org/licenses/by-nc-sa/3.0/), which permits use, distribution and reproduction for non-commercial purposes, provided the original is properly cited and derivative works building on this content are distributed under the same license.

IntechOpen

IntechOpen