We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists

6,300

Open access books available

172,000

International authors and editors

190M

Downloads

Our authors are among the

154

Countries delivered to

TOP 1%

most cited scientists

12.2%

Contributors from top 500 universities

WEB OF SCIENCE™

Selection of our books indexed in the Book Citation Index
in Web of Science™ Core Collection (BKCI)

Interested in publishing with us?
Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected.
For more information visit www.intechopen.com

Effect of Photochemical Advanced Oxidation Processes on the Bioamenability and Acute Toxicity of an Anionic Textile Surfactant and a Textile Dye Precursor

Idil Arslan-Alaton and Tugba Olmez-Hanci
*Istanbul Technical University
 Turkey*

1. Introduction

Surfactants are frequently being used as cleaning, dissolving and wetting agents in household activities and several industries (Utsunomiya et al., 1997; Van de Plassche et al., 1999). For instance in various textile preparation operations (scouring, mercerising, bleaching), surfactant formulations are employed in order to allow thorough wetting of the textile material, emulsification of lipophilic impurities and dispersion of insoluble matter and degradation products (Arslan-Alaton et al., 2007; EU, 2003). Anionic (including alkyl sulphonates, alkyl aryl sulphonates, alkyl sulphates, dialkylsulphosuccinates, and others) and especially nonionic surfactants are the chemicals being more often used for this particular purpose. These multi-purpose surfactants create the main organic pollution load in effluents originating from the above mentioned activities. Surfactants enter the environment mainly through the discharge of sewage effluents into natural water and the application sewage sludge on land for soil fertilizing purposes (Petrovic & Barceló, 2004). Although most of these surfactants are designated as “biodegradable” according to different long-term biodegradability tests (Euratex, 2000) former studies dealing with the biodegradability of surfactants have indicated that their biodegradation in conventional activated sludge treatment systems is in most cases rather incomplete, resulting in the accumulation of partial biodegradation products (Ikehata & El-Din, 2004; Swisher, 1987). A lot of commercial surfactants used today by different industries tend to sorb and hence accumulate on sludge and soil sediments in receiving water bodies due to their amphiphilic characteristics (Swisher, 1987; Staples et al., 2001). Hence, when a surfactant is discharged into the environment without proper treatment at source (e.g. at the treatment facilities of the textile factory), it will enter the sewage treatment works or directly natural waters without any significant structural alteration and may cause serious ecotoxicological consequences due to its bioaccumulation tendency (Ikehata & El-Din, 2004). Consequently, more effective and at the same time economically feasible treatment processes have to be applied to alleviate the problem of partially adsorbed and/or metabolized surfactants in the environment. Moreover, the management of biologically-difficult-to-degrade effluent discharges bearing surfactants remains an important challenge that has to be urgently solved to reduce the concentration of surfactants in effluent discharge at source.

Aryl sulphonates are commercially important textile dye precursors; their global production for dye synthesis is limited to a few countries (e.g. China, India, Pakistan and Egypt) where they create serious environmental problems since they are biologically inert in natural as well as engineered aerobic biotreatment systems. Moreover, due to their very polar and hydrophilic nature, sulphonated textile dye precursors are very mobile in the aquatic ecosystem and hence very difficult to treat via conventional methods (i.e. coagulation, precipitation, adsorption). In addition, it has been postulated that the anaerobic metabolites of sulphonates bearing aromatic amines in their molecular structure are potentially mutagenic and even carcinogenic. From the environmental point of view, the fate of aryl sulphonates and their degradation products in biological treatment units as well as receiving water bodies is still not very clear since until now only limited attention has been paid towards their occurrence, fate and degradability in engineered systems as well as in the natural environment (Jandera et al., 2001). Due to the fact that conventional biological, physical and chemical treatment methods are not very effective in the removal of naphthalene sulphonates, alternative options have to be considered and evaluated.

In the last three decades, so-called Advanced Oxidation Processes (AOPs) have been developed and explored for the treatment of toxic and/or refractory pollutants and wastewaters. Their efficiency and oxidation power relies on the formation of very active species including hydroxyl radicals ($\text{HO}^\bullet$) that violently and nonselectively react with most organic pollutants at diffusion limited rates. Bimolecular rate coefficients obtained for the free radical chain reaction initiated by $\text{HO}^\bullet$ are typically in the range of 10^7 - $10^{11} \text{ M}^{-1} \text{ s}^{-1}$ for most pollutants depending on their structural properties. Among the AOPs, photochemical processes including the UV-C photolysis of H_2O_2 and the Photo-Fenton reaction (UV-C photolysis of H_2O_2 catalyzed by Fe^{2+} ions under acidic pH conditions) are known as the most efficient, feasible and kinetically favorable types. The major drawbacks of AOPs can be listed as (i) their relatively high electrical energy requirements dramatically affecting their operating costs and hence real-scale application as well as (ii) the possibility of undesired oxidation products (more toxic and less bioamenable than the mother pollutant) formation and build-up due to kinetically difficult to control chain reactions in the treatment system. Baxendale and Wilson (1957) first studied the UV-C photolysis of H_2O_2 in water that is the most direct method of $\text{HO}^\bullet$ generation through the homolytic cleavage of H_2O_2 . The following set of reactions explains the main steps of the mechanism of the H_2O_2 photolytic decomposition in water;

The quantum yield of reaction (4) is 1.0 mole $\text{HO}^\bullet$ per mole of photons (1.0 einstein) absorbed by H_2O_2 (Prousek, 1996). The molar absorption coefficient of H_2O_2 at 254 nm is only $18.6 \text{ M}^{-1} \text{ cm}^{-1}$ and hence the efficiency of the H_2O_2 /UV-C process decreases drastically with increasing pollutant concentration and UV_{254} absorbance of the target chemical (CCOT 1995). For heavily polluted effluents, high UV-C doses and/or H_2O_2 concentrations are required.

The Fenton process is being increasingly used in the treatment of organic pollutants. The conventional dark Fenton process involves the use of one or more oxidizing agents (usually H_2O_2 and/or oxygen) and a catalyst (a metal salt or oxide, usually iron) at acidic pHs. Fenton process is efficient only in the pH range 2-4 and is usually most efficient at around pH 2.8 (Pignatello, 1992). In acidic water medium, the most accepted scheme of this radical mechanism is described in the following equations (Sychev & Isak, 1995):

Photo-Fenton oxidation is the photo-catalytically enhanced version of the Fenton process; in the Photo-Fenton process; UV light irradiation (180-400 nm) causes an increase in the $\text{HO}^\bullet$ formation rate and efficiency via photoreduction of Fe^{3+} to Fe^{2+} , thus continuing the redox cycle as long as H_2O_2 is available (Pignatello, 1992; Wadley & Waite, 2004). The reason for the positive effect of irradiation on the degradation rate include the photoreduction of Fe^{3+} to Fe^{2+} ions, which produce new $\text{HO}^\bullet$ with H_2O_2 (Eq. 6) according to the following mechanism;

The main compounds absorbing UV light in the Fenton system are ferric ion complexes, e.g. $[\text{Fe}^{3+}(\text{OH})]^{2+}$ and $[\text{Fe}^{3+}(\text{RCO}_2)]^{2+}$, which produce additional Fe^{2+} by the following photo-induced, ligand-to-metal charge-transfer reactions (Sagawe et al., 2001);

Additionally, reaction (14) yields $\text{HO}^\bullet$, while reaction (15) results in a decrease of the total organic carbon (TOC) content of the system due to the decarboxylation of organic acid intermediates. It is very important to note that both reactions produce ferrous ions required for the Fenton reaction (Eq. 6). The overall degradation rate of organic compounds is considerably increased in the Photo-Fenton process, even at lower concentration of iron salts present in the system (Chen & Pignatello, 1997). The main disadvantage of the iron based

AOPs is the necessity to work at low pH, because at higher pH ferric ions would begin to precipitate as hydroxide. Furthermore, depending on the iron concentration used, it has to be removed after the treatment in agreement with the regulation established for wastewater discharge (Rodríguez, 2003).

Information about the toxicity of organic pollutants and advanced oxidation intermediates appears to be a key factor in order to evaluate the applicability of the AOPs. It should be considered that advanced oxidation may result in the formation of more inert and/or toxic degradation products, since free radical chain reaction-based treatment methods are difficult to control thus requiring the toxicity assessment of the formed advanced oxidation intermediates (Farré et al., 2007; Oller et al., 2007; González et al., 2007). Furthermore, in most cases the final goal of AOPs is to improve the biocompatibility of the effluent in order to apply a biological treatment (Scott & Ollis, 1995; Marco et al., 1997). Consequently, the use of short-term biological screening tests that aim to a rapid estimation of the acute toxicity of a pollutant and its oxidation products during AOP applications has become essential. Until now, several studies investigating relative changes in the toxicity of model pollutants have been reported using photobacteria, cladocerans, microalgae and other test organisms (Wang et al., 2002; Dalzell et al., 2002; Stasinakis et al., 2008). Among the available acute toxicity test protocols, the assessment of respirometric inhibition (decrease in oxygen uptake rate of microorganisms relative to a control sample; e.g. synthetic or real sewage) is an attractive and advantageous option since heterotrophic biomass being present in biological treatment systems are used as the toxicity test organism that enables the simultaneous assessment of acute toxicity and biodegradability by a single test protocol (Paixão et al., 2002; Gendig et al., 2003; Henriques et al., 2005; Stasinakis et al., 2008; Olmez-Hanci et al., 2009).

Bearing the above-mentioned facts in mind, the present work aimed at investigating the photochemical advanced oxidation of a commercially important anionic textile surfactant (dodecyl sulpho succinate; DOS) and a frequently used vinyl sulphone dye intermediate, namely Para base (aniline-4-beta-ethyl sulphonyl sulphate-2-sulphonic acid; PB) employing H_2O_2 /UV-C and Photo-Fenton treatment processes. Treatment performances of the H_2O_2 /UV-C and Photo-Fenton processes were evaluated in terms of DOS, PB, COD and TOC removals. Treatment efficiencies, pseudo-first-order reaction rate coefficients and associated electrical energy requirements were comparatively evaluated for DOS and PB degradation with the H_2O_2 /UV-C and Photo-Fenton processes to decide for the technically and economically more attractive treatment solution for each chemical. In the second part of the study, activated sludge inhibition experiments were conducted with untreated and photochemically pretreated DOS and PB samples in order to examine the inhibitory effect of the model pollutant and advanced oxidation intermediates on the respirometric activity of activated sludge microorganisms.

2. Materials and methods

2.1 Chemicals and reagents

DOS and PB model compounds were supplied by a local textile chemical company and used as received without further purification. Some physicochemical and environmental characteristics of the studied model compounds were summarized in Table 1.

Pollutant	DOS	PB
Property		
Molecular Formula	C ₂₀ H ₃₇ NaO ₇ S	C ₈ H ₁₁ O ₉ S ₃
Molecular Weight (g mol ⁻¹)	444	347
g COD(g chemical) ⁻¹	1.54	1.04
g TOC(g chemical) ⁻¹	0.69	0.28
Molecular Structure

Table 1. Physicochemical properties of the anionic surfactant (DOS) and the vinyl sulphone dye precursor (PB). The COD and TOC equivalencies shown in Table 1 were experimentally obtained by preparing individual calibration curves for varying DOS and PB concentrations in water and determination of the corresponding COD and TOC values.

35% w/w H₂O₂ (Fluka, USA) was used as received without any dilution. Residual H₂O₂ was destroyed with enzyme catalase derived from *Micrococcus lysodeikticus* (100181 U mL⁻¹, Fluka, USA). The ferrous iron catalyst source was prepared for daily use by dissolving FeSO₄.7H₂O (Fluka, USA) in distilled water to obtain a 10% (w/v) stock solution. Several concentrations of HNO₃ (Merck, Germany) and NaOH (Merck, Germany) solutions were used for pH adjustment. HPLC-grade acetonitrile (Merck, Germany) was used as the mobile phase in the HPLC measurements. All other reagents were analytical grade and used without purification.

2.2 UV-C photoreactor and light source

All photochemical treatment experiments were performed using a 3250 mL-capacity batch stainless steel batch reactor (length=84.5 cm; width=8 cm) equipped with a 40W low-pressure, mercury vapor sterilization lamp that was located at the center of the reactor in a quartz glass envelope. The incident light flux of the UV lamp and effective light path length were determined via H₂O₂ actinometry (Nicole et al., 1990) as 1.6 x 10⁻⁵ einstein L⁻¹ s⁻¹ and 5.1 cm, respectively, at 254 nm. During the photochemical experiments, the reaction solution was continuously circulated through the UV-C photoreactor using a peristaltic pump at a rate of 400 mL min⁻¹. For the H₂O₂/UV-C experiments, H₂O₂ was added to the pH-adjusted aqueous DOS and PB solutions and the reaction mixture was fed to the photoreactor via a peristaltic pump. After the sample t=0 was taken, the reaction was initiated by turning on the UV-C lamp. In case of Photo-Fenton oxidation experiments, after adjusting the initial pH of the reaction solutions to 3.0 ± 0.1, e.g. the optimum pH for Photo-Fenton oxidation (Oliveros et al., 1997), Fe²⁺ catalyst was added. In order to eliminate the effect of the dark Fenton reaction, the other reactant (H₂O₂) was added to the reaction mixture at the very end of the suction period. As the whole solution was fed into photoreactor, UV-C lamp was turned on and photo-oxidation was started. For photochemical oxidation experiments, samples were taken at regular time intervals for analyses up to 180 min.

2.3 Experimental approach

For all photochemical oxidation experiments aqueous solutions of DOS and PB were individually prepared and adjusted to an initial COD of 450 mg L⁻¹ since a typical textile preparation and textile dye synthesis wastewater exerts a COD in the range of 400-500 mg L⁻¹ (Zollinger, 2001). It is known that an optimum H₂O₂ concentration exists for the H₂O₂/UV-C

treatment system depending upon the reaction pH, initial organic carbon content, type and molecular structure of the pollutant under investigation (Muruganandham & Swaminathan, 2004; Arslan-Alaton & Erdinc, 2006). In our preliminary experiments the H_2O_2 concentrations (30 mM) were initially selected close to the stoichiometric oxygen equivalent of the aqueous solutions of DOS and PB ($=\text{COD} \times 2.12 \text{ g H}_2\text{O}_2/\text{g O}_2 \approx 28 \text{ mM H}_2\text{O}_2$). For H_2O_2 /UV-C treatment of DOS at 30 mM H_2O_2 concentration resulted in significant degradation both in DOS and organic carbon content. However, the theoretically established H_2O_2 concentration of 30 mM did not result in significant organic carbon removals for PB (data not shown). Considering our preliminary results, it was decided to increase the initial H_2O_2 concentration to 60 mM for H_2O_2 /UV-C treatment of PB. The initial reaction pH was selected as 10.5 for H_2O_2 /UV-C treatment of aqueous DOS solutions, since the effluent pH of a typical textile preparation is in the range 10–11 (EU, 2003), and in previous studies it was observed that the H_2O_2 /UV-C oxidation process was practically pH-independent, and no significant changes in the reaction rate constants were found over a wide pH range of 3–11 (Arslan-Alaton & Erdinc, 2006; Arslan-Alaton et al., 2007). H_2O_2 /UV-C treatment of aqueous PB solutions was investigated at a reaction pH of 3.0.

For Photo-Fenton experiments, H_2O_2 (30 mM) and Fe^{2+} (0.5 mM) concentrations were selected upon consideration of optimum Fe^{2+} : H_2O_2 molar ratios obtained in former related research work and our own experiences in similar case studies (Arslan-Alaton et al., 2009a; 2009b; 2010). Photo-Fenton experiments were conducted at a fixed pH value of 3.0 ± 0.1 that is generally accepted as the optimum pH for iron-based AOPs (Pignatello, 1992).

As being expected for photochemical AOPs (Oppenländer, 2003), the degradation of the original pollutants (in our case DOS and PB) is usually faster than that of their oxidation products, which are typically expressed in terms of the collective parameters COD and TOC. It was also taken into account that treatment conditions may vary for the removal of original pollutant and its degradation products that are usually collectively presented with the environmental sum parameters COD and TOC. Thus in the present study, the process efficiencies were assessed both in terms of DOS and PB, COD and TOC abatement rates. Residual (unreacted) H_2O_2 and pH were also recorded during the entire treatment period. The pH and ionic strength of the synthetic solutions were not controlled throughout the experiments. All experiments were conducted at a constant temperature of 20°C .

As aforementioned, information about the toxicity of degradation intermediates as well as original pollutants appears to be a key issue for the application of AOPs in water and wastewater treatment as well as integrated chemical and biochemical treatment options (Scott & Ollis, 1995; Farré et al., 2007). By considering this important issue in the last stage of the experimental work, relative changes in the inhibitory effect of DOS and PB photochemical degradation intermediates on heterotrophic biomass (sewage sludge) during the application of photochemical oxidation were also examined.

2.4 Activated sludge inhibition experiments

The procedure of the activated sludge inhibition test was based on the test protocol given in the ISO 8192 Method (2007). This method describes the way to assess the inhibitory effects of a test substance on oxygen consumption of activated sludge (resembling sewage) by measuring the respiration rate under defined conditions in the presence of a known biodegradable substrate and different concentrations of the test substance (Ubay Cokgor et al., 2007). The activated sludge used as the heterotrophic biomass was obtained from a municipal tertiary wastewater treatment located in Istanbul and daily fed with synthetic

sewage in accordance with the same test protocol (ISO 8192, 2007). The heterotrophic biomass concentration in the activated sludge was determined according to Standard Methods (APHA/AWWA/WEF, 2005) and expressed as mg L^{-1} of mixed liquid volatile suspended solids (MLVSS). All experiments were run at constant heterotrophic active biomass concentration of 1500 mg L^{-1} to obtain appropriate oxygen uptake rates (OUR) of around $100 \text{ mg L}^{-1} \text{ h}^{-1}$. The COD of the synthetic sewage was adjusted to 480 mg L^{-1} and used as the “readily biodegradable substrate” in the activated sludge inhibition experiments. Any unreacted H_2O_2 remaining in the reaction samples was destroyed with catalase enzyme and the pH of the solutions was adjusted to 7.0 ± 0.2 before conducting the toxicity tests in order to eliminate potential inhibitory effects of hydrogen peroxide and pH, respectively. The blank control was prepared using the same amount of activated sludge and synthetic sewage solution as in the test dilutions, but without adding untreated or treated aqueous DOS and PB samples. The decrease in dissolved oxygen concentration in the blank control and reaction samples was periodically monitored using a WTW InolabOxi Level 2 oxygen meter at different incubation times (15–180 min). OUR values were calculated on the basis of the linear part of the decreasing dissolved oxygen concentration curves versus test time. Percent inhibition of oxygen consumption (I_{OUR}), for every test sample was calculated using the following equation;

$$I_{\text{OUR}}(\%) = [(R_{\text{B}} - R_{\text{T}}) \times 100] / R_{\text{B}} \quad (16)$$

where R_{B} stands for the OUR in the sample blank and R_{T} is the OUR in the sample effluent mixture, respectively. The I_{OUR} values were, thereafter, plotted against the logarithm of the DOS and PB concentrations. The DOS and PB concentrations resulting in percent decrease in OUR's (in mg L^{-1} DOS or PB) after 15 min incubation period was eventually calculated by interpolation of the “log DOS” or “log PB” versus percent “ I_{OUR} ” plots obtained for different DOS and PB concentrations.

2.5 Analytical procedures

Reaction samples were analyzed for DOS-PB, COD, TOC, residual H_2O_2 and pH before, during and after photochemical treatment. CODs were determined by the closed reflux titrimetric method according to ISO 6060 (1989). In order to prevent the positive interference of H_2O_2 to COD analyses, the pH of each sample solution was adjusted to 6.5–7.5 and thereafter catalase enzyme made from *Micrococcus lysodeikticus* (1AU destroys $1 \mu\text{mol H}_2\text{O}_2$ at $\text{pH}=7$, 100181 U mL^{-1} , Fluka grade) was added to destroy any residual H_2O_2 .

TOC was monitored on a Shimadzu VPCN model carbon analyzer (combustion method) equipped with an autosampler. Residual H_2O_2 in the samples was determined titrimetrically by employing the molibdate-catalyzed iodometric method (Official Methods of Analysis, 1980).

The amount of DOS and PB in the aqueous solutions was measured by high-performance liquid chromatography (HPLC, Agilent 1100 Series, USA). DOS was determined with a fluorescence detector (FLD; $\lambda_{\text{ex}} = 225 \text{ nm}$, $\lambda_{\text{em}} = 295 \text{ nm}$) and a C8 column. $3 \text{ mM NaCl} / \text{CH}_3\text{CN}$ (80/20; v/v) served as the mobile phase (flow rate of 1.5 mL min^{-1}) for DOS. The instrument detection limit for DOS (1.5 mg L^{-1}) was determined as the lowest injected standard that gave a signal-to-noise ratio of at least 3 and an accuracy of 80–95%.

PB abatement was monitored with a diode array detector (DAD; $\lambda = 276 \text{ nm}$) and a Novapack C_{18} (Waters, USA) column. $\text{CH}_3\text{CN}/\text{H}_2\text{O}$ (60/40; v/v) was used as mobile phase for the analysis of PB at a flow rate of 1 mL min^{-1} . The column temperature was set as 30°C .

for all measurements and the injection volume was selected as 30 μL . The instrument detection limit (1.5 mg L^{-1}) for PB was determined as the lowest injected standard that gave a signal-to-noise ratio of at least 3 and an accuracy of 80-95%. The limit of quantification was calculated as 10 times of the signal-to-noise ratio as 5 mg L^{-1} .

In case of Photo-Fenton $\text{Fe}^{2+}/\text{H}_2\text{O}_2/\text{UV-C}$ experiments, all analytical measurements were performed after filtration of the treated samples through a $0.45 \mu\text{m}$ membrane filter (Sartorius) in order to remove the settled $\text{Fe}(\text{OH})_3$ sludge. The pH was measured with a Thermo Orion model 720 pH-meter at any stage of the experiments.

2.6 Kinetic analysis

DOS and PB abatements during $\text{H}_2\text{O}_2/\text{UV-C}$ and Photo-Fenton treatment processes followed pseudo-first order kinetics with respect to the model pollutant (DOS and PB). Hence, the kinetic rates could be expressed as follows;

$$\ln C/C_0 = -k_C \times t \quad (17)$$

where k_C is the pseudo-first order rate constant (in min^{-1}), t stands for photochemical treatment time (in min), C_0 and C are the initial and final concentrations of model pollutant (DOS and PB, in mg L^{-1}).

2.7 Electrical energy requirements of the photochemical treatment processes

The photodegradation of aqueous organic pollutants is an energy-intensive process, thus consideration of figures-of-merit definition based on the electrical energy input is appropriate. In order to compare treatment efficiencies for photochemical oxidation processes, it is important to use a general expression and relate the treatment efficiencies directly to operating costs. For this purpose, the electrical energy per order (EE/O) defined as the kWh electrical energy required to degrade a contaminant or group parameter by one order of magnitude in m^3 of contaminant water or wastewater, can be calculated for treatment process (Bolton et al., 2001). Since the EE/O ($\text{kWh m}^{-3} \text{ order}^{-1}$) concept assumes pseudo-first order degradation kinetics with respect to pollutant concentration can be determined from the following formula;

$$\text{EE/O (kWh m}^{-3} \text{ order}^{-1}) = (38.4 \times P) / (V \times k_C) \quad (18)$$

where P is the lamp power (0.04 kW in the present work), V is the reactor volume (3.25 L in the present work), and k_C is the pseudo-first-order rate constant of DOS and PB degradation (min^{-1}).

3. Results and discussion

3.1 Activated sludge inhibition experiments with untreated DOS and PB

The ISO 8192 (2007) specifies a method for assessing the inhibitory or stimulatory effects of substances, mixtures or wastewaters to activated sludge (Paixão et al., 2002). Information generated by this method may be helpful in estimating the effect of a test material on bacterial communities in the aquatic environment, especially in aerobic biological treatment systems (Paixão et al., 2002). In the first part of this experimental study, untreated (original) aqueous DOS and PB solutions were individually exposed to activated sludge inhibition experiments. The obtained semi-logarithmic I_{OUR} (in %) versus DOS and PB concentrations (log DOS and log PB) were presented in Figure 1 (a) and (b), respectively for an incubation period of 15 min.

From Figure 1 (a) it is evident that increasing the DOS concentration resulted in an accelerated inhibition of the OUR value measured relative to the sample blank (synthetic sewage). The I_{OUR} values ranged between 4%-53% from the lowest to highest studied concentrations, respectively, enabling the determination of EC_{30} and EC_{50} values (effective concentrations causing 30 and 50% inhibition in heterotrophic biomass relative to the blank) for DOS, as shown in the insert of Figure 1 (a). These values were established as 338 and 544 $mg\ L^{-1}$ corresponding to the respirometric inhibition levels of 30% and 50%, respectively. This information implied that DOS is an acutely toxic compound at concentrations encountered in the textile preparation process. Hence its treatment after discharge becomes essential. On the other hand, Figure 1 (b) reveals that, although the studied concentration range for PB is appreciably higher, activated sludge inhibition rates always remained below 20%. From the obtained experimental results it can be concluded that PB is not exhibiting an inhibitory/toxic effect on heterotrophic biomass relative to synthetic sewage. However, it should be noted that the inert COD content of PB creates a significant effluent discharge penalty problem for dye synthesis effluent. For both chemicals it is obvious that efficient treatment employing advanced oxidation process is necessary to comply with the environmental regulations and to minimize pollution loads.

Fig. 1. Log(concentration) versus I_{OUR} (%) curves obtained from the activated sludge inhibition experiments for aqueous DOS (a) and PB (b). DOS concentration range: 97-584 $mg\ L^{-1}$; PB concentration range: 144-721 $mg\ L^{-1}$. The selected incubation time is 15 min.

3.2 H₂O₂/UV-C and Photo-Fenton treatment of DOS and PB

Figure 2 presents the H₂O₂/UV-C and Photo-Fenton treatment results for aqueous DOS (a, H₂O₂/UV-C; b, Photo-Fenton) and PB (c, H₂O₂/UV-C; d, Photo-Fenton) solutions in terms of DOS-PB, COD and TOC abatement rates as a function of photochemical treatment time. In the Photo-Fenton experiments all experimental conditions were kept identical with the exception of 0.5 mM Fe²⁺ addition to the reaction solution. The initial COD of the DOS-PB solutions were selected as 450 mg L⁻¹ in these experiments, which is an average, typical COD for effluents containing these model compounds as the main organic pollutant.

As it can be seen from Figure 2 (a) and (b) complete DOS removal was obtained after 60 min for both treatment processes. In terms of the COD parameter, 84% and 92% removals were achieved after 100 min H₂O₂/UV-C and Photo-Fenton treatment, respectively. TOC removals were also close to another; these were obtained as 89% after 100 min H₂O₂/UV-C treatment and 90% at the end of 100 min Photo-Fenton treatment. From these findings it can be concluded that DOS, COD and TOC removal efficiencies were not significantly different or higher for the Photo-Fenton process as compared to H₂O₂/UV-C treatment. Considering that the addition of Fe²⁺ as a photocatalyst and extra chemical as well as the requirement of acidic reaction conditions for iron-based AOPs will affect the operating costs for DOS treatment considerably, it was decided to keep the H₂O₂/UV-C process for DOS treatment. Kinetic rate coefficients and electrical energy calculations shown in Table 2 and explained later on supported this argument.

Figure 2 (c) and (d) depict the results of H₂O₂/UV-C and Photo-Fenton treatment of aqueous PB solution, respectively. As expected, the addition of 0.5 mM Fe²⁺ had a significant positive effect in terms of PB as well as COD and TOC abatement rates as compared with the H₂O₂/UV-C process (see Figure 2 (c) and (d)). Total PB elimination was realized only after 30 min Photo-Fenton treatment, whereas at least 180 min were needed when PB was subjected to H₂O₂/UV-C treatment. Moreover, COD and TOC were only poorly removed via mere H₂O₂/UV-C treatment. For instance, parallel to the slow COD abatement, TOC practically remained unchanged indicating that PB, the mother compound, was converted to different advanced oxidation intermediates but not ultimately oxidized to mineralization end products in the absence of Fe²⁺ ions. At the end of the 120 min treatment period, COD and TOC removals were obtained as 49% (H₂O₂/UV-C treatment) and 98% (Photo-Fenton treatment) as well as 33% (H₂O₂/UV-C treatment) and 100% (Photo-Fenton treatment), respectively. Considering that H₂O₂/UV-C treatment of PB resulted in very poor and insufficient results, Photo-Fenton oxidation appears by far the better option for the efficient treatment of PB.

The results obtained for DOS and PB could be partially attributed to the high absorbance (optical density) of PB at the maximum emission band of the UV-C light source, hindering its effective absorption by H₂O₂, whereas DOS did not compete with H₂O₂ for UV-C light absorption at 254 nm wavelength that is required for the production of HO• radicals via UV-C.

Table 2 summarizes the calculated k_C and EE/O values for the photochemical treatment of DOS and PB in the absence and presence of Fe²⁺ catalyst. From Table 2 it is obvious that for DOS treatment, Fe²⁺ is not essential, whereas the positive effect of the catalyst was very pronounced for PB abatement. Hence, in the forthcoming experiments where changes in the acute toxicity of DOS and PB during photochemical treatment were examined, results were presented only for the selected AOPs (e.g. H₂O₂/UV-C for DOS and Photo-Fenton for PB model pollutants).

Fig. 2. DOS, PB, COD and TOC abatement rates observed during photochemical treatment of DOS (a, H₂O₂/UV-C; b, Photo-Fenton) and PB (c, H₂O₂/UV-C; d, Photo-Fenton). For H₂O₂/UV-C experiments: Initial COD= 450 mg L⁻¹; H₂O₂ = 30 mM (DOS) and 60 mM (PB); pH = 10.5 (DOS) and 3.0 (PB). For Fe²⁺/H₂O₂/UV-C experiments: Initial COD= 450 mg L⁻¹; H₂O₂ = 30 mM; Fe²⁺ = 0.5 mM; pH = 3.0.

Model Pollutants	H ₂ O ₂ /UV-C		Fe ²⁺ /H ₂ O ₂ /UV-C	
	Initial COD= 450 mg L ⁻¹ H ₂ O ₂ = 30 mM (DOS) and 60 mM (PB) pH = 10.5 (DOS) and 3.0 (PB)		Initial COD= 450 mg L ⁻¹ H ₂ O ₂ = 30 mM; Fe ²⁺ = 0.5 mM pH = 3.0	
	k _C (min ⁻¹)	EE/O (kWh m ⁻³ order ⁻¹)	k _C (min ⁻¹)	EE/O (kWh m ⁻³ order ⁻¹)
DOS	0.1500	3.15	0.1016	4.65
PB	0.0230	20.55	0.2084	2.27

Table 2. First-order abatement rate constants and EE/O values derived for the treatment of aqueous DOS and PB solutions with the H₂O₂/UV-C and Fe²⁺/H₂O₂/UV-C processes.

3.3 Activated sludge inhibition results for photochemically treated DOS and PB

The possibility exists that during the applicability of AOPs, more toxic and/or less bioamenable intermediates and/or end products form and accumulate in the reaction solution. In order to evaluate the acute toxicity and bioamenability of photochemical degradation products towards heterotrophic biomass, activated sludge inhibition experiments were conducted during H₂O₂/UV-C of DOS and Photo-Fenton oxidation of PB (Figure 3).

For the activated sludge experiments the OUR of the blank samples (containing only synthetic sewage) was adjusted to around 100 mg L⁻¹ h⁻¹. The OURs of the sample blanks were also given in Figure 3. Figure 3 indicated that a slight increase in the OUR values is observed during photochemical treatment of DOS starting with 71 mg L⁻¹ h⁻¹ and reaching its highest value after 40 min photochemical oxidation. Thereafter, the OUR value dropped down even below its original value indicating that extended oxidation did not improve but reduce the quality of DOS bearing effluent most probably due to the formation of less

biodegradable and hence more inhibitory end products. The trend observed for the OUR values of the PB samples exposed to Photo-Fenton was different; the OUR values increased throughout the entire treatment period from 98 $\text{mg L}^{-1} \text{h}^{-1}$ at the beginning up to 120 $\text{mg L}^{-1} \text{h}^{-1}$ after 80 min Photo-Fenton treatment. These results demonstrate that PB does not cause any inhibitory effect of heterotrophic biomass and the treated reaction solution was even accepted as an extra carbon source for the bioculture as advanced oxidation progressed. The OUR results implied that no acutely toxic/bioinhibitory advanced oxidation products were formed during Photo-Fenton treatment of PB.

Fig. 3. OUR values obtained during photochemical treatment of DOS via $\text{H}_2\text{O}_2/\text{UV-C}$ ($\text{H}_2\text{O}_2=42 \text{ mM}$; $\text{pH}=10.5$) and PB via Photo-Fenton ($\text{Fe}^{2+}=0.72 \text{ mM}$; $\text{H}_2\text{O}_2=40 \text{ mM}$; $\text{pH}=3.0$) processes. Experimental conditions: Initial COD = 450 mg L^{-1} ; Incubation period = 15 min; $\text{OUR}_{\text{blank}}$ for DOS = 92 $\text{mg L}^{-1} \text{h}^{-1}$; $\text{OUR}_{\text{blank}}$ for PB = 118 $\text{mg L}^{-1} \text{h}^{-1}$.

4. Conclusion

The present study aimed at exploring the effect of photochemical advanced oxidation processes ($\text{H}_2\text{O}_2/\text{UV-C}$ and Photo-Fenton treatment) on the treatability and bioamenability of two frequently used industrial chemicals; i.e. an anionic textile surfactant (called DOS herein) and a vinylsulphone dye precursor (called PB herein). The following experimental results were obtained in this work;

- The anionic surfactant DOS exhibited a moderate acute toxicity towards heterotrophic biomass; the respirometric inhibition rate varied between 4% to 53% for the lowest and highest studied DOS concentrations, respectively. Accordingly, EC_{30} and EC_{50} values were established as 338 mg L^{-1} and 544 mg L^{-1} , respectively, for the textile preparation surfactant.
- For the textile dye precursor PB, on the other hand, relative activated sludge inhibition rates always remained below 20% and hence no EC values could be calculated for this model pollutant. Conclusively, PB did not exhibit any toxic effect on activated sludge microorganisms in the studied concentration range.
- DOS, a relatively simply structured, aliphatic compound, could be effectively treated via both $\text{H}_2\text{O}_2/\text{UV-C}$ and Photo-Fenton processes. The difference in the overall removal efficiencies and reaction rate coefficient was not significant and hence it appeared that

mere H_2O_2 /UV-C treatment in the absence of Fe^{2+} photocatalyst was sufficient for complete DOS and associated organic carbon content abatements. The main advantage of the H_2O_2 /UV-C treatment process over Photo-Fenton treatment is its robustness towards reaction pH below pH = 11 hence not requiring a pH adjustment to acidic values.

- For aromatic compounds that strongly absorb UV-C light at 254 nm thus hindering its efficient use by H_2O_2 for $\text{HO}^\bullet$ production, Photo-Fenton treatment improves the degradation rate considerably. PB abatement via H_2O_2 /UV-C treatment process resulted in relatively slow and incomplete degradation rates. In the presence of Fe^{2+} , however, PB degradation was enhanced by a factor of 10 and its removal was complete after 30-40 min Photo-Fenton treatment. These results suggest that the H_2O_2 /UV-C process is not capable of effectively degrading the complicated aromatic structure of PB and under these circumstances; Photo-Fenton treatment is the treatment process of choice.

According to the activated sludge inhibition tests no toxic/bioinhibitory degradation intermediates and/or oxidation end products were formed during and after photochemical treatment of DOS (60 min H_2O_2 /UV-C treatment at an initial pH of 10.5 with 42 mM H_2O_2) and PB (Photo-Fenton treatment for 80 min at pH 3; in the presence of 0.72 mM Fe^{2+} and 40 mM H_2O_2). The obtained findings indicated that photochemical advanced oxidation processes are potential, promising options for the effective treatment of refractory and toxic industrial pollutants.

5. Acknowledgments

The authors acknowledge the financial support of the Scientific and Technological Research Council of Turkey (TUBITAK) under project number 108Y051 and Eksoy Chemicals for the DOS and PB gift samples. The authors also thank Ms. Zeynep Kartal and Ms. Elif Dedetas for their help in the photochemical treatment experiments.

6. References

- American Public Health Association/American Water Works Association/Water Environment Federation (2005). *Standard Methods for the Examination of Water and Wastewater*, 21st Edn., APHA-AWWA-WEF, ISBN 0875530478, Washington D.C., U.S.A.
- Arslan-Alaton, I. & Erdinc, E. (2006). Effect of Photochemical Treatment on the Biocompatibility of a Commercial Nonionic Surfactant Used in the Textile Industry. *Water Research*, Vol.40, No.18, (October 2006), pp. 3409-3418, ISSN 0043-1354
- Arslan-Alaton, I., Cokgor, E.U. & Koban, B. (2007). Integrated Photochemical and Biological Treatment of a Commercial Textile Surfactant: Process Optimization, Process Kinetics and COD Fractionation. *Journal of Hazardous Materials*, Vol.146, No.3, (July 2007), pp. 453-458, ISSN 0304-3894
- Arslan-Alaton, I., Olmez-Hanci, T., Gursoy, B.H. & Tureli, G. (2009a). H_2O_2 /UV-C Treatment of the Commercially Important Aryl Sulfonates H-, K-, J-acid and Para Base: Assessment of Photodegradation Kinetics and Products. *Chemosphere*, Vol.76, No.5, (July 2009), pp. 587-594, ISSN 0045-6535

- Arslan-Alaton, I., Tureli, G. & Olmez-Hanci, T. (2009b). Treatment of Azo Dye Production Wastewaters using Photo-Fenton-Like Advanced Oxidation Processes: Optimization by Response Surface Methodology. *Journal of Photochemistry and Photobiology A: Chemistry*, Vol.202, No.2-3, (February 2009), pp. 142-153, ISSN 1010-6030
- Arslan-Alaton, I., Ayten, N. & Olmez-Hanci, T. (2010). Photo-Fenton-like Treatment of the Commercially Important H-Acid: Process Optimization by Factorial Design and Effects of Photocatalytic Treatment on Activated Sludge Inhibition. *Applied Catalysis B: Environmental*, Vol.96, No.1-2, (April 2010), pp. 208-217, ISSN 0926-3373
- Baxendale, J. & Wilson, J. (1957). The Photolysis of Hydrogen Peroxide at High Light Intensities. *Transactions of the Faraday Society*, Vol.53, pp. 344-356, ISSN 0014-7672
- Bolton, J.R., Bircher, K.G., Tumas, W. & Tolman, C.A. (2001). Figure-of-Merit for the Technical Development and Application of Advanced Oxidation Technologies for both Electric-and Solar-Driven Systems. *Pure and Applied Chemistry*, Vol.73, No.4, (April 2001), pp. 627-637, ISSN 0033-4545
- Calgon Carbon Oxidation Technologies (1995). *The AOP Handbook*, Calgon Carbon Oxidation Technologies (CCOT), Markham, Ontario, Canada
- Chen, R. & Pignatello, J. (1997). Role of Quinone Intermediates as Electron Shuttles in Fenton and Photoassisted Fenton Oxidations of Aromatic Compounds. *Environmental Science and Technology*, Vol.31, No.8, (August 1997), pp. 2399-2406, ISSN 0013-936X
- Dalzell, D.J.B., Alte, S., Aspichueta, E., de la Sota, A., Etxebarria, J., Gutierrez, M., Hoffmann, C.C., Sales, D., Obst, U. & Christofi, N. (2002). A Comparison of Five Rapid Direct Toxicity Assessment Methods to Determine Toxicity of Pollutants to Activated Sludge. *Chemosphere*, Vol.47, No.5, (May 2002), pp. 535-545, ISSN 0045-6535
- European Union (2003). *Reference Document on Best Available Techniques for the Textiles Industry*, European Integrated Pollution Prevention Control (IPPC) Bureau, Seville, Spain.
- Farré, M.J., Brosillon, S., Doménech, X. & Peral, J. (2007). Evaluation of the Intermediates Generated during the Degradation of Diuron and Linuron Herbicides by the Photo-Fenton Reaction, *Journal of Photochemistry and Photobiology A: Chemistry*, Vol.188, No.2-3, (June 2007), pp. 34-42, ISSN 1010-6030
- Gendig, C., Domogala, G., Agnoli, F., Pagga, U. & Strotmann, U.J. (2003). Evaluation and Further Development of the Activated Sludge Respiration Inhibition Test. *Chemosphere*, Vol.52, No.1, (July 2003), pp. 143-149, ISSN 0045-6535
- González, O., Sans, C. & Esplugas, S. (2007). Sulfamethoxazole Abatement by Photo-Fenton. Toxicity, Inhibition and Biodegradability Assessment of Intermediates. *Journal of Hazardous Materials*, Vol.146, No.3, (July 2007), pp. 459-464, ISSN 0304-3894
- Henriques, I.D.S., Holbrook, R.D., Kelly, R.T. & Love, N.G. (2005). The Impact of Floc Size on Respiration Inhibition by Soluble Toxicants-A Comparative Investigation. *Water Research*, Vol.39, No.12, (July 2005), pp. 2559-2568, ISSN 0043-1354
- Ikehata, K. & El-Din, M.G. (2004). Degradation of Recalcitrant Surfactants in Wastewater by Ozonation and Advanced Oxidation Processes: A Review. *Ozone Science and Engineering*, Vol.26, No.4, (August 2004), pp. 327-343, ISSN 0191-9512

- International Standardization Organization (1989). *Water Quality-Determination of the Chemical Oxygen Demand*, 2nd Edn., ISO 6060/TC 147, ICS 13.060.50, Geneva, Switzerland
- International Standardization Organization (2007). *Water Quality-Test for Inhibition of Oxygen Consumption by Activated Sludge for Carbonaceous and Ammonium Oxidation*, 2nd Edn., ISO 8197/TC 147, ICS 13.060.70, Geneva, Switzerland
- Jandera, P., Fischer, J. & Prokes, B. (2001). HPLC Determination of Chlorobenzenes, Benzenesulfonyl Chlorides and Benzenesulfonic Acids in Industrial Wastewater. *Chromatographia*, Vol.54, No.9-10, (November 2001), pp. 581-587, ISSN 0009-5893
- Marco, A., Esplugas, S. & Saum, G. (1997). How and Why Combine Chemical and Biological Processes for Wastewater Treatment. *Water Science and Technology*, Vol.35, No.4, pp. 321-327, ISSN 0273-1223
- Muruganandham, M. & Swaminathan, M. (2004). Decolourisation of Reactive Orange 4 by Fenton and Photo-Fenton Oxidation Technology. *Dyes and Pigments*, Vol.63, No.3, (December 2004), pp. 315-321, ISSN 0143-7208
- Nicole, I., De Laat, J., Dore, M., Duguet, J. P. & Bonnel, C. (1990). Utilisation du Rayonnement Ultraviolet dans le Traitement de Waux: Mesure du Flux Photonique par Actinometrie Chimique au Peroxide d'Hydrogene. *Water Research*, Vol.24, No.2, (February 1990), pp. 157-168, ISSN 0043-1354
- Official Methods of Analysis (1980). *Association of Official Analytical Chemists (AOAC International)*, ISBN 0935584145, Washington D.C., U.S.A.
- Oliveros, E., Legrini, O., Hohl, M., Müller, T. & Braun, A.M. (1997). Industrial Wastewater Treatment: Large-Scale Development of a Light-Enhanced Fenton Reaction. *Chemical Engineering and Processing*, Vol.36, No.5, (September 1997), pp. 397-405, ISSN 0255-2701
- Oller, I., Malato, S., Sánchez-Pérez, J.A., Maldonado, M.I. & Gassó, R. (2007). Detoxification of Wastewater Containing Five Common Pesticides by Solar AOPs-Biological coupled System, *Catalysis Today*, Vol.129, No.1-2, (November 2007), pp. 69-78, ISSN 0920-5861
- Olmez-Hanci, T., Imren, C., Arslan-Alaton, I., Kabdaşlı, I. & Tünay, O. (2009). H₂O₂/UV-C Oxidation of Potential Endocrine Disrupting Compounds: A Case Study with Dimethyl Phthalate. *Photochemical and Photobiological Sciences*, Vol.8, No.5, pp. 620-627, ISSN 1474-905X
- Oppenländer, T. (2003). *Photochemical Purification of Water and Air: Advanced Oxidation Processes (AOPs): Principles, Reaction Mechanisms, Reactor Concepts*, John Wiley, Inc., ISBN 3527305637, Chichester, U.K.
- Paixão, S.M. & Anselmo, A.M. (2002). Effect of Olive Mill Wastewaters on the Oxygen Consumption by Activated Sludge Microorganisms: An Acute Toxicity Test Method. *Journal of Applied Toxicology*, Vol.22, No.3, (May-June 2002), pp. 173-176, ISSN 0260-437X
- Petrovic, M. & Barceló, D. (2004). Fate and Removal of Surfactants and Related Compounds in Wastewater and Sludges, In: *The Handbook of Environmental Chemistry Part I*, Vol. 5, 95-108, Springer, ISSN 1867-979X, Weinheim, Germany

- Pignatello, J.J. (1992). Dark and Photo-Assisted Fe^{3+} -Catalyzed Degradation of Chlorophenoxy Herbicides by Hydrogen Peroxide. *Environmental Science and Technology*, Vol.26, No.5, (May 1992), pp. 944-951, ISSN 0013-936X
- Prousek, J. (1996). Advanced Oxidation Processes for Water Treatment. *Chemical Processes, Chemical Listy*, Vol.90, No.4, (April 1996), pp. 229-237, ISSN 0009-2770
- Rodríguez, M. (2003). *Fenton and UV-Vis Based Advanced Oxidation Processes in Wastewater Treatment: Degradation, Mineralization and Biodegradability Enhancement*, PhD Thesis, Universitat De Barcelona, Facultat De Química, Departament D'enginyeria Química I Metal·lúrgia, Barcelona, Spain
- Sagawe, G., Lehnard, A., Lubber, M., Bahnemann, D. (2001). The Insulated Solar Fenton Hybrid Process: Fundamental Investigations, *Helvetica Chimica Acta*, Vol.84, No.12, pp. 3742-3759, ISSN 0018-019X
- Scott, J.P. & Ollis, D.F. (1995). Integration of Chemical and Biological Oxidation Processes for Water Treatment: Review and Recommendations. *Environmental Progress*, Vol.14, No.2, (May 1995), pp. 88-98, ISSN 0278-4491
- Staples, C.A., Naylor, C.G., Williams, J.B. & Gledhill, W.E. (2001). Ultimate Biodegradation of Alkylphenol Ethoxylate Surfactants and their Biodegradation Intermediates, *Environmental Toxicology and Chemistry*, Vol.20, No.11, (November 2001), pp. 2450-2455, ISSN 0730-7268
- Stasinakis, A.S., Petalas, A.V., Mamais, D. & Thomaidis, N.S. (2008). Application of the OECD 301F Respirometric Test for the Biodegradability Assessment of Various Potential Endocrine Disrupting Chemicals. *Bioresources Technology*, Vol.99, No.9, (June 2008), pp. 3458-3467, ISSN 0960-8524
- Sychev, A.Y. & Isak, V.G. (1995). Iron Compounds and the Mechanisms of the Homogeneous Catalysis of the Activation of O_2 and H_2O_2 and of the Activation of Organic Substrates. *Russian Chemical Reviews*, Vol. 64, No.12, pp. 1105-1129, ISSN 0036-021X
- Swisher, R.D. (1987). *Surfactant Biodegradation*, 2nd Edn., Marcel Dekker, ISBN 0824769384, New York, U.S.A.
- The European Apparel and Textile Confederation (2000), *Textile Industry BREF Document*, Chapters 2-6, Euratex, Brussels, Belgium
- Ubay Cokgor, E., Ozdemir, S., Karahan, O., Insel, G. & Orhon, D. (2007). Critical Appraisal of Respirometric Methods for Metal Inhibition on Activated Sludge. *Journal of Hazardous Materials B*, Vol.139, No.2, (January 2007), pp. 332-339, ISSN 0304-3894
- Utsunomiya, A., Watanukii, T., Matsusi-Fita, K., Nishina, M. & Tomita, I. (1997). Assessment of the Toxicity of Linear Alkylbenzene Sulfonate and Quaternary Alkylammonium Chloride by measuring ^{13}C -Glycerol in *Dunaliella* sp. *Chemosphere*, Vol.35, No.11, (December 1997), pp. 2479-2490, ISSN 0045-6535
- Van de Plassche, E.J., De Bruijn, J.H.M., Stephenson, R.R., Marshall, S.J., Feijtel, T.C.J. & Belanger, S.E. (1999). Predicted No-Effect Concentrations and Risk Characterization of Four Surfactants: Linear Alkyl Benzene Sulfonate, Alcohol Ethoxylates, Alcohol Ethoxylated Sulfates, and Soap. *Environmental Toxicology and Chemistry*, Vol.18, No.11, (November 1999), pp. 2653-2663, ISSN 0730-7268

- Wadley, S. & Waite, T.D. (2004). Fenton Processes, In: *Advanced Oxidation Processes for Water and Wastewater Treatment*, S. Parsons, (Ed.), 111-136, IWA Publishing, ISBN 1843390175, Padstow, Cornwall, U.K.
- Wang, C. X., Yediler, A., Lienert, D., Wang, Z. & Kettrup, A. (2002). Toxicity Evaluation of Reactive Dyestuff, Auxiliaries and Selected Effluents in Textile Finishing Industry to Luminescent Bacteria *Vibrio fischeri*. *Chemosphere*, Vol.46. No.2, (January 2002), pp. 339-344, ISSN 0045-6535
- Zollinger, H. (2001). *Color Chemistry*, 3rd Edn., Wiley-VCH, ISBN 3906390233, Weinheim, Germany

Advances in Treating Textile Effluent

Edited by Prof. Peter Hauser

ISBN 978-953-307-704-8

Hard cover, 154 pages

Publisher InTech

Published online 26, October, 2011

Published in print edition October, 2011

The treatment of textile wet processing effluent to meet stringent governmental regulations is a complex and continually evolving process. Treatment methods that were perfectly acceptable in the past may not be suitable today or in the future. This book provides new ideas and processes to assist the textile industry in meeting the challenging requirements of treating textile effluent.

How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Idil Arslan-Alaton and Tugba Olmez-Hanci (2011). Effect of Photochemical Advanced Oxidation Processes on the Bioamenability and Acute Toxicity of an Anionic Textile Surfactant and a Textile Dye Precursor, *Advances in Treating Textile Effluent*, Prof. Peter Hauser (Ed.), ISBN: 978-953-307-704-8, InTech, Available from: <http://www.intechopen.com/books/advances-in-treating-textile-effluent/effect-of-photochemical-advanced-oxidation-processes-on-the-bioamenability-and-acute-toxicity-of-an->

INTech
open science | open minds

InTech Europe

University Campus STeP Ri
Slavka Krautzeka 83/A
51000 Rijeka, Croatia
Phone: +385 (51) 770 447
Fax: +385 (51) 686 166
www.intechopen.com

InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai
No.65, Yan An Road (West), Shanghai, 200040, China
中国上海市延安西路65号上海国际贵都大饭店办公楼405单元
Phone: +86-21-62489820
Fax: +86-21-62489821

© 2011 The Author(s). Licensee IntechOpen. This is an open access article distributed under the terms of the [Creative Commons Attribution 3.0 License](https://creativecommons.org/licenses/by/3.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

IntechOpen

IntechOpen