We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists

6,300

Open access books available

172,000

International authors and editors

190M

Downloads

Our authors are among the

154

Countries delivered to

TOP 1%

most cited scientists

12.2%

Contributors from top 500 universities

WEB OF SCIENCE™

Selection of our books indexed in the Book Citation Index
in Web of Science™ Core Collection (BKCI)

Interested in publishing with us?
Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected.
For more information visit www.intechopen.com

Introductory Chapter: Overview of ZnO Based Nano Materials and Devices

Ahmed M. Nahhas

1. Introduction

This chapter presents an introductory review about ZnO nanomaterials and nanodevices. ZnO as a wide band gap semiconductor has received a great attention in many research areas. This is due to the electrical, optical and structural properties of the ZnO. These properties make ZnO as one of the major contenders for many photonic applications. ZnO has distinguished electrical and optical properties. ZnO is considered as a potential contender in optoelectronic applications such as solar cells and ultraviolet (UV) emitters. The nanostructured ZnO material has many applications in the area of nano based devices. The UV light can be absorbed by the ZnO based nano material. This can be used in several optical applications. Currently, the nano structures based on ZnO materials devices have attracted attention due to their wide range applications.

2. ZnO properties

ZnO is classified as a negative (*n*-type) semiconductor material as grown. ZnO is one of group 2–4 semiconductor materials. ZnO has a band gap of 3.37 eV. ZnO also has a high binding energy. The ZnO binding energy is about 60 meV [1]. The ZnO material has a high exciton binding energy and high thermal stability [2]. It also has a high optical gain [2]. These properties made ZnO as one of the most interesting materials for electronic and optoelectronic based devices. On the other hand, the ZnO's high binding energy permits the fabrication of several photonic devices with a high optical efficiency [3]. Also, the short wavelength optoelectronic devices are being made based on ZnO's wide band gap [3].

ZnO is a transparent optical material suitable for the visible wavelength region [4]. ZnO is also one of the potential materials for optoelectronic applications [5–7]. The ZnO's characteristic properties were investigated by many research groups. That leads to the improvement of the electrical and the optical properties of ZnO. Many other properties of ZnO allow variety of applications. These applications include photovoltaics, LEDs, photodetectors, and microelectromechanical systems (MEMs) [8–12].

3. ZnO crystalline structure

ZnO normally has a hexagonal structure. The Zinc atoms are tetrahedrally coordinated to four oxygen atoms [13]. Moreover, there are two crystalline structure of ZnO. These structures are the wurtzite and the Zinc-blende. These two structures

Figure 1.
ZnO different crystalline structures [3].

of ZnO lead to a perfect polar symmetry along the hexagonal axis of the ZnO’s crystalline structure. The ZnO based piezoelectricity and spontaneous polarization are due to these crystalline structures. The two ZnO’s crystalline structures are shown in **Figure 1**.

4. ZnO doping

Generally, the doping process is used for enhancing the electrical and the optical characteristics of the material [14]. The undoped *n*-type ZnO is usually due to the oxygen vacancies in the ZnO structure [15, 16]. This makes the doping process of ZnO as *p*-type is very difficult. There are several *p*-type dopants for ZnO nano materials. Lithium is one of the *p*-type dopants for the ZnO. It takes a centered position by replacing the zinc atoms in the wurtzite structure of the ZnO [17]. GaN can be used

Figure 2.
ZnO doping process [25].

with ZnO to bypass the problem of p -type doping of ZnO nano material [18]. GaN is a wide band gap semiconductor with very similar lattice constants to ZnO. The GaN p -type dopant is commonly made with magnesium [18]. Several research groups have reported on the fabrication of ZnO hetero-junction devices. These hetero-junctions devices used materials like silicon [19], aluminum gallium nitride [20], and gallium nitride [21] for the p -type semiconductors. The electrical resistivity is significantly decreasing for ZnO by using doping elements like aluminum [22], gallium [23], and indium [24]. The ZnO doping process is shown in **Figure 2**.

5. ZnO nanostructured material

Recently, several efforts have been made for developing the ZnO film in different nanoshapes. These nanoshapes include the nanorods, nanowires, and nanocubes [23–26]. These nanoshapes of ZnO films can be used in several applications including the UV laser emission, photodetector and LEDs devices.

The nanoshapes of ZnO nanowires and nanorods based devices are becoming an important part of many potential applications. These applications include the optoelectronics, electromechanical nano devices [27] and biosensing [28].

There are several applications were reported based on ZnO based nanomaterials. These applications include the transparent electronic devices [29], the UV light emitters [30], the piezoelectric devices [31], the p - n junction devices [32], the field effect devices [33], the sensors [34], the optoelectronics [35], and the field emission devices [36].

6. ZnO nanowires based devices

ZnO nanowires based devices have many research interests. Recently, many devices based on ZnO nanostructured nanowires were reported. This is due to the high surface area and the low cost of fabrication [37–40]. There are several fabrication methods being used for the growth of the ZnO nanowires. These methods include the vapor liquid solid [41], metal organic chemical vapor deposition [42], chemical bath deposition [43] and hydrothermal method [44] with varied film qualities. The ZnO nanowires image is shown in **Figure 3**.

Figure 3.
ZnO nanowires [45].

7. ZnO nanorods based devices

ZnO based nanorods have received a good interest in various optoelectronic nanoscale devices. These devices include the photovoltaic cells, UV laser diodes [46], LEDs, optical sensors, and UV photodetectors [47]. Several applications based on ZnO require a large surface area. The simplest method to increase the surface of the ZnO layer is by growing nanorods. The larger the surface area the more photons are expected to be absorbed by ZnO layer [48]. One way to improve the crystalline structure and the photoluminescence spectra of ZnO nanorods is by annealing process [48].

The ZnO nanorods are being fabricated using several methods. These fabrication methods include the hydrothermal method [49], metal oxide chemical vapor deposition method [50], pulsed laser deposition method [51], aqueous solution method [52]. In these methods, the surface morphologies, optical and electrical properties of ZnO nanorods are depending on the fabrication parameters. These parameters include the deposition time, temperature, and post deposition annealing. The ZnO nanorods are shown in **Figure 4**.

Other fabrication methods of the ZnO nanoshape films are including the sol-gel technique, RF magnetron sputtering, electron beam evaporation, spray pyrolysis (SP), and molecular beam epitaxy, electrochemical deposition [54]. The electrochemical deposition wet method is a well-established solution based process to obtain ZnO nanoshapes thin films [55]. It has many advantages including the low cost and the temperature deposition over other types of fabrication.

Figure 4.
ZnO nanorods [53].

8. ZnO nano based applications

The ZnO material is being used for many optoelectronic based devices applications. These devices applications include the varistors, sensors [13, 56–59], optical wave guides, UV light emitters [60], LEDs [61], micro-electro-mechanical systems [12], spin electronics [62], solar energies [63], p-n junctions [64], field effect and emissions [65–67], displays [68], acoustic waves [69], and solar cells [6].

IntechOpen

IntechOpen

Author details

Ahmed M. Nahhas
Department of Electrical Engineering, Faculty of Engineering and Islamic
Architecture, Umm Al Qura University, Makkah, Saudi Arabia

*Address all correspondence to: amnahas@uqu.edu.sa

IntechOpen

© 2019 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/3.0>), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

References

- [1] Khan I, Khan S, Nongjai R, Ahmed H, Khan W. Hydrothermal synthesis of zinc oxide powders with controllable morphology. *Optical Materials*. 2013;**35**:1189-1193
- [2] Xu H, Wang H, Zhang Y, He W, Zhu M, Wang B, et al. Structural and optical properties of gel-combustion synthesized Zr doped ZnO nanoparticles. *Ceramics International*. 2004;**30**:93-97
- [3] Kung S, Sreenivas K. Defect free C-axis oriented zinc oxide (ZnO) films grown at room temperature using RF magnetron sputtering. *AIP Conference Proceedings*. 2016;**1731**:1-3
- [4] Li Y, Bando Y, Golberg D. ZnO nanoneedles with tip surface perturbations: Excellent field emitters. *Applied Physics Letters*. 2004;**84**:3603
- [5] Saito M, Fujihara S. Large photocurrent generation in dye-sensitized ZnO solar cells. *Energy and Environmental Science*. 2008;**1**:280-283
- [6] Zhou J, Wu X, Xiao D, Zhuo M, Jin H, Luo J, et al. Deposition of aluminum doped ZnO as electrode for transparent ZnO/glass surface acoustic wave devices. *Surface and Coating Technology*. 2017;**320**:39-46
- [7] Choi Y, Kang J, Hwang D, Park S. Recent advances in ZnO based light-emitting diodes. *IEEE Transactions on Electron Devices*. 2010;**57**:26-41
- [8] Zhang M, Gao X, Barra A, Chang P, Huang L, Hellwarth R, et al. Core-shell structured Si/ZnO photovoltaics. *Materials Letters*. 2015;**140**:59-63
- [9] Hossaini H, Moussavi G, Farrokhi M. Oxidation of diazinon in cns-ZnO/LED photocatalytic process: Catalyst preparation, photocatalytic examination, and toxicity bioassay of oxidation by products. *Separation and Purification Technology*. 2017;**174**:320-330
- [10] Sabah M, Hassan M, Naser M, Al-hardan H, Bououdina M. Fabrication of low cost UV photo detector using ZnO nanorods grown onto nylon substrate. *Journal of Materials Science*. 2015;**26**:1322-1331
- [11] Pandya H, Chandra S, Vyas A. Integration of ZnO nanostructures with MEMS for ethanol sensor. *Sensors and Actuators B: Chemical*. 2012;**161**:923-928
- [12] Taube A, Sochacki M, Kwietniewski N, Werbowy A, Gieraltowska S, Wachnicki L, et al. Electrical properties of isotype and anisotype ZnO/4H-SiC heterojunction diodes. *Applied Physics Letters*. 2017;**110**:1120-1124
- [13] Li L, Zhang Y, Yan L, Jiang J, Han X, Deng G, et al. n-ZnO/p-GaN heterojunction light-emitting diodes featuring a buried polarization-induced tunneling junction. *AIP Advances*. 2016;**6**:125204
- [14] Tvarozek V, Shtereva K, Novotny I, Kovac J, Sutta P, Srnanek R, et al. RF diode reactive sputtering of n- and p-type zinc oxide thin films. *Vacuum*. 2007;**82**:166-169
- [15] Liu G, Rahman E, Ban D. Performance optimization of p-n homojunction nanowire based piezoelectric nanogenerators through control of doping concentration. *Journal of Applied Physiology*. 2017;**118**:94307
- [16] Pemmaraju C, Archer T, Hanafin R, Sanvito S. Investigation of n-type donor defects in Co-doped ZnO. *Journal of Magnetism and Magnetic Materials*. 2007;**316**:e185-e187

- [17] Hamid H, Celik-Butler Z. Li-ZnO nanowire carpet as a micro-newton force sensor with nanometer res. In: IEEE Conference on Sensors; 2017. pp. 1-3
- [18] Saroj R, Dhar S. Relationship between dislocation and the visible luminescence band observed in ZnO epitaxial layers grown on c-plane p-GaN templates by chemical vapor deposition technique. *Journal of Applied Physiology*. 2016;**120**:75701
- [19] Urgessa N, Dobson S, Talla K, Murape D, Venter A, Botha J. Optical and electrical characteristics of ZnO/Si heterojunction. *Physica B: Condensed Matter*. 2014;**439**:149-152
- [20] Alivov R, Kalinina E, Cherenkov A, Look D, Ataev B, Omaev A, et al. Fabrication and characterization of n-ZnO/p-AlGaIn n-ZnO/p-AlGaIn heterojunction light-emitting diodes on 6H-SiC substrates. *Applied Physics Letters*. 2003;**83**:4719
- [21] Alvi N, Riaz M, Tzamalīs G, Nur O, Willander M. Fabrication and characterization of high-brightness light emitting diodes based on n-ZnO nanorods grown by a low-temperature chemical method on p-4H-SiC and p-GaN. *Semiconductor Science and Technology*. 2010;**25**:065004
- [22] Li Y, Meng J. Al-doping effects on structure and optical properties of ZnO nanostructures. *Materials Letters*. 2014;**117**:260-262
- [23] Chen Y, Huang I, Chang S, Hsueh T. Photodetector of ZnO nanowires based on through-silicon via approach. In: IEEE International Interconnect Technology Conference/Advanced Metallization Conference (IITC/AMC); 2016. pp. 123-124
- [24] Yi G, Wang C, Park W. ZnO nanorods: Synthesis, characterization and applications. *Semiconductor Science and Technology*. 2005;**20**:S22-S34
- [25] Viet N, Joao R, Carmen J, Jean-Luc D, Perrine C, Delfina M, et al. Deposition of ZnO based thin films by atmospheric pressure spatial atomic layer deposition for application in solar cells. *Journal of Renewable and Sustainable Energy*. 2017;**9**:021203
- [26] Pan Z, Dai Z, Wang Z. Nanobelts of semiconducting oxides. *Science*. 2001;**291**:1947-1949
- [27] Jianming J, Xiaoqin F, Guibin C. Electromechanical properties of a zigzag ZnO nanotube under local torsion. *Journal of Nano Research*. 2013;**15**:1-9
- [28] Mustafa M, Iqbal Y, Majeed U, Sahdan M. Effect of precursor's concentration on structure and morphology of ZnO nanorods synthesized through hydrothermal method on gold surface. *AIP Conference Proceedings*. 2017;**1788**:30120
- [29] Logothetidis S, Laskarakis A, Kassavetis S, Lousinian S, Gravalidis C, Kiriakidis G. Optical structural properties of ZnO for transparent electronics. *Thin Solid Films*. 2008;**516**:1345-1349
- [30] Pal A, Mohan D. Multi-angle ZnO microstructures grown on Ag nanorods array for plasmon-enhanced near-UV-blue light emitter. *Nanotechnology*. 2017;**28**:415707-415707
- [31] Serhane R, Messaci S, Lafane S, Khales H, Aouimeur W, Bey A, et al. Pulsed laser deposition of piezoelectric ZnO thin films for bulk acoustic wave devices. *Applied Surface Science*. 2014;**288**:572-578
- [32] Nie Y, Deng P, Zhao Y, Wang P, Xing L, Zhang Y, et al. The conversion of PN-junction influencing the

piezoelectric output of a CuO/ZnO nanoarray nanogenerator and its application as a room-temperature self-powered active H₂S sensor. *Nanotechnology*. 2014;**25**:265501

[33] Tan Q, Wang J, Zhong X, Zhou Y, Wang Q, Zhang Y, et al. Impact of ZnO polarization on the characteristics of metal-ferroelectric-ZnO field effect transistor. *IEEE Transactions on Electron Devices*. 2011;**58**:2738-2742

[34] Faia P, Furtado C. Effect of composition on electrical response to humidity of TiO₂:ZnO sensors investigated by impedance spectroscopy. *Sensors and Actuators B: Chemical*. 2013;**181**:720-729

[35] Panda D, Tseng T. One-dimensional ZnO nanostructures: Fabrication, optoelectronic properties, and device applications. *Journal of Materials Science*. 2013;**48**:6849-6877

[36] Zhao Q, Huang C, Zhu R, Xu J, Chen L, Yu D. 2D planar field emission devices based on individual ZnO nanowires. *Solid State Communications*. 2011;**151**:1650-1653

[37] Lokman A, Arof H, Harun W, Harith Z, Rafaie H, Nor R. Optical fiber relative humidity sensor based on inline Mach-Zehnder interferometer with ZnO nanowires coating. *IEEE Sensors Journal*. 2016;**16**:312-316

[38] Willander M, Klason P. ZnO nanowires: Chemical growth, electrodeposition, and application to intracellular nano-sensors. *Physica Status Solidi C*. 2008;**5**:3076-3083

[39] Lupan O, Emelchenko G, Ursaki V, Chai G, Redkin A, Gruzintsev A, et al. Synthesis and characterization of ZnO nanowires for nanosensor applications. *Materials Research Bulletin*. 2010;**45**:1026-1032

[40] Ramgir N, Kaur M, Sharma P, Datta N, Kailasaganapathi S, Bhattacharya S,

et al. Ethanol sensing properties of pure and Au modified ZnO nanowires. *Sensors and Actuators B: Chemical*. 2013;**187**:313-318

[41] Zhao Q, Klason P, Willander M. Growth of ZnO nanostructures by vapor liquid solid method. *Applied Physics A*. 2007;**88**:27-30

[42] Pan M, Fenwick W, Strassburg M, Li N, Kang H, Kane M, et al. Metal organic chemical vapor deposition of ZnO. *Journal of Crystal Growth*. 2006;**287**:688-693

[43] Chiu S, Huang J. Chemical bath deposition of ZnO and Ni doped ZnO nanorod. *Journal of Non-Crystalline Solids*. 2012;**358**:2453-2457

[44] Polsongkram D, Chamninok P, Pukird S, Chow L, Lupan O, Chai G, et al. Effect of synthesis conditions on the growth of ZnO nanorods via hydrothermal method. *Physica B: Condensed Matter*. 2008;**403**:3713-3717

[45] Jabr S, Souissi H, Lusson A, Sallet V, Meftah A, Galtier P, et al. The ratio oxygen/zinc effect on photoluminescence emission line at 3.31 eV in ZnO nanowires. *Journal of Applied Physics*. 2016;**119**:205710

[46] Long H, Fang G, Li S, Mo X, Wang H, Huang H, et al. A ZnO/ZnMgO multiple quantum well ultraviolet random laser diode. *IEEE Electron Device Letters*. 2011;**32**:54-56

[47] Hwang J, Wang F, Kung C, Chan M. Using the surface plasmon resonance of Au nanoparticles to enhance ultraviolet response of ZnO nanorods based Schottky barrier photodetectors. *IEEE Transactions on Nanotechnology*. 2015;**14**:318-321

[48] Sipr O, Rocca F. Zn K edge and O K edge x-ray absorption spectra of ZnO surfaces: Implications for nanorods. *Journal of Physics: Condensed Matter*. 2011;**23**:315501

- [49] Lestari A, Iwan S, Djuhana D, Imawan C, Harmoko A, Fauzia V. Effect of precursor concentration on the structural and optical properties of ZnO nanorods prepared by hydrothermal method. *AIP Conf. Proc.* 2016;**1729**:20027
- [50] Montenegro D, Souissi A, Tomas C, Sanjose V, Sallet V. Morphology transitions in ZnO nanorods grown by MOCVD. *Journal of Crystal Growth.* 2012;**359**:122-128
- [51] Mendelsberg R, Kerler M, Durbin S, Reeves R. Photoluminescence behavior of ZnO nanorods produced by eclipse PLD from a Zn metal target. *Superlattices and Microstructures.* 2008;**43**:594-599
- [52] Baliga B. Gallium nitride devices for power electronic applications. *Semiconductor Science and Technology.* 2013;**28**:74011
- [53] Nivedita Y, Veit W. Controlled growth of ZnO nanorods via self-assembled monolayer. *Journal of Applied Electrochemistry.* 2018;**48**:85-94
- [54] Pearton S, Ren F. GaN electronics. *Advanced Materials.* 2000;**12**:1571-1580
- [55] Fu N, Li E, Cui Z, Ma D, Wang W, Zhang Y, et al. The electronic properties of phosphorus doped GaN nanowires from first principle calculations. *Journal of Alloys and Compounds.* 2014;**596**:92-97
- [56] Yuliah Y, Bahtiar A, Fitrilawati SR. The optical band gap investigation of PVP-capped ZnO nanoparticles synthesized by sol-gel method. *AIP Conf. Proc.* 2016;**1712**:50018
- [57] Roh J, Kim H, Park M, Kwak J, Lee C. Improved electron injection in all solution processed n-type organic field effect transistors with an inkjet printed ZnO electron injection layer. *Applied Surface Science.* 2017;**420**:100-104
- [58] Zhang M, Zhang H, Li L, Tuokedaerhan K, Jia Z. Er-enhanced humidity sensing performance in black ZnO based sensor. *Journal of Alloys and Compounds.* 2018;**744**:364-369
- [59] Ling Z, Wen Z. Room-temperature gas sensing of ZnO based gas sensor: A review. *Sensors and Actuators, A: Physical.* 2017;**267**:242-261
- [60] Konenkamp R, Word R, Schegel R. Vertical nanowire light-emitting diode. *Applied Physics Letters.* 2004;**85**:6004-6006
- [61] Mckinstry S, Marult P. Thin film piezoelectrics for MEMS. *Journal of Electroceramics* *Journal of Electroceramics.* 2004;**12**:7-17
- [62] Ushio Y, Miyayama M, Yanagida H. Effects of interface states on gas sensing properties of a CuO/ZnO thin film heterojunction. *Sensors and Actuators B: Chemical.* 1994;**17**:221-226
- [63] Harima H. Raman studies on spintronics materials based on wide bandgap semiconductors. *Journal of Physics. Condensed Matter.* 2004;**16**:S5653-S5660
- [64] Xiang J, Zhu P, Masuda Y, Okuya M, Kaneko S, Koumoto K. Flexible solar cell from zinc oxide nanocrystalline sheets self assembled by an In-situ electrodeposition process. *Journal of Nanoscience and Nanotechnology.* 2006;**6**:1797-1801
- [65] Khachar U, Solanki P, Choudhary R, Phase D, Ganesan V, Kuberkar D. Room temperature positive magnetoresistance and field effect studies of manganite-based heterostructure. *Applied Physics A.* 2012;**108**:733-738
- [66] Boccuzzi F, Chiorino A, Tsubota S, Haruta M. An IR study of CO-sensing

mechanism on Au/ZnO. Sensors and Actuators B: Chemical. 1995;25:540-543

[67] Singh J, Patil S, More M, Joag D, Tiwari R, Srivastava O. Formation of aligned ZnO nanorods on self grown ZnO template and its enhanced field emission characteristics. Applied Surface Science. 2010;256:6157-6153

[68] Alvi M, Al-Ghamdi A, Husain M. Field emission studies of CNTs/ZnO nanostructured thin films for display devices. Physica B: Condensed Matter. 2017;521:312-316

[69] Lao C, Gao P, Yang R, Zhang Y, Dai Y, Wang Z. Formation of double side teathed nanocombs of ZnO and self catalysis of Zn terminated polar surface. Chemical Physics Letters. 2006;417:358-362