We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists

6,300

Open access books available

172,000

International authors and editors

190M

Downloads

Our authors are among the

154

Countries delivered to

TOP 1%

most cited scientists

12.2%

Contributors from top 500 universities

WEB OF SCIENCE™

Selection of our books indexed in the Book Citation Index
in Web of Science™ Core Collection (BKCI)

Interested in publishing with us?
Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected.
For more information visit www.intechopen.com

Understanding Urban Mobility and Pedestrian Movement

Marija Bezbradica and Heather J. Ruskin

Abstract

Urban environments continue to expand and mutate, both in terms of size of urban area and number of people commuting daily as well as the number of options for personal mobility. City layouts and infrastructure also change constantly, subject to both short-term and long-term imperatives. Transportation networks have attracted particular attention in recent years, due to efforts to incorporate “green” options, enabling positive lifestyle choices such as walking or cycling commutes. In this chapter we explore the pedestrian viewpoint, aids to familiarity with and ease of navigation in the urban environment, and the impact of novel modes of individual transport (as options such as smart urban bicycles and electric scooters increasingly become the norm). We discuss principal factors influencing rapid transit to daily and leisure destinations, such as schools, offices, parks, and entertainment venues, but also those which facilitate rapid evacuation and movement of large crowds from these locations, characterized by high occupation density or throughput. The focus of the chapter is on understanding and representing pedestrian behavior through the agent-based modeling paradigm, allowing both large numbers of individual actions with active awareness of the environment to be simulated and pedestrian group movements to be modeled on real urban networks, together with congestion and evacuation pattern visualization.

Keywords: infrastructure, population dynamics, environmental issues, agent-based modeling, pedestrian behavior

1. Introduction

Currently, the field of urban mobility modeling is experiencing a surge of activity due, in part, to renewed interest in crowd management (including evacuations due to natural and man-made disasters) but also influenced by increased efforts to reduce CO₂ emissions through optimization of urban networks for both traffic and pedestrian purposes [1, 2]. Urban sprawl is a recognized phenomenon for growing cities, and tools, such as urban growth models, have proven valuable for planners and decision-makers in identifying challenges and potential environmental impacts [3]. Expansion of the built environment to meet population demand implies extended daily commutes as well as loss of other land function and is recognized as a critical challenge in global change, not only in countries experiencing explosive industrialization but worldwide [4–9]. Growth in population size of many major cities presents complex logistics in meeting demands for increased numbers of daily commuters and alternative transport modalities. In the UK, for example, the 11 most populous cities since 2015 are to be found in Scotland, (Glasgow and

Edinburgh); the conurbations of Northeast England, the West Midlands, and South and West Yorkshire (adjacent to the cities of Greater Manchester and Liverpool); Bristol and Cardiff in the southwest; and, of course, Greater London [10]. Between mid-2011 and mid-2015, Greater London's population grew by 5.7% to around 8.67 million, compared to that of other city regions (2.3%) and to the average growth (2.7%) for the country as a whole.

Under pressures of increased population growth, short-term crises and long-term policies, city layouts and infrastructure constantly adapt to meet needs, but the many factors involved render solutions for high volume passenger movement far from trivial. Awareness of the consequences of unrestricted urban sprawl has motivated legislation and a global move toward environmental sustainability over several decades, but change is slow [11]. The performance and modalities of transportation networks have attracted considerable attention, fueled mainly by efforts to reduce road congestion and harmful emissions. For example, Transport for London (TfL) (created in 2000) manages the capital's principal road networks, the underground system and its extension, the Docklands Light Railway, and TfL Rail (responsible in conjunction with the Department of Transport for commissioning crossrail, designed to improve East–West transit). While the TfL budget (~10 billion sterling in recent years) demonstrates major commitment to maintenance and new development, its business scorecard also emphasizes the need for a system accessible to all, the “greening” of the city streets and the health benefits for Londoners “traveling actively” [12]. Accommodating positive lifestyle choices such as walking or cycling commutes, as well as decreasing the CO₂ burden from road traffic, has served also to shift more attention toward the pedestrian's city experience. In consequence, this chapter also explores the implications for “traveling actively,” and safely, in London.

From the pedestrian viewpoint, the need for green spaces in city planning has long been recognized [13], but factors for *active travel* remain complex. Digital street mapping and mobile technology have improved familiarity and navigation within the urban environment, but, while novel modes of individual transport (such as smart urban bicycles and electric scooters) reduce the emission burden, road usage is increasingly multifaceted. Inevitably therefore, strategic emergency management is complicated by the challenge of prompt multimodal evacuation of dense urban areas [14]. In discussing plausible modeling approaches which capture principal factors influencing rapid transit to daily destinations (such as schools and offices), as well as leisure trips to parks and entertainment venues, consideration is given not only to throughput but also efficient evacuation from these high-density locations. The focus, specifically, is on the flexibility which agent-based modeling brings to representing pedestrian behavior. The paradigm permits individual actions, awareness of the environment, and pedestrian group movements to be modeled simultaneously on real urban networks.

Pedestrians are distinguished by a number of key features, such as personal choice, variable dynamics, and vulnerability. Debatably, they have the least predictable behavior patterns, although it has been shown that crowded venues restrict optimal choice [15–18]. Specifically, it has long been demonstrated that pedestrians can move freely *only* when pedestrian densities are small [15]. Designing urban infrastructure in order to increase pedestrian activity, therefore, has to balance often conflicting requirements of personal characteristics (such as walking speed), against considerations of safety. The problem is that parameter space is greatly expanded by variation in pedestrian profiles; for example, age, speed, knowledge of the environment, individual or group transit, entrance and exit point to the network, time of day, and occupation density (among other factors) all affect efficient transit as well as the logistics of congestion and evacuation. Variable dynamics

Figure 1.
Aerial views of Singapore (left) and Zurich (right) urban layouts. Both cities consistently rank in the top 10 in the world for urban layout and mobility [20, 28, 29].

can be illustrated by examples of walking patterns for an average shopper, which are markedly distinct from pedestrians in a business district. Similarly, an elderly person typically moves differently to a young one, as does a native to a tourist and so on. Even within a particular scene, e.g., a shopping district, logistics are different for the successfully laden pedestrian and those still browsing [19].

As a consequence of this diversity, shaping sustainable city infrastructure relies on understanding pedestrian movement patterns and the environmental and behavioral reasons that guide them, together with provision of suitable public transportation options at key locations. Cities with strong track record in infrastructural design for mobility include Singapore and Zurich (**Figure 1**). Arguably due to large budgets, it has been shown that quality and safety of urban infrastructure do not relate solely to wealth, as good planning practices are vital [20]. Looking ahead, GPS-enabled mobile apps are likely to shape pedestrian behavior trends further, with awareness of urban layout (such as important intersections, walking routes, street signs, and transport alternatives), less reliant on physical observation than ‘in-app’ street map layouts, together with walking time estimates based on the historical consumer mix [21].

Investing resources in sustainable city planning is not for the fainthearted. Burgeoning demand for access and choice continues to threaten limits for air quality, noise, energy consumption, and biodiversity. The last hundred years has seen urban population growth concentrated on less than 3% of the world’s surface but with the corresponding environmental footprint disproportionately impacting climate: currently, 75% of greenhouse gas emissions can be attributed to cities with ecological effects many times larger than the actual urban area occupied [22]. Socioeconomic implications, such as health and well-being, are also a cause for concern: in France and elsewhere, urban mobility plans are now a required component of the urban planning process for the future [23], while global city initiatives, such as the 10 Aalborg Commitments [24], attempt to define basic guidelines for sustainable development.

2. Overview of modeling approaches

Within the broader agenda of sustainable urban planning, computer modeling has gained increased popularity as a versatile tool. The ability to explore *in silico* the nature and effect of change can facilitate the planning process, providing insight on the parameters, key dependencies and potential pitfalls, as well as complementing pilot schemes.

Emergency evacuation typically follows natural disasters, terrorist attacks on transport networks or at major events, as well as other causes of injury or where crowd dynamics destabilize [25]. The so-called climatic “extreme events” have markedly increased over the last decade, with ever-more severe consequences [26]. Increased frequency of such events, together with increased population density (mainly concentrated in urban areas and regions experiencing rapid urbanization, such as Asia) [26], has led to some of the largest losses of infrastructure in recent history. Besides highlighting the need for preemptive action and resilient infrastructure, extreme event prediction is widely employed to mitigate the human cost and employ successful evacuation strategies (as in the very recent example of Cyclone Fani’s landfall in India and Bangladesh (2019) where more than 2.8 million people were evacuated ahead of the storm) [27].

Approaches to modeling crowd behavior, pedestrian flows, and evacuation methods are varied and range from studies looking at flows of people as a paradigm [30–32] to the analysis of individual behavior patterns [33–36]. Early work aimed to describe pedestrian motion through physical model types including fluid dynamic and social forces, based on Newtonian mechanics [37]. Pedestrian motion can be described, for example, using a sum of different force vectors—namely, attractive, repulsive, driving, and fluctuating. However, the downside of these models is their reliance on sophisticated mathematical expressions that become intractable on expansion for newly discovered parameters and behaviors. Further, individual movement is represented as a superposition of pedestrian interactions, not only nontrivial to solve but often opaque to interpretation [38].

Key features to be incorporated are the agenda of the individual (purpose of journey) as well as interaction with the built and demographic environment—road traffic, urban layout, and crowd size. Two elements present particular difficulty. Pedestrians do not always follow simple logic or “stimulus-and-response”-based behavior and, unlike other road users (such as motorized vehicles or bicycles) do not need to, and indeed do not, follow preset movement lines. This freedom in choice and execution of movement means that any model must allow for randomness, treating individual behavior as unique to some extent.

2.1 Pedestrian movement

Two main model types can be distinguished for pedestrian interactions, namely, those for route choice and road crossing behavior, respectively. The former category is concerned with optimizing route layouts to achieve shortest travel times between origin and destination under various constraints, such as emergency road closures or congested pathways: investigations of crowd behavior and evacuation dynamics mainly utilize these scenarios, e.g., [39]. In contrast, road crossing models focus on pedestrian decision-making and the nature of interactions on road crossings: here key elements include aspects such as crossing gap (gap acceptance theory) and the use and location of the crossing itself (utility theory), e.g., [40].

Further categorization is possible by model scale, usually denoted microscopic or macroscopic. Macroscopic models are often route choice ones and are underpinned by the mathematics of fluid mechanics and queueing theory. Earlier examples include optimization of pedestrian network topologies [41] based on pedestrian queueing networks, representing crowds as single, flowable entities [42] and resolution of bottlenecks by disaggregating upstream and downstream flows around the point of congestion [30]. More recent work includes formulating pedestrian flows as a family of measures and flow maps [43] and vision-based models [44]. Microscopic models currently account for the majority of pedestrian movement studies [45], with some of the first models in this space based on the

cellular automata (CA) paradigm [46]. In CA, the environment and street layouts are represented as matrices of cells with individual pedestrians being able to move from cell to cell by discrete steps in a given model iteration. Update between iterations is performed by applying a matrix of cell state translation rules (the transition matrix) to model successive movements (**Figure 2**). Historically, CA models were used to describe various pedestrian movement scenarios in both route choice and pedestrian crossing categories, from bi-directional pedestrian flows on footpaths [33] to interactions of pedestrians with the urban layout [47].

Increase in computing power over the last decade has seen expansion of the CA paradigm with next-generation simulations for pedestrians based on multiple agents. These multi-agent or agent-based models (ABM) achieve microscopic levels of simulation, based on artificial intelligence concepts [45]. In agent-based systems, pedestrians are modeled as fully autonomous entities with cognitive and behavioral learning characteristics. Early applications included analysis of global movement patterns [50] and impact of pedestrian space allocation during movement [34]. Recent examples include [48, 49] where the former considers interactions of pedestrian agents in counterflow situations and the latter employs ABM to simulate different categories of pedestrian behavior at congestion points in a large city layout. The ABM approach, combined with the processing power of large computing clusters, enables effects of individual human choice within precise urban geometries to be modeled realistically. The practical potential for the future of city design and provision is considerable (e.g., smart city initiatives—such as [51]).

2.2 Evacuation dynamics

In modeling disaster scenarios, normal pedestrian movement simulation does not apply. Evacuation of metropolitan areas requires rapid crowd dispersion by safe routes to non-hazard zones at short notice. In terms of large-scale natural disasters such as cyclones, circumstances are even more extreme in terms of volume of

Figure 2.
An example of a cellular automata model with transition matrix [54]. (A) A particle (individual) with possible transitions, (B) Matrix of transition probabilities, and (C) Simulation of pedestrians leaving room with single door.

people movement and area affected; for example, a few million persons might need to be moved to safety from an area of 160 square kilometers [27, 52]. Evacuation models again, therefore, have a clear division by scale, based on the area impacted: small-scale evacuations may involve isolated locations, such as rooms, buildings, and stadia, while large-scale evacuations can include anything from suburban and urban metropolitan areas (with high population density) to tracts of land with different population densities [53].

Microscopic models for building evacuation have been around for some time [54]. A useful categorization is provided by the US National Institute for Standards and Technology (NIST) [55], based on orientation, building type applicability, size of grid, user-perspective, type of behavior, and type of movement. Of particular interest in the NIST nomenclature is the classification of models into behavioral and movement types. Behavioral models simulate action-taking by pedestrians, depending on the specific emergency circumstances, while movement models concentrate on evacuation flows. Models, which incorporate both individual action and evacuation strategies, are classified as mixed.

Further subdivision is possible according to the nature of the behavior exhibited. Thus, implicit behavior models, conditional behavior models, models utilizing artificial intelligence, and probabilistic models have all been proposed, of which the first are the simplest. The behavioral response of individual pedestrians is built into movement patterns or response delays but is not modeled explicitly as a *conscious choice* [56]. Conditional approaches follow an “if-then” rule pattern—evacuee behavior is modeled as a response to structural characteristics or structural changes in the surrounding environment [57]. All models simulate individual pedestrians through modeling the human intelligence aspect of their behavior directly (as opposed to indirectly via movement parameters as for other model types) [58]. Probabilistic models assign behavior probabilities to individual groups permitting random outcomes for each model run, with statistics analyzed after repeated runs. Compared with AI models, parameterization can be based on summary data for real disaster events [49]. Agent-based models (ABM) (combining both AI and probabilistic approaches) thus offer considerable strengths (discussed in more detail below).

2.3 Model choice

Choice of the right model does not always involve the more complex or even the most realistic since complexity requires a large set of parameters, for which empirical estimates are often unavailable (e.g., profiles of people in a given evacuation context), so simplicity can be an advantage. Moreover, the mode of evacuation can be a critical determinant (applicable almost exclusively to macroscopic models). For large-scale evacuations, the majority of research to date has assumed vehicular transport (predominantly car-based) movement [14]. However, this is sometimes neither practical nor possible and can, on occasion, lead to further escalation of disaster situations by contributing to congestion [59]. In other cases, no such transport option is available, and/or existing public transport cannot be used in the immediate vicinity [60]. In 2005, for example, Hurricane Katrina left 80% of New Orleans in the US state of Mississippi flooded, with some parts under nearly 5 m. of water [61]. In consequence, investigation of exclusively pedestrian-based evacuations in circumstances where utilizing of usual transport modes is not an option (e.g., earthquake disasters or floods) is gaining prominence.

In this context, **Figure 3** illustrates New Orleans (map taken from [62] with vehicular evacuation routes shown in green and population densities in orange). Implications for loss of access to routes for car transport are clear.

Figure 3.
 Map of New Orleans showing the sectors of an evacuation plan obtained via optimized modeling. Blue lines indicate secondary roads used in evacuation routes. Green lines indicate roads used as one-way contraflow evacuation routes. The orange shading indicates population density, with darker shading indicating greater density [62].

Well-established early traffic simulation models, such as PARAMICS, VISSIM, and CORSIM [63–65], have recently become popular also for emergency evacuation scenarios, using adjusted parameter values, e.g., acceleration of vehicles and reaction time, which differ in disaster situations [66, 67]. However, other transport options, such as the rail system (arguably an effective evacuation mechanism due to larger capacity), have not been extensively modeled (although included in existing urban evacuation plans (e.g., for Chicago [68])).

Clearly, however, major disruption to (or congestion of) available transport networks, combined with the high population density in urban areas, means that evacuation on foot provides a vital mode of escape. Pedestrian evacuation models of this type have only recently begun to feature in the development of city evacuation plans, while adaptation of existing evacuation model tools is again necessary to accommodate features involved [45].

Increasingly important, however, in modeling both urban mobility and evacuation scenarios are new technology tools, such as volunteered geographic information (VGI) systems. VGI systems allow for collection and dissemination of global urban data, based on user-generated content and peer-review, and thus allow creation and curation of geographical datasets that would otherwise be too cost-prohibitive to assemble for individual research purposes. A good example of a VGI system is OpenStreetMap (OSM), an open project with the purpose of creating nonproprietary geographical maps of the world [69]. Led by the OpenStreetMap Foundation, its stated goal is to encourage the development and distribution of free geospatial data for anyone to use and share. Particularly attractive is its fine-grained coordinate layout and geographic metadata associated with each map element. OSM maps provide a good backdrop on which to develop both CA and AB model types. These can incorporate both quantitative (e.g., street lengths and lane numbers) and qualitative (street types, nearby amenities) map data to accurately simulate grid “cells” (in the CA type) or free-flowing pedestrian environments (for ABM).

3. Pedestrian behavior

As urban environments expand, routine travel to work or other destinations typically takes longer and can be increasingly affected by congestion and delays for both public and private transport modes. Alternative lifestyle choices such as walking and cycling can prove both healthy and efficient but are also subject to constraints of the built environment and demographics. Although pedestrian behavior has been studied for more than several decades [70], predominantly with respect to self-organization patterns and interaction of pedestrian flows [20], additional parametrization has become possible relatively recently due to expansion in computing power. In consequence, the questions addressed have become more complex and more relevant for both normal movement and for emergency scenarios. Examples cited include the use of models to analyze evacuation patterns from enclosed spaces (such as buildings, underground stations, and other public venues) [27, 71, 72], to address large-scale problems in morphological urban structure as well as to understand cognitive behavior in the context of disasters (such as hurricanes and terrorist attacks among others) [38, 73].

3.1 Groups or individuals

Addressing self-organization [15, 32], some studies report that, rather than wholly random or individual movement, interactions inside and between groups lead to formation of typical walking patterns. Distinction exists between travel as a single individual or within a group, however, so that while pedestrian behavior is diverse, with each individual permitted flexible options for movement through crowds or definition of “optimal” route, such groups or crowd pressure act as limiting factors to free choice [74]. Equally, knowledge of the built environment and configuration of the urban street network augments visual perception and cognitive understanding of spatial complexity to determine route choice and understanding of the way in which directional change complements distance [75, 76]. Consequently, while motorized (and non-motorized) road-using vehicles are constrained by traffic rules, signalization, and street orientation, pedestrian flows are subject to fewer fixed rules, exhibiting greater randomness at every time point during free movement [45] but subject to continuous real-time reassessment and rapid adaptation of route choice under congestion. **Figure 4a** and **b** illustrates some of the flexibility of choice available to the pedestrian under his or her perception of advantage to be gained during urban travel.

The figures serve to highlight those properties which strongly motivate bottom-up modeling of pedestrian movement; the agent basis provides a flexible tool for analysis of complex social behavior [78], with agents *actively aware* of their environment (traffic, adjacent pedestrians, and the street network).

3.2 Real urban networks

Perceptions of the network also depend, however, on how well this can be represented, and the importance of VGI (noted above) has led to considerable model refinement. For example, in [49] the authors introduced a discrete, behavior-driven space–time framework, allowing pedestrian movement to be modeled on a real urban network. The main focus is on exploring the potential of the approach through example scenarios and investigation of simple hypotheses of pattern evolution. The research considered pedestrian movement originating from three main “cognitive features” [76, 79]: (i) walking strategy, (ii) spatial awareness, and (iii) knowledge of the urban grid. **Figure 5** shows emergence of flow patterns

Figure 4.
(A) Examples of different pedestrian behavior depending on interaction with other pedestrians during street crossing [77]. (B) Examples of different pedestrian behavior depending on shortest route perception; green, shortest distance is the least actual cost path; red, least angle change requires pedestrians to course correct their path toward “most likely” turns; blue, least turns put the highest “cost” of the route into actual turns needed to reach the destination.

originating from such features in a hypothetical peak commute hour scenario for several hotspots in the City of London’s financial district.

Unfortunately, normal cognitive behavior patterns do not apply in emergencies, and route choice during a disaster scenario involves elements that are not present during regular commutes. Among others, these include decision-making under pressure, limited visibility, unclear evacuation routes, and dependency on others in the same group (and in authority) to indicate optimum or safe direction. Additionally, crowd dynamics can change rapidly. It has been shown that crowd turbulence restricts movement at extreme densities (a phenomenon observed during recent crowd disasters) [38] and also modeled by [80, 81]. Thus self-organizing behaviors, designed to optimize motion on the urban network under normal conditions, break down at high crowd densities and for bottlenecks that occur during large evacuation scenarios [38]. Simple patterns, such as formation of unidirectional pedestrian flows in bidirectional traffic, disappear and are replaced with other collective patterns like long-range collisions and stop-and-go waves that lead to serious participant injuries during mass events. In an attempt

Figure 5. Simulation of pedestrian flow size using commute hotspots in a hypothetical City of London peak hour scenario with agents displaying full knowledge of urban grid; right, original OpenStreetMap of the financial City of London district; left, hotspot flow rate model (number of pedestrians passing per second) for the map section.

to understand the forces and factors involved, recent studies have considered merging behavior of pedestrians under different scenarios as well as models for collision avoidance [32, 82, 83].

In summarizing model choices and trying to understand pedestrian behavior, it seems clear that advantage lies in replacing classical physics models with a more cognitive approach, tailored to single-person (agent) granularity. In evacuation scenarios, in particular, behavior is based on the concept of heuristics, namely, quick and simple cognitive processes that tend to pare down visual perception of the world and optimize for speed (a crucial aspect of emergency decision-making). Agent-based models also permit simulation of well-known “grouping” behavior during such scenes, including cohesive bounds and “herding,” where groups of individuals decide to communicate, act, and stay together as a group. These fine-grained clustering aspects of behavior are not well-captured by physical approximation [84].

4. Agent-based modeling

4.1 Advantages and scope

Building on earlier discrete methods (such as cellular automata), agent-based modeling (ABM) has gained considerable popularity for the representation of individual pedestrian interactions. The approach has several key advantages, the most important being the expressive and intuitive nature of the modeling language, its suitability to high-performance execution environments, adaptability to inclusion of heterogeneous behavior, and incorporation of stochasticity [85, 86]. The origins of application of ABM to pedestrian modeling lie in simulations of social behavior and decision-making, introduced in detail in [87]. From early models, where agents of two distinct types populated a simple grid [88], use has expanded to representation of complex real-world situations and social behavior involving millions of entities (e.g., TRANSIMS [89]).

The modeling strengths of the agent-based approach for pedestrian behavior are wide-ranging. Characteristics of individual pedestrians can be defined, including estimates of their spatial awareness using cognition precepts,

combining with preferential choices determined for different social groups. ABM can be used to investigate behavior patterns that incorporate rules of movement along pedestrian routes as well as intermediate decision and conflict points. Dynamic volunteered geographic information system data (such as that from the OpenStreetMap platform) can be utilized, permitting analysis of arbitrary city networks and comparison of the effect of grid structure and amenity distribution. Interaction of multiple social groups can also be investigated, for example, those consisting of pedestrians who have “directed” (e.g., point-to-point) patterns as opposed to those progressing at “leisure” (with patterns that are more random and less easily graphed). Such features offer the potential for these models to explore urban flows and congestion and the way in which changes in network morphology affect route choice. Equally, characteristics of the urban networks in responding to changing demand can also be modeled as well as disruptions impacting individual agent paths and travel times. ABM also compares well with statistical prediction techniques for pedestrian flows that have gained popularity in recent years, such as multiple regression analysis (MRA) [90]. This type of analysis relies on known parameters such as length of pedestrian routes and visual connectivity between points to estimate e.g. throughput numbers per given unit area [91]. While useful for estimating and understanding aggregate numbers representing pedestrian flow data, difficulties arise in accounting for aspects such as urban network architecture and layout [92]. Although agent-based models cannot access real pedestrian movement data on a large-scale urban level to model flows through individual streets, known information about individual pedestrian behavior does enable fine-grained implementation to explore different mobility scenarios at individual street level (within the large city model) as well as stochastic approximation for areas with sparse data.

4.2 Visualization of pedestrian behavior on urban networks

In simulating crowd and group dynamics, ABM enables exploration of force effects at different crowd densities by using discrete grid cells with assigned *force vectors* [93] and demonstration of local patterns for random pedestrian walks, utilizing aspects of both micro- and macro-simulations [94].

In **Figure 6**, an extract from OpenStreetMap shows a section of central London’s financial district for which the agent-based model has been used to simulate different types of progression, i.e., point-to-point or directional walking (that might relate to a commute) vs. the more random progression (associated perhaps with tourist sight-seeing). The implications for density and dispersion of occupation are indicated by the coloring. In the first part of the figure, clear preferred routes are the most congested and are colored red, the next preferred yellow, and so on. Hotspots are clearly identified. In the second part of the figure, clustering occurs at “sights” rather than along routes, but hotspots are often offset in terms of access. Clearly these scenarios represent different challenges in the case of closures or evacuation requirements. Shown specifically here are entrance points to alternative transport modes (black squares and red triangles, respectively), such as the underground. In some scenarios these may of course be unavailable or closed down in the immediate emergency zone.

In [49] the authors show how a general agent-based model combined with VGI data can be utilized to describe a wide variety of pedestrian behaviors covering both emergency and non-emergency situations. ABMs perform well in modeling individual pedestrian behavior as *generic state machines*. For every pedestrian we can specify a generic decision-transition-waiting flow. Individual states can then be further broken down to simulate fine-grained psychological or perceptual aspects

of individuals. In the example of non-emergency behavior (i.e., daily commute, travel, leisure), we can break down the decision state to distinguish an individual’s knowledge of the urban network they are traversing. A person with partial or limited knowledge exhibits a different behavior set compared to a person with full knowledge who can optimize travel based on this and grid perception. Other factors also contribute to decision-making—e.g. personal walking preference (aggressive, cautious, or random), age, pedestrian group size, and so on. As an example, **Figure 7** illustrates age and walking preference-based differences in terms of time taken and distance traveled overall for the financial sector of the City of London grid. In evacuation scenarios, a similar decision state can be used to simulate behavioral aspects under emergency conditions; decision factors can range from group dynamics, placement of safe areas, visual perception under reduced visibility conditions, and “fear.” Transition and waiting states aim to simulate the action part of the behavior, namely, execution and re-evaluation as the situation develops. This state transition diagram is illustrated in **Figure 8**.

Figure 6. An example of an agent-based model simulating the congestion areas of the London financial district for hypothetical pedestrian flows: left, point-to-point walking behavior from a set of local underground stations (denoted by black squares) to place of work; right, random behavior simulating, e.g., tourist traffic originating from underground stations and converging at local points of interest. Adapted from [49].

Figure 7. Simulation of age-based agent route performance when traversing an urban network [49], for pedestrians of different behavioral types.

Figure 8.
 An agent decision-transition-waiting diagram, as implemented by the agent-based model in [49].

This type of model detail facilitates understanding of actual patterns observed in both traffic and pedestrian flows and evacuation scenarios. Similar features can occur for pedestrians to those found in traffic modeling (e.g., lane formation—as agents have to wait for other agents on the same route choice path to move out of the way). Route choice preferences (and those with high throughput) are clearly visible. Moreover, as lanes form, the ABM model allows for re-evaluation of routes based on dynamic parameters like congestion (e.g., during large crowd events, where destination nodes in the urban or evacuation grid display become jammed, usually due to too few approaches, or alternative exits rendered unreachable due to blocking by incomers or slow movers). Congestion avoidance of fellow pedestrians in free movement and in crowds is also readily simulated using the agent basis. Pedestrians make optimal choices in the context only of perceived *local* grid congestion (as opposed to global knowledge of congestion points). Finally, ABM allow for clear identification of network *inflection points*, when impact of crowd size on travel or evacuation times becomes exponential rather than linear.

It should be emphasized again that a critical aspect of ABM performance for these problems is the choice of VGI or GIS platforms used to source the grid information. A platform such as OpenStreetMap permits extraction and visualization of relatively accurate street-level details, not only with respect to street geometry and space but also in terms of street metadata such as throughput and physical street characteristics—e.g., length and width of sidewalk, etc. These data are critical to provision of accurate grid simulations and assessment of pressure points and associated risks. Furthermore, the ability to edit the data to permit experimental analysis of the impact of alternative urban layouts and scenarios is important in building a relevant model, with a potential for understanding, anticipating, and responding to a range of pedestrian behavior. Linkage to geographic information systems (GIS), combining spatial and temporal aspects, additionally promises an effective geo-simulation tool facilitating interpretation of the urban environment [95]. Nevertheless, models using *both* separate crowdsourced GIS and ABM are relatively rare [96], and further investigation of social behavior patterns is clearly required.

5. Conclusion

In this chapter, we have discussed factors influencing pedestrian urban mobility, which motivate ongoing research in commute efficiency, together with the

wider implications for health and safety. Urban grids with high throughput typically utilize multiple transport modes and require efficient navigation, with non-motorized options increasingly seen as important in terms of reduction of harmful CO₂ emissions and benefits to health. In addition, infrastructure expansion and population growth present increased challenges for city management and emergency responders. Recently, the ability to visualize urban networks with greater accuracy has received considerable impetus from the emergence of new tools, such as VGI platforms, on which detailed simulations can be built. The use of stochastic agent-based models in these simulations has proven particularly useful in terms of evaluating urban layouts and the diverse patterns of pedestrian movement. Moreover, ABM combined with VGI demonstrates considerable potential in modeling a range of real-world situations, ranging from crowd formation and dispersion to evacuation in the event of natural and man-made disasters.

Author details

Marija Bezbradica* and Heather J. Ruskin
Advanced Research Computing Centre for Complex Systems Modelling
(ARC-Sym), School of Computing, Dublin City University, Dublin, Ireland

*Address all correspondence to: marija.bezbradica@dcu.ie

IntechOpen

© 2019 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/3.0>), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

References

- [1] Vermuyten H, Beliën J, De Boeck L, Reniers G, Tony W. A review of optimisation models for pedestrian evacuation and design problems. *Safety Science*. 2016;**87**:167-178. DOI: 10.1016/j.ssci.2016.04.001
- [2] Ge YE, Long J, Xiao F, Shi Q. Traffic modeling for low-emission transport. *Transportation Research Part D: Transport and Environment*. 2018;**60**:1-6. DOI: 10.1016/j.trd.2017.11.001
- [3] Goetz A. Suburban sprawl or urban centres: Tensions and contradictions of smart growth approaches in Denver, Colorado. *Urban Studies*. 2013;**50**(11):2178-2195. DOI: 10.1177/0042098013478238
- [4] Martellozzo F, Clarke KC. Measuring urban sprawl, coalescence, and dispersal: A case study of Pordenone, Italy. *Environment and Planning. B, Planning & Design*. 2011;**38**(6):1085-1104. DOI: 10.1068/b360890
- [5] Li XH, Liu JL, Gibson V, Zhu YG. Urban sustainability and human health in China, East Asia and south East Asia. *Environmental Sustainability*. 2012;**4**(4):436-442. DOI: 10.1016/j.cosust.2012.09.007
- [6] Chadchan J, Shankar R. An analysis of urban growth trends in the post-economic reforms period in India. *International Journal of Sustainable Built Environment*. 2012;**1**(1):36-49. DOI: 10.1016/j.ijsbe.2012.05.001
- [7] Liu Y, Chen J, Cheng W, et al. Spatiotemporal dynamics of the urban sprawl in a typical urban agglomeration: A case study on southern Jiangsu, China (1983-2007). *Frontiers in Earth Science*. 2014;**8**(4):490-504. DOI: 10.1007/s11707-014-0423-1
- [8] Sun L, Wei J, Duan DH, Guo YM, Yang DX, Jia C, et al. Impact of land-use and land-cover change on urban air quality in representative cities of China. *Journal of Atmospheric and Solar - Terrestrial Physics*. 2016;**142**:43-54. DOI: 10.1016/j.jastp.2016.02.022
- [9] Wei YD, Ewing R. Urban expansion, sprawl and inequality. *Landscape and Urban Planning*. 2018;**177**:259-265. DOI: 10.1016/j.landurbplan.2018.05.021
- [10] Population dynamics of UK city regions since mid-2011, Office for National Statistics, GB, October 2016. pp. 1-26
- [11] Tikoudis I, Walid O, Alexandros D, Lara E. Rethinking Urban Sprawl: Moving Towards Sustainable Cities. 2018. DOI: 10.1787/9789264189881-en
- [12] Mayor of London, Transport for London, TfL, Budget 2018/19, 2018. pp. 1-82
- [13] Swanwick C, Dunnett N, Woolley H. Nature, role and value of green space in towns and cities: An overview. *Built Environment*. 2003;**29**(2):94-106
- [14] Shiwakoti N, Sarvi M. Understanding pedestrian crowd panic: A review on model organisms approach. *Journal of Transport Geography*. 2013;**26**:12-17. DOI: 10.1016/j.jtrangeo.2012.08.002
- [15] Helbing D, Molnar P, Farkas IJ, Bolay K. Self-organizing pedestrian movement. *Environment and Planning. B, Planning & Design*. 2001;**28**:361-383. DOI: 10.1068/b2697
- [16] Ma J, Gong WG, Lo SM, Fang M. New insights into turbulent pedestrian movement pattern in crowd-quakes. *Journal of Statistical Mechanics: Theory and Experiment*. 2013;**23**:02028. DOI: 10.1088/1742-5468/2013/02/P02028

- [17] Duives DC, Wang G, Kim J. Forecasting pedestrian movements using recurrent neural networks: An application of crowd monitoring data. *Sensors (Basel)*. 2019;**19**(2):382. DOI: 10.3390/s19020382
- [18] Cantillo V, Arellana J, Rolong M. Modelling pedestrian crossing behaviour in urban roads: A latent variable approach. *Transportation Research Part F: Traffic Psychology and Behaviour*. 2015;**32**:56-67. DOI: 10.1016/j.trf.2015.04.008
- [19] Cochoy F, Hagberg J, Canu R. The forgotten role of pedestrian transportation in urban life: Insights from a visual comparative archaeology. *Urban Studies*. 2015;**52**(12):2267-2286. DOI: 10.1177/0042098014544760
- [20] Couzin ID, Krause J. Self-organization and collective behavior in vertebrates. *Advances in the Study of Behavior*. 2003;**32**:1-75. DOI: 10.1016/S0065-3454(03)01001-5
- [21] Laurier E, Brown B, McGregor M. Mediated pedestrian mobility: Walking and the map app. *Mobilities*. 2016;**11**(1):117-134. DOI: 10.1080/17450101.2015.1099900
- [22] Grimm NB, Faeth SH, Golubiewski NE, Redman CL, Wu J, Bai X, et al. Global change and the ecology of cities. *Science*. 2008;**319**:756-760. DOI: 10.1126/science.1150195
- [23] Mestayer P, Abidi A, André M, et al. Urban mobility plan environmental impacts assessment: A methodology including socio-economic consequences - The Eval-PDU project. 10th Urban Environment Symposium, Urban Futures for a Sustainable World. Jun 2010, Göteborg, Sweden. 11p. fhal-00614951f. HAL ID: hal-00614951
- [24] Sustainable Cities, The Aalborg Commitments [Internet]. Available from: http://www.sustainablecities.eu/fileadmin/repository/Aalborg_Commitments/Aalborg_Commitments_English.pdf [Accessed 11-05-2019]
- [25] Carriou C, Ratouis O. Is there a model for sustainable urban planning? Series: The Renewed Relevance of Urban-Planning Models? pp. 1-7 [Internet]. Available from: Metropolitiques.eu [Accessed 11-05-2019]
- [26] World Economic Situation and Prospects. New York, UN: Depart. of Economic and Soc. Affairs; 2013. pp. 1-207
- [27] Augustijn-Beckers EW, Flacke J, Retsios B. Investigating the effect of different pre-evacuation behavior and exit choice strategies using agent-based modeling. *Procedia Engineering*. 2009;**3**:23-35. DOI: 10.1016/j.proeng.2010.07.005
- [28] Solar Panel In Singapore, COO Publin Domain. [Internet]. Available from: <https://www.publicdomainpictures.net/en/view-image.php?image=32911&picture=solar-panel-in-singapore> [Accessed 11-05-2019]
- [29] Location ETH Zurich, Zentrum. [Internet]. Available from: <https://www.ethz.ch/en/news-and-events/media-information/images/standort-eth-zentrum.html> [Accessed 11-05-2019]
- [30] Hoogendoorn S, Daamen W. Self-organization in pedestrian flow. In: Hoogendoorn SP et al., editors. *Traffic and Granular Flow '03*. Berlin, Heidelberg: Springer; 2005. pp. 373-382. DOI: 10.1007/3-540-28091-X_36
- [31] Huang L, Xia Y, Wong SC, Shu C-W, Zhang M, Lam WHK. Dynamic continuum model for bi-directional pedestrian flows. *Proceedings of the Institution of Civil Engineers - Engineering and Computational*

Mechanics. 2009;**162**(2):67-75. DOI: 10.1680/eacm.2009.162.2.67

[32] Duives DC, Daamen W, Hoogendoorn SP. State-of-the-art crowd motion simulation models. *Transportation Research Part C: Emerging Technologies*. 2013;**37**: 193-209. DOI: 10.1016/j.trc.2013.02.005

[33] Weifeng F, Lizhong Y, Weicheng F. Simulation of bi-direction pedestrian movement using a cellular automata model. *Physica A: Statistical Mechanics and its Applications*. 2003;**321**(3-4):633-640. DOI: 10.1016/S0378-4371(02)01732-6

[34] Teknomo K, Gerilla GP. Mesoscopic Multi-Agent Pedestrian Simulation. In: Inweldi PO, editor. *Transportation Research Trends*. Vol. 1. Nova Science Publishers, Inc; 2008. p. 14. ISBN 978-1-60456-031-2

[35] Lee JYS, Lam WHK. Simulating pedestrian movements at signalized crosswalks in Hong Kong. *Transportation Research Part A: Policy and Practice*. 2008;**42**(10):1314-1325. DOI: 10.1016/j.tra.2008.06.009

[36] Papadimitriou E, Lassarre S, Yannis G. Introducing human factors in pedestrian crossing behaviour models. *Transportation Research Part F: Traffic Psychology and Behaviour*. 2016;**36**: 69-82. DOI: 10.1016/j.trf.2015.11.003

[37] Chraïbi M, Kemloh U, Schadschneider A, Seyfried A. Force-based models of pedestrian dynamics. *Networks & Heterogeneous Media*. 2011;**6**(3):425-442. DOI: 10.3934/nhm.2011.6.425

[38] Moussaïd M, Helbing D, Theraulaz G. How simple rules determine pedestrian behavior and crowd disasters. *Proceedings of the National Academy of Sciences*. 2011;**108**(17):6884-6888. DOI: 10.1073/pnas.1016507108

[39] Hoogendoorn SP, Bov PHL. Pedestrian route-choice and activity scheduling theory and models. *Transportation Research Part B: Methodological*. 2004;**38**(2):169-190. DOI: 10.1016/S0191-2615(03)00007-9

[40] Oxley J, Fildes B, Ihsen E, Charlton J, Days R. Crossing roads safely: An experimental study of age differences in gap selection by pedestrians. *Accident Analysis and Prevention*. 2005;**37**:962-971. DOI: 10.1016/j.aap.2005.04.017

[41] Mitchell DH, Smith JMG. Topological network design of pedestrian networks. *Transportation Research Part B: Methodological*. 2001;**35**(2):107-135. DOI: 10.1016/S0191-2615(99)00039-9

[42] Hughes RL. A continuum theory for the flow of pedestrians. *Transportation Research Part B: Methodological*. 2002;**36**(6):507-535. DOI: 10.1016/S0191-2615(01)00015-7

[43] Piccoli B, Tosin A. *Archive for Rational Mechanics and Analysis*. 2011;**199**(3):707-738. DOI: 10.1007/s00205-010-0366-y

[44] Degond P, Appert-Rolland C, Pettré J, Theraulaz G. Vision-based macroscopic pedestrian models. *Kinetic and Related Models*. 2013;**6**:809-839. DOI: 10.3934/krm.2013.6.809

[45] Papadimitriou E, Yannis G, Golias J. A critical assessment of pedestrian behaviour models. *Transportation Research Part F: Traffic Psychology and Behaviour*. 2009;**12**(3):242-255. DOI: 10.1016/j.trf.2008.12.004

[46] Blue VJ, Adler JL. Emergent fundamental pedestrian flows from cellular automata microsimulation. *Transportation Research Record*. 1998;**1644**(1):29-36. DOI: 10.3141/1644-04

- [47] Liu R, da Silva JPC, da Maia Seco AJ. A Bi-modal microsimulation tool for the assessment of pedestrian delays and traffic management. In: The Proceedings of the 9th International Association of Travel Behaviour Research Conference, Gold Coast, Australia. 2000
- [48] Heliövaara S, Korhonen T, Hostikka S, Ehtamo H. Counterflow model for agent-based simulation of crowd dynamics. *Building and Environment*. 2012;**48**:89-100. DOI: 10.1016/j.buildenv.2011.08.020
- [49] Bezbradica M, Ruskin HJ. Modelling impact of morphological urban structure and cognitive behaviour on pedestrian flows. In: Murgante B et al., editors. *Computational Science and its Applications – ICCSA 2014*. Vol. 8582. Cham: LNCS, Springer; 2014. pp. 268-283. DOI: 10.1007/978-3-319-09147-1_20
- [50] Batty M, Multi-Agent Simulation JB. Computational dynamics within GIS. In: Martin D, Artkinson P, editors. *Innovations in GIS VII: Geocomputation*. London: Taylor & Francis; 2000. pp. 55-71
- [51] Smart cities. Cities using technological solutions to improve the management and efficiency of the urban environment. European Commission, 2014-2020. Available from: https://ec.europa.eu/info/eu-regional-and-urban-development/topics/cities-and-urban-development/city-initiatives/smart-cities_en. Accessed: [11-05-2019]
- [52] Naghawi H, Wolshon B. Performance of traffic networks during multi-modal evacuations: Simulation-based assessment. *Natural Hazards Review*. 2012;**13**(3):196-204. DOI: 10.1061/(ASCE)NH.1527-6996.0000065
- [53] Lämmel G, Grether D, Kai N. The representation and implementation of time-dependent inundation in large-scale microscopic evacuation simulations. *Transportation Research Part C: Emerging Technologies*. 2010;**18**(1):84-98. DOI: 10.1016/j.trc.2009.04.020
- [54] Burstedde C, Klauck K, Schadschneider A, Zittartz J. Simulation of pedestrian dynamics using a two-dimensional cellular automaton. *Physica A: Statistical Mechanics and its Applications*. 2001;**295**(3-4):507-525. DOI: 10.1016/S0378-4371(01)00141-8
- [55] Kuligowski ED, Rd P. A Review of Building Evacuation Models. National Institute of Standards and Technology; 2005. p. 156
- [56] Ioannis K, Nick S, Rahul N, Stephen JG. Implicit crowds: Optimization integrator for robust crowd Simulation. *ACM Transactions on Graphics*. 2017;**36**(4):136:1-136:13. DOI: 10.1145/3072959.3073705
- [57] Tan L, Hu M, Lin H. Agent-based simulation of building evacuation: Combining human behavior with predictable spatial accessibility in a fire emergency. *Information Sciences*. 2015;**295**:53-66. DOI: 10.1016/j.ins.2014.09.029
- [58] Rahman A, Mahmood AK. Agent-based simulation using prometheus methodology in evacuation planning. In: *International Symposium on Information Technology*, Kuala Lumpur. 2008. pp. 1-8. DOI: 10.1109/ITSIM.2008.4632061
- [59] Litman T. Lessons from Katrina and Rita: What major disasters can teach transportation planners. *Journal of Transportation Engineering*. 2006;**132**(1):11
- [60] Kovács G, Spens KM. Humanitarian logistics in disaster relief operations. *International Journal of Physical Distribution and Logistics Management*. 2007;**37**(2):99-14. DOI: 10.1108/09600030710734820

- [61] Future flood losses in major coastal cities. *Nature Climate Change*. 2013;**3**:802-806. DOI: 10.1038/nclimate1979
- [62] Pillac V, Van Hentenryck P, Even C. A conflict-based path-generation heuristic for evacuation planning. *Transportation Research Part B: Methodological*. 2016;**83**:136-150. DOI: 10.1016/j.trb.2015.09.008
- [63] Cameron GDB, Duncan GID. *The Journal of Supercomputing*. 1996;**10**:25. DOI: 10.1007/BF00128098
- [64] Halati A, Lieu H, Walker S. CORSIM - corridor traffic simulation model. In: *Traffic Congestion and Traffic Safety in the 21st Century: Challenges, Innovations, and Opportunities*. Chicago, Illinois; 1997. pp. 570-576
- [65] Fellendorf M, Vortisch P. Microscopic traffic flow simulator VISSIM. In: Barceló J, editor. *Fundamentals of Traffic Simulation*. International Series in Operations Research & Management Science. Vol. 45. New York, NY: Springer; 2010. DOI: 10.1007/978-1-4419-6142-6_2
- [66] Tu H, Tamminga G, Drolenga H, de Wit J, van der Berg W. Evacuation plan of the city of Almere: Simulating the impact of driving behavior on evacuation clearance time. *Procedia Engineering*. 2010;**3**:67-75. DOI: 10.1016/j.proeng.2010.07.008
- [67] Ronchi E, Gwynne SMV, Rein G, Wadhvani R, Intini P, Bergstedt A. e-Sanctuary: Open Multi-Physics Framework for Modelling Wildfire Urban Evacuation. Project Report. National Fire Protection Association; 2017
- [68] City of Chicago, Central Business District Evacuation Plan. Published by Chicago Police Department on 16-07-2005
- [69] OpenStreetMap, [Internet]. Available from: <https://www.openstreetmap.org>. [Accessed 11-05-2019]
- [70] O'Flaherty CA, Parkinson MH. Movement on a city Centre footway. *Traffic Engineering and Control*. 1972;**13**:434-438
- [71] Kirchner A, Klüpfel H, Nishinari K, Schadschneider A, Schreckenberg M. Discretization effects and the influence of walking speed in cellular automata models for pedestrian dynamics. *Journal of Statistical Mechanics: Theory and Experiment*. 2004;**10**:10011. DOI: 10.1088%2F1742-5468%2F2004%2F10%2Fp10011
- [72] Pan X, Han CS, Dauber K, Law KH. A multi-agent based framework for the simulation of human and social behaviors during emergency evacuations. *AI & Society*. 2007;**22**(2):113-132. DOI: 10.1061/40794(179)92
- [73] Lu Q, George B, Shekhar S. Capacity constrained routing algorithms for evacuation planning: A summary of results. In: Bauzer Medeiros C, Egenhofer MJ, Bertino E, editors. *Advances in Spatial and Temporal Databases SSTD 2005*. Lecture Notes in Computer Science. Vol. 3633. Berlin, Heidelberg: Springer; 2005. pp. 291-307. DOI: 10.1007/11535331_1F
- [74] Moussaïd M, Perozo N, Garnier S, Helbing D, Theraulaz G. The walking behaviour of pedestrian social groups and its impact on crowd dynamics. *PLoS One*. 2010;**5**(4):1-7. DOI: 10.1371/journal.pone.0010047
- [75] Duckham M, Kulik L. "Simplest" paths: Automated route selection for navigation. In: Kuhn W, Worboys MF, Timpf S, editors. *Spatial Information Theory, Foundations of Geographic Information Science COSIT 2003*.

Lecture Notes in Computer Sciences. Vol. 2825. Berlin, Heidelberg: Springer; 2003. pp. 169-185. DOI: 10.1007/978-3-540-39923-0_12

[76] Hillier B, Iida S. Network and psychological effects in urban movement. In: Cohn AG, Mark DM, editors. Spatial Information Theory COSIT 2005. Lecture Notes in Computer Sciences. Vol. 3693. Berlin, Heidelberg: Springer; 2005. pp. 475-490. DOI: 10.1007/11556114_30

[77] Fujii H, Uchida H, Yoshimura S. Agent-based simulation framework for mixed traffic of cars, pedestrians and trams. *Transportation Research Part C: Emerging Technologies*. 2017;**85**:234-248. DOI: 10.1016/j.trc.2017.09.018

[78] Crooks A, Castle C, Batty M. Key challenges in agent-based modelling for geospatial simulation. *Computers, Environment and Urban Systems*. 2008;**32**(6):417-430. DOI: 10.1016/j.compenvurbsys.2008.09.004

[79] Antonini G, Bierlaire M, Weber M. Discrete choice models of pedestrian walking behavior. *Transportation Research Part B: Methodological*. 2006;**40**(8):667-687. DOI: 10.1016/j.trb.2005.09.006

[80] Helbing D, Johansson A, Al-Abideen ZH. Crowd turbulence: The physics of crowd disasters. In: *The Fifth International Conference on Nonlinear Mechanics (ICNM-V)*. 2007. pp. 967-969 arXiv:0708.3339

[81] Helbing D, Mukerji P. Crowd disasters as systemic failures: Analysis of the love parade disaster. *EPJ Data Science*. 2012;**1**. DOI: 10.2139/ssrn.2191620

[82] Aghabayk K, Ejtemai O, Sarvi M, Sobhani A. Understanding pedestrian crowd merging. *Transportation Research Procedia*. 2014;**2**:768-773. DOI: 10.1016/j.trpro.2014.09.086

[83] Weiss T, Litteneker A, Jiang C, Terzopoulos D. Position-based Multi-Agent dynamics for real-time crowd Simulation - MiG 2017. In: *Proceedings of MiG '17*, Barcelona, Spain, November. Vol. 9. 2017. pp. 8-10. DOI: 10.1145/3136457.3136462

[84] D'Orazio M, Spalazzi L, Quagliarini E, Bernardini G. Agent-based model for earthquake pedestrians' evacuation in urban outdoor scenarios: Behavioural patterns definition and evacuation paths choice. *Safety Science*. 2014;**62**:450-465. DOI: 10.1016/j.ssci.2013.09.014

[85] Gilbert N, Troitzsch KG. *Simulation of the Social Scientist*. 1st Ed. Buckingham. Vol. 308. Philadelphia: Open University Press; 1999

[86] Fiedrich F, Burghardt P. Agent-based Systems for Disaster Management. *Communications of the ACM*. 2007;**50**(3):41-42. DOI: 10.1145/1226736.1226763

[87] Castle CJE, Crooks AT. Principles and Concepts of Agent-Based Modelling for Developing Geospatial Simulations. London: CASA Working Papers, Centre for Advanced Spatial Analysis, UCL; 2006. p. 110

[88] Schelling TC. Dynamic models of segregation. *Journal of Mathematical Sociology*. 1971;**1**:143-186. DOI: 10.1080/0022250X.1971.9989794

[89] Cetin N, Nagel K, Raney B, Voellmy A. Large-scale multi-agent transportation simulations. *Computer Physics Communications*. 2002;**147**:559-564. DOI: 10.1016/S0010-4655(02)00353-3

[90] Omer I, Kaplan N. Using space syntax and agent-based approaches for modeling pedestrian volume at the urban scale. *Computers, Environment and Urban Systems*. 2017;**64**:57-67. DOI: 10.1016/j.compenvurbsys.2017.01.007

[91] Ueno J, Nakazawa A, Kishimoto T. An analysis of pedestrian movement in multilevel complex by space syntax theory: In the case of Shibuya Station. *Journal of Civil Engineering and Architecture*. 2009;**118**:1-12. DOI: 10.17265/1934-7359/2012.07.002

[92] Raftery N. Social and technical challenges to the adoption of space syntax methodologies as a planning support system (PSS) in American Urban Design. *The Journal of Space Syntax*. 2010;**1**(1):230-245

[93] Henein CM, White T. Agent-based modelling of forces in crowds. In: Davidsson P, Logan B, Takadama K, editors. *Multi-Agent and Multi-Agent-Based Simulation MABS 2004*. Lecture Notes in Computer Sciences. Vol. 3415. Berlin, Heidelberg: Springer; 2005. pp. 173-184. DOI: 10.1007/978-3-540-32243-6_14

[94] Longley PA, Batty M, editors. *Advanced Spatial Analysis: The CASA Book of GIS*. Redlands (USA): ESRI Press; 2003. p. 464

[95] Crooks AT, Castle CJE. The integration of Agent-based modelling and geographical information for geospatial Simulation. In: Heppenstall AJ, Crooks AT, See LM, Batty M, editors. *Agent-Based Models of Geographical Systems*. Dordrecht (Netherlands): Springer; 2012. pp. 219-251. DOI: 10.1007/978-90-481-8927-4_12

[96] Andrew TC, Sarah W. GIS and agent-based models for humanitarian assistance. *Computers, Environment and Urban Systems*. 2013;**41**:100-111. DOI: 10.1016/j.compenvurbsys.2013.05.003