We are IntechOpen, the world's leading publisher of Open Access books Built by scientists, for scientists

6,300

Open access books available

172,000

International authors and editors

190M

Downloads

Our authors are among the

154

Countries delivered to

TOP 1%

most cited scientists

12.2%

Contributors from top 500 universities

WEB OF SCIENCE™

Selection of our books indexed in the Book Citation Index
in Web of Science™ Core Collection (BKCI)

Interested in publishing with us?
Contact book.department@intechopen.com

Numbers displayed above are based on latest data collected.
For more information visit www.intechopen.com

Introductory Chapter: Fundamentals of Semiconductor Photocatalysis

Mohammed Muzibur Rahman

1. Introduction

In semiconductor photo-catalysis, generally it is used to design, characterize, and potential photocatalytical applications with doped or undoped nanostructural materials especially considering their particle sizes as well as shapes. Nanostructured materials, for example, porous metal oxides, metal nanoparticles, porous carbons, and their composites are widely studied for their potential applications in energy conversion/storage devices, gas storage, photocatalysis as well as in electrocatalysis. Photocatalysis is the phenomena, which occurs in catalysis by influence of photons. An efficient photocatalyst is a conductive nanomaterial, which directly absorbs incident light to bring up to higher energy states, which provides such energy to a reacting substance to make a chemical reaction occur. The mechanism of *photocatalytic* water splitting over *semiconductor photocatalysts* is also discussed in this chapter. Thermodynamically, the reaction of complete water splitting under normal conditions is a highly endothermic process because the change in the standard Gibbs energy is very large.

2. Literature review

For photocatalytic applications, the location of the TiO_2 nanoparticle plays an important role in the photoactivity, since various nanoparticles should be accessible for both photons and reactive molecules. The advantages of using these materials as support for TiO_2 in relation to photocatalytic processes are addressed by comparing the photocatalytic activity of TiO_2 nanoparticles deposited by different routes with TiO_2 nanoparticles on mesoporous materials [1–3]. Three-dimensional nanostructures have interconnected networks of bulk materials and larger accessible surface areas with respect to their lower dimensional counterparts. The surface functionalities, controllable host-guest interactions, and size-selective sensing properties are enabled due to the spatial arrangement of particles within three-dimensional framework [4–15].

Here, catalysts based on Ti-containing mesoporous silica have been developed from different synthetic pathways for selective oxidation of bulky organic compounds and photoreduction of greenhouse gases [16–18]. To support particles of TiO_2 on mesoporous silica, maintaining or improving its photocatalytic activity is not an easy task as, in addition to be strongly attached to the substrate for avoiding leakage, nanoparticles' size, location, and agglomeration should be controlled to have accessibility for adsorbates and incident photons [19–22]. Nanostructure of

rare earth material is appropriate for these applications that can be synthesized with different methods, for example co-precipitation, hydrothermal, sol-gel, combustion, stearic acid route, pechini, cathode plasma, electrolysis, co-ions complexation, molten salt, and other approaches [13]. Rare-earth-based materials were used in different fields. In this section, we study a brief review of rare-earth-doped materials, rare-earth-based oxide-oxide composites, metal-modified semiconductors, and mixed-oxide materials in the fields of photocatalytic application as solar energy generation. When a photon is absorbed by rare-earth-based material using the energy gap of the materials, electron-hole pairs are generated in the photocatalysis mechanism [23–27]. Semiconductor photocatalysis can be of two types, homogeneous photocatalysis and heterogeneous photocatalysis, depending on the phase differences of reactants and catalysts, which triggered the concept of advanced oxidation processes at the end of twentieth century. TiO_2 is the semiconductor, which can act as both the hetero- and homogenous photocatalyst photoreactions. There are numerous semiconductors, which can be coupled with other semiconductors and can be incorporated into heterostructures or composites. So, another example of inorganic heterostructure is the template-free simple synthesis of CdS-ZnO nanocomposites. This self-assembled flower-like structure resulted from coupling of two semiconductors, which increased the charge separation and demonstrated greater photocatalytic activity [28, 29].

Negheshi et al. attempted to improve the activity of mesoporous tungsten trioxide, and titanium dioxide (m-WO_3 and m-TiO_2) photocatalysts, which convert methane into methanol, by loading the ultrafine metal clusters as co-catalyst on the photocatalysts. They have succeeded in loading ultrafine metal-cluster co-catalysts onto m-WO_3 and m-TiO_2 , and thereby improving their photocatalytic activity in presence of mesoporous nanomaterials. The photocatalytic activity measurements clearly demonstrated that the loading of such co-catalysts is effective in improving the activity for both types of photocatalysts. It is important to appropriately select the element of the co-catalyst according to the photocatalyst to improve the photocatalytic activity. In this approach, the particle diameter of the co-catalyst was reduced to approximately 1.0 nm to increase the reactive surface area [29–32]. Textile dyes and other industrial dyestuffs constitute one of the largest groups of organic compounds that signify enhancing environmental pollution.

Contaminated water means undesirable substances; it adversely affects the quality and makes it inappropriate for use. Various sources such as residential, commercial, industrial practices, etc. contaminate the water and its sources as well. Wastewater parameters vary widely and depend on the source it is produced from. They are usually pathogenic, nonpathogenic microorganisms, organic, or inorganic [33, 34]. The toxic and carcinogenic nature of these dyes and their manufacturing precursors represent a danger to human beings and perturbation in aquatic life. The enlarged public concern about these environmental pollutants and the creation of international environmental standards have prompted the need for the development of novel treatment methods for converting organic pollutants (such as dye effluents) to harmless compounds. Reductive cleavage via anaerobic biological treatment generates potentially carcinogenic intermediates or end products, especially aromatic amines. Physical processes are like reverse osmosis, flocculation, absorption, air-stripping, combustion, and aerobic biological oxidation, which are nondestructive, and these processes only shift the pollutants from one medium to others, thus creating secondary pollution [35–38]. For the past two decades, a lot of research is going on for advanced oxidation processes, pointing out its potential vital role in the wastewater purification, in which the high oxidizing potential species like hydroxyl radicals are utilized as an alternative way of treating undesirable organic pollutants. Advanced oxidation processes shows great effort in solving the

bio-recalcitrant water-pollutant issues at near-ambient temperature and pressure [39–41]. Heterogeneous photocatalysis is a method wherein a blend of photochemistry and catalysis is operable and suggests that light and catalyst are necessary to bring out a chemical reaction. Lately, there has been a developing enthusiasm in usage of semiconductors as photosensitizers for the complete oxidative mineralization of pollutants by oxygen [42, 43]. Heterogeneously scattered semiconductor surfaces give both a fixed situation to impact the chemical reactivity of a wide scope of adsorbates and a means to initiate light-induced redox reactivity in these feebly related molecules.

When a semiconductor is intact with an aqueous solution, thermodynamic equilibration takes place at the interface. This may result in the development of a space-charge layer inside a slight surface area of the semiconductor, in which the electronic vitality bands are commonly twisted downward or upward, respectively, in the instances of p- and n-type semiconductors. The space-charge layer thickness is typically in the range of $1\text{--}10^3$ nm, contingent upon the dielectric constant and carrier density of the semiconductor. If this semiconductor perceives photons with energies that are more noteworthy than that of the respective material's band gap energy, electron-hole pairs are produced and parted in the space-charge layer. The development of new and noble nanotechnology is urgently required for introducing the eco-friendly, safe, facile, non-toxic routes in synthesis-to-applications, which can be used by industrial sectors in broad scale.

Recently, the nanotechnology offers the control growth of semiconductor substances at the nanoscale, which exclusively facilitates the novel photocatalytic applications with transition doped semiconductor catalysts. Photocatalysis, reactions supported out in the presence of a low-dimensional semiconductor and light, is rapidly becoming one of the most dynamic areas of catalysis research, with potential applications in areas such as environmental, solar, renewable energy, medicine, and sensors [44–47]. Here, in this book, it presents an overview of current photocatalyst fundamental, substantial applications, and enactment of the research in worldwide. This investigated the techniques of photocatalyst preparation, various types of characterization, and possible industrial applications related to solar photocatalyst researches.

Author details

Mohammed Muzibur Rahman

Center of Excellence for Advanced Materials Research (CEAMR) and Chemistry Department, Faculty of Science, King Abdulaziz University, Jeddah, Saudi Arabia

*Address all correspondence to: mmrahmanh@gmail.com

IntechOpen

© 2019 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/3.0>), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

References

- [1] Gustafsson H, Isaksson S, Altskär A, Holmberg K. Mesoporous silica nanoparticles with controllable morphology prepared from oil-in-water emulsions. *Journal of Colloid and Interface Science*. 2016;**467**:253-260
- [2] Subhan MA, Jhuma SS, Saha PC, Alam MM, Asiri AM, Al-Mamun M, et al. Efficient selective 4-aminophenol sensing and antibacterial activity of ternary $\text{Ag}_2\text{O}_3\cdot\text{SnO}_2\cdot\text{Cr}_2\text{O}_3$ nanoparticles. *New Journal of Chemistry*. 2019;**43**:10352-10365
- [3] Wahid A, Asiri AM, Rahman MM. One-step facile synthesis of $\text{Nd}_2\text{O}_3/\text{ZnO}$ nanorods for an efficient selective 2,4-dinitrophenol sensor probe. *Applied Surface Science*. 2019;**487**:1253-1261
- [4] Rahman MM, Sheikh TA, Asiri AM, Awual MR. Development of 3-methoxyaniline sensor probe based on thin $\text{Ag}_2\text{O}@ \text{La}_2\text{O}_3$ nanosheets for environmental safety. *New Journal of Chemistry*. 2019;**43**:4620-4632
- [5] Rahman MM, Wahid A, Alam MM, Asiri AM. Efficient 4-Nitrophenol sensor development based on facile $\text{Ag}@ \text{Nd}_2\text{O}_3$ nanoparticles. *Materials Today Communications*. 2018;**16**:307-313
- [6] Rahman MM, Alam MM, Asiri AM. Sensitive 1,2-dichlorobenzene chemi-sensor development based on solvothermally prepared FeO/CdO nanocubes for environmental safety. *Journal of Industrial and Engineering Chemistry*. 2018;**62**:392-400
- [7] Rahman MM. A label-free kanamycin sensor development based on $\text{CuO}-\text{NiO}$ hollow-spheres: Food samples analyses. *Sensors & Actuators: B Chemical*. 2018;**264**:84-91
- [8] Rahman MM, Alam MM, Asiri AM. 2-Nitrophenol sensor-based wet-chemically prepared binary doped $\text{Co}_3\text{O}_4/\text{Al}_2\text{O}_3$ nanosheets by an electrochemical approach. *RSC Advances*. 2018;**8**:960-970
- [9] Rahman MM, Ahmed J, Asiri AM. Thiourea sensor development based on hydrothermally prepared CMO nanoparticles for environmental safety. *Biosensors and Bioelectronics*. 2018;**99**:586-592
- [10] Ahmed J, Rahman MM, Siddiquey IA, Asiri AM, Hasnat MA. Efficient hydroquinone sensor based on zinc, strontium and nickel based ternary metal oxide (TMO) composites by differential pulse voltammetry. *Sensors and Actuators B: Chemical*. 2018;**256**:383-392
- [11] Hu Y, Martra G, Zhang J, Higashimoto S, Coluccia S, Anpo M. Characterization of the local structures of Ti-MCM-41 and their photocatalytic reactivity for the decomposition of NO into N_2 and O_2 . *The Journal of Physical Chemistry. B*. 2006;**110**:1680-1685
- [12] Li J, Zhou C, Xie H, Ge Z, Yuan L, Li X. Titanium-containing mesoporous materials: Synthesis and application in selective catalytic oxidation. *Journal of Natural Gas Chemistry*. 2006;**15**:164-177
- [13] Hossain MA, Elias M, Sarker DR, Diba ZR, Mithun JM, Azad MAK, et al. Synthesis of Fe- or Ag-doped TiO_2 -MWCNT nanocomposite thin films and their visible-light-induced catalysis of dye degradation and antibacterial activity. *Research on Chemical Intermediates*. 2018;**44**:2667-2683
- [14] Rahman MM, Asiri AM, Youssef TE, Marwani HM. Photocatalytic degradation of Remazol Brilliant Orange 3R using wet-chemically prepared $\text{CdO}-\text{ZnO}$ nanofibers for environmental remediation. *Material Express*. 2016;**6**:137-148

- [15] Zinatloo-Ajabshir S, Salavati-Niasari M, Sobhani A, Zinatloo-Ajabshir Z. Rare earth zirconate nanostructures: Recent development on preparation and photocatalytic applications. *Journal of Alloys and Compounds*. 2018;**767**:1164-1185
- [16] Liu Y, Deng Y, Sun Z, Wei J, Zheng G, Asiri AM, et al. Hierarchical Cu₂S microsponges constructed from nanosheets for efficient photocatalysis. *Small*. 2013;**9**:2702-2708
- [17] Jamal A, Rahman MM, Khan SB, Faisal M, Asiri AM, Khan AAP, et al. Hydrothermally preparation and characterization of un-doped manganese oxide nanostructures: Efficient photocatalysis and chemical sensing applications. *Micro and Nanosystems*. 2013;**5**:22-28
- [18] Ahmed J, Rahman MM, Siddiquey IA, Asiri AM, Hasnat MA. Efficient bisphenol-A detection based on the ternary metal oxide (TMO) composites by electrochemical approaches. *Electrochimica Acta*. 2017;**246**:597-605
- [19] Rahman MM, Ahmed J. Cd-doped Sb₂O₄ nanostructures modified glassy carbon electrode for efficient detection of melamine by electrochemical approach. *Biosensors and Bioelectronics*. 2018;**102**:631-636
- [20] Subhan MA, Saha PC, Rahman MM, Ahmed J, Asiri AM, Al-Mamun M. Fabrication of a 2,4-dinitrophenol sensor based on Fe₃O₄@Ag@Ni nanomaterials and studies of their antibacterial properties. *New Journal of Chemistry*. 2018;**42**:872-881
- [21] Alam MM, Asiri AM, Uddin MT, Inamuddin MAI, Awual MR, Rahman MM. One-step wet-chemical synthesis of ternary ZnO/CuO/Co₃O₄ nanoparticles for sensitive and selective melamine sensor development. *New Journal of Chemistry*. 2019;**43**:4849-4858
- [22] Rahman MM, Alam MM, Asiri AM. Efficient phenolic sensor development based on facile Ag₂O/Sb₂O₃ nanoparticles for environmental safety. *Nanoscale Advances*. 2019;**1**:696-705
- [23] Hussein MA, Alam MM, Alenazi NA, Alamry KA, Asiri AM, Rahman MM. Nanocomposite based functionalized polyethersulfone and conjugated ternary ZnYCdO nanomaterials for the fabrication of selective Cd²⁺ sensor probe. *Journal of Polymer Research*. 2018;**25**:262
- [24] Sheikh TA, Rahman MM, Asiri AM, Marwani HM, Awual MR. 4-Hexylresorcinol sensor development based on wet-chemically prepared Co₃O₄@Er₂O₃ nanorods: A practical approach. *Journal of Industrial & Engineering Chemistry*. 2018;**66**:446-455
- [25] Rahman MM, Alam MM, Asiri AM. Selective hydrazine sensor fabrication with facile low-dimensional Fe₂O₃/CeO₂ nanocubes. *New Journal of Chemistry*. 2018;**42**:10263-10270
- [26] Awual MR, Hasan MM, Islam A, Rahman MM, Asiri AM, Khaleque MA, et al. Offering an innovative composited material for effective lead(II) monitoring and removal from polluted water. *Journal of Cleaner Production*. 2019;**231**:214-223
- [27] Awual MR, Hasan MM, Asiri AM, Rahman MM. Cleaning the arsenic(V) contaminated water for safe-guarding the public health using novel composite material. *Composites Part B: Engineering*. 2019;**171**:294-301
- [28] Awual MR, Hasan MM, Islam A, Rahman MM, Asiri AM, Khaleque MA, et al. Introducing an amine functionalized novel conjugate

material for toxic nitrite detection and adsorption from wastewater. *Journal of Cleaner Production*. 2019;**228**:778-785

[29] Awual MR, Islam A, Hasan MM, Rahman MM, Asiri AM, Khaleque MA, et al. Introducing an alternate conjugated material for enhanced lead(II) capturing from wastewater. *Journal of Cleaner Production*. 2019;**224**:920-929

[30] Awual MR, Hasan MM, Rahman MM, Asiri AM. Novel composite material for selective copper(II) detection and removal from aqueous media. *Journal of Molecular Liquids*. 2019;**283**:772-780

[31] Awual MR, Hasan MM, Asiri AM, Rahman MM. Novel optical composite material for efficient vanadium(III) capturing from wastewater. *Journal of Molecular Liquids*. 2019;**283**:704-712

[32] Rao GV, Sree GS, Mohan BS, Anjaneyulu RB. A simple and green synthesis of Zinc oxide nanoparticles using *Gloriosa superba* leaves extract. *International Journal of Green and Herbal Chemistry*. 2018;**7**(2):373-378

[33] Robertson P. Semiconductor photocatalysis: An environmentally acceptable alternative production technique and effluent treatment process. *Journal of Cleaner Production*. 1996;**1996**(4):203

[34] Turchi CS, Ollis DF. Photocatalytic degradation of organic water contaminants: Mechanisms involving hydroxyl radical attack. *Journal of Catalysis*. 1990;**122**:178

[35] Awual MR, Khraisheh M, Alharthi NH, Luqman M, Islam A, Karim MR, et al. Efficient detection and adsorption of cadmium(II) ions using innovative nano-composite materials. *Chemical Engineering Journal*. 2018;**343**:118-127

[36] Awual MR, Alharthi NH, Hasan MM, Karim MR, Islam A, Znad H, et al. Inorganic-organic based novel nano-conjugate material for effective cobalt(II) ions capturing from wastewater. *Chemical Engineering Journal*. 2017;**324**:130-139

[37] Awual MR, Hasan MM, Eldesoky GE, Khaleque MA, Rahman MM, Naushad M. Facile mercury detection and removal from aqueous media involving ligand impregnated conjugate nanomaterials. *Chemical Engineering Journal*. 2016;**290**:243-251

[38] Katowah DF, Rahman MM, Hussein MA, Sobahi TR, Gabal MA, Alam MM, et al. Ternary Nanocomposite based poly(pyrrole-co-O-toluidine), cobalt ferrite and decorated chitosan as a selective Co^{2+} cationic sensor. *Composites Part B: Engineering*. 2019;**175**:107175

[39] Rahman MM, Alam MM, Alamry KA. Sensitive and selective m-Tolylhydrazine sensor development based on CdO nanoparticles decorated multi-walled carbon nanotubes. *Journal of Industrial and Engineering Chemistry*. 2019;**77**:309-316

[40] Rahman MM, Hussain MM, Arshad MN, Awual MR, Asiri AM. Arsenic sensor development based on modified with (E)-N'-(2-nitrobenzylidene)-benzenesulfonohydrazide: A real sample analysis. *New Journal of Chemistry*. 2019;**43**:9066-9075

[41] Abdu-Zied BM, Alam MM, Asiri AM, Schwiager W, Rahman MM. Fabrication of 1,2-dichlorobenzene sensor based on mesoporous MCM-41 material. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*. 2019;**562**:161-169

[42] Karim MR, Alam MM, Aijaz MO, Asiri AM, Dar MA, Rahman MM. Fabrication of 1,4-dioxane sensor

based on microwave assisted PANi-SiO₂ nanocomposites. *Talanta*. 2019;**193**:64-69

[43] Alam MK, Rahman MM, Rahman MM, Kim D, Asiri AM, Khan FA. In-situ synthesis of gold nanocrystals anchored graphene oxide and its application in biosensor and chemical sensor. *Journal of Electroanalytical Chemistry*. 2019;**835**:329-337

[44] Rahman MM, Alam MM, Asiri AM. Carbon black co-adsorbed ZnO nanocomposites for selective benzaldehyde sensor development by electrochemical approach for environmental safety. *Journal of Industrial and Engineering Chemistry*. 2018;**65**:300-308

[45] El-Shishtawy RM, Al-Ghamdi HA, Alam MM, Al-Amshany ZM, Asiri AM, Rahman MM. Development of Cd²⁺ sensor based on BZNA/nafion/glassy carbon electrode by electrochemical approach. *Chemical Engineering Journal*. 2018;**352**:225-231

[46] Hussain MM, Asiri AM, Arshad MN, Rahman MM. Fabrication of a Ga³⁺ sensor probe based on methoxy benzylidene benzene sulfo no hydrazine (MBBSH) by an electrochemical approach. *New Journal of Chemistry*. 2018;**42**:1169-1180

[47] Rahman MM, Alam MM, Asiri AM, Islam MA. 3,4-Diaminotoluene sensor development based on hydrothermally prepared MnCo_xO_y nanoparticles. *Talanta*. 2018;**176**:17-25